MONOGRAPHS ON INDUSTRIAL CHEMISTRY

Edited by Sir Edward Thorpe, C.B., LL.D., F.R.S.

Emeritus Professor of General Chemistry in the Imperial College of Science and Technology,
South Kensington; and formerly Principal of the Government Laboratory, London.

INTRODUCTION

DURING the last four or five decades the Applications of Chemistry have experienced an extraordinary development, and there is scarcely an industry that has not benefited, directly or indirectly, from this expansion. Indeed, the Science trenches in greater or less degree upon all departments of human activity. Practically every division of Natural Science has now been linked up with it in the common service of mankind. So ceaseless and rapid is this expansion that the recondite knowledge of one generation becomes a part of the technology of the next. Thus the conceptions of chemical dynamics of one decade become translated into the current practice of its successor; the doctrines concerning chemical structure and constitution of one period form the basis of large-scale synthetical processes of another; an obscure phenomenon like Catalysis is found to be capable of widespread application in manufacturing operations of the most diverse character.

This series of Monographs will afford illustrations of ese and similar facts, and incidentally indicate their ꝫ on the trend of industrial chemistry in the near They will serve to show how fundamental and al is the relation of principle to practice They

will afford examples of the application of recent knowledge to modern manufacturing procedure. As regards their scope, it should be stated the books are not intended to cover the whole ground of the technology of the matters to which they relate. They are not concerned with the technical *minutiæ* of manufacture except in so far as these may be necessary to elucidate some point of principle. In some cases, where the subjects touch the actual frontiers of progress, knowledge is so very recent and its application so very tentative that both are almost certain to experience profound modification sooner or later. This, of course, is inevitable. But even so such books have more than an ephemeral interest. They are valuable as indicating new and only partially occupied territory; and as illustrating the vast potentiality of fruitful conceptions and the worth of general principles which have shown themselves capable of useful service.

Organic Compounds of Arsenic and Antimony. By G. T. MORGAN, F.R.S., F.I.C., M.R.I.A., D.Sc., A.R.C.Sc., Professor of Applied Chemistry, City and Guilds Technical College, Finsbury, London. 16s. net.

Edible Oils and Fats. By C. A. MITCHELL, F.I.C. 6s. 6d. net.

Coal and its Scientific Uses. By W. A. BONE, D.Sc., F.R.S., Imperial College of Science and Technology, South Kensington. 21s. net.

The Zinc Industry. By ERNEST A. SMITH, The Assay Office, Sheffield. 10s. 6d. net.

Colour in Relation to Chemical Constitution. By E. R. WATSON, M.A., D.Sc., Professor of Chemistry, Dacca College, Bengal. 12s. 6d net.

The Applications of Electrolysis in Chemical Industry. By ARTHUR J. HALE, B.Sc., F.I.C., Finsbury Technical College, London.

The Natural Organic Colouring Matters. By A. G. PERKIN, F.R.S., The Dyeing Department, The University, Leeds; and A. E. EVEREST, D.Sc., PH.D., Technical College, Huddersfield.

The following Volumes are in preparation:—

Liquid Fuel for Internal Combustion Engines. By Sir BOVERTON REDWOOD, Bart., D.Sc., F.R.S.E., and J. S. S. BRAME, Royal Naval College, Greenwich.

Catalysis in Industrial Chemistry. By G. G. HENDERSON, M.A., D.Sc., LL.D., F.R.S., The Royal Technical College, Glasgow.

Synthetic Colouring Matters: Sulphur Dyes. By G. T. MORGAN, D.Sc., A.R.C.S., F.R.S., Finsbury Technical College, London.

Synthetic Colouring Matters: Vat Colours. By JOCELYN F. THORPE, C.B.E., D.Sc., F.R.S., Imperial College of Science and Technology, South Kensington.

Naphthalene. By W. P. WYNNE, D.Sc., F.R.S., The University, Sheffield.

Synthetic Colouring Matters: Azo-Dyes. By FRANCIS W. KAY, D.Sc., The University, Liverpool.

Utilisation of Atmospheric Nitrogen: Synthetical Production of Ammonia and Nitric Acid. By A. W. CROSSLEY, C.M.G., D.Sc., F.R.S., F.I.C., King's College, Strand.

Cement. By BERTRAM BLOUNT, F.I.C.

The Principles and Practice of Gas-purification. By EDWARD V. EVANS, F.I.C., Chief Chemist, South Metropolitan Gas Company.

Refractories. By J. W. MELLOR, D.Sc.

Ozone and Hydrogen Peroxide: their Properties, Technical Production and Applications. By H. VINCENT A. BRISCOE, D.Sc., A.R.C.S., Imperial College of Science and Technology, South Kensington.

Industrial Applications of the Rarer Metals. By WILLIAM G. WAGNER and W. E. F. POWNEY, A.I.C.

Cellulose-Silk. By C. F. CROSS, B.Sc., F.R.S., F.I.C.

The Electric Arc in Chemical Industry. By J. N. PRING, D.Sc., The University, Manchester.

By-Product Coking Practice. By ERNEST BURY, M.Sc.

Organic Synthetic Reactions: their Application to Chemical Industry. By JULIUS B. COHEN, B.Sc., Ph.D., F.R.S.

Synthetic Colouring Matters: Triphenylmethane Dyes. By R. ROBINSON, D.Sc., Professor of Organic Chemistry in the University of Liverpool.

Synthetic Colouring Matters: Anthracene and Allied Dye-stuffs. By F. W. ATACK, M.Sc. Tech., B.Sc. (Lond.), F.I.C. of the Municipal School of Technology, Manchester.

Synthetic Colouring Matters: Acridine and Xanthene Dye-stuffs. By JOHN T. HEWITT, M.A., D.Sc., F.R.S., University of London (East London College).

Synthetic Colouring Matters: Azine and Oxazine Dye-stuffs. By JOHN T. HEWITT, M.A., D.Sc., F.R.S., University of London (East London College).

Synthetic Drugs: Local Anæsthetics. By W. H. HURTLEY, D.Sc., St. Bartholomew's Hospital; and M. A. WHITELEY, D.Sc., Imperial College of Science and Technology, South Kensington.

LONGMANS, GREEN AND CO.
LONDON, NEW YORK, BOMBAY, CALCUTTA, AND MADRAS.

COAL AND ITS SCIENTIFIC USES

Bone

+V

COAL AND ITS SCIENTIFIC USES

BY

WILLIAM A. BONE

D.Sc., Ph.D., F.R.S.

*Professor of Chemical Technology in the Imperial College of Science and Technology,
London ; Formerly Livesey Professor of Coal Gas and Fuel Industries in the
University of Leeds ; Honorary Member of the American Gas Institute
and of the Institution of Gas Engineers ; Chairman of the British
Fuel Economy Committee (1915–17)*

WITH ILLUSTRATIONS

TO

THE MEMORY OF MY DEAR WIFE

KATE BONE

PREFACE

I HAVE endeavoured in this monograph to give in essential outline an account of the present state of science and practice in relation to Coal and its various Uses.

In consenting to undertake the task I was conscious, on the one hand, that so wide and important a subject could hardly be treated adequately by any one writer in a volume of such moderate dimensions as this present. On the other hand, I felt that, in the national interest, there was great need for some responsible scientific worker in Fuel Technology to review the various aspects of the Coal Question as it stands to-day. And as much new information had come to my knowledge as Chairman of the British Association Fuel Economy Committee in 1915–17, it was hardly possible for me not to accede to the Editor's request.

In drawing up the scheme for the book, I made it my chief objective to give the scientific public, and especially the chemical section of it, as clear and succinct an account as I could of the statistical, chemical, and technical aspects of the subject as a whole, without unnecessary detail or too much mechanical illustration. And whilst I have made no attempt to write what would be called a scientific treatise, I have consistently endeavoured throughout to give due prominence to the underlying scientific principles.

The scheme of the book has been so arranged that, beginning with a chapter on the general and statistical aspects of the Coal Question from a national standpoint, there follows a review of the present state of science regarding the origin and chemistry of coal, including its distillation, oxidation, and combustion. The latter part of the book is devoted to a consideration of the principal economic and industrial uses of coal as a fuel, to each of which one or more chapters have been assigned. The volume closes with an account of the subject of " Surface Combustion,"

which has been included in response to many requests from various friends.

I am fully aware that in reviewing so complex a subject as the Chemistry of Coal, I was entering upon controversial ground, but I trust that those whose work I have dealt with will find that I have succeeded in my desire to present an entirely impartial, although at the same time critical, account of the matter in its essential aspects.

The book has, however, been written during a period of quite exceptional stress of academic and professional duties, and amid many distractions arising therefrom; therefore, I trust that my readers will be lenient towards any omissions or defects which they may discover in the text.

My task has been considerably lightened by the kindness of many colleagues and friends who have helped me by their advice after perusing the various chapters. My special thanks are due to Mr. A. W. Flux, M.A., in reference to the statistical review in Chapter I; to Professor W. W. Watts, F.R.S., and Mr. G. W. Lamplugh, F.R.S., in regard to the geological matters touched upon in Chapter II; to Professor W. E. Dalby, F.R.S., for perusing the Chapter on " Heat Transmission in Boilers "; to Messrs. T. Pridgin Teale, F.R.S., and H. James Yates in connection with Chapter XII; to Professor J. B. Cohen, F.R.S., of Leeds, in connection with Chapter XIII; and, lastly, to my relative, Mr. T. C. Hutchinson, and my old pupil, Mr. E. Bury, M.Sc., both of the Skinningrove Iron Co., Ltd., for their guidance in respect of Chapter XIX.

I am also indebted to the courtesy of numerous engineering firms, whose coal-using plants or appliances are described or referred to in the text, for much information and the loan of appropriate diagrams and photographs. Among those I would particularly mention are: Messrs. Joseph Adamson & Co.; Clayton, Son & Co., Ltd.; R. & J. Dempster, Ltd.; Dowson and Mason Gas Plant Co., Ltd.; Frasers & Chalmers, Ltd.; Humphreys & Glasgow, Ltd.; Lymn Chemical Engineering Co., Ltd.; Merz & McLellan; Perry & Co., Ltd. (Bow); Power Gas Corporation, Ltd.; Successors to the Otto Coke Oven Co., Ltd.; Underfeed Stoker Co., Ltd.; and West's Gas Improvement Co., Ltd.

I also desire to say that, with the Editor's kind acquiescence, I have made full use of the valuable information contained in the following articles in his *Dictionary of Applied Chemistry*, namely, (1) " Coke," by Ernest Bury, M.Sc.; (2) " Coal Gas,"

by Dr. Harold G. Colman; and (3) "Water Gas," by the late Professor V. B. Lewes. And, naturally, also I have drawn a good deal from my own article on " Fuel " in the same publication.

I must also thank many authors, publishers, and other scientific or professional friends for their kindness in allowing me to reproduce diagrams, tables, and other illustrations from their memoirs or issues, all of which I have endeavoured to acknowledge duly, either in the text or in the footnotes thereto. Among these I would specially mention here are the following: Professor J. S. S. Brame; Messrs. H. R. Kempe, J. B. C. Kershaw, M. Longridge; Drs. Vernon Harcourt and R. V. Wheeler; the Editors of the *Iron and Coal Trades Review* and of the *Gas Journal;* Messrs. Edward Arnold, Benn Bros., Ltd. (publishers of the *Gas World*), and Charles Griffin & Sons; the Councils or Managers of the American Gas Institute, of the Chemical Society, of the Iron and Steel Institute, and of the Royal Institution of Great Britain.

I must, finally, express my warmest thanks to my assistant, Mr. R. J. Sarjant, B.Sc., A.R.C.S., for his indispensable help in revising the typescript, checking calculations, preparation of curves, and reading the proof sheets, as well as to Mr. Cecil Godfrey, A.R.C.S., for kindly indexing the volume. Also I desire to thank Miss B. Butler for the great care which she has bestowed upon preparing the typescript and the numerous tables illustrating the text.

The writing of the book has been a labour of love, for it is dedicated to the memory of one who was my constant companion and inspiration during eighteen supremely happy years of scientific work in Manchester, Leeds, and London, and whose personality was a delight to all who enjoyed her friendship.

WILLIAM A. BONE.

Imperial College of Science and Technology, London.
. *June* 1918.

CONTENTS

LIST OF PLATES

LIST OF TABLES

COAL AND ITS SCIENTIFIC USES

CHAPTER I

INTRODUCTORY—THE COAL QUESTION—ITS IMPORTANCE TO THE NATION AND THE EMPIRE

" COAL in truth stands not beside, but entirely above, all other commodities. It is the material source of the energy of the country—the universal aid—the factor in everything we do. With coal almost any feat is possible or easy; without it we are thrown back into the laborious poverty of early times. . . . The progress of science, and the improvement in the arts, will tend to increase the supremacy of steam and coal " (W. Stanley Jevons on *The Coal Question*, 1865).[1]

When Jevons endeavoured, more than fifty years ago, to awaken public opinion to the vital importance of the coal question to the industrial future of the nation, this country held an un-rivalled position as a producer of coal. For out of a total world's output of 130 million tons, no less than 80 million tons, or practically 60 per cent., were raised in Great Britain. The then known immense coal reserves of North America, as well as those of the States now comprising the German Empire, had scarcely been touched, chiefly because neither of these countries had as yet reached a state of industrial or economic development at all comparable with our own. And although the cost of getting bituminous coal in Pennsylvania (Pittsburg) was even then less than one-half the general price at British and German mines, the proximity of all our principal coalfields either to the sea, on the one hand, or to supplies of ironstone, on the other, combined with the natural skill and aptitude of our people in regard to mechanical invention, had combined to place us in a position of unique advantage over all other countries.

[1] A third edition of Jevons's remarkable book on *The Coal Question* (1868), revised by A. W. Flux, was published in 1906 (Macmillan & Co.).

B

The rise of the industrial supremacy which Great Britain enjoyed throughout the nineteenth century may be dated from the years 1730 to 1735 when the Abraham Darbys, father and son, re-discovered and revived the art of smelting iron with pit coal, which had been in abeyance since the days of Dud Dudley (1599 to 1684), who had originated it in 1621. The substitution of pit coal for wood charcoal as fuel in the blast furnace had an immediate and far-reaching effect upon the economic future of Great Britain and, through it, upon the welfare of mankind in general.

During Elizabethan times the inroads upon our forests to supply charcoal for the iron furnaces of Sussex and neighbouring counties, then the chief seat of iron smelting in England, had become so serious that Parliament found it necessary to interfere with an Act prohibiting the further extension of the industry. But with Dudley's discoveries the necessity for such restrictions disappeared, and such was the development of the iron industry in England during his lifetime, that the outputs of our 300 furnaces has been thought by some to have reached possibly 100,000 tons per annum. Unfortunately disaster overtook him, and for fifty years after his death the use of pit coal fell altogether into abeyance. So rapidly then did the industry decline that, in 1740, there remained but fifty-nine furnaces in blast, yielding an annual output of a little more than 17,000 tons, and in that year 30,000 tons of iron had to be imported to meet the national requirements. The population of England and Wales, which, according to the best estimates, had grown from 5·6 millions in 1630 to 6·25 millions in 1711, then came to a standstill, or actually declined, during the next thirty years until, in 1741, it stood no higher than 6·15 millions.

This was, however, the turning point; the next thirty years saw an increase in the population of no less than a million persons, whilst the annual output of our iron furnaces had increased at least threefold. A century after the Darbys' achievement the population had increased to 14 millions, and the annual output of iron to about 750,000 tons.

The year 1828 brought James Neilson's revolutionary invention of preheating the air before it reached the fuel in the blast furnace, which ushered in another era of expansion, and may be said to have laid the foundation of nearly all subsequent developments in the direction of fuel economy in iron smelting.

Just as the need of pumping the mines was the chief incentive to the first pioneers of the steam engine, so the development of

steam-power by British engineers during the eighteenth century greatly increased the commercial prospects of coal mining; for it is said that " the steam engine produced a new era in the mining and commercial interests of Britain, and, as it were, in an instant, put every coalfield which was considered as lost within the grasp of its owners. Collieries were opened in every district and such has been the astonishing effect produced by this machine, that great coal was shipping free on board in the river Forth in the year 1785 at 4s. 10d. per ton; that is, after a period of seventy years, coal had only advanced 2d. per ton, while the price of labour and all materials was doubled." [1]

As the result of the new industrial life and enterprise which sprang up everywhere throughout the Kingdom from the inventions of the Darbys, Newcomen, Smeaton, James Watt and others, attention was directed to the deplorably backward state of its internal communications. Until the middle of the eighteenth century the wretched conditions of such high roads as there were in England rendered them all but useless for goods traffic. Canals there were none, although Holland, France, and even Russia had already developed efficient and extensive canal systems. But, as Jevons pointed out, " until coal supplied the purpose, there was not spirit enough in this country to undertake so formidable a work as a canal."

The first canal cut in England was in 1755 to convey coal from St. Helens to the Mersey; thereupon the Duke of Bridgwater engaged Brindley to construct his famous canal for the purpose of transporting coal from his collieries at Worsley to Manchester, the accomplishment of which is said to have saved 7s. 6d. per ton on the carriage, and to have immediately reduced the price of coal in Manchester from 7d. to $3\frac{1}{2}d.$ per cwt. (120 lb.). A rapid development of the canal system in England followed; thus before Brindley died in 1772, he had designed and carried out the Grand Trunk Canal, connecting the Trent and Humber with the Mersey, the Staffordshire and Worcestershire Canal, the Oxford Canal, and the Stockwith and Chesterfield Canal. By the year 1810 there had been constructed 2000 miles of canals in England alone at a cost of £50,000,000, and some of the companies owning them paid large dividends.

necessity of cheapening the carriage of coal from hildon to the wharves on the Tees at Stockton construction of the first public railway. This

1 *Trade*, p. 24, quoted by Jevons (1906 edition, p. 120).

TABLE I

was opened between Whitton Park Colliery, Darlington, and Stockton on September 27, 1825, and the rapid extension of railways and steam locomotives which followed the success of this venture was " mainly due to the traffic and wealth occasioned by the use of coal in manufacture." [1] So much so that George Stephenson used to say, " The strength of Britain lies in her iron and coal beds; and the locomotive is destined, above all other agencies, to bring it forth. The Lord Chancellor now sits upon a bag of wool, but wool has long since ceased to be emblematical of the staple commodity of England. He ought to sit upon a bag of coals." [2]

And if it was to the traffic and wealth in coal that the nation mainly owed the development of its internal communications (canals and railways) during the century 1750 to 1850, it may with equal truth be said that one of the chief factors in the maintenance of the supremacy of its mercantile marine since 1850 has been its ever-increasing export trade in coal, as the figures in Tables I and II show :—

TABLE II

Year.	Total Net Tonnage of Ships on the Registers of the British Empire (Million Tons).	Ratio. British Empire Tonnage. / Whole World's Tonnage.
1855	5·00	—
1873	7·55	0·432
1890	9·69	0·578
1900	10·75	0·486

Moreover, the overwhelming supremacy in shipbuilding which the United Kingdom and the Empire had established over all other nations by the end of the nineteenth century (as shown in Table III) is to be ascribed to cheap coal and iron, combined with (so far as the United Kingdom is concerned) favourable geographical position, climatic conditions, and free imports. And it is not too much to say that the future maintenance of our marine supremacy is intimately bound up with the cheap production of coal, iron, and steel; from this point of view the relatively increasing cost during recent years of fuel in Great Britain, as compared with America, is a matter of serious national concern.

[1] Jevons, *The Coal Question*, p. 125.
[2] Smiles's *Lives of the Engineers*, Vol. III., p. 357 (quoted also by Jevons, *ibid.*, p. 126).

TABLE III

NUMBER AND TONNAGE OF SHIPS OF 100 TONS GROSS AND UPWARDS
BUILT DURING 1900

Country.	Sail.		Steam.		Total.		Percentage of Total.
	No.	Tonnage.	No.	Tonnage.	No.	Tonnage.	
Great Britain and Empire	41	12,826	669	1,497,001	710	1,509,837	64·42
United States	105	118,387	91	184,952	196	303,339	12·92
Germany .	37	16,982	71	203,417	108	220,399	9·40
France . .	53	96,334	13	31,094	66	127,428	5·44
All other Countries .	88	19,442	128	163,409	216	182,851	7·82
Total .	324	263,971	972	2,079,873	1296	2,343,854	100·00

With regard to the position of the United Kingdom as a producer of coal during the past fifty years, it may be remarked that not only (as is shown in Table IV) has the average output of coal per head of population steadily increased, but also the price of it at the pithead has increased, both absolutely and relatively to that of other commodities, a condition which has applied equally to other European countries. Indeed for many years past there has been no material difference between the average pithead prices of coal in Great Britain and Germany, and it is probable that the upward tendency in both countries will continue, owing to the steadily increasing costs in operating the mines. On the other hand, coal is produced in the United States at a materially lower cost than in any European country, and the pithead price there had for some years previous to the war shown no upward tendency, but rather the reverse.

The case of iron is different, for whilst our output of pig iron per head of population had, before the war, become practically stationary, the cost of its manufacture had been kept down by improved methods and organisation, and in 1913 it was certainly much lower than it was fifty years ago. At the outbreak of the war we were not producing sufficient steel to meet our own industrial demands, and but for the help of American steel-makers we should not have been able during the war to cope with the demands for munitions. Also, the devastation of Belgium and Northern France has meant a serious reduction in European

6

steel plants outside the Central Empires. Hence many people consider that the time is ripe for increasing the output capacities of British iron and steel plants. But if, as will be shown in a later chapter, the price of coal is, and probably will always be, a serious item in the cost of manufacturing both pig iron and steel, the prospects of extending our steel industries on any sound commercial basis is largely bound up with the proper development and utilisation of our best seams of coking coals, and with the achievement of the utmost economy in fuel throughout the whole series of processes from the ore to the finished steel sections.

TABLE IV

OUTPUT OF COAL AND PIG IRON IN THE UNITED KINGDOM

Decennial Period.	Coal.			Pig Iron.	
	Million Tons per Annum.	Tons per Head of Population per Annum.	Average Pit-head Price, Shillings per Ton.	Million Tons per Annum.	Tons per Head of Population per Annum.
			s. d.		
1865–74	111·5	3·54	5 11	5·65	0·18
1875–84	144·5	4·21	6 10	7·25	0·21
1885–94	172·5	4·62	6 3	7·50	0·20
1895–1904	214·5	5·17	7 5	8·60	0·21
1905–14	263·0	5·80	8 7	9·65	0·21

The general movement of coal values, both absolute and relative, in Great Britain during the past seventy years may be illustrated by the following average figures from the "declared" values per ton of coal exported from the United Kingdom, as compared with Sauerbeck's index numbers for the values of commodities generally.

TABLE V

Years.	Average Value of Coal Exported.		Proportionate Numbers.	Sauerbeck's Index Numbers. (All commodities.)
	s.	*d.*		
1840–4	7	3	73·9	92·2
1865–9	9	9½	100·0	100·0
1890–4	11	1	113·2	68·6
–14	12	7	128·5	82·8

THE WORLD'S COAL RESERVES

As, therefore, it can hardly be questioned that the chief material basis of the great industrial expansion of this country during the past century has been our abundant supplies of easily obtainable coal, and that our whole economic future is bound up with our ability to maintain abundant supplies of relatively cheap fuel, it is important that our present position as regards coal, compared with that of other nations and the world at large, should be clearly apprehended.

According to an exhaustive report upon the World's Coal

FIG. 1.—World's Estimated Reserves of Coal, 1913, 7,397,553 Million Tons.

Resources issued by the International Geological Congress in 1913, the total probable and possible reserves of coal of all kinds (including anthracites, bituminous coals, and lignites) available within 6000 feet of the earth's surface, are estimated to be 7,397,553 million metric tons; or approximately 6000 times the world's present total annual consumption. Therefore the world as a whole need have no fear of any speedy exhaustion of its coal supplies.

Of the estimated total reserves, 6·75 per cent. are anthracites (mainly located in China), 52·75 per cent. are bituminous coals, and 40·5 per cent. belong to the less valuable sub-bituminous class, which includes all the lignites and Tertiary brown coals (see Fig. 1).

A survey of the geographical distribution of the estimated reserves shows that no less than 69 per cent. of the total are located in America (almost wholly North America), 17·3 per cent. in Asia, 10·6 per cent. in Europe, 2·4 per cent. in Oceania, and only 0·8 per cent. in Africa (see Fig. 2). It is a significant fact that the two tropical continents of South America and Africa are practically destitute of coalfields of any economic importance. The future wealthy republics of South America must continue, as heretofore, to import coal, machinery, and heavy manufactured goods, in exchange for agricultural produce and raw materials.

Pursuing the matter a little further, we find that of the total

FIG. 2.—Percentages of World's Total Coal Reserves.

estimated reserves, 51·8 per cent. are located in the United States, 16·4 per cent. in Canada, 13·5 per cent. in China, 5·7 per cent. in Germany, 2·6 per cent. in Great Britain, 2·3 per cent. in Siberia, 2·2 per cent. in Australia, and only 0·8 per cent. in Russia (see Fig. 3). China's resources may have been under-estimated, otherwise the relative positions of the remaining countries are probably substantially as stated.

The fact that the available reserves of coal in Great Britain only amount to about one-fortieth, whilst those of the whole Empire do not amount to more than about one-fourth of the world's estimated total, is one which ought to be weighed by every one responsible for the economic development of our national and imperial resources, especially in view of the fact that the United States, whose competition in the immediate

future will probably be much more severely felt than ever before, possesses more than half the estimated world's coal, and that also in regard to the two prime considerations of quality and cost of production she probably compares favourably with Great Britain and the Empire.

A better criterion, however, of the position of the United Kingdom relative to that of other countries is perhaps afforded by considering the relation of coal reserves to the population in four of the principal coal-bearing countries of the world. In

FIG. 3.—Percentages of World's Total Coal Reserves.

making such a comparison it is necessary to differentiate between the economically much more valuable anthracitic and bituminous coals of the Carboniferous Series (A and B) and the less important sub-bituminous Tertiary coals (C), that is to say the Lignites and Brown coals.

From these figures (Table VI), it will be seen that so far as classes A and B are concerned, the reserves per head of population in the United Kingdom, although only about one-fifth of those in the United States, do not compare so unfavourably with those in Germany, and are more than the average for the world as a

whole. Moreover, almost every variety of economically valuable coals is found in the British Coal Measures, and their quality is on the whole superior to those of European coals generally. More problematical, however, is the position of China, whose enormous reserves have been much less explored than those of other countries; but from what is already known, nearly 40 per cent. of China's reserves consist of high-class anthracites or anthracitic coals, and the remainder are practically all bituminous varieties.

TABLE VI

Country.	Population, Millions.	Estimated Total Reserves. Millions of Tons.		Estimated Reserves. Tons per Head of Population.		
		A and B	C	A and B	C	Total.
United States	105	2,000,000	1,800,000	19,000	17,000	36,000
Germany . .	65	410,000	13,400	6,300	200	6,500
United Kingdom	46	190,000	*nil*	4,000	*nil*	4,000
China . . .	400	1,000,000	600	2,500	1·5	2,500
The World .	1500	4,500,000	3,000,000	3,000	2,000	5,000

The World's Increasing Demands for Coal

The world's demands for coal, which in 1863 amounted to some 130 million tons per annum only, had by 1913 increased to nearly 1250 million tons per annum. Such a tenfold increase in fifty years represents a " compound interest " rate of practically 5 per cent. per annum throughout the whole period. During the last ten years of it this rate of increase was fully maintained, as follows :—

Year.	Total Demand. Mill. Tons.
1903	800
1908	1000
1913	1250

and it is hardly likely that the rate will diminish after the conclusion of the war.

During the last decade these demands have been principally supplied by three countries, namely, the United States, Great Britain, and Germany, which between them have annually raised practically 83 per cent. of the total coal consumed in the world, as is shown in the following Table :—

TABLE VII

WORLD'S OUTPUT OF COAL : MILLIONS OF TONS

	1903	Per cent.	1908	Per cent.	1913	Per cent.
United States	319·5	40·0 ⎫	415·8	41·5 ⎫	562·6	45·0 ⎫
Great Britain	230·4	28·8 ⎬ 83·4	261·5	26·0 ⎬ 82·3	287·4	23·0 ⎬ 83·3
Germany . .	116·6	14·6 ⎭	148·6	14·8 ⎭	191·5	15·3 ⎭
France . .	34·3	4·3	36·8	3·7	40·1	3·2
Belgium . .	23·8	3·0	23·7	2·3	22·8	1·8
Russia . .	16·5	2·0	29·4	2·9	28·8	2·3
British Possessions . .	26·5	3·3	42·0	4·2	50·0	4·0
All other countries . .	32·4	4·0	43·2	4·3	66·8	5·4
Total . .	800·0	100·0	1000·0	100·0	1250·0	100·0

If now the average outputs of anthracitic and bituminous coals [1] from each of the three countries in question for the three quinquennial periods since the year 1900 be examined (Table VIII), it will be found that the output of the United States has been increasing at a " compound interest " rate of 6 per cent. per annum, that of Germany at a compound rate of 4 per cent. per annum, whilst the British output has increased at a compound rate of only 2 per cent. per annum. Assuming that these relative rates of increase are maintained after the war, it may be predicted that Germany's output will overtake that of Great Britain about twenty years hence, when each country will be producing some 420 million tons per annum.

TABLE VIII

COAL PRODUCTIONS OF UNITED STATES, GREAT BRITAIN, AND GERMANY
QUINQUENNIAL AVERAGES, 1900–1914

Millions of Tons per Annum

	United States.	Great Britain.	Germany.
1900–4	288·2	226·8	112·5
1905–9	400·5	256·0	139·8
1910–14	519·2	269·9	168·7
Approximate per cent. Compound Interest Increase	6·0	2·0	4·0

[1] Lignites and Brown coals have been excluded from this review because of their relative unimportance, although Germany annually raises large quantities of low-grade Brown coals for home consumption.

The actual outputs for each year during the whole period in question are plotted in Fig. 4.

FIG. 4.—Coal Productions, in Millions of Tons, of the United States, Great Britain, and Germany—1900 to 1914.

BRITISH OUTPUTS AND EXPORTS OF COAL

How closely the continuous increases in the British outputs of coal during the forty-five years previous to the war had followed a 2 per cent. compound interest law is shown in the following table of quinquennial averages in millions of tons per annum of the total coal raised in Great Britain between the years 1870 and 1914 inclusive.

TABLE IXA

COAL PRODUCTION IN GREAT BRITAIN

QUINQUENNIAL AVERAGES,
1870–1914

Millions of Tons per Annum

Period.	Average Output.	Calculated at 2 % Compound Interest.
1870–4	121·5	121·5
1875–9	134·0	131·1
1880–4	156·0	148·1
1885–9	165·0	163·5
1890–4	180·0	180·5
1895–9	202·0	199·3
1900–4	227·0	220·1
1905–9	256·0	243·0
1910–14	270·0	268·2

These averages are shown as a curve in the next diagram (Fig. 5) which also indicates the proportion of the whole production which had been retained for home consumption. It should also be added that there has been an appreciable increase in the amount of coal consumed per annum per head of population during the period in question, namely, from about 3·5 to about 4·35 tons.

Much has been written upon the question of our coal export trade from opposite standpoints. In some quarters its rapid increase within recent years is viewed with feelings of concern, whilst other people regard a large coal export trade as a necessary condition of our maritime supremacy.

FIG. 5.—Quinquennial Averages of Coal Production in Great Britain.

During the past sixty years our coal export trade has increased something like twentyfold, as regards both the quantities and the values of coal exported. Moreover, its value relative to other values exported has, during the same period, increased fourfold, until in 1913 it constituted about 10 per cent. of our total exported values. Thus in that year, we exported 97·7 million tons (or 34 per cent. of our total output) valued at £53,000,000.

Another feature of our export trade is that whereas both the United States and Germany export considerable quantities of coal by land, their oversea exports are trifling compared with ours, so that in the year 1912 we actually transacted over 70 per cent. of the whole sea-borne coal trade of the world. Several factors have contributed to this astonishing result. One is the

proximity of our finest steam coal seams to our ports, notably so the South Wales coalfield, which now exports more than 60 per cent. of its total output; another is the increased demands for coal from Europe and South America; while a third factor has been the phenomenal growth of our mercantile marine, which for successful competition with foreign tonnage depends upon good outward as well as inward cargoes. For inasmuch as the inward cargoes are chiefly foodstuffs and raw materials of considerable bulk in relation to their values, while our exports (except coal) are chiefly machinery and manufactured articles, whose bulk is small in relation to their values, our shipowners are in a position to offer low freights for outward cargoes. Hence the view that maritime supremacy and a large coal export trade are interdependent.[1]

Probable Duration of British Coal Reserves

The probable duration of British coal reserves has been investigated by two Royal Commissions. The first one, which was appointed largely in consequence of the late Professor Jevons's book in 1865, reported in 1871, and the second reported in 1905. Since that date, however, Dr. Strahan, the Director of the Geological Survey of England and Wales, has published a revised estimate in the Report of the International Geological Congress for 1913, whilst more recently still (1915) Professor H. Stanley Jevons, following up his late father's work, has published another estimate in his book on *The British Coal Trade*. These various estimates are as follows :—

Estimates of Reserves of British Coal within 4000 feet of the Surface

			Million Tons.
First Royal Commission,	1871	.	146,480
Second Royal Commission,	1905	.	141,635
Dr. A. Strahan,	1912	.	178,727
Prof. H. Stanley Jevons,	1915	.	197,000

[1] It has been estimated that the total earnings of our shipping, including vessels employed in the home trade, in the year 1913 amounted to £162,000,000. Shipbuilding in the United Kingdom employed 210,000 persons and £150,000,000 of capital; port and harbour authorities 60,000 persons and £140,000,000 of capital; whilst miscellaneous dependent activities employed 260,000 persons and £100,000,000 of capital, the total being 530,000 persons and £390,000,000 of capital (*vide* a lecture on "Foreign Trade and Investments Abroad," by Mr. Edgar Crammond, F.S.S., to the Institution of Civil Engineers, March 12, 1917, as reported in *The Times* Engineering Supplement, March 30, 1917).

In making such estimates two overruling factors have to be considered, namely :—(1) the maximum depth at which it is practicable to conduct mining operations; and (2) the minimum thickness of seams which can be profitably worked. The first of these factors is determined principally by the increase in temperature as we descend into the bowels of the earth. In Great Britain the temperature at 50 feet below the surface is constant throughout the year at 50° Fahr., and then it increases 1° Fahr. for every 60 feet lower in depth. Both of the Royal Commissions adopted 4000 feet as the maximum limit of practicable working, at which depth the temperature might be expected to be 116° Fahr. and one foot as the minimum workable thickness of seam.[1]

Moreover, it should be noted that the Royal Commissions' figures represent the estimated *net* available amount of coal remaining unworked after certain allowances had been made, not only for coal which must be left underground as barriers for the support of surface buildings, but also for losses in working due to faults and other natural causes, which allowances amounted to about 20,000 million tons according to the 1905 Commission's estimate. Also, the 1905 estimate did not include the Kent coalfields and other " concealed " Measures, which were taken into account in Dr. Strahan's revised estimate. Professor H. S. Jevons, who considered that Dr. Strahan erred if anything on the safe side, gave 197,000 million tons as a maximum quantity within 4000 feet of the surface. If then 200,000 million tons be taken as an approximate outside figure, and an allowance of 15 per cent. be made for " pit wastage," the net coal which will actually be available *at the surface* would be about 170,000 million tons, or say about 580 times the amount actually raised in the year 1913.

The most important aspect of the coal question for Great Britain is not so much how long can our reserves possibly last, having regard to the probable continuation of the present upward tendency of our annual outputs, but how long can we continue to get the available coal at a cost which shall not place us as a nation at a disadvantage relative to our nearest competitors. Coal is a gift of Nature which hitherto we have for the most part squandered in all sorts of foul and wasteful ways, polluting the air of heaven with the smoke of it. Nature has also imposed

[1] The greatest depth at which coal mining operations are at present carried out in Great Britain is 3500 feet, and in Europe (Belgium) 3773 feet.

limits to our stores of it, which will possibly be reached some-
time in the future scarcely more distant than are our own times
from those of Queen Bess, and certainly not more (as it would
seem) than from those of the Black Prince. Moreover, as
Jevons pointed out and as subsequent experience has so far
confirmed, the more economy that is practised in the use of
coal, the more will its consumption increase, for as he truly
said : " Economy multiplies the value and efficiency of our chief
material; it indefinitely increases our wealth and means of sub-
sistence, and leads to an extension of our population, work, and
commerce, which is gratifying in the present, but must lead to
an earlier end. Economical inventions are what I should look
forward to as likely to continue our rate of increasing con-
sumption. Could we keep them to ourselves, indeed, they would
enable us, for a time, to neutralise the evils of dearness when
coal begins to get scarce, to keep up our accustomed efficiency
and push down our coal shafts as before. But the end would only
thus be hastened—the exhaustion of our seams more rapidly
carried out." [1]

THE PURPOSES FOR WHICH COAL IS CONSUMED IN THE UNITED KINGDOM AND THE MEANING OF FUEL ECONOMY

Although, in Great Britain, coal both is, and long will continue
to be, the principal source of all artificial light, heat, and power,
its proper utilisation involves a good deal more than increased
efficiency in respect either of power production or of heating
operations generally, important as these undoubtedly are. For,
when suitably handled by the chemist, coal yields a whole series
of valuable by-products which form the raw materials of im-
portant chemical industries, and the problem of " coal-economy "
involves the whole question of the recovery of such by-products,
and the consequent mitigation, or even abolition, of the smoke
nuisance which, directly and indirectly, costs the country many
millions of pounds per annum.

Thus from the tars resulting from the distillation of coal in
gas works, and from the manufacture of metallurgical coke, are
obtained ammonium salts, a whole series of aromatic hydro-
carbons (benzene, toluene, anthracene, naphthalene, etc.) and
other products, which form the basis of the manufacture of
synthetic dyes and drugs, as well as that of high explosives,

[1] Third edition (1906), p. 156.

and the more general and efficient recovery of such products is essential to the establishment upon a firm basis in this country of industries manufacturing such synthetic chemicals.

With regard to ammonium salts, which are chiefly valuable as fertilisers for the production of foodstuffs, out of 432,618 tons of ammonium sulphate made in the United Kingdom in 1913, no less than 369,557 tons were derived from coal, as follows :—

TONS OF AMMONIUM SULPHATE PRODUCED FROM COAL IN

Gas Works.	By-product Coke Oven Plants.	Gas Producers.	Iron Works.
182,180	133,816	33,605	19,956

How much more ammonium sulphate might have been produced by a more scientific handling of British coals is shown by the fact that, in the same year, nearly 500,000 tons of ammonium sulphate were produced in Germany from a much smaller output of coal, containing on the average a somewhat smaller percentage of nitrogen than is found in British coals.

The distillation of coal at comparatively low temperatures (400° to 600° C.) constitutes another important means, as yet insufficiently explored by the chemist, of realising the possibilities of coal as a source of motor spirit and fuel oils for marine purposes.

But if, as Jevons insisted, the more economy that is practised in the use of coal, the more will its consumption increase, we cannot expect to prolong the duration of our national coal reserves by the more scientific use of them. The object of any national movement in the direction of fuel economy should be to ensure our coal being utilised, in the national interest, to the best and fullest advantage by every class of consumer. True economy, it has been said, lies not so much in using sparingly as in using well.

It is impossible to give any exact figures for the amount of coal used for various purposes in this Kingdom, and although estimates have, at one time or another, been made, they cannot be regarded at best as more than very approximate. In 1903 Mr. (now Sir) George Beilby made such an estimate for the Second Royal Commission on Coal Supplies, and, assuming that the same relative proportion between the various uses of coal still hold good, a further estimate for the year 1913 may be given, as follows :—

ANALYSIS OF THE USES OF COAL IN THE UNITED KINGDOM

		1903. Mill. Tons.	1913. Mill. Tons.
(1)	Mines and Factories	71·0	80·0
(2)	⌠Iron and Steel Industries . . .	28·0	30·0
	⌡Other Metallurgical Industries . .	1·0	2·0
(3)	Brickwork, Potteries, Glass, and Chemical Works	5·0	6·0
(4)	Gas Works	15·0	18·0
(5)	Railways	13·0	15·0
(6)	Coasting Vessels	2·0	2·0
(7)	Domestic Purposes	32·0	36·0
	Total	167·0	189·0
	Total for Power Purposes . .	52·0	80·0

According to the above estimate, four-fifths of the coal annually consumed in the Kingdom can be accounted for under three heads, namely, (1) approximately 40 per cent. is used for generating mechanical power; (2) another 20 per cent. is carbonised either in gas works or for the manufacture of metallurgical coke; (3) whilst about 20 per cent. is used for domestic purposes.

The foregoing may be compared with the following official figures for the year 1907 (Census of Production) :—

			1907 Mill. Tons
Total Coal raised			266·6
Less—			
	(1) Coal Exported	66·6	
	(2) Bunker Coal for Foreign-going Vessels	18·6	
			85·2
	Total		181·4
(1)	Used in operating the Mines		16·7
(2)	Carbonised in Gas Works		15·4
(3)	For Blast Furnace Coke, etc.		21·1
(4)	Other Iron, Steel, Engineering and Shipbuilding Industries		15·8
(5)	Other Manufacturing Purposes		38·7
(6)	Locomotive Coal on Railways . . .		12·9
(7)	Coastwise Bunkers		2·2
(8)	All Other Purposes		61·5

That up to the present we have, as a nation, been wasteful and improvident in both getting and utilising coal cannot well be disputed. Under the present individualistic conditions, a vast quantity of usable coal is left behind in the mine simply because it does not pay to bring it to the surface. The Committee appointed by the British Association in 1915 for the Investigation of Fuel Economy and the proper Utilisation of Coal, in drawing special attention to the national importance of checking this waste by finding out in what ways the less valuable grades of coal can be turned to good account, expressed the opinion that " much of the coal now left behind in the mines ought to be converted into useful forms of energy and products for public purposes, and one of the most important aspects of the fuel economy problem in Great Britain is the devising and organising of means for making it possible to raise the hitherto wasted coal at an economic advantage." [1]

In regard to the realisable margins of economy in the coal actually consumed in the Kingdom, the Second Royal Commission on Coal Supplies reported in 1905 that the possible saving in our then annual coal consumption of 167 million tons amounted to between 40 and 60 million tons; and in 1916, the British Association Fuel Economy Committee expressed the view that " notwithstanding the improved apparatus which has been put into use in the best factories throughout the country during the last ten years, the average result obtained for the country as a whole still lags behind the best obtainable to-day in as great a proportion as it did in 1905." [2]

In July 1916 the then Prime Minister (Mr. Asquith) appointed a Sub-Committee of the Reconstruction Committee, under the chairmanship of Lord Haldane, to consider the Conservation of our Coal Supplies.[3] And in February 1917, the Committee of the Privy Council for Scientific and Industrial Research, on the recommendation of their Advisory Council, who had conferred on the matter both with Lord Haldane's Committee and with the British Association Committee, decided to establish a permanent Fuel Research Board to organise and carry out investigations into fuel problems. This step may be welcomed as a sign that the Government has at length realised its responsibilities to the nation in regard to the coal question.

[1] *British Association Reports*, 1916 (Newcastle-on-Tyne), p. 192.
[2] *Ibid.*, p. 193.
[3] The Report of Lord Haldane's Sub-Committee (now known as the Coal Conservation Committee of the Ministry of Reconstruction) will shortly be published (1918).

The Cost of getting Coal in the United Kingdom and Pit-head Prices

In connection with this all-important question a very informing paper, entitled " The Economics of Coal Production," was read before the London Section of the Society of Chemical Industry on December 4, 1917, by Professor Henry Louis of Newcastle-on-Tyne, from which the following details have been taken.

It is first of all pointed out that the cost of coal at the pit-mouth is made up of five items, namely :—(1) the value of it in its unsevered condition in the seam, which is covered by the term " royalty " ; (2) the wages paid to the men engaged in its extraction; (3) the costs of various materials necessarily employed in connection with the working of a mine; (4) the cost of administration and other incidental expenses; and (5) the profit to the colliery proprietor, including the interest upon the capital employed.

According to official figures, the average cost of coal at the pit-head in the United Kingdom for the year 1913 was 10s. 1½d., and Professor Louis has calculated that this cost would on the average be distributed as follows :—

TABLE IXʙ

	Per Cent.	s.	d.
1. Royalty . . .— . .	5·35	0	6·5
2. Wages	62·55	6	4
3. Materials	16·45	1	8
4. Administration . . .	7·00	0	8·5
5. Interest and Profit . .	8·65	0	10·5
	100·00	10	1·5

It would thus appear that labour is by far the principal item in the total cost of coal production. The item of wages may be subdivided into three parts, namely, those paid to (a) hewers, who actually get the coal and receive practically half of them ; (b) other underground workers, who receive rather more than 30 per cent.; and (c) surface workers, who receive nearly one-fifth of them. It is a regrettable, and perhaps also a significant, fact that the average amount of coal produced per worker em-

ployed at the mines of Great Britain has been steadily decreasing during the past thirty years, as the following figures show :—

Decade.	Average Annual Output per Worker. Tons.
1883–92	320
1893–1902	295
1903–12	280

These figures, as Professor Louis remarks, " may be to some little extent accounted for by the fact that the thicker and more easily worked seams are gradually becoming exhausted, and the production from the thinner seams is gradually forming an increasing proportion of the total, but the diminution in efficiency due to this cause should be far more than counter-balanced by the increased use of underground machinery, especially of coal cutters and face conveyors, which greatly multiply the working capacity of the hewer."[1] And he considers that an increase in the output per man employed is imperative in the interests of the nation at large.

Between the pit-head and the consumer there intervenes the railway or steamship company and the various merchants or middlemen. Professor Louis estimates that the average distance travelled by coal which comes into London by rail is something like 130 miles, and that the average freight is somewhere about 9s. per ton. The average cost of bringing coal from the collieries in Durham by sea to the London market (including discharging at the wharves) in 1913 is put at 5s. 7d. per ton, and the average price of sea-borne coal in barges in the Thames at 21s. per ton. There is no doubt room for some economies here, for not only might the cost of transit by rail be cheapened, but it is unquestionable that the whole system of distribution at present in vogue might with advantage be simplified and cheapened.

The effect of the war upon the annual outputs and pit-head prices of coal in Great Britain is shown from the following official figures for the three years 1914–16 inclusive :—

Year.	Total Output-Million Tons.	Average Price at Pit-head. s. d.
1914	265·6 .	. 9 11·8
1915	253·2 .	. 12 5·6
1916	256·3 .	. 15 7·25

[1] *Journ. Soc. Chem. Industry,* **38,** 23, 1209.

CHAPTER II

THE ORIGIN AND FORMATION OF COAL

To understand the nature and composition of coal, as well as the different classes and varieties of it met with in our coalfields, we must consider the kind of materials from which it originated, as well as the conditions under which these materials were, in the fulness of geological time, gradually transformed into the coal seams as we now know them. Our knowledge of these matters, of course, necessarily suffers from the recognised imperfections in the geological record, and, therefore, the scientific imagination has often to fill in gaps where precise information or definition is wanting. Therefore, while we are tolerably certain of the vegetable origin of coal, any view or theory concerning the factors and conditions operative at the various successive stages in the subsequent long transformation process is necessarily somewhat speculative and subject to reservation. Certain well-attested features which stand out prominently in the record may, however, be regarded as more or less common ground.

Although many classes and varieties of coal occur in Nature, all of them represent some stage or product of the primary decomposition and subsequent transformation, under the combined influence of slowly increasing pressure, and possibly also of temperature, of the vegetable *débris* of primæval forests and swamps. This process has gone on in several of the great geological periods, and, so far as its early stages are concerned, is being repeated to-day under somewhat different conditions in our modern peat bogs and deltas, where enormous masses of water-logged vegetable *débris* are decomposing under bacterial influence.

A consideration of the geographical distribution of the world's principal coalfields shows that all the important fields adjacent to the North Atlantic and Arctic areas (which include nearly all the fields of North-West Europe and in the eastern part of North

23

America) originated in what geologists call the Carboniferous Period of the Primary Era; while what may be termed the " Indian Ocean " group of coalfields (which include those of China, India, Australia, and South Africa) originated in the somewhat later Permo-Carboniferous Period. Mesozoic coals are found in the interiors of North America and Asia (intra-continental group); while Tertiary coals are chiefly found in what may be termed the Pacific borderland (west of North America, Japan, and New Zealand), as well as in regions bordering on the Gulf of Mexico and the Mediterranean.

The great coalfields of the Carboniferous System originated in a new monster vegetation flourishing in a rich virgin soil, with an equable if not subtropical climate, and large areas of shallow sea, to which great quantities of sediment were borne from rivers. Vegetable tissue has in all ages, then as now, been built up by the action of chlorophyll under the influence of sunlight, stimulated by minute quantities of mineral salts drawn in by the roots, upon atmospheric carbon dioxide and moisture, which action sets up a complex series of chemical changes, with the intermediate formation of sugars and starches, ultimately resulting in the production of celluloses and ligno-celluloses, as the basis of all woody tissue.

Celluloses, which form the structural basis of the vegetable world, comprise a class of carbohydrates of the general formula $nC_6H_{10}O_5$ (C = 44·4, H = 6·2, and O = 49·4 per cent.). Taking $C_6H_{10}O_5$ as the simple " constituent group " of cellulose, in which there are grounds for believing that four out of the five oxygen atoms react as OH groups, it is probable that the celluloses are aggregates of such constituent groups in a special molecular configuration of cyclic character. The process of " lignification " in the plant cell is, according to Cross and Bevan, characterised by the formation of groups of the general form—

$$O:C\underset{\underset{(OH)_2}{C}\!-\!-\!-\!-\underset{(OH)_2}{C}}{\overset{\overset{H}{C}\!=\!=\!=\!=\overset{H}{C}}{}}CH_2$$

Ligno-celluloses may be regarded as built up primarily of (1) a *lignone* portion, consisting of a reactive " keto R. hexene group " and a " furfurose " (*i. e.* furfural-yielding) complex; and (2) a *cellulose* portion, which, however, is not homogeneous but re-

solvable into a more resistant and a less resistant group, as follows :—

Ligno-Celluloses

Celluloses — Lignone

α and β — Furfurose Keto R.

Hexene Group.

In general, and for statistical purposes, it may be considered that the process of " lignification " is essentially a dehydration of cellulose—

$$2C_6H_{10}O_5 = C_{12}H_{18}O_9 + H_2O,$$

and that, under normal conditions of growth, the ligno-celluloses are further progressively dehydrated.

Schultze and Schuppe have investigated the composition of wood tissue, and the latter expresses it as an aggregate of cellulose and a lignone complex $C_{19}H_{18}O_8$, thus—

$$5C_6H_{10}O_5, C_{19}H_{18}O_8,$$

from which it would appear that whilst wood tissue is similarly constituted to a typical ligno-cellulose, it contains a higher proportion of lignone and a lower proportion of cellulose.[1]

The percentage composition of these various substances may be summarised as follows :—

		C.	H.	O.
Celluloses	$C_6H_{10}O_5$	44·40	6·20	49·40
Ligno-celluloses	$C_{12}H_{18}O_9$	47·05	5·88	47·05
Wood tissue	$5C_6H_{10}O_5, C_{19}H_{18}O_8$	49·66	5·74	44·60
Wood		49·0–50·4	6·0–6·25	45·0

The vegetable forms which flourished in the Carboniferous Period were of simpler structure, but of much greater size than those which are predominant to-day—gigantic ferns, club mosses, horsetails, and forms intermediate between ferns and cycads— and it is demonstrable that in certain cases (*e. g.* the Moira seam near Loughborough in Leicestershire) entire beds of coal have been formed from the spores of such plants.

Much controversy has waged round the question whether or not coal formation has occurred upon the actual site of the original vegetable growth, and in certain cases the question can

See Cross and Bevan's *Cellulose*, 1916 edition.

be answered affirmatively. The necessary conditions in such a case would be a dense forest growth in swampy areas (estuarine or in great inland swamps), together with such oscillations in level as are known to have occurred during the Carboniferous Period. The rotting vegetable *débris* would, during a period of subsidence, be overlaid with layers of water-deposited sands and clays, which on re-elevation, would provide a suitable soil for renewed vegetable growth. Proof of such conditions is afforded by the occurrence of " under-clays " or fire-clays with fossil roots (stigmaria) below the coal seams in certain areas (*e. g.* the Yorkshire coalfield). Other coalfields, however, undoubtedly owe their origin to enormous masses of vegetable *débris* brought down from higher levels and deposited either in deltas or in land-locked seas or lakes. Such fields show no fossil roots in the under-strata, and in some cases fossil remains of aqueous and marine life are found immediately above and below the coal seams.

Imagine then such vegetable *débris*—whether in the actual site of growth or after transportation by river to some other place—decaying under shallow water or other covering sufficient to protect it from direct atmospheric action. Bacterial action (aërobic fungi and anaërobic organisms, the relative influences of which depend on the varying water level in the bog and the formation of ulmic acid) would set in, much as in existing peat bogs, with evolution of enormous quantities of marsh gas (methane) and carbon dioxide. Thus M. Renault, from an extensive study of peat formation, represents the transformation from cellulose to a bituminous coal by the equation—

$$4C_6H_{10}O_5 = C_9H_6O + 7CH_4 + 8CO_2 + 3H_2O.$$

A substance of the formula C_9H_6O would contain $C = 83.1$, $H = 4.6$, $O = 12.3$, which approximates to the composition of an average bituminous coal.

Such primæval swamp forests would, with gradual fall in level, become submerged to a greater extent, and be covered with water-borne *débris* and mineral matter, which, on subsequent re-elevation, would be ready for a fresh vegetable growth. Repetitions of the process—*i. e.* submersions alternating with re-elevations or filling up—would produce several distinct deposits of decomposed vegetable matter separated by mineral matter of sedimentary origin, which would ultimately give rise to the various separate seams of coal found in our modern coalfields.

Finally, such successive deposits would, in the course of geological time, become buried as a whole under newer mineral strata, whose accumulation would " blanket " the incipient coal measures, causing a gradual increase in both temperature and pressure. Moreover, it is known that, during the later stages of the Carboniferous Period, the " blanketed " strata were subjected to intense disturbances, the effect of which would be to cause the present distribution and local destruction by denudation of the measures. These causes, operating successively, would sufficiently account for the transformation of the original decaying woody tissue into bituminous coal and anthracite. Moreover, such changes would necessarily involve both great shrinkage in bulk and loss of weight in the original vegetable *débris;* thus it has been demonstrated that the existing coal-fields represent about 20 to 28 per cent. only of the original weight and one-tenth only of the bulk, of the original woody tissue from which they were formed.

As might be expected from its origin and mode of formation, coal is by no means uniform in character or composition. Differences in respect both of the character of the original organic *débris,* and of the physical conditions under which it was deposited and subsequently transformed in the coalfields, have contributed to produce the innumerable grades and varieties of coal, ranging from highly bituminous gas coals to anthracites, such as are found in British coalfields. Indeed coal is a generic term which includes a great many characteristic individual types and intermediate gradations, and it is the business of the chemist to define these and to discover how each may be utilised to the best advantage.

British Coalfields

The succession of strata in the Carboniferous System, and the occurrence of the Coal Measures therein, is so well represented by their development in Great Britain that it will suffice for the purpose of this general review if, for the present, we confine our attention to the predominating features of our own coalfields. A glance at a geological map of Great Britain will show that practically all the areas in which the Carboniferous System comes to the surface lie, in England, between two parallel lines, the one drawn through Hull and Portland and the other through Berwick and Pembroke, and in Scotland between similar parallels, the one drawn through Dunbar and Stranraer and the other through

Perth and Dumbarton. In all the areas to the north and north-west of the said two strips of country (*i. e.* the Scottish Highlands and the Borderland, Cumberland (except the north-west part) and Westmoreland, Central Wales, and also Devon and Cornwall) the surface strata are nearly all of pre-Carboniferous origin, and in such areas no Coal Measures are found. On the other hand, in the great area to the south-east of the Hull to Portland line, the Carboniferous strata are now overlain by later Mesozoic and Tertiary strata, and it is probable that coal-bearing measures lie deep underground in parts at least of this area.

The rocks of the Carboniferous System fall into three main divisions, namely :—(1) the *Carboniferous or Mountain Limestone*, undoubtedly of marine origin, resting on the Old Red Sandstone (Devonian) or older rocks, and attaining to a maximum thickness of 2000 feet in South-West England, in South Wales, and in Derbyshire. The upper portion of this Formation consists of shales and sandstones (*e. g.* the Yoredale Rocks in the borderland between Yorkshire and Lancashire). The thickness of the limestone beds diminishes and that of the shales increases northwards, until in Scotland they develop into a sequence of coal-bearing strata known as the Edge Coal series ; (2) the *Millstone Grit*—a series of coarse sandstones and shales containing towards the north a few thin coal seams ; and (3) the *Coal Measures* proper, which consist of alternations of shales and sandstones together with the main coal seams, and in some localities nodular deposits of clay iron-stone (ferrous carbonate), making altogether a thickness of many thousands of feet (12,000 to 14,000 at their maximum development). These measures naturally fall into three groups, namely (*a*) the *Lower*, (*b*) the *Middle*, and (*c*) the *Upper Measures*, all of which contain workable coal seams. The more valuable seams are as a rule in the *Middle Measures*. The uppermost strata consist of clays, marls, and sandstones similar in character to those of the Permian System which usually lie immediately above the Carboniferous Series.

It is probable that nearly the whole of Great Britain south of the Scottish Highlands (with the exception of Cumberland and Westmoreland, Central Wales and its eastward extension, and Cornwall), was in Carboniferous times laid down with continuous sheets of vegetable *débris*, which were subsequently transformed into coal seams, and that the discontinuities now observable in the coal areas were caused by post-Carboniferous disturbances, and subsequent denudations. Thus, for example, there is little

doubt but that the now separate coalfields of Lancashire and Yorkshire were originally laid down as one sheet of coal measures, the continuity of which was subsequently broken by the elevation of the Pennines followed by extensive denudations.

In the actual coalfields, the coal occurs in a number of more or less regular layers or seams separated by bands of mineral matter; these seams vary in thickness from a few inches to several feet and may often be followed continuously for a considerable distance without material change in character, as for example, in the celebrated " Barnsley Seam " of the Yorkshire coalfield. Sometimes, however, the continuity of the seams in a coalfield is repeatedly interrupted by faults, as for instance, in the North Staffordshire and Lancashire coalfields, both of which are much faulted. The thickest seam in this country was the celebrated Ten-Yard Seam in the South Staffordshire coalfield, which in the neighbourhood of Dudley formed one almost continuous mass of from 30 to 40 feet in thickness, but further north it splits up into eight seams, which, with the intervening shales and sandstones, attain a total thickness of 400 feet in the northern end of the field (Cannock Chase).

The coalfields of Great Britain may be grouped geographically into three principal areas, each having distinctive features, namely : (*a*) *Southern* (South Wales, Forest of Dean, Bristol, and Kent); (*b*) *Central* (Lancashire and North Wales; Yorkshire, Derbyshire, and Nottinghamshire; Leicestershire; Staffordshire, and Warwickshire); and (*c*) *Northern* (Scotland, Northumberland and Durham, and Cumberland). This grouping is that adopted by Dr. Walcot Gibson in his well-known book on *The Geology of Coal Mining*, to which the reader is referred for more detailed information than it is possible to give in this chapter. The more important fields are as follows :—

(1) *South Wales* (Monmouth, Glamorgan, Carmarthen, and Pembrokeshire), covering an area of about 850 square miles, of which 150 are under the sea, with seams from 1 to 12 feet (average 2·5 to 3·0 feet) thick, and yielding all classes of coal, namely, bituminous (31 per cent.) steam coals (47 per cent.), and anthracites (22 per cent.).—The Carboniferous strata lie in an elongated basin which is almost completely surrounded by older formations, and complicated towards the south by an anticlinal fold running east and west. The basin is much faulted, and the rivers have cut a series of deep valleys along which the coal seams crop out. Speaking generally, and for corresponding depths below the

surface, there is a gradual transition in the character of the coal from the coking varieties in the east and south-east, through the first-class steam coals of the centre, to the semi-anthracites and anthracites in the west and north-west. The supposition that the anthracitisation has been due to the seams having been subjected to an increasing earth pressure has been questioned by Strahan and Pollard (*Memoirs of the Geological Survey*, 1908) who, from the fact that the ash content of the anthracites is invariably much lower than that of the bituminous seams which are their continuation, suggest that the difference between the two classes of coal may be due to some original disparity in the vegetable *débris* from which they have been derived. In the eastern and south-eastern sections of the field, the upper and middle parts of the measures are chiefly worked, yielding good coking and bituminous coals; in the central sections, the middle parts of the measures (the Pennant Series) predominate, whilst in the extreme west the seams occur in lower parts of the measures only. The percentage composition of the more important classes of coals usually falls within the following limits :—

TABLE X

Class.	C.	H.	O. and N.	S.	Ash.	Volatiles
Anthracites	91·0—93·0	3·0—3·7	1·9—3·5	0·7—1·0	0·7—1·7	5·0—6·0
Steam . .	85·0—90·0	4·0—4·7	3·5—4·5	0·7—1·5	2·0—3·3	7·0—20·0
Bituminous (coking) .	80·0—95·0	5·0—5·5	—	—	—	20·0—25·0

(2) *Forest of Dean.*—A small field (34 square miles) forming a complete basin between the Wye and Severn valleys, and containing thirty-one seams, of which only sixteen exceed 1 foot in thickness. The total thickness of the measures is 2765 feet, and they are completely girdled by older formations. The coals resemble in character those found in the eastern section of the South Wales field; the upper and middle parts of the measures yield excellent gas and house coals, whilst the lower parts, which, however, are difficult to work, owing to accumulations of water therein, contain good steam coals.

(3) *Bristol* (Somerset and Gloucester). — The coalfields of this region form a number of basins of varying areas (total = 2385 square miles), the edges and outlines of which are masked by newer rocks, so that there are five or six detached " exposed "

fields and a considerable intervening area of " concealed " coal-fields. They may be divided into three groups, namely : (*a*) *Southern*, with twelve workable seams, having a total thickness of 23 feet, (*b*) *Central*, with thirty-five seams, of average total thickness of 65 feet, and (*c*) *Northern*, with seven seams, having an average total thickness of 10 feet. The measures are divided into upper and lower portions by a sandstone bed, some 2000 to 2500 feet in thickness, known as the Pennant Rock, which, although it contains locally some thin coal seams, is practically unproductive. The upper parts of the measures (the Radstock and Farringdon Series) yield bituminous house and gas coals; the lower part (Kingswood and Vobster Series) yield both house and coking coals. The combined annual outputs of the various fields is comparatively small, and is almost all consumed locally.

(4) *Kent*.—This field, which was first actually proved by an experimental boring at Shakespeare's Cliff, Dover, begun in 1886, in which Coal Measures were encountered at a depth of 1100 feet below the surface, is generally considered to be a west-ward prolongation of one of the basins of the N. French and Belgian coalfields (Liége, Calais, etc.). The coals are similar to those of the Somerset field and are all bituminous in character.

(5) *Staffordshire*, divided into (*a*) North Staffordshire (100 square miles), and (*b*) South Staffordshire (150 square miles).—In the *North Staffordshire*, or *Potteries*, area the Carboniferous sequence (*i. e.* of upper, middle, and lower coal-bearing measures underlaid by the Millstone Grit and Carboniferous Limestone) is complete although much broken by faults. With the exception, however, of two seams, which have been worked along the eastern boundary in the lower portions of the measures, all the principal workable seams (fourteen in number) occur in the middle portions of the measures and most of them average 6 feet in thickness. They yield good coking as well as gas, house, and furnace coals. Some of the seams are worked in conjunction with the Black Band ironstone found in the Coal Measures in this area.

The *South Staffordshire* area is divided by a fault into a northern and a southern section. The northern section contains some fourteen workable seams in the middle portions of the measures; towards the south the measures thin out considerably in respect of total thickness, and a number of the individual seams are found to have converged, finally forming the once famous Dudley Ten-Yard Seam. Neither Millstone Grit nor Carbonifer Limestone occur below the coal-bearing measures. The

obtained include both gas, house, and furnace varieties; but neither "steam" nor "hard coking" coals are found. In places the coals have been damaged by igneous intrusions such as that of Rowley Regis.

(6) *Warwickshire.*—This coalfield comprises an area of about 60 square miles in the North and North-East of Warwickshire, between Tamworth, Nuneaton, and Coventry, in which the sequence of the Carboniferous rocks is the same as that found in South Staffordshire (*q.v.*). The total thickness of the productive measures is greatest in the north, where also the individual seams are most numerous; towards the south the measures get thinner and some of the separate seams converge to form much thicker ones, as in South Staffordshire. The coals are generally "oxidised" and, therefore, non-coking, with a high percentage of "volatiles."

(7) *Leicestershire.*—The "exposed" coalfield in North-West Leicestershire covers an area of about 30 square miles, beyond and around which, however, the Coal Measures continue for another 54 square miles as a "concealed" field under later Triassic rocks. Unlike the coal-bearing measures in South Staffordshire and Warwickshire, those of Leicestershire are underlaid by Millstone Grit and Carboniferous Limestone. The coals are free-burning and similar in type to those of Warwickshire.

(8) *Yorkshire, Derbyshire, and Nottinghamshire.*—This, perhaps the largest of all our British coalfields, comprises an area of 808 square miles of "exposed" and 1328 square miles of "concealed" measures. The "exposed" measures stretch in an unbroken line for a distance of 65 miles from Leeds in the north to Nottingham in the south, the breadth being about 23 miles at its maximum towards the north, and about 10 miles at its minimum near the southern end. Throughout the area the sequence of the Carboniferous Formation is complete, the coal-bearing measures being underlaid by the Millstone Grit and the Carboniferous Limestone, and they have nowhere been affected by igneous intrusions. The upper measures have been proved in boring operations under the New Red Sandstones, but they are everywhere unproductive of coal. The chief workable seams nearly all belong to the middle parts, although one or two important seams occur in the lower parts of the measures. The coals are highly bituminous, with from 25 to 45 per cent. of "volatiles," and, although varied in character, are nearly all of high-grade quality. Some of the best English house and gas coals, as well as good coking and steam coals are derived from the different

seams in this field. Speaking generally, most of the seams found north of Sheffield have marked coking properties, although none of the coals yields so good or hard a metallurgical coke as do the famous Durham coking coals. South of Sheffield the coking properties of the coals diminish, but their gas-making qualities improve. In the southern part of the field (Notts) the seams have apparently been " oxidised," and although the coals obtained from them yield a large amount of gas, they are non-coking. The celebrated Barnsley Bed yields a hard " steam " coal which is a good locomotive and marine boiler fuel, whilst the well-known Silkstone Beds are unsurpassed for their gas and house coals.

(9) *Lancashire.*—An irregular area, much faulted and broken by an E.-W. anticline, extending from Burnley in the north to Ashton-on-Lyne on the south (with a long tongue projecting southwards through Stockport to Macclesfield), and from Oldham in the east to St. Helens in the west. The total " exposed " area is about 500 square miles. The principal seams in the southern and central areas of the field are all found in the middle parts of the measures, the upper parts nowhere containing workable seams. The seams in the lower part of the measures become important in the northern districts in the neighbourhood of Accrington and Burnley. The coals got from the seams in the middle parts of the measures belong almost exclusively to the " gas-coal " class and generally contain from 30 to 35 per cent. of " volatiles." Several of these seams, notably the Yard Mine, Arley, and Trencherbone, yield a fairly good coking coal. The famous " Mountain Mine " seams occurring in the lower parts of the measures (Burnley and Accrington) yield coals containing from 26 to 27 per cent. of " volatiles," which produce a coke almost, if not quite, equal to the best Durham coke.

(10) *North Wales* (Flintshire and Denbighshire).—This field (area = 103 square miles) is similar in character to the Lancashire field. All the workable seams, however, are in the middle parts of the measures. The coals are similar in character to those occurring in the southern and central portions of the field; they contain from 33 to 35 per cent. of " volatiles," and yield a fair quality of coke.

(11) *Durham and Northumberland.* In the great Northern region of which Durham and Northumberland form an important part, there is a development of coal seams (more strongly marked the farther north) in Lower Carboniferous Rocks, the equivalent

D   33

of the Carboniferous Limestone, a feature which is absent in the Midland and Southern fields. The total area of the Durham and Northumberland field is about 800 square miles. In the Limestone Series there are a few workable seams which increase in number and thickness from south to north, but in the main part of the field the coal occurs chiefly in the middle parts of the measure. The southern and western districts of Durham produce, perhaps, the finest coking coals in the world, containing from 22 to 28 per cent. of " volatiles," and comparatively small amounts of sulphur or ash. The central district (Sunderland to Newcastle) produces fine qualities of gas and house coals. The Northumberland seams are for the most part " oxidised "; they contain a rather large amount of moisture and are non-coking. They are largely used for steam coals, and they are excellent as " gas-producer " coals.

(12) *Cumberland or Whitehaven Coalfield.*—The area of this field is 150 square miles, and the character of the coals is in general similar to those obtained from the northern districts of Durham.

(13) *Scotland.*—The Scottish coalfields extend from Fifeshire on the east, across a belt between the Forth and Clyde, thence westwards into Lanarkshire and Ayrshire, with an isolated small area in Midlothian. The upper parts of the measures are well developed throughout the area; the middle measures attain a thickness of from 800 to 1500 feet. Below the latter is the " edge-coal " group in the Carboniferous Limestone Series, highly inclined at its outcrop (Fifeshire, Midlothian), and containing bands of cannel. Generally speaking, the coals are bituminous, with a high percentage of " volatiles." The best coking varieties are found in the neighbourhood of Glasgow, and the coking seams stretch as far eastward as the Firth of Forth. The Ayrshire coals are chiefly non-coking, and are excellent as " gas-producer " coals. In Fifeshire the seams in the Carboniferous Limestone in the neighbourhood of Dunfermline yield first-class steam and house coals. The Scottish coalfields have been subjected to igneous intrusions to an extent rarely met with in England, and, consequently, some of the bituminous seams have been locally converted into steam coals and anthracitic varieties.

CHAPTER III

THE CHEMICAL COMPOSITION OF COAL

A. INTRODUCTION—OCCLUDED GAS—MOISTURE—ASH—COAL WASHING —SALTS IN COAL

FROM what is known of their origin and mode of formation it may in general be anticipated that all coals, whatever their geological age, will contain (1) various combustible organic compounds, complex in structure and of high molecular weight, representing the degradation or transformation products of the ligno-celluloses, resinous matters, and proteids in the vegetable *débris* from which they were originally derived; and (2) variable amounts of mineral matter, which give rise to the " ash " remaining when the coal is burnt, and which represent partly the small amount of mineral matter in the original vegetation, or the soil in which it grew, and partly also other associated mineral matters either deposited contemporaneously with the coalfield or subsequently introduced by infiltrations.

The various organic bodies, which together form what is sometimes termed the " coal substance," are all compounded chiefly of the elements carbon, hydrogen, oxygen, nitrogen, and sulphur, the relative proportions of which may be determined with considerable accuracy by the usual methods employed for the analysis of organic compounds generally. But the ascertainment of the nature of the various complexes which make up the coal substance, and still more so of the relative proportions in which they are present in any particular coal, is a problem beset with such difficulties that its solution has hitherto proved well-nigh beyond achievement by any present known method of chemical attack.

OCCLUDED GAS

It has been long recognised that coals, like most other non-vitreous solids, have the power of " occluding " gases, and as during the process of their formation from the original vegetable *débris* vast quantities of gases were evolved, it is to be expected

35

that coal as it occurs in the seam will contain " occluded " gases. Any gas so occluded in freshly-won coal, which as a rule does not exceed 5 c.cs. per gram, may be withdrawn by continuous exhaustion of the finely divided coal either at the ordinary temperature or at 100° C. The composition of such gas varies considerably, but carbon dioxide, methane, or nitrogen are usually found therein. It has been suggested that two active processes are simultaneously set up as soon as the coal is removed from the seam, namely (1) an exudation of methane and other saturated hydrocarbons, and (2) an absorption of air causing oxidations within the coal substance. These processes, operating independently but concurrently, would, it is claimed, account for the observed variation in the composition of the gas withdrawn from samples of coal of different origin.[1]

The subject has been investigated at different times by E. von Meyer in Germany, by W. J. Thomas, Bedson, McConnell, Trobridge, and R. V. Wheeler in England, and by S. W. Parr in America. The following typical figures are taken from the result of an extensive investigation by W. J. Thomas in 1875 upon the gases occluded in British coal :—[2]

TABLE XI

Coal.	c.cs. of Gas per Gram.	Percentage Composition of Gas.			
		CO_2.	CH_4.	N_2.	O_2.
Bituminous . . .	0·559	36·42	0·00	62·78	0·80
„ . . .	0·551	5·44	63·76	29·75	1·05
Semi-bituminous . .	0·736	12·34	72·51	14·51	0·64
Steam	2·501	13·21	81·64	4·66	0·49
„	1·474	18·90	67·47	12·61	1·02
„	5·555	2·65	93·13	4·25	—

The following analyses by P. P. Bedson and R. V. Wheeler indicate, as might be supposed, that ethane, as well as methane, is occluded in coal dusts, a circumstance to which attention has also been drawn in the Report of the Austrian Fire Damp Commission. R. V. Wheeler has found measurable quantities of carbon monoxide also in the occluded gases.

[1] S. W. Parr and Perry Barker, " Occluded Gases in Coal," *University of Illinois Bulletin*, No. 32 (1909).
[2] *Journ. Chem. Soc.* XIII. (1875), p. 793.

	Durham Coal Hutton Seam (Bedson).	Lancashire Coal Lower Mountain Mine (R. V. Wheeler).
Total gas in c.cs. per gram	1·6	1·375
CO_2, (H_2S and NH_3)	4·35	1·00
CO	—	2·10
C_2H_4	—	0·40
C_2H_6	6·65	8·10
CH_4	71·15	80·35
O_2	2·80	0·40
N_2	15·05	7·65
	100·0	100·00

MOISTURE IN COAL

Coal, when freshly mined, often contains much water (" pit water "). Most of it is lost, more or less rapidly according to the hygrometric conditions of the atmosphere and other circumstances, by a natural process of " air drying." The remainder is completely lost when the finely divided coal is maintained for a short time at 105° C. It is, however, to be borne in mind that the amount of water present in a coal at any moment is liable to variation, according to " atmospheric " conditions, and the circumstances of its storage. Thus a coal which has undergone a considerable amount of " air drying " in dry summer weather will slowly re-absorb moisture if exposed to a damp atmosphere. Hence the moisture content of a stored coal tends to increase in *damp* and to decrease in *dry* weather, and does not remain quite constant for long together.

Such variations led the chemists who were responsible for organising the chemical work in connection with the investigation of Canadian Coals, recently carried out under the auspices of the Dominion Department of Mines, to adopt, as a standard of air drying which should be independent of variations in atmospheric conditions, the plan of always drying a crushed sample of coal until its weight became constant in a current of air which had been drawn at the laboratory temperature through a solution of calcium chloride of sp. gr. 1·30. Since the vapour pressure of such a solution is approximately 0·58 that of pur water, and is not materially affected by small changes of ter perature in the neighbourhood of the usual laboratory temper

ture, the method would produce a result corresponding to " air drying " at such temperature in an atmosphere of 58 per cent. humidity.[1] But inasmuch as all bituminous coals are liable, some more than others, to absorb oxygen slowly on exposure to air, it would perhaps be preferable to carry out such a process in a current of nitrogen or other inert gas, where considerable accuracy is required.

Messrs. Porter and Ralston,[2] of the U.S. Bureau of Mines, have recently published a paper on " Some Properties of Water in Coal," in which it is suggested that a discrimination should be made between what they term " free " water and " inherent " or " combined " water in coals. They also infer that the inherent water has a sub-normal vapour pressure, indicating the presence of variable proportions of colloidal matter in coals. This, however, is a subject which requires further investigation, especially in regard to lignitic coals, before any definite conclusions can be formed.

MINERAL MATTER (ASH) IN COAL

A *dry* coal always contains a variable amount of mineral matter associated with the coal substance itself and which gives rise to the ash when the coal is burnt. This mineral matter varies greatly in amount, colour, composition, and fusibility, and if either unduly large in amount or highly pyritic in character may affect detrimentally the commercial value of a coal.

A distinction must be drawn between the heavier mineral matter (" dirt "), such as pyrites (sp. gr. 5·0), shale (sp. gr. 2·5), and gypsum (sp. gr. 2·3), often irregularly mixed with freshly mined small coal (sp. gr. 1·2 to 1·3), and from which a separation can be effected either by hand picking or by mechanical washing (*q. v.*) and what is sometimes termed true or " fixed " ash of the coal, which is disseminated more or less uniformly throughout its entire mass and cannot be so removed. The heavier " dirt " represents either sedimentary mineral matter (*e. g.* shale) which was deposited contemporaneously with the coalfield, and which forms the " partings " between the various seams, or mineral matter (*e. g.* FeS_2) which may have been introduced by infiltrations of various solutions after the coal was laid.

The " fixed ash " of a coal varies considerably both in amount

---

[1] *Reports on an Investigation of the Coals of Canada*, Vol. II. (1912), p. 131.
[2] *Technical Paper* 113, U.S. Bureau of Mines.

and composition according to the locality of the seam from whence it is derived. Also, variations may sometimes occur both in the amount and character of the " ash content " along a particular seam. Such differences are usually gradual so long as they relate to the same " horizon " or axis of the seam, but they may be abrupt in a vertical direction in the seam, especially when the successive layers of the coal in it show marked differences in texture (*e. g.* the Barnsley Seam, South Yorkshire Coalfield). The investigation of the variations in the ash content of a particular coal seam, both along its main axis and also in directions vertical thereto at different selected places, may, therefore, be a very important matter in regard to the chemical survey of the seam.

No rule concerning the fixed mineral matter can be stated. It rarely amounts to less than 2 per cent. of the weight of the coal, and it may occasionally exceed 20 per cent. In a really first-class coal it should not be more than 7 or 8 per cent., and beyond a 12 per cent. content its presence may involve serious loss or inconvenience to the consumer. In the United States within recent years the practice has become prevalent of fixing a " standard ash content " when a contract for the supply of coal is made. The seller is then entitled to receive a premium of 1 per cent. per ton for each whole per cent. that the average ash in the consignment supplied is less than the stipulated standard percentage. An increase of 2 per cent. in the ash content over the standard figure is allowed without altering the contract price, but any excess beyond this 2 per cent. margin involves a deduction from the contract price amounting usually to 2 cents per ton for each 1 per cent. by which the ash content exceeds the penalty limit. (See also Chapter XI.)

A distinction must, however, be drawn between the " fixed " mineral matter as it actually occurs in the coal and the " ash " which remains when the coal is burnt, for these are not necessarily or usually the same, owing to chemical interactions during combustion between the mineral constituents, the air, and the coal substance itself.

The colour of the ash from a coal varies from a pure white (or cream) to a dark chocolate colour according to its ferruginous character, and its fusibility varies with its chemical composition over a wide range. A remarkably pure white ash which the author once found to an extent of 33·9 per cent. in an Australian bituminous coal contained—

$SiO_2 = 53\cdot4$, $Al_2O_3 = 44\cdot0$, $CaO = 2\cdot0$, alkalies etc. $= 0\cdot5$ per c⟨

together with only the merest trace of iron oxide. Needless to say such a material would be infusible at the highest temperature ordinarily attained in a boiler or reverberatory furnace, and its presence, even in moderately large amount, would not interfere with the "free burning" qualities of the coal substance.

The following table will give some idea of the great variations found in the composition of the ashes of some typical English coals :—

TABLE XIIA

	Northumberland Steam Coal.	Durham Hard Coking Coal.	Barnsley Hard Coal, South Yorkshire.	Lancashire Coals.				
				Wigan 4 Ft. Seam.	Arley.	Trencher-bone.	Wigan 6 Ft. Seam.	Florida.
Colour of Ash.	Grey.	Buff red.	Cream.	Dark red.	Chocolate.	Dark red.	Chocolate.	Dark red.
SiO_2	40·6	44·5	48·0	31·40	26·40	39·40	33·80	30·00
Al_2O_3	38·9	39·0	35·0	21·15	28·00	28·49	21·75	19·15
Fe_3O_4	6·75	12·3	2·5	22·85	32·42	22·85	29·30	22·14
MnO	—	—	—	0·55	nil	0·40	nil	0·65
CaO	5·27	}traces	9·25	16·25	7·00	4·30	3·00	11·10
MgO	trace			0·10	2·88	1·08	3·25	3·65
SO_3	5·20	2·1	} 5·25	7·00	2·74	3·26	8·58	13·29
P_2O_5 and Alkali	} —	0·7		0·11	0·28	0·17	0·32	—

The relation of the fusibility of the ash of a coal to its chemical composition is a very important, though somewhat complex, question, concerning which the present state of our knowledge is not sufficiently definite to warrant the laying down of any precise rules. Inasmuch, however, as the simplest coal ash consists primarily of alumina and silica, to which, as the composition increases in complexity, are added chiefly lime and oxides of iron in varying proportions, the question of its fusibility is related to that of the fusibility of alumino-silicates (e. g. blast furnace slags) in general. The fusion points of mixtures of two constituents such as silica and alumina will vary regularly with the relative proportions of each, and there is a certain "eutectic" mixture of lowest melting-point. Similarly successive additions of lime C to a given mixture AB of silica and alumina will progressively lower its melting-point until a certain limiting propor-

tion ABC of lowest melting-point is reached, after which further additions of C will gradually raise the melting-point above this minimum temperature. Similar effects would again be produced by adding a fourth constituent D (Fe_3O_4) to a particular mixture ABC of alumina, silica, and lime. Hence the fusibility of the ash from a particular coal is commonly observed to increase up to a certain point sometimes with its ferruginous character, sometimes, however, with its lime content, and, speaking generally, with the content of some " most variable " constituent.

The question has been investigated by Dr. J. T. Dunn of Newcastle - on - Tyne, who has published the results of his analyses and fusion-point determinations of a series of nineteen different coals[1] (chiefly Northumberland = N, Durham = D, and West of Scotland = S), from which the following are selected as typical examples :—

TABLE XIIв

Dr. J. T. Dunn's Analyses and Melting-point Determinations

No. of Sample	3	5	7	8	10	12	14	16	17	18
Origin	N.	D.	D.	N.	S.	S.	D.	N.	D.	Spitz-bergen.
SiO_2	36·90	40·40	42·10	42·70	41·20	49·30	47·10	51·10	51·80	51·15
Al_2O_3	25·82	29·34	30·67	35·05	33·45	35·40	37·39	35·93	38·25	44·70
Fe_2O_3	25·00	15·21	21·70	8·79	17·14	7·29	11·14	4·86	5·64	1·25
MnO	0·30	0·30	0·30	trace	0·40	0·30	0·40	trace	trace	trace
CaO	3·71	4·61	0·99	5·84	3·70	2·96	0·82	2·78	0·45	1·15
MgO	2·10	1·96	0·76	1·30	1·78	1·34	0·65	0·80	0·74	0·36
Alkali	4·79	7·23	2·55	2·09	0·83	1·90	1·38	3·32	1·71	1·20
TiO_2	1·38	0·95	0·92	1·16	1·41	1·51	1·12	1·21	1·41	1·15
Melting-point C.	1150°	1230°	1340°	1380°	1390°	1460°	1460°	1480°	1500°	—

From Dr. Dunn's work it would appear that the melting-point of a coal ash may vary between as low as 1000° and 1500° C. (or even higher), according to its chemical composition, and that, although at present no general law can be formulated, the melting-point as a rule rises as the relative total *molecular* proportion of basic oxides to silica diminishes. It may be noted

[1] *Journ. Soc. Chem. Ind.*, 1918, **37**, p. 17T.

that the composition of the infusible Spitzbergen ash (No. 18) is nearly the same as that of the Australian example already quoted.

The coking properties of a coal are undoubtedly influenced to some extent by the composition of its ash, as also is the rapidity of combustion of the coal substance. Then, again, a highly ferruginous ash such as is yielded by a pyritic coal, forms a fusible ferrous silicate which is a prolific source of "clinkering" trouble in furnaces and the like. For a given class of "steam" or "furnace" coals, the less ferruginous the ash the better; the same consideration would apply to the selection of a "gas-producer" coal from a number of otherwise suitable varieties. The formation of a fusible ferrous silicate from the ash constituents in the furnace of a locomotive boiler under high draught conditions is usually responsible for the formation of "swallow nests" in the front openings of the boiler tubes which so seriously impair the steaming capacity of the boiler.

Coal Washing [1]

The practice of washing small coal to free it from "dirt," which was introduced into this country from the Continent in connection with the by-product coking industry, is one of growing importance. It depends on the same principles and involves similar mechanical appliances as does ore concentration in ordinary mining operations, with, however, the difference that whereas in ore concentration the valuable concentrate is heavier and much less bulky than the impurities which are rejected, in coal washing it is the lighter and more bulky material which is saved whilst the heavier impurities are rejected; for coal is one of the lightest of commercially important "minerals."

All coal-washing processes depend on the principle that if a mixture of coal and "dirt" be subjected to the action of moving water, accompanied by some sufficiently rapid "jerking" action, the heavier "dirt" will sink more rapidly than the lighter coal which will be carried forward by the flow. By suitably regulating the flow of water and the mechanical agitation in relation to the amount and grade of the material put through the apparatus in a given time, and by arranging for the re-washing

of the coal and dirt, respectively, resulting from the first operation, an almost complete separation of the two on a commercial scale can be ultimately effected.

The coal as it comes from the mine is usually passed first of all over a belt where any large lumps of shale or shaley coal are picked out by hand. Then it is screened to separate the lump coal from the smaller grades, for in most cases it is only the latter that are treated in the washing. Sometimes, however, the whole of the mine output is crushed to a limited extent, in order to detach more completely the worthless mineral matter from the coal, after which the crushed material is screened into suitably graded sizes before it goes to the washery.

In the best practice the coal to be washed is screened into a number of different sizes (*e. g.* nuts $= \frac{3}{4}$ inch to 1 inch, beans $= \frac{1}{2}$ inch to $\frac{3}{4}$ inch, peas $= \frac{1}{4}$ inch to $\frac{1}{2}$ inch, and fines $= 0$ to $\frac{1}{4}$ inch mesh), and each size is separately washed. The " fines " should preferably be removed, otherwise a troublesome slurry may be formed in the washery. It may here be pointed out that if coal as won from the mine be screened into a number of different sizes, the smaller grades, and especially the fines, are usually found to contain a greater proportion of mineral matter than the larger sizes. A big lump of coal usually contains a minimum proportion of ash, having regard to the average ash content of the seam whence it came. This is due to the circumstance that, in general, the friability of a coal increases with a growing mineral content. It has also been found in " washery " practice, that whereas small masses of mineral impurities may be easily separated from pieces of coal up to (say) from three to six times their own size, it is much more difficult to effect a satisfactory separation if the " size ratio " is much greater than about six; and in general, the greater the difference between the specific gravities of the coal and the associated mineral matter, the greater the " size ratio " which can be allowed for effective washing.

The chief types of appliances employed in coal-washeries are (1) *trough washers*, in which the graded coal is fed continuously into the upper end of a narrow inclined trough up which a set of scrapers are slowly moved on an endless chain arrangement against a regulated downward flow of water. The material is thus kept in a continual state of movement against the descending stream of water. The heavier refuse is carried upwards and finally discharged at the top, whilst the lighter coal, being carri

downwards by the water, is discharged at the bottom; (2) *jig washers*, in which the coal is continuously fed on to a sieve immersed in a trough of upward flowing water. Either the sieve is given a rapid "jerky" motion, or the sieve being fixed, a rapid pulsating motion is imparted to the water flowing through it. In either case a stratification of the lighter coal and the heavier mineral matter is effected gravitationally, and the separated coal is continuously pushed out at the top of the apparatus by the new material which is being fed into it.

The different washing schemes in vogue may be divided into two main classes, namely (1) those in which the coal is sized and graded before it goes to the "washery"; and (2) those in which, after all lump coal above (say) 3 inches has been removed, the main bulk of the coal is subjected to a preliminary washing, then screened into sizes, the smaller of which are subsequently re-washed.

The following scheme (Fig. 6) relating to a plant erected some years ago at the Monopol Colliery near Dortmund, may be cited as an example of the first of the above-mentioned classes. The coal as it came from the mine was screened into three sizes, namely (1) cobbles, (2) intermediates, and (3) smalls. The two first-named sizes were loaded direct into trucks for immediate despatch to the buyer, but the "smalls" were again screened and then washed in accordance with the plan shown in the diagram.

The performance of a British Baum Washery at a colliery in the North of England may be described as representative of one of the best modern systems of coal-washing. The special feature of this particular plant is that all coal below 2 inches square is washed in a Baum Washer Box (Plates I and II), which is divided into two sections or compartments, E and M, each containing a fixed sieve bed, that, K (Plate I), of the first compartment, where all the larger and heavier dirt is removed, being set at a slight upward inclination in the direction of the overflow, whilst that, R, of the second compartment, where the lighter dirt is removed, is fixed horizontally. The necessary pulsating motion is imparted to the water in the two compartments by means of compressed air at about 2 lb. per square inch pressure, which is admitted intermittently at T, *well below the level of the sieves*, through a special regulating valve provided with a sleeve piston which is moved up and down by means of an eccentric. The result is a short and energetic upward movement of the water in the washing compartment, followed by a

PLATE I.—Baum Washer Box (Front Elevation).

PLATE II.—Baum Washer Box (End Elevation).

gentle downward movement, which allows ample time for the materials on the washer bed to segregate in accordance with their respective specific gravities, the heavier dirt going to the bottom and the lighter coal remaining on the top. The washed coal is then separated into three sizes, namely, (1) *nuts* (2 inches

SMALLS
↓
SCREENS

LARGE NUTS 1¾ to 3¼"   NUTS ⅝ to 1¾"   FINES under ⅝"

WASHER   WASHER   WASHER

CLEAN COAL AND WATER   DIRT

DIRT

SETTLING TANKS

CLEAN COAL

WASHERS

SCREEN   TOWER◄ COAL AND WATER   DIRT

COAL   WATER

PUMP WELL

WATER   SLUDGE

BACK TO WASHER   MIXED WITH "FINES" AND RE-WASHED

FIG. 6.

to ⅝ inch); (2) *peas* (⅝ inch to ⅜ inch); and (3) *fines* (below ⅜ inch). The " fines " are subsequently re-washed and drained on a special Slurry Refiner, which ultimately delivers the fine-washed coal in a comparatively dry condition.

The water drained from the " fines " is sent forward to an elevated Settling Tank consisting of a circular inverted cone carried on columns. The tank is placed at a sufficiently high

level to enable the clarified water to be returned to the Washery at the required head for working same, also to force the slurry settling in the bottom of the tank on to the Slurry Refiner where the slurry is drained along with the " fines."

The plant in question (Plate III) deals each hour with 100 tons of coal, containing 22·5 per cent. of mineral matter, and reduces the latter to between 6·5 and 7·0 per cent. with a loss of less than 2 per cent. of the coal substance itself, the net ex- ·penditure of water amounting to no more than 15 gallons per ton of coal washed.

The following figures, taken from a Report by F. C. Lincoln of the University of Illinois, may be cited as showing the marked improvement effected in a low-grade coal by washing it in suitably screened sizes :—[1]

TABLE XIII

	Raw Coal.	Coal as Screened and Washed.				
		1¾″ to 3¼″	1″ to 2¼″	⅝″ to 1¼″	₁₆″ to ⅝″	0 to ₁₆″
% Ash	20·81	8·53	8·31	8·96	9·6	12·65
% Sulphur . . .	3·84	3·11	2·98	3·12	3·0	3·13
Calorific Value B.Th.Us. per lb. .	11,166	13,125	13,185	12,095	12,935	12,445

In conclusion, the following summarised results of a trial with a Canadian coal from the Emery Seam of the Dominion Coal Co., conducted by Dr. J. B. Porter on the experimental washing plant in the Mining Department of the McGill University, Mon- treal,[2] will give a still better idea of the possibilities of coal- washing in relation to low-grade coals. The coal, already crushed to pass a 3-inch screen, was further reduced to a 1-inch in a " Comet " breaker, after which it was passed through a revolving screen of three sections perforated with ⅝, ⅜ and ¼ inch round holes respectively. The resulting grades of ¼ inch and upwards were finally washed in two sizes, namely, ¼ to ⅜ inch, and ⅜ to 1 inch, respectively, in a jig washer, whilst the fines (0 to ¼ inch) were separately treated in another type of washer. The original coal, as delivered from the mine, contained (when dry) 11·1 per

---

[1] *University of Illinois Bulletin*, No. 69 (1914).
[2] *Investigation of the Coals of Canada*, by J. B. Porter and R. J. Durley, Vol. I. (1912), pp. 198 to 200.

PLATE III.—Interior of Baum Coal Washing Plant.

cent. of ash, 2·5 per cent. of sulphur, and had a calorific value of 13,122 B.Th.Us. per lb.

RESULT OF WASHING TEST

TABLE XIV

	Sizes between 1″ and ½″.		Sizes between ½″ and ¼″.		Sizes below ¼″.
	Quantity lb.	% Ash.	Quantity lb.	% Ash.	lb.
Original Coal . .	3170	10·2	1757	9·1	1214
Washed Coal . .	2790	5·6	506	5·4	973
Refuse	372	46·7	182	46·7	113
Slimes	—	—	17	19·1	105

TABLE XV

	lb.	Calorific Value B.Th.Us. per lb.	% Ash.	% Sulphur.
Original Coal	6141	13,122	11·1	2·5
Washed Coal	5434	13,878	5·8	2·1
Refuse	635	—	47·5	—
Other Products	73	—	—	—

Decrease in Ash   due to Washing = 47·8 per cent.
   ,,   ,, Sulphur   ,,   ,,   ,, = 16·0 ,,   ,,
Increase ,, Boiler Evaporation   ,, = 5·8 ,,   ,,
Decrease ,, Clinkers in Boiler Furnace = 52·2 ,,   ,,

SALT IN COALS

Some coals, besides containing insoluble mineral matter, are impregnated with minute quantities of soluble salts, principally the chlorides of sodium, potassium, and magnesium, and are thus called " salty coals." The presence of such salts in coking coals is very detrimental to the brickwork of the coke-oven walls at high temperatures, for it is commonly agreed that " salty " coals produce a far more rapid corrosion of the refractory oven walls than those which are comparatively free from " salty " constituents. It may here be pointed out also that soluble salts may be introduced into a coal, originally comparatively free from them, during any " washing " process preparatory to charging the coal into the ovens, unless care is taken to avoid using water containing an undue proportion of such soluble salts. Hence the

importance, in the case of coals used for the manufacture of hard metallurgical coke, to determine the amounts of soluble salts (especially chlorides) which they contain, and also to examine from time to time the water used in the washery.

A " salty " coal recently examined in the author's laboratories at the Imperial College of Science and Technology, London, in connection with an investigation by Messrs. W. C. Hancock and W. E. King into the effects of such coals upon the refractory linings of coke ovens at high temperatures, was found to contain as much as 0·648 per cent. of soluble mineral salts, of which the chlorine content was 19·6 per cent. (*i. e.* equal to 32·3 per cent. NaCl). The disintegrating action of such a coal upon the oven linings was very marked, especially when charged into the oven in a wet condition. Apparently moisture in the slack coal had assisted matters by acting as a carrier of soluble salts of the alkali metals from the coal to the hot firebrick linings, and the salts so transferred had caused a marked disintegration therein, especially towards the end of the coking period when the temperature in the oven was at its highest. The alkalies so deposited in the pores of the firebrick produced a fusible vitreous coating or glaze upon the surface in contact with the coal, which glaze subsequently became broken up under the combined influence of the rapid temperature changes in the oven and the abrasive action of the coke and coal during the discharging and re-charging operations.

As a typical example of the transfer of alkalies from a " salty " coal to firebrick at high temperatures and the influence of moisture thereon, the following results of laboratory experiments may be quoted in which a standard firebrick test-piece weighing 5 grams, was exposed to the action of three successive charges, each of 10 grams, of a particular salty coal, A or B, for altogether $3 \times 9 = 27$ hours at 1000° C. The coal had been previously ground until it passed a ¼ inch linear mesh, and it was used " dry " or " moist " in alternate experiments.

Total Alkalies in the Original Test-piece = 1·66 per cent.

	Coal A.		Coal B.	
	Dry	Moist	Dry	Moist
Total percentage alkalies found in test-piece after the experiment.	2·49	2·70	2·74	3·91

CHAPTER IV

THE CHEMICAL COMPOSITION OF COAL (*contd.*)

B. THE COAL SUBSTANCE—ITS ULTIMATE ANALYSIS AND YIELD OF "VOLATILE MATTER"—CALORIFIC VALUES OF COALS

FOR the purposes of the comparison and classification of coals it is usual to disregard the variable proportions of mineral matter, as well as of mechanically held water which they may contain, and to fix attention upon the character and composition of the "coal substance" itself.

The coal substance, although always compounded of the same elements carbon, hydrogen, oxygen, nitrogen, and sulphur, is in reality a very complex material, about which it must be confessed chemists are still in a state of considerable ignorance. In this chapter we shall confine our attention to the elementary ultimate composition of the coal substance, its "proximate" analysis by carbonisation tests at definite temperatures, and the calorific values of coals.

It will have been understood, from what has been said in the preceding chapter on the origin of coal, that inasmuch as coal-fields have been formed from vegetable *débris* in nearly all the great geological epochs, the present-day coals represent widely different intermediate stages in the wood-to-anthracite series, anthracite being regarded for the moment as the end product thereof, although, as will be explained later, it may not be and is not necessarily so.

Such a series would include (1) *Peat*, which may be regarded as the initial stage in the transformation process and, geologically speaking, of very recent origin (quaternary); (2) the "sub-bituminous" *Brown Coals* and *Lignites*, which are nearly all of Tertiary or Cretaceous origin, and therefore intermediate between peat and the true coals; (3) the great class of "*Bituminous Coals*," which mainly date back to Carboniferous or Permo-Carboniferous times; and (4) the *Anthracitic Coals* and *Anthracites*, which belong to the oldest classes.

It must further be recognised that, whilst there is little doubt

E

but that the transformation process from wood to coal has been much the same in all geological periods, there may have been considerable variations in the original vegetable *débris* transformed, which variations would also help to explain some of the marked differences observed in present-day coals. Thus, for instance, some authorities have suggested that the difference between the anthracites and bituminous coals of the Carboniferous period may be ascribed to some difference in the character of the vegetable *débris* from which they originated. Bearing such qualifications in mind, and considering for the moment the wood-to-anthracite series as successive stages in a process which has tended to the same end product, it will be seen, from the following figures for the ultimate composition of the principal dry " ashless " raw fuels comprised in the series, that the net result has been a progressive concentration in the carbon content and a corresponding diminution in the relative proportion of oxygen in the organic matter, a circumstance which is also marked by a steady increase in the calorific value of the product as the series is ascended.

TABLE XVI

	Carbon Per cent.	Hydrogen Per cent.	Oxygen Per cent.	Nitrogen Per cent.	Calorific Value K.C. Us. per kg.
Wood	50·0	6·0	43·5	0·5	4000—4300
Peat	50—64	4·5–6·8	28—48	0·75–3·0	5000—6000
Brown Coals and Lignites . . .	60—75	5·0	20—35	0·75–1·75	6000—7000
Bituminous Coals .	75—90	4·5–5·5	5–15	0·75–1·75	8000—9000
Anthracites . .	90—95	2·5	3·0	0·5–1·0	8000–9000

ULTIMATE ANALYSIS

The ultimate analysis of a coal consists in determining the percentages of elementary carbon, hydrogen, nitrogen, and sulphur in a properly prepared *dry* sample ; the difference between the sum of these percentages, *plus* the percentage of ash, and 100 is usually returned as oxygen, meaning of course oxygen in the coal substance itself, apart from that in the associated mineral matter.[1] The oxygen figure so deduced is, therefore,

---

[1] It is assumed that the percentages of other elements (such as arsenic, phosphorus, etc.) are so small as not to affect the calculation.

subject to whatever balance of error there may be in the estimation of the total of the other constituents, which error may be appreciable, especially where the percentage of *ash* differs materially from the original mineral content of the coal. Indeed, such disparity between " ash " and " mineral content " is always a possible source of error in coal analysis.

With regard to the difficulty of calculating the oxygen content of a coal, the following opinion, published by the Coal Analysis Committee of the American Chemical Society in 1899 (*Journ. Amer. Chem. Soc.*, 21, p. 1129) may be quoted :—

" The method to be used in calculating the oxygen of the coal presents, perhaps, the question of greatest difficulty. If we could be sure that all the sulphur is present in the form of pyrites, and that this is converted into ferric oxide in the ash, the oxygen should be found by subtracting from 100 the sum of carbon, hydrogen, nitrogen, ash, and five-eighths of the sulphur. This probably is the safest rule which can be given for general use, and especially for coals high in sulphur. The operator should, however, satisfy himself as to whether the ash is practically free from sulphates, and, if possible, whether the sulphur is mainly in the form of pyrites. If necessary, the rule should be modified, in particular cases, accordingly."

CARBON AND HYDROGEN

The percentages of these two elements are always determined by burning a weighed quantity (0·25 to 0·50 gram) of the *dry* coal in a current of dry oxygen in a hard glass tube, the products being passed (in the tube) over moderately heated lead chromate, which retains oxides of sulphur produced by the oxidation of iron pyrites or organic sulphur compounds in the coal. The water and carbon dioxide produced by the combustion of the coal, are caught up by suitable absorbents (*e. g.* dehydrated calcium chloride for water, and a 1 : 1 aqueous solution of caustic potash for carbon dioxide) and weighed. The procedure is essentially the same as that generally adopted for the determination of carbon and hydrogen in organic compounds and needs no further description. To any one thoroughly experienced in the analysis of organic substances the method in itself presents no difficulties, and the amounts of carbon dioxide and water produced can certainly be estimated with

considerable accuracy. Where inexperienced persons some-times fail is either (1) through lack of the particular manipulative skill and judgment required, which is only acquired after con-siderable practice, or (2) because they neglect some obvious precaution.

For instance, it is essential (1) that the oxygen used should be dried before entering the heated tube *over the same drying agent as is afterwards used to absorb the* H_2O *produced during combustion;* (2) that before the tubes or bulbs containing the absorbents for water and carbon dioxide respectively are finally weighed, they shall have been allowed to cool in a dry chamber to the temperature of the balance room, which should be recorded, and a proper correction applied if its temperature has changed materially during the experiment.

Also, in carrying out the combustion of a coal containing a highly ferruginous and fusible ash, it is inadvisable to heat the coal to more than about 800° C. or otherwise minute particles of carbon are liable to be " protected " from the action of the oxygen by the semi-fused ash, and so escape combustion.

The residual " ash " may be weighed as a check on the ordinary ash determination ; in the case of a ferruginous ash it is, however, liable to give a slightly higher result than that obtained by the ordinary method, because of the usually more complete oxida-tion of the iron in the combustion tubes than in the muffle furnace.

It is the author's general experience in regard to the " com-bustion analysis " of organic compounds generally (1) that whilst there is a tendency for the *carbon* to come out somewhat lower than its true value, this error does not on the average exceed half of 1 per cent. of the true value; and (2) that the *hydrogen* on the average comes out very near to (if anything slightly higher than) the true value.

SPECIAL SOURCES OF ERROR IN THE ESTIMATION OF CARBON AND HYDROGEN IN COALS

It has frequently been pointed out that the association of calcium (or magnesium) carbonate with the coal substance will, by reason of its decomposition ($CaCO_3 = CaO + CO_2$) at red heat, cause the experimental determination of carbon by the combustion method to give a too high result, whereas the associa-

tion of hydrated minerals, such as gypsum ($CaSO_4$, $2H_2O$), would similarly cause the hydrogen to come out too high. In order to illustrate the magnitude of the errors so introduced, the following calculations have been made :—

(A) The influence of the presence of 1 per cent. of calcium carbonate in a dry coal containing 80 per cent. of carbon, and

(B) The influence of the presence of 1 per cent. of gypsum in a dry coal containing 5 per cent. of hydrogen.

(A) *Dry Coal containing 80 per cent. Carbon and 1 per cent. $CaCO_3$.*

By combustion of 1 gram coal :—

0·8000 gram C	would yield .	2·9333 grams CO_2
0·0100 ,, $CaCO_3$	,, ,, .	0·0044 ,, ,,

Total = 2·9377

Thus the total carbon dioxide obtained on analysis would exceed that actually found by combustion of the carbon by 44 parts in 29,333 or (say) by 0·15 per cent. only of the true " carbon " figure. So that the percentage of carbon calculated from the total carbon dioxide obtained in the analysis would be 80·12 instead of 80·00, which is about *half* the usual average " experimental error " in the carbon determination.

(B) *Dry Coal containing 5 per cent. Hydrogen and 1 per cent. Gypsum.*

By combustion of 1 gram coal :—

0·0500 gram hydrogen	would yield	0·4500 gram H_2O
0·0100 ,, $CaSO_4$, $2H_2O$	,, ,,	1·0021 ,, ,,

Total = 0·4521

Thus the total water obtained on analysis would exceed that actually found by combustion of the hydrogen by 21 parts in 4500 or (say) by about 0·5 per cent. of the true " hydrogen " figure. So that the percentage of hydrogen calculated from the *total* water obtained in the analysis would be 5·025 instead of 5·00, which is also well within the usual experimental error.

Nitrogen

The accurate estimation of this element in coal is very important. It probably exists in at least two forms, namely (1) as compounds (possibly of an " imino " type) which decompose between (say) 300° and 900° C. giving rise to ammonia, and which are the source of the ammonia obtained when the coal is carbonised in coke ovens or in gas-works retorts; and (2) in much more stable (possibly " nitride ") types of compounds which on thermal decomposition do not yield ammonia.

The fact that the whole of the nitrogen in coal can be extracted as ammonia by heating it to redness in a current of steam is now well known to chemists, and is the basis of the Mond " Ammonia Recovery " Gasification Process. Dr. Ludwig Mond in his Presidential Address to the Society of Chemical Industry in 1889 on this subject mentioned that it had been customary in his laboratory to estimate the nitrogen in coke simply " *by burning it in a current of steam* " which converted the whole of it into ammonia.

Total Nitrogen.—This may be, and usually is, estimated by the following modification of the well-known Kjeldahl method, which the author has found to work very well :—

Weigh out 1 gram of the coal, pulverised so that it will pass through fine muslin, into a Jena glass flask specially designed so that the whole of the subsequent operations can be carried out in it. Then add 15 c.cs. of fuming sulphuric acid and about 1 gram of mercury. Heat gently for 2 or 3 hours, at the end of which all black particles should have disappeared. Allow the contents of the flask to cool, then carefully add a little cold water and a few drops of phenolphthalein solution. Next, run in very carefully (with external cooling) sufficient of a strong solution of caustic potash to make the liquid strongly alkaline. Then add 15 c.cs. of a solution of sodium sulphide (containing 40 grams per litre) to precipitate the mercury compound as HgS. Add a small piece of zinc to prevent bumping, and distil for 20 to 30 minutes into 20 c.cs. of decinormal sulphuric acid. From the amount of acid neutralised by the NH_3 evolved the nitrogen in the coal may be calculated (1 c.c. of decinormal acid neutralised = 0·0014 gram of nitrogen in the coal). Two such estimations should always be made simultaneously and the mean result taken. Moreover, a *blank* experiment should also be made in order to correct for any ammonia evolved from the

materials other than the coal used in the experiment. In laboratories where such nitrogen determinations are made daily, it is sufficient if a blank experiment be made once a week.

SULPHUR

Sulphur is always a deleterious element in coal from every point of view. It is present chiefly in three forms, namely (1) as iron pyrites (FeS_2); (2) as gypsum ($CaSO_4$, $2H_2O$); and (3) in the form of organic compounds in the coal substance itself. On carbonising a coal in gas retorts or coking ovens, between a quarter and a third of the sulphur is expelled with the gases, chiefly as H_2S, CS_2, and thiophene, the remainder being retained by the coke.

(*a*) *Sulphur in the Coal.*—The method employed in the author's laboratory consists essentially in igniting a weighed amount of the finely divided coal or coke (2 to 3 grams) with three times its weight of a mixture of 2 parts of light magnesium oxide (MgO) and 1 part of pure anhydrous sodium carbonate (Na_2CO_3) in a porcelain dish or large crucible for $1\frac{1}{2}$ hours in a muffle furnace.[1] Afterwards the charge is washed out into a beaker, excess of hydrochloric acid *plus* bromine water is added; the excess of bromine is then boiled off and, after vigorous stirring, the liquid is filtered. The sulphate in the filtrate is then precipitated with a slight excess of barium nitrate and finally ignited and weighed as $BaSO_4$ in the usual manner. Determinations are usually made in triplicate, and a blank experiment is always simultaneously performed in order to determine the " correction " to be applied on account of any traces of sulphate in the materials employed or the fixation of sulphur dioxide by them from the furnace gases.

(*b*) *In the Ash.*—In general the ash is fused in a platinum crucible with excess of an intimate mixture of $NaCO_3$ and K_2CO_3 *plus* KNO_3 to ensure the conversion of all sulphur compounds into soluble sulphates. The fused mass is subsequently extracted with excess of hot dilute hydrochloric acid and the extracted sulphates are then determined in the usual way. The exact procedure in such an analysis necessarily varies with the composition of the ash (which should always have been qualitatively ascertained beforehand), and must be left to the discretion of the operator.

[1] In laboratories provided with a suitable supply of electricity, the use of an electrically heated muffle is recommended for the fusion process.

COAL AND ITS SCIENTIFIC USES

Estimation of the Yields of Volatile Combustible Matter by Coals

For commercial purposes coals are classified according to their suitability or otherwise for certain specific economic ends, e. g. steam raising, furnace firing, gas making, the manufacture of a dense metallurgical coke, low temperature distillation and the like. The usefulness of any given coal for a particular purpose depends largely upon its yield of combustible " volatile " matter expelled when it is carbonised under certain specified conditions and upon the character of the resulting carbonaceous residue. Various coals show marked differences in behaviour when so carbonised, and from a properly conducted laboratory test (sometimes called a " proximate analysis ") on such lines much valuable general information may be gained respecting the economic value of a given coal.

When so treated some coals swell up and, after passing through a marked state of intumescence, yield a strongly coherent residue (coke). These are usually designated " caking " coals. Others, again, exhibit no sign of intumescence and yield an incoherent carbonaceous residue; such are called " non-caking " coals, and they are usually *either* rich in oxygen and burn with a long smoky flame, *or* rich in carbon and burn with a short smokeless flame. Between these two extremes there are many intermediate types possessing more or less caking properties. Owing, however, to the fact that the yield of " volatile matter " from a given coal varies within wide limits according to the conditions, of which temperature is the most important, under which it is carbonised, it is necessary to prescribe certain " standard " conditions for such tests, which conditions must be strictly observed throughout if the results are to be of any comparative value. The following two standard tests may be cited by way of illustration.

(a) *The American Test.*—In 1899 the American Chemical Society recommended the following method for the determination of " Volatile Combustible Matter," which has since been accorded international recognition.

" Place, 1 gram of fresh, undried, powdered coal in a platinum crucible, weighing 20 to 30 grams, and having a tightly fitting cover. Heat over the full flame of a Bunsen burner for 7 minutes. The crucible should be supported on a platinum triangle with the bottom 6 to 8 c.ms. above the top of the burner. The flame should be fully 20 c.ms. high when burning free, and

56

the determination should be made in a place free from draughts. The upper surface of the cover should burn clear but the under surface should remain covered with carbon. To find the Volatile Combustible Matter, subtract the percentage of moisture from the loss found here " (*Journ. Amer. Chem. Soc.*, 1899, 21, p. 1122).

Practically the same test was adopted by the Canadian Coal Survey chemists, except that it was carried out on the *dry* instead of the *undried* coal, as in the American procedure. It has always seemed to the author that a test carried out under such conditions, and on so small a quantity of coal, in a *platinum* crucible, is open to criticism, both on account of the well-known intense " catalytic " influence of hot platinum upon such thermal decompositions, and also because of temperature conditions. Also, it does not enable a sufficiently reliable judgment to be formed about the " coking " properties of the coal. Accordingly, after investigating the matter some years ago for himself, the author ceased to employ the method in his laboratory, preferring the following, which, if carried out under " standard " conditions, has proved to be quite reliable within the limits required for commercial purposes.

(*b*) *The Crucible Test.*—Twenty grams of the dried coal are weighed out (to the nearest centigram) into a No. 3 Morgan Fireclay crucible, which has been just previously heated to redness in a muffle and then allowed to cool in a chamber containing an efficient drying agent. The crucible and its contents (lid on) are then put into a muffle furnace, the temperature of which has been raised to 900° C. and kept constant at such degree by proper regulation of the gas supply. The charge of coal is thus " carbonised," the resultant inflammable volatile matters escape from the crucible, either through the hole in the lid or round the edge of it, and are ignited as they issue therefrom and mix with air in the muffle. Heating is continued for 10 minutes after the evolution of inflammable gases has entirely ceased. The crucible containing the carbonaceous residue is then withdrawn and set to cool in the " drying " chamber, after which it is quickly re-weighed. A subsequent examination of the carbonaceous residue enables a good idea to be formed of the " coking " properties of the coal, and as a *comparative test* of the properties of different coals it is most valuable. The test should always, however, be carried out simultaneously in *duplicate* if not in triplicate charges. How nearly the results from two or

more such charges are found to agree may be illustrated by the following examples taken at random from laboratory records :—

(1)	35·3	34·9	35·5	.	.	Mean = 35·2
(2)	32·5	30·5	32·8	.	.	Mean = 31·9
(3)	24·8	23·4	—	.	.	Mean = 24·1
(4)	16·9	17·6	—	.	.	Mean — 17·25
(5)	13·4	13·8	—	.	.	Mean = 13·6
(6)	9·8	10·2	—	.	.	Mean = 10·0

Per cent.

If the experimental results are referred to the " dry ashless " coal, they enable a useful *proximate* classification of coals for commercial purposes to be made on similar lines to that of Regnault-Grüner's table (*q. v.*) somewhat as follows :—

TABLE XVII

	% Volatile at 900° C.
1. Anthracites	Below 8 } Non-caking.
2. Anthracitic Coals	8 to 15 }
3. Semi-bituminous Steam Coals .	15 to 20 Feebly caking.
4. Hard Coking Coals	20 to 30 Yield a dense metal-lurgical coke.[1]
5. Gas Coals—Strong Coke . .	30 to 35 Strongly caking.
6. Gas Coals—Porous Coke . .	35 to 40 Weakly caking.
7. Non-caking—Long Flame Furnace Coals	Above 40 Non-caking.

According to the author's experience it rarely happens, in regard to English coals, that the *caking* properties are not in substantial agreement with such a classification. Some exceptions are, however, to be met with among the South Wales coking coals, which contain less than 20 per cent. of volatile matter, and among Scottish non-caking varieties.

Further useful information can be obtained about a coal by comparing the percentages of volatile matter expelled from it at different selected temperatures (say 500°, 700°, and 900° C.) when heated in the crucible. The chief requisite for properly carrying out such a series of tests is a muffle type of furnace so designed that a temperature may be maintained fairly constantly at the selected degrees for a sufficient period to enable the " carbonisation " to be completed at each degree of heat.

[1] N.B.—The best Durham Coking Coals all fall within this class.

Thus, for example, it was found that the following percentages of volatile matter (referred to the dry ashless coal) were expelled from a lignitic coal at the temperatures named :—

Temperature				500°	700°	900°
Per cent. Volatile Matter		.	.	31·0	38·0	43·7

results which closely agreed with those actually realised when the same coal was afterwards carbonised on a large scale (*e. g.* at 500° C. the loss of " volatile " on a large scale was found to be 31·3 per cent. on the dry coal).

As a typical example of how results yielded by the Crucible Method compare with those obtained by the American Method (*a*), the case of a Durham Coking Coal tested in the author's laboratory by both methods may be quoted. By the American Test it yielded 23·4 per cent. of volatile combustible matter; by the Crucible Test it yielded 26·1 per cent. at 900° C. and 21·7 per cent. at 600° C. Thus the American Test gave a result corresponding to some temperature apparently about mid-way between 600° and 900° C.

CALORIFIC VALUE

The calorific value, or total amount of heat obtainable by the combustion of a given coal, is expressed by the number of parts by weight of water which may be heated through 1° on the thermometric scale, in the neighbourhood of the normal temperature (15° C. or 60° Fahr.), by the complete combustion of unit weight of the coal under conditions such that the whole of the heat of combustion is transferred without loss to the water, and that the products leave the system at atmospheric temperature and pressure. The metric unit of heat adopted for technical purposes (the K.C.U.) is the quantity of heat required to raise 1 kilogram of water through 1° C. in the neighbourhood of 15° C., whilst the British Thermal Unit (B.Th.U.) is the amount of heat required to raise 1 lb. of water through 1° Fahr. in the neighbourhood of 60° Fahr. Thus it follows that :—

1 K.C.U. = 3·9683 (or approx. 4) B.Th.Us.
1 B.Th.U. = 0·252 (or approx. ¼) K.C.U.

The calorific value of a coal may, therefore, be defined *either* (1) as the number of kilograms of water which may be heated through 1° C. in the neighbourhood of 15° C. by the complete

combustion of 1 kilogram of it; *or* (2) as the number of pounds of water which may be heated through 1° Fahr. in the neighbourhood of 60° Fahr. by the complete combustion of 1 lb. of it, in either case the conditions being such that the coal is taken *dry* (*i. e.* dried at 105° C. until its weight has become constant), that the whole of the heat is transferred without loss to the water, and that the products leave the system at the atmospheric temperature and pressure. It may be shown by calculation that a calorific value of x K.C.Us. per kilogram is equivalent to $1·8\, x$ B.Th.Us. per lb. or conversely, that x B.Th.Us. per lb. are equivalent to $0·5555\, x$ K.C.Us. per kilogram.

Seeing that every coal contains hydrogen, a distinction is sometimes drawn between its *gross* and *net* calorific values, the former implying that the products of combustion have *all* been cooled down to atmospheric temperature (15° C. or 60° Fahr.), the latter, however, that the heat liberated by the condensation of the steam produced on combustion, and by the subsequent cooling of the water down to 15° C. (or 60° Fahr.) has not been included. The difference between the two values will amount to 622 K.C.Us. per kilogram, or 1119·6 B.Th.Us. per lb. of steam produced by the combustion of the fuel. For scientific purposes the *gross* calorific value is invariably employed, but it is usual to use the *net* value in calculations relating to steam boiler trials, furnace operations and the like.

The determination of the calorific value of a coal may be best carried out by burning a known weight of it in compressed oxygen in some form of bomb calorimeter, that known as the Berthelot-Mahler apparatus being well adapted for the purpose. In the hands of an experienced worker, the method is more accurate than any yet devised, provided that all the proper " corrections " (*e. g.* for " radiation " and for the formation of nitric acid) are properly determined and applied in each experiment. The details of the experimental procedure are now so well known, and have been so often set forth both in laboratory manuals and technical publications, that there is perhaps no need for their reproduction here. The " water equivalent " of the bomb and its accessories is best determined by burning a known weight of compressed naphthalene in it A comparison between the value so obtained and that calculated from the known weights and specific heats of its separate parts serves as a good test of the proper heat insulation of the bomb in the calorimeter, which is apt at times to become defective. In the author's laboratory

it is customary to make such a comparison frequently, as a precaution against possible error which might otherwise escape detection. With ordinary care duplicate determinations on the same coal sample should give results agreeing within 50 K.C.Us., and when special precautions are taken within 25 K.C.Us. on about 8000 K.C.Us. per kilogram.

It must always be remembered, however, that the bomb method gives the heat of combustion under "*constant volume*" and not under "*constant pressure*" conditions, but as the combustion of a bituminous or anthracite coal in oxygen is attended by very little change in chemical volume (*e. g.* $C_9H_6O + 10O_2 = 9CO_2 + 3H_2O$) the difference between the two values is perhaps negligible in practice. Strictly speaking, however, the necessary small correction ought to be applied to the "bomb" results in deducing the true "*constant pressure*" value.

The following formula is sometimes used by engineers for calculating the calorific value of a coal from its chemical composition :—

$$Q = \tfrac{1}{100} \; (8080 \; C + 34{,}460 \; (H - \tfrac{1}{8} \; O) + 2250 \; S)$$

where C, H, O, and S = the percentage of carbon, hydrogen, oxygen, and sulphur, respectively in the dry coal. Although such a procedure can hardly be defended from a theoretical point of view, yet in cases where the *oxygen content of the coal is low* it is remarkable how nearly such "calculated" values often agree with those actually found by the bomb calorimeter.

Thus, in a Report by the Government Laboratory upon the calorific values of some forty-five South Wales Coals investigated for the Geological Survey (vide *Memoir upon the Coals of South Wales*, by Drs. A. Strahan and W. Pollard, 2nd Ed., 1915, p. 2), the values calculated by means of the above formula came out within 0·5 per cent. of those actually found experimentally in no less than twenty-eight cases, whilst only in one case was the difference between the two figures greater than 2 per cent. Of the forty-five coals in question, only six contained more than 6 per cent. of oxygen, and in no case did the oxygen content exceed 9 per cent.

That there is often a fairly close agreement between the results calculated by means of the above formula and those actually found by the bomb calorimeter in cases where the oxygen content of the coal is low also agrees with the author's experience. When, however, the oxygen content exceeds, say, about 7·5 per cent

two results do not usually show more than a rough agreement, and with high oxygen content, such as is met with in " oxidised " or lignitic coals, there is usually a marked disagreement.

This may be illustrated by the following tabulated results (Table XVIII) for a series of seventeen different coals, whose oxygen contents range from 2·5 up to 26·0 per cent., taken from one of the author's laboratory note-books. It will be noted that there usually is a much closer agreement between the " found " and " calculated " values in the case of the nine coals whose oxygen contents were all less than 5 per cent. than in the other eight cases in which the oxygen contents were all greater than 7·5 per cent.

TABLE XVIII

	Ultimate Composition. Percentages.				Calorific Values. K.C.Us. Per Kilogram.	
	C.	H.	S.	O.	Found.	Calcd.
1. Ekenberg Peat Briquette	58·35	5·42	0·5	26·0	5987	5463
2. Malay Lignitic L. . .	68·40	5·75	0·4	17·8	6538	6751
3. Notts Slack B. . . .	65·35	5·00	0·45	12·0	6320	6497
4. Japanese F. Coal . .	71·60	5·80	0·14	11·2	7165	7394
5. Lancashire B. . . .	78·45	5·26	1·38	10·7	7718	7721
6. Yorkshire B. . . .	73·10	5·52	1·20	8·7	7192	7457
7. Yorks B.	77·18	6·37	1·10	8·5	7990	8087
8. Durham B.	79·0	5·3	1·0	7·5	8027	7908
9. Durham B.C. . . .	83·6	5·0	1·0	3·0	8206	8373
10. E. Indian S.B. . . .	77·15	4·5	2·5	4·0	7690	7665
11. Scotch A.	87·3	4·05	0·1	4·0	8270	8279
12. S. Wales B.	79·3	4·4	0·4	3·0	7761	7795
13. S. Wales A.	85·4	3·65	1·2	3·2	8050	8046
14. S. Wales A.	89·4	3·42	1·15	2·6	8360	8316
15. S. Wales A.	87·5	3·30	0·7	3·5	8135	8070
16. S. Wales A.	86·41	3·48	0·57	4·0	8104	8010
17. S. Wales A.	90·4	3·34	0·9	2·5	8390	8357

L   = Lignitic.
B   = Bituminous.
B.C. = Bituminous—Hard Coking.
S.B. = Semi-bituminous.
A.   = Anthracite or Anthracitic.
F.   = a Resinous (" Fatty ") coal.

CHAPTER V

C. CLASSIFICATION OF COALS

COALS may be classified from the point of view either of their geological characteristics or of their suitability for various commercial purposes; some systems attempt to combine as far as possible both these objects. None of the existing systems can be regarded as entirely satisfactory from a chemical point of view, and indeed it must be confessed that, owing largely to our ignorance of the nature and proportionate distribution of the principal constituents of the coal substance, a sufficient basis for a scientific " chemical " classification of coals does not at present exist. Hence the importance of further research by chemists into the nature of coal.

Any complete classification of coal must include the following three principal groups—each of which may be recognised by certain characteristic group features :—

A. Sub-bituminous or Lignitic (Non-caking—Carbon usually below 75 per cent.).

B. Bituminous Coals (Caking or Non-caking—Carbon usually 75 to 90 per cent.).

C. Anthracites or Anthracitic Coals (Non-caking, rich in Carbon, low in Hydrogen).

THE REGNAULT-GRÜNER CLASSIFICATION

The earliest classification of coals is due to Regnault, who was the first chemist to make accurate ultimate analyses of them. He found that the principal commercial types of coal could be defined, within fairly narrow limits, by their ultimate compositions, and especially by their carbon and oxygen contents. The French metallurgist Grüner extended the Regnault system, which for commercial purposes is still a useful one, although cases of coals which do not altogether fall into line with it are occasionally met with. It is set forth in a slightly modified and modernised form in Table XIX the numbers in which all refer to the " dry ashless " coal substance.

TABLE XIX

The Regnault-Grüner Classification of Coals (As Revised by the Author)

Genus.	Class.	Chief Uses.	Percentage Composition.			% Volatiles at 900°C.	% Fixed Carbon.	Character of Carbonaceous Residue.
			C.	H.	O+N+S.			
A. Lignites	Non-caking	—	60 to 75	about 5·0	20 to 35	above 45	below 55	Non-coherent
B. Bituminous	[1] Non-caking Long Flame	Reverbatory Furnaces	75 to 80	4·5 to 5·5	15 to 20	40 to 45	55 to 60	Non-coherent
	[2] Caking Long Flame	Gas-making	80 to 85	about 5·6	10 to 15	32 to 40	60 to 68	Very Porous Coke
	[3] Hard Coking	Coke Manufacture	84 to 89	5·0 to 5·6	5·5 to 11·0	26 to 32	68 to 74	Dense Coke
	[4] Hard Coking Short Flame	Coke Manufacture and Steam Raising	88 to 90	4·5 to 5·5	5·5 to 6·5	18 to 26	74 to 82	Very Dense Coke
B.C. Semi-bituminous	Non-caking Short Flame	Steam Raising	90 to 92	4·0 to 4·5	4·0 to 5·5	15 to 20	80 to 85	Weakly Caking or Non-coherent
C. Anthracitic and Anthracites	[1] Anthracitic Non-caking	Steam Raising	92 to 94	3·0 to 4·0	3·0 to 4·5	8 to 15	85 to 92	Pulverulent
	[2] Anthracites Non-caking	Domestic and Central Heating; Malting Kilns				below 8	above 92	

All the numerical data in the above table refer to the dry ashless coal.

64

Considering now the various classes included in this table more in detail, we have in their natural order :—

A

LIGNITIC OR SUB-BITUMINOUS COALS (Lignites and Brown Coals).—A large class of principally Tertiary coals which are widely distributed over the Central European plain, the Southern States of North America (Texas, Arkansas, and Louisiana), and of Cretaceous coals occurring also in the United States over a large area, between latitudes 49° and 43° N. and longtitudes 100° to 107° W. (North Dakota, Montana and Wyoming), as well as in Canada. Large deposits are also found in Australia and the Malay Peninsula. They may be sub-divided according to their external characters and geological ages into (1) Woody or Fibrous Brown Coals, which retain a distinct ligneous structure; (2) Earthy Brown Coals, which are devoid of organic structure and readily crumble under pressure; (3) Common Lignites, of a dark brown colour and a slatey cleavage (*e. g.* Bovey coal); and (4) Bituminous Lignites, which are black in colour and have a conchoidal fracture.

One of the characteristic features of the lignites is the large amount of water (up to 50 per cent.) which they contain, and it has been proposed to use this fact as a basis of distinction between them and the lowest grades of bituminous coals. It was suggested in the *Bulletin* No. 218 of the United States Geological Survey (1903) that all coals containing 10 per cent. or more of water should be classed as lignites, but although the latter almost invariably contain a higher percentage of water than 10, later investigations by the Survey have shown that some unquestionably bituminous coals found in the Mississippi Valley likewise contain more than 10 per cent. of moisture. Hence the suggested distinction would not appear to be universally valid. Lignites readily lose part of their water content on air-drying, and in so doing they generally disintegrate, in some cases crumbling to powder, in others with well-marked laminar cracks.

Until quite recently, except in Germany and Austria-Hungary where 87·1 and 27·4 million tons respectively were raised for home consumption in 1913, lignites have not been considered as of great economic value, but the problem of utilising their immense deposits of lignites is an important one for Australia, Canada, Malaya, and other parts of the Empire.

F   65

Lignites, when dried, are readily reduced to powder in a disintegrator, and with addition of a suitable binder, may be again consolidated into serviceable briquettes under pressure. The ash content usually varies between 5 and 15 per cent., but may run considerably higher, whilst the nitrogen content usually lies between 0·5 and 1·5 per cent. They burn with a very long smoky flame, and are generally quite devoid of caking properties, and do not yield a coherent coke. On low temperature distillation they yield a variety of valuable decomposition products, including petrols, kerosene, fuel and lubricating oils, solid paraffins, pitch, ammonium sulphate, the nature and uses of which have for some time past been the subject of close investigation in the author's laboratory. There are undoubted commercial possibilities in the world's lignite resources which will well repay the attention of fuel chemists.

In Germany and Austria lignites have been largely used for firing boilers, for the heating of evaporating pans, and also in the case of some of the better qualities, to a limited extent for metallurgical purposes.

B

BITUMINOUS COALS.—This term is applied to a whole series of " flaming " coals of Carboniferous or Mesozoic origin. The Regnault-Grüner Classification sub-divides them into four classes, which, however, may be considered really as three, namely :—

(1) *Super-bituminous Coals*, yield at 900° more than 40 per cent. of volatile matter and a non-coherent carbonaceous residue. They burn with a very long and highly luminous " smoky " flame, and for that reason are chiefly valued for the firing of reverberatory furnaces and the like. They are also used to some extent as house coals, because of their " free burning " qualities. They are not, however, good for steam raising, and their non-caking character renders them quite useless for coke manufacture.

(2) *Gas Coals*, which at 900° C. yield between 32 and 40 per cent. of volatile matter and a porous coke of moderate strength. They comprise all the best gas-coals. They burn with a long luminous flame, and on distillation pass through a stage of intumescence, during which gas is freely expelled.

(3) *Hard Coking Coals*, which at 900° C. yield between 20 and 32 per cent. of volatile matter and a very dense and hard coke. They are chiefly valued for the manufacture of metallurgical

coke, but they are not suitable for steam raising, because on burning in the boiler furnace they form dense masses of coke which can only be completely consumed by an excessive air supply.

BC

SEMI-BITUMINOUS.—A class of steam coals yielding as a rule from 15 to 20 per cent. of volatile matter at 900° C. which includes all the best Welsh " Admiralty " steam coals. They are usually only feebly caking, and burn well in a good draught with a short smokeless flame.

C

(1) ANTHRACITIC.—Hard steam coals yield at 900° C. between 8 and 15 per cent. of volatile matter. They are non-caking and burn with a short non-luminous flame.

(2) ANTHRACITES.—Coals yielding less than 8 per cent. of volatiles at 900° C. are usually classed together as anthracites. In Great Britain they are found for the most part in the west and north-west border of the South Wales coalfield (West Glamorgan, Breconshire, Carmarthenshire, and Pembrokeshire) over an area of 137,000 acres, and to a small extent in certain localities in Scotland (Ayrshire, Linlithgow, and Fife), where the bituminous seams have been subjected to intrusion of molten igneous material subsequent to the formation of the original coalfield. Nearly 80 per cent. of the world's reserves of anthracites are said to be located in China, and there are extensive fields also in Russia and the United States (Pennsylvania).

Anthracites are usually distinguished by their very low ash content and comparative freedom from sulphur, and, owing to their cleanliness and smokeless combustion, they are chiefly used for domestic heating in specially constructed closed stoves, for central heating furnaces, for drying malt, curing rubber, and for other special purposes where a smokeless fuel of great purity is required. The total quantity of anthracite raised in Great Britain in the year 1913 was 5,194,620 tons, of which 4,833,159 tons came from South Wales; nearly 3 million tons were exported chiefly to France, Italy, Germany, Sweden, and Holland. The advantages of using anthracite for domestic heating are more appreciated on the Continent, where closed slow combustion stoves are largely used, than in England, where the open fireplace is the rule.

Until quite recently it has generally been believed that anthr-

cites represent the final stage in the transformation of the original mother-substance of coal, through the intermediate stages represented by lignites and bituminous coals. In support of this view may be cited the fact that anthracites are found in areas which are known to have been subjected to great earth movements after the coalfields were originally laid. But the fact that in the South Wales coalfield, where the character of the seams gradually changes from bituminous to anthracitic along a line running roughly south-east to north-west, the ash content diminishes as the " anthracitisation " increases is considered by some to be difficult to reconcile with the theory that the anthracite has been formed by the expulsion of volatile matter from what were originally bituminous seams. It has, therefore, been suggested that in this particular area the anthracite has been formed from a different type of original vegetable *débris*. In this connection attention may be called to the remarkable fact that whereas, in the case of the bituminous coals, the caking properties, as well as the strength and density of the coke produced therefrom at high temperatures, progressively increase with diminishing yields of volatiles at 900° C. until they attain a maximum at from 20 to 25 per cent. thereof, these properties disappear almost abruptly as soon as the yield of volatiles falls much below 20 per cent. The semi-bituminous steam coals, yielding from 15 to 20 per cent. of volatiles at 900° C. are all either non-caking or only feebly so, in marked contrast with the hard coking coals yielding a little more than 20 per cent. of volatiles. Again, non-caking coals are either (1) anthracites, anthracitic, or semi bituminous, which are rich in carbon, with a very low oxygen content, or (2) those either with a high oxygen content (exceeding 15 per cent.) or derived from seams which apparently at some period subsequent to the formation of the coalfield had become " oxidised " by exposure to atmospheric influences, *e. g.* Warwickshire and Leicestershire seams.

SELECTION OF COALS

In selecting a coal for any particular purpose, the following points may usefully be borne in mind :—

(1) The best *gas-coals* are those in which the $O : H$ ratio is approximately 2·0. They usually yield 32 to 38 per cent. of volatiles at 900° (reckoned on the dry ashless coal), and a fairly porous coke.

(2) The best *coking coals* usually yield between 20 and 30 per cent. of volatiles at 900° C. They are strongly caking, and have a ferruginous ash.

(3) The best *steam-coals* are found among those which yield between 10 and 20 per cent. of volatiles at 900° C.; they are non-caking, or only feebly so, and they should have a non-ferruginous ash.

(4) For gas generation, where the whole of the coal is to be gasified in a "producer" under the influence of a mixed steam-air blast for the making of "Producer Gas," it is best to select, whenever available, either a non-caking or feebly-caking coal with, if possible, an infusible non-ferruginous ash. Strongly caking coals are to be avoided.

(5) The coals freest from sulphur, arsenic, and with the *purest and lowest ash contents* are the anthracites.

WEDDING'S CLASSIFICATION

Wedding, an eminent German authority, has proposed to divide coals into six principal groups, according to the percentage of volatile matter yielded by the dry ashless fuel as follows :—[1]

TABLE XX

Class.	Percentage Yield of Volatiles.
1. Lean Anthracitic Coals	5·0 to 10·0
2. Sintering Coals (old) poor in gas	10·0 to 15·5
3. Caking Coals (old) poor in gas	15·5 to 33·3
4. Caking Coals (recent) rich in gas	33·3 to 40·0
5. Sintering Coals (recent) rich in gas	40·0 to 44·4
6. Sand Coals (recent) rich in gas	44·4 to 50·0

In drawing up this classification Wedding had chiefly in mind the caking properties of coals, which increase uniformly in the directions 1 to 3 and 6 to 4 of the table, and attaining a maximum about mid-way in Classes 3 and 4. Apparently he was of opinion that in general the percentage of volatiles yielded by a coal diminishes with its geological age, a view which many chemists have held, but which the author regards as questionable and misleading. Certainly the coals included in the first four classes of the table are all of Carboniferous (or Permo-Carboniferous)

[1] *Grundriss der Eisenhüttenkunde*, p. 46.

origin, and an attempt to discriminate between their respective geological ages on the grounds of chemical properties or behaviour alone is of doubtful validity. Wedding indeed qualified this view by the further statement that the properties of the seams in a grown coalfield are subject to considerable variations according to the thickness of the overlying strata.

The weak point about such a classification is that it does not discriminate sufficiently between the valuable semi-bituminous (volatiles = 15 to 20) and hard coking (volatiles = 20 to 33) classes, otherwise it is quite a useful scheme for metallurgists and has the advantage of not depending on the exact ultimate analysis of the coal.

C. A. SEYLER'S CLASSIFICATION

Mr. C. A. Seyler, as the result of a special study of the coals of South Wales, which comprise numerous varieties ranging from bituminous through semi-bituminous and anthracitic coals up to anthracites, has put forward a chemical classification based upon the percentages of carbon and hydrogen in the pure coal substance (see Table XXI).[1] He divides coals into five principal genera, according to their hydrogen contents; each genus is then sub-divided into a number of species according to the percentage of carbon. The classification thus really depends on two factors, namely, in the first place upon the hydrogen content, and in the second, upon a C :'H ratio.

Drs. A. Strahan and W. Pollard, of the Geological Survey of England and Wales, in [their recent *Memoir upon the Coals of South Wales* [2] adopted Seyler's general plan and nomenclature as one of the best so far available for the purpose of scientific classification, and defined the observed limits for the five principal genera as follows :—

TABLE XXI

Genus.	Percentage H.	Ratio.
1. Anthracitic	under 4·0	over 22
2. Carbonaceous	4·0 to 4·5	20·3 to 23·35
3. Semi-bituminous	4·5 to 5·0	16·6 to 20·4
4. Bituminous	5·0 to 5·8	14·6 to 18·2
5. Per-bituminous.	over 5·8	12·9 to 14·7

[1] *Proc. S. Wales Inst. Engineering*, XXI., p. 483, and XXII., p. 112.
[2] First edition 1907; second edition 1915.

Also the United States Geological Survey, independently of Mr. Seyler's previous work, and after considering several other possible schemes, finally adopted the following classification which is also based upon the C : H ratio in the pure coal substance.[1]

TABLE XXII

Group.	Description.	Ratio C : H.
A.	Graphite	
B. } C. }	Anthracite	{ ? to 30 { ?30 to 26
D.	Semi-anthracitic	?26 to 23
E.	Semi-bituminous	?23 to 20
F. } G. } H. } I. }	Bituminous	{ 20 to 17 { 17 to 14·4 { 14·4 to 12·5 { 12·5 to 11·2
J.	Lignitic	11·2 to 9·3 ?
K.	Peat	?9·3 to ?
L.	Wood	7·2

Whilst there thus seems to be a considerable weight of geological opinion in favour of adopting the C: H ratio for the pure coal substance as the most satisfactory basis of classification at present available for their purposes, chemists will hardly rest satisfied with any such empirical scheme. Sixty years ago (1857) W. Stein in his well-known *Chemische und Chemisch-technische Untersuchangen der Steinkohlen Sachsens* pointed out the uncertainty of conclusions concerning the properties of coals based merely upon the percentages of carbon and hydrogen, respectively, which they contain. Again, in 1898, W. Carrick Anderson and Roberts, in reporting the results of their investigation upon some typical Scottish coals of the Lanarkshire and Stirlingshire coalfields, remarked that the outstanding feature was the close approximation in elementary chemical composition of coals drawn from localities geographically far apart and from strata of different geological age, quoting as an example the close similarity between the ultimate composition of the famous Lanarkshire splint coal and those of the soft coals both above and below it.[2] The author's own investigations upon typical English coals have brought to light some interesting examples of coals possessing

---

[1] *Report on the Coal Testing Plant of the U.S. Geol. Survey*, Vol. I., 1906, pp. 156–73.

[2] *Journ. Soc. Chem. Ind.*, 1898, p. 1013.

quite different properties whose elementary compositions are very similar.

Certainly no present-day chemist who is familiar with the innumerable cases of isomerism among the compounds of carbon would for a moment accept any view which implied that such isomerism is not to be met with in coals. Coal is, of course, not a single homogeneous substance, but a heterogeneous mixture, in varying proportions, of several different types of substances of great molecular complexity which probably individually exist in many isomeric forms. And no classification can be regarded as satisfactory from a chemical standpoint, however useful it may be in other respects, which does not in some way or other take into account the nature and proportionate distribution of the principal constituents in the coal substance. Unfortunately, owing to our scanty knowledge of such matters, sufficient data for such a classification are not yet forthcoming.

CHAPTER VI

THE CHEMICAL COMPOSITION OF COAL (*contd.*)

D. THE CONSTITUENTS OF THE COAL SUBSTANCE AND THE ACTION OF VARIOUS REAGENTS AND SOLVENTS THEREON

I. GENERAL

IF, as has been explained in the preceding chapters, the coal substance may be regarded from a chemical standpoint as essentially a mixture in variable proportions of the degradation or transformation products of the ligno-celluloses, proteids, and resinous matters comprising the original vegetable *débris*, it is all-important to know not only how far chemists have succeeded in detecting, or discriminating between, these several products in the coal substance, but also how each class of products is likely to affect the properties and uses of the coal, and especially how each class behaves when the coal is subjected to destructive distillation. For, viewed even from the lowest plane of immediate practical utility, our chemical knowledge of coal must be considered deficient until we are able, not only to give a rational analysis of any particular coal, but also to predict the influence of each type of constituent upon the behaviour of the coal at all temperatures, and upon the yields of the various products obtainable when it is distilled at any given temperature. And although it cannot be said that we have as yet reached such a point, it is well to know what should be the immediate goal of our endeavours, and what progress is being made in its direction.

Among the parent substances in the organic *débris* from which coals have originated, we are chiefly concerned with the following three principal classes:—

(a) *Celluloses*, i. e. ligno-celluloses, essentially carbohydrates $n(C_{12}H_{18}O_9)$ of a cyclic type.

(b) *Resinic*, i. e. gums, resins, and waxes, all of which are compounded of carbon, hydrogen, and oxygen, but may belong to many different chemical types.

(c) *Nitrogenous*, i. e. proteid bodies, or compounds of carbon, hydrogen, oxygen, nitrogen, and sulphur.

73

These bodies have, during the formation of coal, been subjected first of all to the disintegrating influence of decay, as in modern peat bogs, followed by the combined action, continued through long geological ages, of great pressure and a slowly rising temperature, which latter, however, has certainly not exceeded 300° C. and may have been considerably less. In such circumstances the relatively unstable cellulosic and proteid constituents would certainly undergo such profound changes as would mask, if they did not entirely obliterate, their original characters, whilst it might be expected that the more stable resinous constituents would be affected to a considerably less degree.

There is some evidence also that small quantities of hydrocarbons are present in coals, whether associated with the resinic constituents or independently of them is not yet quite certain, but they are neither so prominent nor invariable as the three principal types which may now be considered more in detail.

(a) Cellulosic (or Humic) Derivatives

Renault in his well-known researches upon peat found that fungi and anaerobic bacteria play the most important part in the preliminary breakdown of the vegetable fibre into ulmic or humic compounds of the average composition :—

$$
\begin{aligned}
\text{Carbon} &= 65\cdot30 \\
\text{Hydrogen} &= 3\cdot85 \\
\text{Oxygen} &= 30\cdot85
\end{aligned}
$$

Mulder, Einof, Proust, and Braçannot have identified such bodies as the chief " cellulosic " constituents of peat, whilst Herz has found similar substances, which he called carbo-humic and carbo-ulmic acids, in lignites, and to which he assigned the following average composition :—

	Carbon.	Hydrogen.	Oxygen.
Carbo-ulmic acid . . .	62·36	4·77	32·87
Carbo-humic „ . . .	64·59	5·15	30·26

In 1897 H. von Feilitzen and B. Tollens,[1] reporting the results of their chemical researches upon peat and its formation, stated that the cellulose content of a peat bog examined by them

[1] *Ber. deut. Chem. Ges.*, 1897, **30**, pp. 2571 to 2584.

rapidly diminished with the depth, as the following figures show :—

	Mean Percentage of Cellulose.
Sphagnum cuspidatum at surface	21·1
Peat { at 20 to 100 c.m. below surface . . .	15·20
„ 100 „ 200 „ „ „ . . .	6·87

Similarly they also found that the quantity of pentosans $C_5H_8O_4$ present in the dry peat rapidly diminishes, and at the same time the total carbon content increases in almost like proportion, with the depth, as follows—

	Percentages in the Dry Peat.	
Depth below Surface in c.ms.	Pentosans.	Total Carbon.
20 to 100	12·75	51·08
100 „ 200	9·75	53·52
200 „ 300	5·87	58·66

These observations indicate how quickly the original cellulose, or other carbohydrate constituents of vegetable tissue, may be transformed into other products under the influence of decay organisms in a peat bog; and therefore, whilst in some lignites the original woody structure is well preserved, it is not to be expected that the original cellulose or ligno-cellulose is present in coals except in a greatly altered condition. The well-known fact, however, that both dry woody tissue and the coal substance show an early elimination of water when moderately heated in absence of air strongly suggests a "cellulosic" type of constituent as predominant in coal. Moreover, in 1901 S. Stein[1] obtained black products resembling coal in both outward appearance and elementary composition (C = 81·3 and H = 3·8 per cent.) by heating wood with water in sealed tubes to 290° C. for five hours, whilst more recently Bergius, by heating cellulose under pressure to a temperature of 340° C. has produced an "artificial coal" of the composition :—

	Per cent.
Carbon	84·0
Hydrogen	5·0
Oxygen	11·0

[1] *Chem. Centralblatt*, 1901, ii. 950 and *J. C S. Abstracts*, 1902, ii. p. 87.

(b) *Nitrogenous Constituents*

Vegetable proteid matter is even more susceptible than cellu-losic bodies to the influence of decay organisms, and therefore, whilst the nitrogenous constituents of present-day coals may be regarded as having probably originated from proteids, they can only have survived in very greatly altered forms.

The elementary composition of proteids varies between the following limits:—

				Per cent.
Carbon	.	.	.	50·0 to 55·0
Hydrogen	.	.	.	6·9 „ 7·3
Nitrogen	.	.	.	15·0 „ 19·0
Oxygen	.	.	.	19·0 „ 24·0
Sulphur	.	.	.	0·3 „ 2·4

Now since the nitrogen of coal usually varies between 0·75 and 1·75 per cent. with an average of, say, 1·25 per cent., it would seem unlikely that the amount of proteid degradation products contained in them exceeds on the average 10 per cent. of the total coal substance, and the proportion may be even less.

If a coal be heated out of contact with air, the evolution of ammonia is first observed, according to Carrick Anderson and Roberts, at 333° C. in the case of a gas coal, and at 480° in the case of anthracitic types. Later on, M. G. Christie in an investi-gation upon the nitrogenous contents of peat, gas coals, and anthracites, proved that whilst the evolution of ammonia begins at about 350° C. in the case of a gas coal, and at 450° in the case of anthracites, the principal evolution occurs between 500° and 700°, after which it almost ceases.[1] Only a small portion, usually not exceeding one-fifth, of the total nitrogen is ever evolved as ammonia in this way, the greater part of it remains firmly held in the residual coke. O. Simmersbach[2] has recently studied in great detail the distribution of the nitrogen between coke, tar, ammonia, hydrogen cyanide, and free nitrogen at various tem-peratures of carbonisation from a Silesian coal containing 1·396 per cent. nitrogen and 6·63 per cent. ash.

[1] *Inaug. Diss. Aachen*, 1908.
[2] *Stahl und Eisen*, 1914, **34**, 1153 and 1209

TABLE XXIII

Carboni-sation Tem-perature C.°	Percentage of the Nitrogen appearing in				
		Gas.	NH₃.	Tar.	HCN.
600	71·69	18·13	7·81	2·12	0·25
700	65·43	12·13	18·13	3·65	0·66
800	63·65	10·73	21·28	3·47	0·87
900	58·40	12·14	24·12	4·15	1·19
1000	49·98	21·53	23·15	4·11	1·23
1100	41·39	30·51	23·09	3·70	1·31
1200	26·43	45·10	22·84	4·21	1·42

It will thus be seen that the maximum formation of ammonia occurs at 900°, whilst upwards of 50 per cent. of the nitrogen remains in the coke up to 1000° and more than 25 per cent. at 1200°.

The distribution of its nitrogen when coal is distilled on a large scale may be illustrated by the following table of average results obtained (1) in testing some eighty Scottish coals (N = 0·915 up to 1·873 per cent.) at the Provan Gas Works in Glasgow, under conditions prevailing in a modern gas-retort, and (2) in coking a Durham coal (N = 1·57 per cent.) in Otto-Hilgenstock ovens at Blayden-on-Tyne.[1] It will be observed that the principal effect of the higher temperature in the coke oven as compared with the gas-works retort was to drive more nitrogen (as N_2) out of the residual coke, although it also caused a perceptible, though not material, lowering of the yields of ammonia and other basic nitrogen products.

		Gas-works.	Coke Ovens.
Percentage of the Original Nitrogen	remaining in the coke . . .	58·3	43·31
	appearing as bases in the tar .	3·9	2·98
	recovered as ammonia . . .	17·1	15·16
	,, ,, cyano-compounds	1·2	1·43
	appearing as N_2 in the gas . .	19·5	37·12
		100·0	100·00

It thus appears that in large-scale distillation operations not more than 20 per cent. of the original nitrogen is recovered as ammonia and that upwards of 40 per cent. of it remains in the

[1] A. Short, *Journ. Soc. Chem. Ind.*, 1907, p. 581.

coke, even though the contents of the carbonising chamber have been raised to between 1000° and 1100° C.

So firmly is the residual nitrogen combined in the coke that, according to M. G. Christie's researches (*loc. cit.*), it is only very slowly expelled from it (as free nitrogen) as the temperature is gradually raised from 900° to 1900° C., and he considers it to be present in the original coal in an extraordinary stable " nitride " form as distinguished from the much less stable " imino " nitrogen existing as organic compounds which decompose below 900° C. yielding ammonia. Harger,[1] who has drawn attention to the very different results obtained in the estimation of nitrogen in coal by the Dumas and Kjeldahl methods respectively, also discriminates between what may be termed the " ammonia-yielding " nitrogen, which he suggests exists in a side chain in the parent molecule, and the " fixed nitrogen " which is stable at red heat, and which he thinks is probably present in some ring formation.[2] It therefore seems necessary to recognise the presence of at least two types of nitrogenous constituents of widely different stabilities in coal, each of which behaves according to its own nature on distillation. And the existence of so stable a type as that which Christie has designated the " nitride " constituent is in itself proof of the profound changes which the original proteid matter must have undergone in the process of coal formation.

It has been shown by the researches of Carrick Anderson and others that the nitrogenous constituents of coal are without influence upon its caking properties; the proteid origin of these compounds also accounts for the occurrence of " organic " sulphur in coal.

(c) *The Resinic Constituents*

The occurrence of fossil gums and resins has been frequently observed in peats, lignites, and other Tertiary coals. Mulder isolated from Friesland peats a number of resins similar to those which he had observed in lignites from districts as far apart as Saxony, Moravia, and New Zealand. Carrick Anderson and Henderson[3] in a report upon some Japanese coals noted the frequent occurrence in them of pieces of clear bright resin of the size of peas or beans, an observation which the author

---

[1] *Journ. Soc. Chem. Ind.*, 1914, p. 389.   [2] *Ibid.*
[3] *Ibid.*, 1902, p. 241.

can confirm from his own experience with certain Manchurian coals.

With regard to British coals, as long ago as 1838 James F. W. Johnston [1] isolated round masses of resin, seldom larger than a pea, from the coals of the Middleton Collieries near Leeds, and reported having observed thin layers of resinous materials between those of the coal. Analyses of the isolated resin masses were made, showing the following mean composition:—

$$
\begin{aligned}
\text{Carbon} &= 86\cdot2 \\
\text{Hydrogen} &= 8\cdot0 \\
\text{Oxygen} &= 5\cdot8 \\
\hline
&\ 100\cdot0
\end{aligned}
$$

Mallet [2] also has published the following analyses of a fossil resin which was found in " small drops or tears of round or ovoid forms varying from the size of a pea to that of a hazel nut " in the coal measures in the neighbourhood of Wigan. It contained no nitrogen:—

	(1)	(2)
Carbon . . .	76·74	77·15
Hydrogen . . .	8·86	9·05
Oxygen . . .	10·72	10·12
Ash . . .	3·68	3·68
	100·00	100·00

Recently an American investigator, White, of the United States Geological Survey, has drawn attention to the evidence of the widespread occurrence of resinous constituents in coals of all ages, and has given the following particulars of the composition of a resin cast from a Montana coal:—[3]

	As Taken. %	Ash-free. %
Carbon . . .	72·69	76·40
Hydrogen . . .	8·85	9·30
Oxygen . . .	13·61	14·30
Ash . . .	4·85	—
	100·00	100·00

[1] *Phil. Mag.* (iii.), 12, p. 261. [2] *Ibid.* (iv.), 4, p. 261.
[3] *U.S. Geol. Survey Paper* 85 E., pp. 65 to 83.

It is probable, as White has remarked, that the carboniferous floras were at least as richly productive of resinous substances as those of later periods, and inasmuch as the chemical stabilities of such resins, when exposed to the action of decay organisms, are presumably much greater than those of either celluloses or proteids, it seems reasonable to suppose that they have undergone less alteration during the long transformation process, although it is probable that various "condensation" changes have occurred. It is therefore to be anticipated that the resinous constituents of coal will exhibit much less divergence from their parent types than do the degradation products of either the celluloses or proteids.

On the other hand, chemical investigation seems to show that the resinic constituents may be expelled or decomposed by heat fairly readily at comparatively low temperatures. Thus Carrick Anderson and Henderson found that the resinic constituents of certain non-caking Scottish coals could be driven off by heating them to between 300° and 315° C in a current of carbon dioxide. The mixture of resins, with possibly other bodies, so eliminated had an elementary composition (C = 80·7, H = 9·5, and O — 9·8 per cent.) not unlike that of ordinary resin. Also it was found that the coking properties of caking coals were greatly impaired by such removal of resinic bodies.

The later researches of R. V. Wheeler and other workers indicate that the resinic constituents rapidly decompose between 400° and 700° C. yielding chiefly paraffin hydrocarbons but little hydrogen, within which temperature range also the cellulosic derivatives certainly lose water (water of constitution) if they do not further decompose. Moreover, it is probably the rapid decomposition of the resinic constituents at comparatively low temperatures which is responsible for the long luminous flames and black smoke produced when raw bituminous coals are burnt in furnaces.

It may here be remarked that the term "resin" includes a large number of complex substances, of widely different chemical types, which are difficult to classify on any scientific plan. They are all (or nearly so) of vegetable origin, and are regarded by physiologists as waste products of plant metabolism, in which case those derived from plants of the same genus or order might be expected to have a similar chemical constitution. They are chiefly obtained either by the spontaneous evaporation of oleoresinous juice exuded from the trunks of trees, or by the extrac-

tion of other parts of plants by means of such solvents as alcohol or ether, or they are found as " minerals " (*e. g.* amber) which have undoubtedly been produced by extinct vegetation.

They are all more or less amber-like, translucent and amorphous solids, or semi-solids, which soften at temperatures much below their melting points, which are rather indefinite. They exhibit in a marked degree the phenomenon of superfusion, and whilst insoluble in water, they are generally soluble in alcohol, ether and chloroform, from which solutions they may be precipitated in a colloidal form by the addition of any electrolyte such as aqueous hydrochloric acid. In this way they may be obtained as a white precipitate which slowly turns brown, owing to internal molecular rearrangements. The latter are independent of the influence of either oxygen or light.

In their natural condition resins are not chemically homogeneous, but are mixtures of allied substances. As a rule they contain (*a*) a *resinol acid*, which apparently contains both OH and COOH groups; (*b*) a saponifiable *resine* ester; and (*c*) a non-saponifiable *resene*, which is inert towards alkalies. They are termed resinol-resins, resine-resins, or resene-resins, according as constituent *a*, *b*, or *c* predominates. They also usually contain a carbonyl CO group. Another class of resins, known as resino-tannols, contain one or more of the constituents *a*, *b*, *c*, together with a tannic acid complex, and are fermentable. A recent authority, commenting upon the difficulty of defining or classifying resins, has remarked:[1] " So widely do the various resins that have been studied differ from one another chemically, that it seems likely that as a class they will ultimately disappear, being taken to fill in groups here and there in the structure of organic chemistry."

The mere knowledge that coals contain " resinic constituents " does not, therefore, carry us very far. No one has been able to define their real chemical nature; nor is it yet possible to say whether or not they differ in different types of coal, and if so, then to what extent. Before such questions can be satisfactorily answered much further chemical research is needed.

[1] Prof. A. Senier in his article upon " Resins " in Thorpe's *Dict. of Applied Chemistry*, Vol. IV., p. 559. The reader is also referred to A. Tschirch's *Die Harze und die Harzebehälter*, Leipzig, 1900.

COAL AND ITS SCIENTIFIC USES

II. Methods of Chemical Investigation

The methods hitherto employed by chemists in investigating the nature of the coal substance may be summarised under three principal heads, namely:—

(i) Chemical attack by means of various reagents which oxidise, decompose, or otherwise alter the coal substance.

(ii) The action of solvents which are supposed to extract fractionally certain constituents without radically altering them.

(iii) The action of heat, *i. e.* distillation either of the original coal or of certain extracted constituents thereof at definite temperatures and the examination of the various products so obtained.

The general character of the results yielded by the first two of these methods will be discussed in this chapter, leaving the third method to be dealt with separately later on.

(i) *Chemical Attack by Reagents.*—The reagents chiefly employed have been sulphuric and nitric acids, caustic alkalies, bromine, ozone and oxygen. Coal being a heterogeneous mixture of complex substances, all of which are amorphous, and most of them in forms which are imperfectly soluble in any known reagent, the chemist has naturally endeavoured to transform some of them by known chemical treatment into simpler and more easily definable products, capable of separation, purification, and recognition by ordinary analytical methods. Such attempts, however, have been largely abortive, because although such transformation products can be obtained, the yields are either so small, or the products themselves are in such an advanced stage of decomposition, that they afford but little reliable evidence as to the nature of the original coal constituents. And, again, where higher yields or less degraded products have been obtained, they have usually consisted of inseparable mixtures or solutions of amorphous or colloidal bodies which almost preclude further analysis. Incidentally, however, a good deal of valuable general information has accrued as the result of such experiments.

In 1891–2 Friswell[1] pointed out that by treating coals with dilute nitric acid some portions thereof may be converted into lustrous black and brittle substances, insoluble in water but

[1] *Proc. Chem. Soc.*, 1891–2, p. 9.

ᵗˡv forming dark solutions.

ᵗᵛᵃ precipitation of

.ᵤᶜ in solutions of

.ᵢ ᵢᵉ extent in pure

ᶜquently applied this

ᵗᵢⁿg that the resulting

.. were of a fairly definite

.tᵣ:—

ᶜᵉnt.

ᵢ to 63·5

- 75 „ 3·3

:ᵣ·o „ 32·5

3·3 „ 4·8

0·3 „ 0·7

.ᶜ obtained from both caking and non-

.ᵤⁿ of nitric acid was exothermic and

ᵢₐt amounting to between 10 and 23 per

...ᶜ coal taken.[2] The fact that a preliminary

ᵢᵣᵢⁿous constituent by heating the coal to

.ₐt of carbon dioxide did not materially affect

.ᵤᵗᵉ nitric acid, or the character of the resulting

ᵢᵤᶜᵗs, proved that those " coal acids " are derived

ᵢᵢₒᵣic or proteid constituent, or more probably from

ᵗₕₐt the constant presence of sulphur therein is a

ᵣ proof of the existence of " organic " sulphur in

ᵛ has shown that a mixture of monohydrated sulphuric
ᵣᵢ·ᵣic acids will dissolve lignites as well as bituminous coals,
rise to acidic oxidation products which he termed " ulmic "

.ᵣ Also Boudouard[3] has stated that in his experiments
ᵢᵣₒ spheric oxidation at 100° produced " humic " acids which,
ᵗ·ᵣr extraction by means of potassium hydroxide solution and
ᵤbsequent reprecipitation and purification, gave analytical
results corresponding to one or other of the formulæ $C_{18}H_{14}O_6$,
$C_{18}H_{16}O_9$, or $C_{18}H_{14}O_{11}$. He also observed that the invariable
effect of such atmospheric oxidation is to destroy completely
the coking properties of a coal, and to increase the proportion
of " volatiles " expelled from it on carbonisation.

[1] *Journ. Soc. Chem. Ind.*, 1898, p. 1013.
[2] *Proc. Glasgow Phil. Soc.*, 29, pp. 72 to 96.
[3] *Compt, rend.,* 1908, 147, 986, and *Bull. de la Soc. Chim.*, 5 (Series 4)
378 (1909).

In 1912 Donath and Bräunlich,[1] having previously investigated the action of dilute nitric acid upon coals, extended their work to a study of the products obtained by repeated fusions of the coal substance with alkaline hydroxide (e. g. KOH) at 250° and subsequent extraction with water. Brown coal, charcoal, and carbonised organic materials generally were found to give dark brown solutions, whilst those given by bituminous coals, coke, and graphite were colourless. Brown coals were almost completely converted into humic acids which could be separated into two fractions, one of which (1) was completely soluble in concentrated alkali, whilst the other (2) required the alkali to be very dilute   After precipitation from their respective alkaline solutions by acid a further difference was found between the two fractions in that (1) was completely soluble, and (2) insoluble in a 10 per cent. solution of ammonium carbonate. Fraction (1) contained, besides oxalic acid, a crystalline substance which gave a red coloration with ferric chloride, and a fatty acid. It was also found that a mixture of equal volumes of concentrated nitric and sulphuric acid reacts violently with brown coals and wood, but only slowly with true coals.

Similar results to the above have been obtained in the author's laboratory by the potash fusion method, but it is extraordinarily difficult to separate any pure substance from the resulting complex mixture of acid products. In one experiment, however, a small quantity of a crystalline acid, melting at 149°, and possessing other similar properties to those of adipic acid, $CO_2H \cdot (CH_2)_4 \cdot CO_2H$ was obtained. A mixture of this acid with an equal quantity of pure synthetic adipic acid melted also sharply at 149°, so that the identity of the two was thus satisfactorily established.

With regard to the action of halogens, it has long been known that bituminous coals react with bromine in the coal, as though they contain " unsaturated " or cyclic groups. In this connection it is interesting to note that in 1901 Fischer of Göttingen found that coals which are most liable to rapid oxidation and spontaneous ignition are also those which absorb bromine most readily,[2] a subject which will be again referred to in Chapter IX when the spontaneous oxidation of coal is considered. A research is in progress in the author's laboratory upon the absorption of bromine by coals, the result of which has shown that the halogen acts upon bituminous coals in the cold possibly by

[1] *Chem. Zeit.*, 1912, **86**, p 373.   [2] *Gas World*, April 13, 1901.

 ·n " and " adsorption."
·, after twenty-four hours,
drogen bromide is evolved.
recently published a paper [1] in
··n of coal extracted by pyridine
Cross and Bevan [2] have shown
' by chlorine with the production
·· imilar to that previously obtained
·· sue, also that the coal is so profoundly
potassium chlorate and dilute hydro-
·ne entirely soluble in alkalies. By
·r separation by means of suitable organic
acetone) a series of complex chlorinated
·lucts was obtained.
·· work which must be noticed in this review is
r and Gluud, who have found that by suspend-
·· ·r through which a stream of ozone is passed, it
·olves, forming a dark brown solution of a sub-
·· has the smell of caramel and a pronounced acid
i· slightly soluble in alcohol, sparingly so in ether,
··st insoluble in light petroleum. The investigation of
·· ·r is being pursued further by them.[3]
action of oxygen upon coals will be fully considered in
··r IX hereof.

·) *The Action of Solvents.*—This method of attacking the coal
·· ·tion is, whenever applicable, undoubtedly preferable to either
· the other two, inasmuch as it enables substances to be extracted
with the minimal alteration to the coal substance. The diffi-
culty is to find solvents that will differentiate sufficiently between
the main constituents of the coal and extract a large proportion
of some one of them, without at the same time having some
depolymerising or other similar action upon the whole structure.

Smythe's Work.—One of the first workers to employ the method
systematically was J. A. Smythe, who investigated at Göttingen
the solvent action of benzene, chloroform, ethyl alcohol, ethyl
ether, light petroleum, and acetone, in the order named, upon
a brown coal from Brühl near Cologne. Of these ethyl ether
and petroleum ether were found to have very little effect upon
the coal, whilst benzene, chloroform, and alcohol all extracted

· [1] *Journ. Gasbeleuchtung*, 1915, **58**, p. 515
[2] *Phil. Mag.* 5 Sec. XIII., p. 328.
[3] *Ber. deut. Chem. Ges.*, 1916, **49**, 1472.

quantities of resinous bodies varying between 1·8 to 3·0 per cent. of the whole coal substance.

From the chloroform extract (1·8 per cent.) which was deep brown in colour, there was precipitated by the addition of petroleum ether to its solution, a brown amorphous resin, melting at 94° with slight decomposition, and having a composition (C = 76·45, H = 9·91, O = 13·64 per cent.) approximating to the formula $C_{18}H_{24}O_2$.

The dark brown benzene extract (3 per cent) could be further divided into two portions, the one soluble and the other insoluble in ether. From the portion soluble in ether boiling acetone extracted a pale yellow amorphous resin melting at 78° to 80°. The portion insoluble in ether on distillation under a pressure of 8 m.m. came over between 300° and 350° C., condensing to an amber-coloured liquid which set to a light yellow waxy solid. After purifying this by treatment with a mixture of benzene and petroleum ether, it was finally obtained as a perfectly white crystalline solid melting at 81° to 82°, having a composition agreeing with the formula $C_{13}H_{26}O$. The whole scheme for the fractionation and purification of the original benzene extract was as follows:—

BENZENE EXTRACT (3 per cent.)	(a) SOLUBLE IN ETHER	BROWN AMORPHOUS POWDER m.p. 135° to 140° $C_{14}H_{18}O_2$	PORTION SOLUBLE IN ACETONE Pale Yellow Solid, m p. 78° to 80° C 79 23, H 12 83, O 7 97
	(b) INSOLUBLE IN ETHER	AMORPHOUS POWDER m p 80° to 83° C 77 75, H 11 77, O 18 48 per cent	DISTILLED UNDER 8 m m PRESSURE White Crystalline Solid $C_{13}H_{26}O$, m.p. 81° to 82° C 79·18, H 13 04, O 7 78

The most notable feature of these results is the close resemblance between the chemical composition and physical properties of the end products obtained by the purification of the two fractions *a* and *b*; they are both resins melting at 80° and having a composition conformable with the formula $C_{13}H_{26}O$.

The Action of Pyridine.—In 1899 P. P. Bedson, in a paper before the North of England Institute of Mining Engineers, drew attention to the fact that pyridine has a remarkable solvent action upon bituminous coals, and subsequently, at his suggestion, P. Baker examined its action upon four different coals,

(1) a South Wales Anthracite, which was practically effected by it; (2) a Durham Gas Coal (Hutton Seam) from which 20·4 per cent. was extracted; (3) a Durham Coking Coal (Brockwell Seam), which yielded 11·5 per cent.; and (4) a New Zealand Brown Coal, which yielded 5·65 per cent. Carrick Anderson was also informed of the method, and used it in his researches upon the coals of Bengal and Japan in 1902.[1] The details of Bedson's own work were ultimately embodied in a paper read before the Newcastle-on-Tyne Section of the Society of Chemical Industry in 1908,[2] since which time the method has been extensively employed by other investigators, who have considerably added to our knowledge of its significance.

As originally introduced by Bedson, the method consisted essentially in submitting a weighed amount of the finely divided coal to the action of pyridine in a Soxhlet extraction apparatus for several hours. From the pyridine solution so obtained, after removing the greater portion of the solvent by distillation under reduced pressure, the dissolved matter was precipitated by dilute hydrochloric acid, filtered off, and subsequently washed, dried and weighed. The portion of the coal undissolved by the pyridine was also washed to free it from any of the retained solvent, and finally dried and weighed. This treatment was afterwards modified by him in the following particulars:—(1) the coal was ground so as to pass through a sieve of 30 meshes to the linear inch, (2) 5 grams of it were mixed well with sufficient sand to make a column rising to the top of the syphon tube of a Soxhlet apparatus, the mixture of coal and sand resting in the apparatus upon a layer of broken clay pipe-stems and a pad of absorbent wool, (3) the extraction of the coal was allowed to proceed for several hours until it was judged to be complete by the absence of colour in the pyridine flowing through the syphon tube of the Soxhlet apparatus, and (4) the solution was finally brought into an evaporating basin and the pyridine evaporated off in a good current of air; the dried residue was then broken up and heated on the water bath until the odour of pyridine had disappeared.

The pyridine solutions so obtained from coals are dark brown in colour with, sometimes, a green fluorescence, and the proportion of the coal substance extracted ranges from practically zero in the case of anthracites up to between 35 and 40 per cent. in the case of a good gas coal. The extract remaining after the

[1] *Journ. Soc. Chem. Ind.*, 1902, p. 241.   [2] *Ibid.*, 1908, p. 147.

solvent has been driven off is a chocolate brown amorphous solid, which on ignition decomposes with intumescence, yielding a large proportion of " volatiles " and a swollen residue of coke.

Bedson published the following particulars (Table XXIV) of results obtained with six different gas coals procured from the Redhaugh Gas Works, Newcastle-on-Tyne, with which the actual working results as regards yields of gas and coke had been definitely established at the works.

TABLE XXIV

PROFESSOR P. P. BEDSON'S EXPERIMENTS WITH COALS FROM REDHAUGH GAS WORKS

Coal.	Yield of Gas Cub. Ft. per Ton.	Illuminating Power of Gas Candles.	Yield of Coke Cwt. per Ton.	% Ashes in Coke.	Percentages on Coal.		Percentages on Dry Ashless Coal.	
					Volatile.	Pyridine Extract	Volatile.	Pyridine Extract
A.	11,381	16·63	13·55	8·53	34·10	32·36	35·69	33·86
B.	11,392	16·50	13 51	8 92	33 28	33·59	34·60	34·93
C.	11,646	16·40	13 73	8 50	31 91	24 58	34 78	26 80
D.	11,108	16·00	14·25	7·80	31·70	22 81	33·47	24 08
E.	10,913	10·39	13·36	10 80	33 65	29 97	36 39	32·42
F	10,730	15·76	13 29	15·12	30·87	22·53	33 48	24·43

The Manager of the Redhaugh Gas Works (Mr. Thomas Hardie) described A and B as " good " gas coals, C and D as " medium," whilst E and F he regarded as being " bad " ones, but from Bedson's experiments there was apparently no correlation between the amounts of pyridine extracts obtained from them and either their gas making qualities or their yields of volatiles. As the result, however, of investigation upon these and other coals, including typical Durham coking varieties, Bedson was able to say that " the extracts in each case were found to be rich in volatile constituents, and in the coking assay gave highly intumescent cokes, whereas the residues left after extraction were almost devoid of coking properties. In the case of the coking coal from the Brockwell Seam, the portion insoluble in pyridine had not completely lost the coking power, but yielded a coke much less bulky than that left by the original coal." Also that in an examination of the different parts of the Busty Seam coal from Birley, Co. Durham, the " bright coal " contained considerably more matter extractable by pyridine than the associated " dant " or " mother of coal," for whereas the " bright

10·38 per cent. of extract, the "dant" behaved to anthracite and yielded only a fraction of a per cent.

Wheeler and his co-workers [1] have further examined method which, if supplemented by a subsequent chloroform tion of the original pyridine extract, they consider may be for the complete separation of the cellulosic and resinic stituents of coal. The method of extraction employed by m was as follows :—

The coal, ground to pass through a sieve of 94 meshes to the linear centimetre, was extracted in separate portions of 10 grams (each contained in a filter paper thimble) in a Soxhlet apparatus. The flask of each extraction apparatus contained about 200 c.cs. of pure pyridine which was kept gently boiling on an electrically heated sand bath, overheating being carefully guarded against. Each 10 grams portion was treated for a week continuously, the pasty mess in the thimble well stirred, and then further extracted for a week with fresh pyridine.

When extraction was complete, the solution was filtered and the pyridine distilled at 60° under reduced pressure, a fine stream of air being allowed to bubble through the liquid to ensure rapid evaporation. When most of the pyridine had been removed in this way, the mass remaining in the distillation flask was washed out on to a clock-glass by a fine jet of warm pyridine. Removal as far as possible of the last traces of pyridine was effected by heating the clock-glass at a temperature of 80° in a current of dry air, and, after being ground to a fine powder, the chocolate-coloured solid was finally kept in a vacuous desiccator over strong sulphuric acid to complete the removal of pyridine. The residue of the coal, insoluble in pyridine, was washed with ether, and then heated in a similar manner to the dried extract.

To obtain the chloroform extract, 10 grams of the dried pyridine extract were treated in an extraction thimble in a Soxhlet apparatus with 200 c.cs. of pure chloroform for two weeks on a water bath, and the chloroform then distilled off in a partial vacuum. The chloroform extract and the residue were freed from chloroform in a manner similar to that employed by freeing the pyridine extract and residue from pyridine.

The results obtained by Wheeler and Clark on subjecting a typical bituminous coal to the aforesaid double extraction, by

[1] Burgess and Wheeler, *Journ. Chem. Soc.*, 1911, **99**, p. 649. Clark and Wheeler, *ibid.*, 1913, **103**, p. 1704.

which means they claim to have made " a complete, or nearly complete, separation between the resinous constituents and the degradation products of the celluloses of which coal is conglomerated," are shown in the following diagram :—

% COMPOSITION
C = 82·92
H = 5·58
N = 1·35
S = 1·70
O = 8·45

COAL (VOLATILES = 36·73 per cent.)

SOLUBLE IN PYRIDINE ↗ = 20

SOLUBLE IN CHLOROFORM ↗ = 4

$\begin{cases} C = 85\cdot33 \\ H = 7\cdot08 \\ N = 1\cdot71 \\ S = 1\cdot32 \\ O = 4\cdot56 \end{cases}$ VOLATILES = 77·33 per cent.

INSOLUBLE IN CHLOROFORM ↗ = 16

$\begin{cases} C = 77\cdot32 \\ H = 5\cdot14 \\ N = 2\cdot07 \\ S = 1\cdot21 \\ O = 14\cdot26 \end{cases}$ VOLATILES = 31·88 per cent.

INSOLUBLE IN PYRIDINE ↗ = 80

$\begin{cases} C = 80\cdot81 \\ H = 5.23 \\ N = 2\cdot14 \\ S = 1\cdot41 \\ O = 10\cdot41 \end{cases}$ VOLATILES = 34·96 per cent.

In view of the claim made by the authors in question, it is to be regretted that they did not investigate, and define more closely, the physical properties of their final products, and as they stand, the above results are open to three criticisms, namely :—(1) that the sum total of nitrogen in their products is nearly double that in the original coal treated, showing that some of the solvents had been retained by the various fractions, despite the pains taken to remove it, (2) that a product containing as much as 1·71 per cent. of nitrogen and 1·32 per cent. of sulphur, as did the portion soluble in both pyridine and chloroform, cannot be regarded as a reasonably pure "resinous" body, and (3) that inasmuch as the total oxygen in the various fractions is about 1·27 times that in the original coal, there had apparently been some absorption of oxygen during the extraction processes, no precaution having been taken to exclude air.

From his own experience of the action of solvents upon coals, the writer is inclined to think (1) that the method described by Wheeler does not effect quite so clear and complete a separation of the resinic and cellulosic constituents as he supposed, (2) that in applying it he did not sufficiently take into account the nitrogenous constituents of the coal, and (3) that the non-exclusion of oxygen in his experiments may have appreciably affected his results.

Wahl,[1] who examined the action of pyridine upon a number

[1] *Compt. rend.*, 1912, **154**, p. 1094.

of continental coals, mixed the dried powdered sample with an inert salt (NaCl, or K_2SO_4) soluble in water but insoluble in pyridine, and extracted the mixture in a Soxhlet apparatus in the usual manner. He subsequently concentrated the filtered pyridine solution in a vacuum, poured the residual liquid into concentrated hydrochloric acid, and after collecting and washing the pyridine extract in a filter, he finally dried it. His results (Table XXV) confirmed Bedson's observations that there is no relation between the weights of extractable matter and of " volatiles " yielded by the coal on ignition. In the cases of coals which yielded a large proportion of extract, the coking power was not lost, but the coke from the residue was much more compact than that obtained from the original coal. On the other hand, it was stated that the coke obtained from the extracts was extremely " puffy " (boursouflé), and that on mixing the extract with the residue the original coking properties were reproduced.

TABLE XXV

	Percentages on Dry Ashless Coal.		Percentages of Volatiles in Insoluble Residue.
	Extract.	Volatiles.	.
Bethune Fosse II	29·3	35·09	31·48
Frankenholtz Couche X	19·7	40·83	35·80
,, ,, XI . . .	19·0	43·88	39·04
,, ,, XII . . .	18·0	41·44	38·08
Lens Fosse III . . .	25·9	35·97	32·24
,, ,, VII . . .	trace	13·96	14·32
,, ,, VIII . . .	0·45	21·76	22·75
Spanish Lignite	22·9	46·49	40·68
Boghead	6·45	55·21	54·38

The following comparative figures for the elementary compositions of the original sample, and of the corresponding pyridine extract and residue, in the case of the Bethune coal indicate a surprisingly small difference between them:—

	C.	H.	N.	S.	O.
Original Coal . .	85·95	5·55	1·18	0·76	6·56
Extract . . .	85·55	6·09	1·41	0·53	6·42
Residue . . .	84·66	5·23	—	—	—

Subsequently to the foregoing researches, Harger[1] has found

[1] *Journ. Soc. Chem. Ind.*, 1914, p. 389.

that not only the speed, but also the practical limit, of the solvent action attained when the coal is extracted in a Soxhlet apparatus, is greatly exceeded when the operation is carried out in a sealed glass tube at 160° to 180° C. under pressure. Thus a Lancashire " Arley " coal which yielded only 22·5 per cent. of soluble extract by the Soxhlet method after 14 days, gave as much as 40·5 per cent. in a sealed tube after 24 hours, and, moreover, a greater quantity of extract was obtained in the sealed tube in 24 hours than after months in the Soxhlet apparatus. From these facts, as well as from the circumstances that (as he states) chemical analyses of the soluble and insoluble portions from the same bituminous coal show but little difference between their ultimate composition (*vide* also Wahl), and that all the fractions contain more nitrogen than does the original coal (*vide* Wheeler), he agreed that the action of pyridine upon coal is not a case of ordinary solution, but that it is essentially a depolymerising one, a conclusion which seems to be supported by the work of other investigators.

From researches recently carried out in the author's laboratory, the details of which it is hoped will be published shortly, it would appear that in order to obtain any reliable comparative results with a series of coals by the Soxhlet extraction method, attention must be paid to the purity of the pyridine, and especially to its being anhydrous. Commercial pyridine contains picolines and lutidines, which may be oxidised by means of nitric or chromic acids to the corresponding carboxylic acids and so removed. It also has a strong affinity for water forming hydrates, principally C_5H_5N, $3H_2O$, b.p. 95°. Now we have found that the presence of these hydrates diminishes and retards the action of pyridine upon coal, so that it is necessary in comparative experiments not only to use purified anhydrous pyridine, and to dry the coal before its extraction, but also to exclude any subsequent entry of water vapour into the apparatus. Moreover, we have discovered that if, during the extraction process, the contents of the apparatus are exposed to an atmosphere containing oxygen, the latter is absorbed, and not only is the extraction thereby retarded, but various oxidations occur which affect the coal substance to a degree which varies with the character of the coal affected, some coals being much more susceptible than others to such change. Hence, in order to get really comparable figures with different coals, we have found it necessary to carry out the Soxhlet extraction in an inert atmosphere of nitrogen, and in

subsequently concentrating or treating the resulting solution to avoid as much as possible any contact with air. The unrestricted access of air in both Bedson and Wheeler's experiments may, we think, have appreciably affected their results.

Various general observations made during the course of the researches referred to in the previous paragraph indicate that, besides any ordinary solvent action which pyridine may have upon the resinic constituents, which is probably fairly rapid, it also at the same time slowly attacks and resolves into simpler molecular aggregates the complex structure of the coal substance as a whole. Or, to suggest an analogy which in the circumstances seems permissible, if the coal substance be regarded as a structure built of bricks and mortar, with various other materials incorporated therewith, the action of pyridine may perhaps be likened to that of an agent which gradually loosens the brickwork, at the same time removing preferentially (but not exclusively) the mortar as the structure is unbuilt.

It has also been discovered in the author's laboratory that the resinic constituents may be removed from a bituminous coal and obtained in a purified state, free from nitrogen and sulphur compounds, by subjecting it to the action of a boiling mixture of equal parts of amyl alcohol and pyridine under suitable conditions with exclusion of air. Details of the method will shortly be published elsewhere, but by boiling 1 kilogram of a Yorkshire coal with 2 litres of the mixture of amyl alcohol and pyridine for two days, and subsequently purifying the crude resinous extract, a pure non-nitrogenous resene substance has been isolated. It melted at 42° C. and had the following elementary composition :—

$$C = 81.92 \quad H = 9.50 \quad O = 8.58 \text{ per cent.}$$

A further development of this method promises well to become a general one for the isolation and separation of the resinic constituents from coals, uncontaminated with the cellulosic or proteid degradation products, and it is hoped that it may facilitate the detailed study of the chemical nature of the resinic constituents in coals from different fields and seams.

The Action of other " Basic " Solvents.—Among other organic bases which are known to have a similar " solvent " action upon the coal to pyridine should be mentioned aniline (b.p. 184°) and quinoline (b.p. 238°), both of which have been investigated in

this connection by Vignon.[1] In the case of aniline he boiled 100 grams of the powdered coal with 500 grams of the solvent in a litre flask for 4 hours at 180°. The liquid was then filtered under reduced pressure, and the extract was precipitated by the gradual addition of sufficient hydrochloric acid to the cold filtrate. Vignon found that the degree of solvent action varies considerably according to the nature of the coal, being greatest with a rich gas coal, and that the method offers a ready means of distinguishing between " fat " and " lean " coals in this connection, as the following figures indicate :—

	Percentages of the Dry Ashless Coal. Extracted.
(1) Rich Gas Coal (*grasse à gaz*) . . .	26·8
(2) Medium Coal (*demi-grasse*) . . .	7·2
(3) Lean Coal (*maigre*)	1·8

Analyses of one of the coals, and of the "extract" obtained from it, gave the following figures, showing that the extract, like those obtained by Bedson, Wheeler and others by the action of pyridine upon coals, contains notable quantities of both nitrogen and sulphur.

	C.	H.	N.	S.	Ash.	Coke.
Original Coal	81·5	4·9	1·7	1·1	3·1	72·05 per cent.
Extract	83·50	5·6	1·37	1·05	0·46	69·69 ,, ,,

The " coke " yielded by the " extract " was swollen and agglomerated, whilst that from the insoluble residue was powdery.

The solvent action of quinoline at its boiling point (238°) upon coals was found to be almost three times as great as that of pyridine (b.p. 114·5°), and nearly twice as great as that of aniline (b.p. 184°) under similar conditions (see below), from which it would appear as though the action of these " basic " solvents is primarily a question of temperature, which again suggests an " unbuilding " of the coal structure.

Solvent.	B.P.	Percentage extracted from Rich Gas Coal.
Pyridine	114·5°	17·3
Aniline	184°	26·8
Quinoline	238°	47·3

The Action of Phenol.—Two American investigators, Parr and

---

[1] *Compt. rend.*, 1914, 158, p. 1421.

Hadley,[1] have recently found that considerable proportions of the coal substance may be extracted by heating it with phenol at 100° for 20 hours in an atmosphere of carbon dioxide. As much as 35 to 40 per cent. was extracted from coals having " high volatile contents," and between 20 to 30 per cent. from those whose " volatile contents " were low. In all cases the insoluble " residues " were non-caking, the " extracts " contained the " coking " constituents and gave the larger yield of " volatile " than the original coal, and both the " residues " and the " extracts " absorbed oxygen at the ordinary temperature.

The Work of F. Fischer and W. Gluud upon the Extraction of Coals by Benzene under High Pressure.—If, as seems probable, while such agents as pyridine, aniline, quinoline, and phenol may extract much more from coal than do more neutral solvents, their action involves some radical changes, or unbuilding of the coal substance itself, and therefore does not discriminate between its various constituents as sharply as an extraction method ought to do, chemists will be compelled to devise means for accelerating and improving the action of such other solvents as benzene, toluene, alcohol and chloroform, which presumably extract the more soluble constituents in the form in which they actually exist in the coal substance without causing any fundamental chemical change in it.

With this end in view, F. Fischer and W. Gluud of the Kaiser Wilhelm Institute for Coal Investigations in Berlin have recently studied the action of benzene upon coals at temperatures and pressures approximating to the critical constants of the solvents (about 288° C. and 50 atmospheres), with most interesting results.

The extractions were carried out in a steel bomb (62 c.m. long and 12 c.m. internal diameter with walls 2 c.m. thick) capable of withstanding a pressure of 200 atmospheres. Each charge of coal (1 to 2 kilos, broken to the size of hazel nuts) was suspended in a wire gauze basket within the bomb, so as to prevent any contact with the walls thereof, and extracted with from 3 to 3½ litres of benzene, heat being applied to the bomb externally by means of a powerful triple burner surrounded by a sheet-iron cylinder to concentrate the heat as far as possible. The temperature was raised to 275° C., corresponding to a pressure of about 55 atmospheres, and maintained at that degree for an hour, after which the heat was cut off

[1] *Journ. Soc. Chem. Ind.*, 1915, p. 213.

and the bomb allowed to cool slowly. Each sample of coal was repeatedly extracted in this manner. Finally the resulting benzene solutions, which had a strong green fluorescence in reflected light, and a dark port-wine colour when viewed in thin layers by transmitted light, were distilled on the water bath (under pressure of 200 m.m. at the finish) and the residual extract weighed.

The following particulars of an experiment with an Osterfield bituminous coal, which on repeated extraction at atmospheric pressure by means of boiling benzene (80° C.) in a reflux apparatus had yielded only 0·1 per cent. of its weight to the solvent, will indicate how extraordinarily effective was the change to a temperature of 275° and a pressure of 55 atmospheres in promoting the solvent action: -

Quantity of Coal taken = 1300 grams.　　　Solvent used = 3·5 litres.

Weight of }	1st Extrn.	2nd Extrn.	3rd Extrn.	4th Extrn.	5th Extrn.
Extract }	40 grams.	22 grams.	11 5 grams.	8 grams	5 5 grams.

Total extract = 87 grams = 6 7 per cent of the Coal taken

There was no liberation of gas on opening the cooled bomb after each extraction, from which the investigators concluded that the temperature had not been high enough during the experiment to cause even incipient decomposition of the coal, which, according to Wheeler, begins at 270° C. The residual extracted coal had not materially altered in appearance, although it had lost some of its lustre and internal cohesion. The viscosity of the successive extracts increased as the process was continued, and on pouring the united extracts, mixed with sufficient benzene to make them flow easily, into 500 c.c. of petroleum ether, 45 grams of a brown powder separated out. On heating this powder it softened at 140° and melted at about 150°. From this description of its properties it was presumably resinic in character, though this surmise needs to be confirmed by further investigation. From the portion remaining in solution in the petroleum ether there was recovered on evaporation about 12 grams of a viscous reddish yellow fatty oil.

In another experiment, in which 1 kilo of a Weban Brown Coal was subjected to three successive extractions in the bomb with 3 litres of benzene at a temperature of 260° and a pressure of 60 atmospheres, no less than 251 grams of "extract" was obtained, although the fact that a considerable amount of gas, smelling strongly of sulphuretted hydrogen, was liberated on opening the bomb suggests that incipient chemical

decomposition had occurred during the extraction process. In a third experiment, 1820 grams of a Wehofen Cannel Coal, on being subjected to a similar triple extraction with 3·5 litres of benzene, yielded altogether 3 per cent. of its weight of extract against only 1·1 per cent. when extracted with the boiling solvent at atmospheric pressure in a reflux apparatus.

As the result of this investigation the method of extraction with benzene and other similar solvents has undoubtedly acquired a greater scientific, and possibly even technical, importance than it had attained hitherto, although it is too soon yet to say how far it will advance the solution of the problem of the chemical constitution of coal. Much will depend upon whether or not further investigation will warrant the underlying assumption that the employment of temperatures as high as 250° to 260° C. with what are usually regarded as " neutral " solvents does not involve any material alteration of the coal substance, a point of cardinal importance in connection with the interpretation of all such work.[1]

The Work of Pictet, Ramseyer and Kaiser.—The only other recent work that throws much light on this aspect of the subject is that of Pictet, Ramseyer and Kaiser,[2] who, after studying the nature of the tars obtained by the distillation of bituminous coals under reduced pressure (" vacuum tars "), applied themselves to determine whether or not the constituent of such tars (chiefly cyclic hydroaromatic hydrocarbons C_nH_{2n}, ranging from C_9H_{18} to $C_{13}H_{26}$ inclusive, and a crystalline $C_{24}H_{40}$) exist as such in the original coal.

They accordingly proceeded to extract 5½ tons (say 5500 kilos) of Montrambert coal with boiling benzene in reflux. apparatuses for 4 days, and on subsequently concentrating the resulting solution by distillation to 20 litres and adding 100 litres of light petroleum thereto, 2·7 kilos of an amorphous brown powder was precipitated, whilst the remaining solution yielded on evaporation of the solvent 10·6 kilos of a liquid resembling " vacuum tar." Subsequent fractional distillation of it gave the following hydrocarbons :—

Dihydrotoluene C_7H_{10}, *Dihydrometaxylene* C_8H_{12}, *Dihydromesitylene* C_9H_{14}, also $C_{11}H_{16}$, $C_{14}H_{16}$, $C_{12}H_{12}$ (? solid), *Dihydrofluorene*, C_8H_{14}, C_9H_{16}, $C_{10}H_{20}$, $C_{11}H_{22}$, $C_{12}H_{24}$, $C_{13}H_{26}$, and

---

[1] Since this paragraph was written, Dr. Wheeler has informed the author that he has recently found evidences of decomposition in certain coals at temperatures even as low as 180° C.

[2] See also the *Gas World*, Jan. 13, 1917.

$C_{20}H_{40}$. Of these the $C_{11}H_{22}$, $C_{12}H_{24}$, $C_{13}H_{26}$, and $C_{20}H_{40}$ were identified with those found in vacuum tar, which in their turn were the same as those found by Mabery in Canadian petroleum. Hence the French investigators concluded that such hydrocarbons actually exist in coal, which they regard as a solid hydrocarbonaceous material impregnated with a liquid chemically very nearly resembling petroleum. It must, however, be remembered that, whilst the products obtained by the Frenchmen resemble those got by Fischer and Gluud, their yields were many times smaller, namely about 0·25 per cent. of the coal substance as against up to 6–7 per cent. in the German experiments. Moreover, whilst doubtless there are grounds for believing that the coal substance may be in some cases impregnated with petroleum hydrocarbons, it is hardly safe to base a general conclusion respecting the nature of coal upon the finding of only 0·25 per cent. of them in a particular sample.

CHAPTER VII

THE CHEMICAL COMPOSITION OF COAL (*contd.*)

E. THE THERMAL DECOMPOSITION OF THE COAL SUBSTANCE IN LOW TEMPERATURE CARBONISATION

AN accurate knowledge of how each of the main types of the constituents of the coal substance behaves when subjected to dry distillation at various definite temperatures, including a complete analysis of all the products (solid, liquid, and gaseous) obtainable at each temperature, would be of the greatest value, not only immediately to the technologist, but also as a means of elucidating the purely chemical aspects of the nature of coal. In the present chapter the question will be considered primarily from the latter point of view.

Owing very largely to the fact that for more than a century coal has been carbonised on a large scale, formerly at red heat (say 700° to 850° C.) in cast-iron retorts, and latterly at high temperatures (900° to 1100° C.) in fireclay retorts, for the manufacture of towns gas ("coal gas"), and thanks also to the fact that within the past twenty years the manufacture of metallurgical coke by carbonising "coking coals" in ovens at temperatures above 1000° C. has become associated with by-product recovery systems, which lend themselves to scientific investigation and control, much knowledge has accumulated concerning the nature and yields of "high temperature" distillation products from different classes of coals. These include (1) coke which is essentially carbon *plus* the ash of the coal, (2) benzenoid and phenolic tars and hard pitch, (3) ammoniacal liquor, and (4) from 10,000 to 12,000 cub. ft. of gas per ton of coal, the *net* calorific value of which may be anything between, say, 500 and 550 B.T.Us. per cub. ft. at 0° C. and 760 m.m. pressure. The principal constituents of such a "coal gas" are hydrogen (45 to 55 per cent.), methane (30 to 35 per cent.), with, invariably, smaller proportions of ethylenic hydrocarbons C_nH_{2n} of an average composition probably approximating to that of propylene (C ¯¯

99

benzene (C_6H_6), carbon monoxide (CO), carbon dioxide (CO_2), and nitrogen (N_2). But the mere obtaining of such products, and the known variations (both qualitative and quantitative) in them, according to the nature of the coal carbonised and also to the temperature and other conditions to which it is subjected, although of great economic importance, do not help us very far in unravelling the chemistry of the coal substance, because they represent, not the primary products of its initial decomposition by heat, but the end result of a complex series of secondary decompositions and interactions of the primary products. It is, therefore, chiefly upon the study of the decomposition of the coal substance at low temperatures that we must base any conclusion as to its nature.

Owing to the fact that the low temperature distillation of coal (at from, say, 400° to 600° C.) has the effect of decomposing the smoke-producing part of the coal substance and yielding (1) in the case of suitable classes of caking coals, a porous " *semi-coke* " which is smokeless in its combustion, (2) certain quantities of " fuel oils " and " motor spirit," and (3) a comparatively small proportion of rich gas, containing chiefly methane, ethane, together with ethylenic hydrocarbons, C_nH_{2n}, hydrogen (5 to 15 per cent.), and oxides of carbon, high expectations of its future commercial possibilities have been raised in some quarters. But the matter is still so much in the early stages of its technical development that the author wishes it to be understood that he is now concerned solely with its scientific aspects without in any way committing himself to any view or opinion about its commercial prospects.

Among recent researches upon the thermal decomposition of coal, those of M. J. Burgess and R. V. Wheeler [1] are perhaps of first importance inasmuch as they deal in great detail with the volumes and composition of the gases evolved when typical coals are maintained at progressively increasing temperatures up to 1100° C.

In their experiments 200 grams of a powdered South Yorks. (Altofts) Silkstone bituminous coal were maintained in a vacuum (20 m.m.) successively at temperatures of 100°, 200°, 300°, 350°, 400°, and 450° C. for a sufficient time to allow of equilibrium being established in the system at each successive stage in the heating operations. The various gases and condensable products

---

[1] *Journ. Chem. Soc.*, 1910, **97**, 1917; 1911, **99**, 649; 1914, **105**, 131; *vide* also A. H. Clark and R. V. Wheeler, *ibid.* 1913, **103**, 1704.

evolved between each successive temperature stage were separately collected for subsequent examination. The apparatus was arranged as shown in Figs. 7a and 7b,[1] and each experiment extended over 4 to 8 weeks continuously.

The principal facts established during the experiments, the results of which are summarised in Table XXVI, were (1) that

Fig. 7a.—Distillation Apparatus used by Burgess and Wheeler.

Fig. 7b.—Platinum Retort used by Burgess and Wheeler.

" occluded " or " condensed " gases, mainly the higher paraffin hydrocarbons, continue to be evolved in small quantities up to 150° or even 200° C., (2) that at about 200° there is a copious evolution of water (" water of constitution ") which continues right up to, and probably beyond, 450°, (3) that between 270° and 300° sulphuretted hydrogen is freely evolved, which circumstance the authors in question ascribed to the decomposition of organic sulphur compounds; this evolution practically ceases at 300°,

[1] Reproduced from drawings kindly lent to the author by Mr. R. V. Wheeler.

TABLE XXVI

SUMMARY OF BURGESS AND WHEELER'S EXPERIMENTS ON THE DISTILLATION OF COAL IN A VACUUM

Temperature Interval.	Up to 100°.	100° to 200°.	200° to 300°.	300° to 350°.	350° to 400°.
Volume of Gases evolved in c.cs. at N.T.P. per 100 grams of Coal	34·0	65·5	58·5	98·5	40·00
Percentage Composition of the Gases — H_2S	—	—	35·35	1·70	0·70
CO_2	6·7	8·85	10·90	20·95	2·85
CO	1·4	2·66	1·05	3·40	3·40
C_2H_4	0·85	0·85	18·85	1·90	2·35
C_nH_{2n}	1·30	2·90	18·85	17·90	6·15
C_nH_{2n+2}	84·55	81·00	13·35	37·22	46·55
H_2	1·90	2·73		15·35	36·90
O_2	1·65	0·70			
			$C_2H_6 = 0·55$	$C_2H_6 = 0·15$	$C_2H_6 =$ trace
Remarks	Paraffins included Higher Members than C_2H_6	Paraffins included C_5H_{12}	H_2S appeared at 270° C_4H_8 isolated from the Products	Evolution of H_2S almost ceased at 300° Critical Decomposition Temperature reached at 350°	
	Occluded Gases up to 200°		Evolution of Water began at 200°, and of Oils at 310°		

and, simultaneously, olefines higher than ethylene make their appearance, until, at 350° or thereabouts, they either fall off or disappear, (4) that liquids other than water begin to distil over as a reddish-brown oil at 310°, but inasmuch as its appearance is unaccompanied by any marked evolution of gas the authors regard it as being " liquated " out of the coal conglomerate rather than as a decomposition product of the coal substance (*vide* Pictet, Ramseyer and Kaiser, p. 97), (5) that a critical decomposition point is reached at about 350°, which is marked by a rapid increase in the gas evolution and the appearance of much viscous oil, (6) that the gaseous hydrocarbons evolved up to 450° consist of methane, ethane, propane, butane, and even pentane, as well as of ethylene and higher olefines, and (7) that neither benzene nor its homologues could be detected in the condensable liquid products, and the authors regard their formation at such low temperatures as extremely doubtful.

The foregoing experiments, having established a temperature of *circa* 350° C. as the point at which the decomposition of the coal substance begins, led the authors in question to investigate in detail (1) the ratio of gas evolution, (2) the total volume of gas and its composition, and (3) the amounts of tar yielded by the following four representative British coals at various constant temperatures between 450° and 1000° C.

TABLE XXVII

Coal.	A.	B.	C.	D.
Character and Origin	Bituminous Altofts (S. Yorks) Silkstone	Anthracitic Pontyberen	Bituminous Abertilley S. Wales	Semi-bituminous Penrhycyber S. Wales
Per cent. Ash Content	5·51	3·9	7·65	3·5
Percentage Composition of the Dry Ashless Coal C .	80·50	92·66	85·72	90·72
H .	5·45	3·14	4·93	4·23
N .	1·42	0·99	1·09	2·99
S .	2·93	1·01	0·92	0·81
O .	9·70	2·20	7·34	1·25

An intimate mixture of 2 grams of the dried sample, pulverised so as to pass a sieve of 240 meshes to the linear inch, with 3 grams of fine white sand, which had been previously ignited, were heated in a small tubular platinum retort (21·5 c.m. long and 1·7 c.m.

internal diameter), the open end of which was silver-soldered into a gun-metal collar through which connection was made with (1) a weighed platinum " tar scrubber " packed with ignited asbestos, and (2) a graduated glass gas-holder (capacity = 2 litres), a mercurial pressure gauge being inserted in the system between (1) and (2). The retort was heated electrically in a platinum-wound resistance furnace (the temperature of which was measured by a platinum and platinum-rhodium thermojunction) for a period of


FIG. 8.—Gaseous Products of Distillation of Coal A at Different Temperatures.

time (2 hours) sufficient for the decomposition to be completed at the particular temperature selected. It was ascertained that the coal attained the temperature of the furnace within about 2 minutes after the commencement of each experiment.

As the main interest of the experiments centres on the volumes of each of the principal gaseous products obtained at the various experimental temperatures, it will be sufficient for our purpose to reproduce from the original paper the following curves (Figs. 8, 9, and 10) setting forth these data for the aforesaid coals A, B, and D.[1] The reader is referred to the memoir for other details.

[1] The author is indebted to Dr. R. V. Wheeler and the Council of the Chemical Society for their kind permission to reproduce these curves.

The principal facts established by this part of the investigation were (1) that with all coals, whether bituminous, semi-bituminous, or anthracitic, there is a well-defined temperature between 700° and 800°, which corresponds with a marked and rapid increase in the quantity of hydrogen evolved; (2) that with bituminous coals such increase in the quantity of hydrogen evolved falls off at temperatures above 900°, but with anthracitic coals it is maintained up to 1100°; (3) that the evolution of hydrocarbons


Fig. 9.—Gaseous Products of Distillation of Coals B and D at Different Temperatures.

of the paraffin series ceases almost entirely at temperatures above 700°; (4) that ethane, propane, butane, and probably higher members of the paraffin series form a large percentage of the gases evolved at temperatures below 450°; and (5) that the *rate* at which carbon monoxide is evolved is uniform throughout a distillation at any one temperature, and is maintained right up to the end, whilst the rates in the case of the other gases fall off, moreover, this CO-rate increases with the temperature.

From the above facts Burgess and Wheeler argued (1) that coal contains two types of compounds of different degrees of ease of decomposition; the one, the least stable, yielding the paraffin

hydrocarbons and no hydrogen; the other decomposing with greater difficulty and yielding hydrogen alone (or possibly hydrogen and the oxides of carbon) as its decomposition products; (2) that very probably the difference between one coal and another is determined mainly by the proportions in which these two types of compounds exist, anthracite, for example, containing but little of the more unstable constituents; (3) that the true " coal substance," apart from the traces of sulphur compounds that mask its

FIG. 10.—Distillation of Coal A *in vacuo* at 950° C.

character, is compounded of the two types which behave so differently under the action of heat; and (4) that the presence of carbon monoxide in the gases is most probably due to the elimination of water from hydroxy-compounds, and the subsequent reaction of the steam thus formed with the carbon. In a later paper, in conjunction with A. H. Clark and C. B. Platt, Wheeler explains that in using the terms " *hydrogen-yielding* " and " *paraffin-yielding* " constituents, he does not mean that hydrogen in the one case, or paraffin in the other, is the *sole*, but that it is only the *predominant* decomposition product in each case. He also expressed his belief that the " *hydrogen-yielding* " is the cellulosic, and the " *paraffin-yielding* " the resinic constituent of coal.

The main facts observed by Wheeler and his co-workers in this connection were confirmed by the independent work of Vignon on French coals.[1] This investigator distilled various samples of coal at successive temperatures of 400°, 600°, 850°, 1000°, and 1200°, showing (1) that unsaturated hydrocarbons almost all pass over below 600° and disappear entirely at higher temperatures; (2) that methane and other paraffins form from 60 to 80 per cent. of the whole gas up to 800°, after which they decrease rapidly with further rise in temperature; (3) that between 800° and 1000° hydrogen predominates, but in turn diminishes above 1000°; and (4) that very high temperatures promote the formation of carbon monoxide.

It would, therefore, appear that there is no room for any serious difference of opinion upon questions of fact in this connection, and that in particular Wheeler's principal discovery of a temperature somewhere between 700° and 800° at which the evolution of hydrogen rapidly increases has been substantially confirmed. When, however, it comes to the interpretation of the facts, agreement with his conclusions is by no means unanimous, and in particular two well-known American investigators (H. C. Porter and G. B. Taylor) [2] have expressed strong dissent from his view that the aforesaid rapid increase in the evolution of hydrogen between 700° and 800° really marks " a well-defined decomposition point " or a " critical period " at which, after the decomposition of a less stable " paraffin-yielding " resinic constituent has been practically completed, that of a more stable " hydrogen-yielding " cellulosic constituent begins. Indeed the fact that " water of constitution," as Wheeler himself states, begins to be copiously evolved from a bituminous coal at as low a temperature as 200°, and continues up to and beyond 450° suggests the early decomposition of " cellulosic " rather than that of " resinic " constituents.

Moreover, it has always appeared to the writer that, in interpreting his experiments, Wheeler has overlooked the probable behaviour of the nitrogenous constituents, which do indeed form as important a part of the coal substance as, say, the resinic constituents, and ought not therefore to be ignored. For if, as both Carrick Anderson and M. G. Christie (*loc cit.*) have independently shown, the "ammonia-yielding" nitrogenous constituents of coal begin to decompose between 330° and 480°,

[1] *Compt. rend.*, 1912, **155**, p. 1514.
[2] *Proc. Amer. Gas Institute*, 1914, IX. i., pp. 234

and rapidly do so at from 500° to 700°, then it is certain that Burgess and Wheeler's results must have been materially influenced by this factor, as indeed the following figures from the amounts of ammonia in these gases prove:—

COAL A

Temperature	450°	500°	600°	700°	800°	900°
Total Gases in c.cs. per gram. Coal	12·0	29·9	99·0	124·0	218·0	268·0
Percentage NH_3	4·7	1·35	1·40	1·60	1·00	1·0

COAL C

Temperature	500°	600°	700°	800°	900°
Total Gases in c.cs. per gram Coal	33·5	83·0	135·0	208·0	254·0
Percentage NH_3	2·00	0·70	1·10	0·85	*nil*

The American investigators referred to (*q. v*) have suggested that the marked increase in the production of hydrogen at 750° or thereabouts, in Burgess and Wheeler's experiments, may have been due to the secondary decomposition of volatile matters (tar and gases), and unquestionably the employment by Burgess and Wheeler of a tubular *platinum* retort for heating the coal in the particular series of experiments referred to would greatly influence all secondary changes of a catalytic character, and it therefore affords their critics a valid ground of objection. Also Vignon's experiments, in which an *iron* tube was used, though less open to question, are not entirely immune from such criticism.

In this connection it should be remembered that, according to the researches of Bone and Coward, whilst methane is a very stable hydrocarbon at 800°, and is only slowly resolved into its elements between that temperature and 1200°, both ethane and ethylene decompose fairly rapidly at 700° and are most unstable at all temperatures above 800°. Also, that methane is always a prominent decomposition product of the other two, being formed by the "hydrogenation" of unsaturated residues such as $:CH_2$ and :CH, which are undoubtedly produced momentarily and play an important *rôle* in hydrocarbon decomposition at high temperatures. Hydrogen would certainly be produced at 700° to 800° by the secondary decomposition of the vapours of low temperature tars, but some of it would probably also disappear at that temperature on account of the "hydrogenations" referred to. And whilst it is difficult to arrive at any precise or final conclusion

in weighing up the *pros* and *cons* of the case, the writer is on the whole inclined to think that, whereas Burgess and Wheeler's experiments would probably not be affected materially by the secondary decomposition of methane until well above 800°, those between 600° and 900° were to some extent influenced by other secondary hydrocarbon decompositions and interactions, but probably not sufficiently to throw doubt upon their principal conclusion that there exists a temperature point between 700° and 800° at which some "hydrogen-yielding" constituent (or perhaps, to put it better, "complex") in the coal substance begins to decompose rapidly.

In conjunction with D. T. Jones, Wheeler has recently studied the condensable tars formed by the distillation of coals[1] under pressures of from 5 to 40 m.m. at temperatures up to 430° C. Two bituminous coals were selected, one from Scotland and the other from Co. Durham, of the following composition:—

Proximate Analyses of Dry Coal.		Ultimate Analyses of the Dry Ashless Coal.					
Volatiles.	Ash.	C.	H.	N.	S.	O.	
Scottish Coal 26·36..	3·28	86·92	4·98	1·75	0·79	5·56	per cent.
Durham Coal 30·81..	4·10	86·88	5·41	1·75	1·25	4·71	,, ,,

The tars obtained, amounting to about 6·5 per cent. of the weight of the coal, yielded on distillation up to 300° (1) about half its weight of soft pitch, sp. gr. $1·128 \frac{15}{15}°$, entirely soluble in chloroform and free from carbon, and (2) a mixture of oils, boiling below 300°, of the following composition:—

(a) Between 40 and 45 per cent. of "ethylenic" unsaturated hydrocarbons, for the most part richer in carbon than the mono-olefines.

(b) About 40 per cent. of naphthenes (C_nH_{2n}), and liquid paraffins (C_nH_{2n+2}), the former greatly predominating.

(c) Between 12 and 15 per cent. of phenolic bodies, chiefly cresols and xylenols.

(d) About 7 per cent. of aromatic compounds, chiefly homologues of naphthalene (? *dimethylnaphthalene*) but not naphthalene itself. Benzene, anthracene, and solid aromatic hydrocarbons were absent, nor was there any evidence of the presence of toluene nor homologues of benzene in more than minute quantities.

(e) Traces of pyridine bases.

[1] *Journ. Chem. Soc.*, 1914, **105**, 141, 2562; 1915, **107**, 18? **100**, 708.

In a later series of experiments Jones and Wheeler studied separately the behaviour on distillation of the three fractions into which the coal substance may be divided by successive extraction by means of pyridine and chloroform, namely (*a*) the portion insoluble in pyridine ("cellulosic"), (*b*) that soluble in pyridine but insoluble in chloroform, (*c*) that soluble in both pyridine and chloroform ("resinic"). The coal selected for this purpose was the Durham coal used in the previous series of experiments (*q. v.*), and the results of the further treatment of it were briefly as follows :—

(i) 150 *grams of Fraction* (*a*) yielded, at temperatures between 390° and 450° *in vacuo*, chiefly phenolic products, and an oil containing $C = 86 \cdot 04$ and $H = 11 \cdot 35$ (*i. e.* $C + H = 97 \cdot 39$) per cent. The contents of the flask showed no tendency to cake during the distillation (*i. e.* up to 450°), and the residual non-volatile material remaining in the flask after the experiment was a fine powder.

(ii) 150 *grams of Fraction* (*b*) similarly yielded oils, of which 40 per cent. were phenolic and the remainder " of a resinous nature." The non-volatile residue was of the same powdery character as in (i).

(iii) 65 *grams of Fraction* (*c*) softened at 90°, and melted at 102°. Gases began to be evolved at 170°. On continuing the distillation up to 400°, considerable quantities of paraffin wax distilled over at 250°, and large volumes of gases were evolved at 320°. The condensable products consisted of a viscous resin-like substance, which on re-distillation yielded an oil containing olefinic hydrocarbons, and an oil, boiling between 180° and 250° at atmospheric pressure, containing $C = 87 \cdot 31$, $H = 10 \cdot 00$ ($C + H = 97 \cdot 31$) per cent. No phenols were produced, and the 23 grams of residue left in the distillation flask were a hard compact pitch, containing $C = 87 \cdot 96$, $H = 5 \cdot 67$ ($C + H = 93 \cdot 63$) per cent. completely soluble in pyridine.

The most important points which Jones and Wheeler claim to have established with regard to such low temperature tars are :— (1) the absence of benzene and its homologues, but the presence of homologues of naphthalene in them; the latter point, if confirmed, would be of considerable interest as bearing on the

chemical structure of coal; (2) the predominance in them of " ethylenic" unsaturated hydrocarbons and naphthenes; (3) the formation of phenolic bodies exclusively for what are presumably the " cellulosic " constituents of the coal; and (4) the striking contrast between the compact pitchy residue yielded by the supposed " resinic" constituent and the non-coherent powder left behind by the other constituent, which again clearly demonstrates the predominant influence of the resinic bodies in determining the coking power of coal.

Before passing on to the description of the work of other investigators it will be convenient if we now record the latest views of Jones and Wheeler, as summarised at the end of their third paper on the Constitution of Coal [1] in the following paragraphs :—

(1) Coal is considered to have been formed from decayed vegetable matter by the action of pressure and temperature. The temperature cannot have approached 300°.

(2) The coal conglomerate can be resolved by means of solvents into cellulosic and resinic portions.

(3) The cellulosic derivatives contain compounds, the molecules of which possess the furan structure, and yield phenols when destructively distilled. There are also compounds present, the molecules of which have structures resembling that of the carbon molecule, but it is unlikely that " free carbon " is present in coal. The cellulosic derivatives are probably few in type.

(4) The resinic derivatives contain compounds in which alkyl, naphthene and unsaturated hydroaromatic radicals are attached to larger and more complex groupings. It is doubtful whether aromatic groupings are present. Under the influence of pressure the bulk of the resinic derivatives have become highly polymerised. The oxygenated resinic derivatives are chiefly oxides, probably cyclic oxides; esters, lactones, anhydrides, acids, and ketones are absent or present only in small quantity.

(5) Hydrocarbons are present in the resinic portions of coal; saturated hydrocarbons (paraffin) are, however, present in small quantity only.

(6) The main distinction between low temperature distillates

[1] *Journ. Chem. Soc.*, 1916, **109**, 707.

from coal and petroleum is the absence of phenols in the latter. This is held to be corroborative evidence of the non-cellulosic orgin of petroleum.

The foregoing statements, embodying as they do the considered opinions of two chemists whose researches have enriched our knowledge by many new and important facts, must necessarily command attention if they do not altogether compel assent. There will be no difficulty in accepting conclusions (1), (2), and (3), although with regard to (2), as well as to the conception of the constitution of the coal substance, embodied in the paragraphs as a whole, most chemists will view with surprise the omission of any reference whatsoever to the presence of nitrogenous constituents. Paragraphs (3) and (4), however, bristle with controversial points, and suggest ideas which do not seem to have been as yet sufficiently substantiated. Also there is some inconsistency between Jones and Wheeler's conclusion that the phenolic products, present to an extent of 12 to 15 per cent. in the tars obtained by them on distilling coals up to 430° in a vacuum, are derived from the cellulosic constituents of coal [paragraphs (3) and (4)] and the equally definite previous assertions by Burgess and Wheeler that these " hydrogen-yielding " cellulosic constituents only decompose freely above a critical temperature defined as being between 750° and 800°. Indeed, as will be seen later, strong exception has been taken to Wheeler's interpretation as a whole of the thermal decomposition of coal by two American investigators, H. C. Porter and G .B. Taylor (q. v.).

We must next consider, as supplementing the work of Jones and Wheeler, the exhaustive investigations by Pictet and Bouvier upon the composition of the 60 kilos of " vacuum tar " obtained by them on distilling 1½ tons of Montrambert coal at 450° under a pressure of 15 to 20 m.m.[1] They stated that the tar contained neither phenols (vide, however, Jones and Wheeler, and a later statement by Pictet, Kaiser and Labouchère) nor aromatic hydrocarbons, but yielded both on decomposition at red heat. The presence of alcohols and unsaturated hydrocarbons was proved, but not in sufficient quantity to admit of identification. After freeing the crude tar from such alcohols by treatment with sodium, and from unsaturated hydrocarbons by shaking it up with anhydrous liquid sulphur dioxide, which

[1] Compt. rend , 1913, 157, p. 1436; 1915, 160, p. 629, and Ber., 1915, 48 p 926.

...... and removes them, the residual "saturated" hydro-
...... were resolved by fractional distillation at atmospheric
...... into the following constituents, all of which were of the
...... (C_nH_{2n}) type of hydrocarbons :—

Formula.	B.P. at 730 m.m.	Density.	N_D.
C_9H_{18}	135–137°	0·7590[20°]	1·4212[20°]
$C_{10}H_{20}$	160–161°	0·7680[20°]	1·4272[20°]
$C_{10}H_{20}$	172–174°	0·7765[22°]	1·4196[22°]
$C_{11}H_{22}$	189–191°	0·7838[22°]	1·4234[22°]
$C_{12}H_{24}$	211–213°	0·7862[21°]	1·4293[21°]
$C_{13}H_{26}$	227–229°	0·7953[20°]	1·4379[20°]

The authors in question pointed out that the physical constants
of their hydrocarbons are nearly the same as those previously
found by Mabery from the saturated hydrocarbons of similar
constitution isolated from Galician and Californian petroleums.
They identified the hydrocarbon C_9H_{18} as 1:3:5 trimethyl-
*cyclo*hexane (hexahydromesitylene), since with nitric acid it
yielded dinitromesitylene.

$$CH_3 \cdot HC \quad CH_2$$
$$H_2C \diagdown \diagup CH \cdot CH_3$$
$$CH_3 \cdot HC \quad CH_2$$

On continuing the distillation of the oil under 15 m.m. pressure,
they obtained a fraction which solidified into colourless needles
melting at 62–63°, and having a density of 0·9128 at 25°. It
had a formula $C_{30}H_{60}$ and seemed to be identical with the melene
obtained in 1849 by Brodie from the products of the dry distilla-
tion of beeswax.

With regard to the composition of the 2 per cent. of hydroxy-
compounds contained in this "vacuum tar," Pictet in conjunction
with Kaiser and Labouchère subsequently proved the presence
of hexahydro-*p*-cresol, $C_7H_{14}O$ (b.p. 170–175° C.), as well as a
series of homologous phenolic bodies, including $C_8H_{16}O$ (b.p.
185–190°), $C_9H_{18}O$ (b.p. 198–200°), $C_{10}H_{16}O$ (b.p. 213–215°),
and $C_{11}H_{18}O$ (b.p. 226–228°), which they believe probably occur
as such in coal, because similar substances have been extracted
from coal by benzene. The tar also contained 0·2 per cent. of
bases, among which were a primary aromatic amine C_7H_9N
(possibly a mixture of toluidines), and a number of secondary

bases C_8H_7N (b.p. 225°), C_9H_9N (b.p. 247–250°), $C_{10}H_{11}N$ (b.p. 250–260°), $C_{11}H_{13}N$ (b.p. 260–265°), and $C_{12}H_{15}N$ (b.p. 270–280°), which had the odour of quinolines and yielded picrates only slightly soluble in alcohol.[1]

D. T. Jones has recently advanced the practical study of the thermal decomposition of such cyclic saturated hydrocarbons by heating *cyclo*hexane (C_6H_{12}), methyl*cyclo*hexane (C_7H_{14}), and di- and tetra-hydronaphthalenes ($C_{10}H_{10}$ and $C_{10}H_{12}$) in contact with porous porcelain, the temperature of which was slowly raised until the decomposition point was attained in each case.[2] This in the case of the two first-named hydrocarbons was between 490° and 510°, and for dihydronaphthalene it was at 390°. The principal facts established were :—

Cyclohexane at 500° yielded benzene, which formed 20 per cent. of the liquid products, and a gas containing :—C_6H_6 and Olefines $= 26\cdot1$, $C_3H_2 = 0\cdot2$, $C_2H_4 = 8\cdot5$, $C_2H_6 = 21\cdot9$, $CH_4 = 3\cdot0$, and $H_2 = 40\cdot3$ per cent.

Methylcyclohexane at 530° yielded liquids and a gas containing :—C_6H_6 and Olefines $= 12\cdot8$, $C_2H_2 =$ trace, $C_2H_4 = 10\cdot6$, $C_2H_6 = 12\cdot0$, $CH_4 = 22\cdot5$, and $H_2 = 42\cdot1$ per cent.

1:4 *Dihydronaphthalene* at 420° yielded naphthalene, and a gas containing :—$CH_4 = 14\cdot6$, and $H_2 = 85\cdot4$ per cent.

1:2:3:4 *Tetrahydronaphthalene* at 530° yielded naphthalene, and a gas containing :—C_6H_6 and Olefines $= 3\cdot3$, $C_2H_4 = 3\cdot5$, $C_2H_6 = 4\cdot0$, $CH_4 = 9\cdot0$, and $H_2 = 80\cdot2$ per cent.

In a later paper[3] Jones has detailed the results of his investigation of the thermal decomposition of the low temperature tars previously obtained from coals by Wheeler and himself (*loc. cit.*). The method adopted was to decompose small quantities of the tar at successive temperature increments of 50° beginning at 550° C. (the lowest temperature at which the decomposition became rapid enough for convenient study) by distilling a small quantity of the vapour over heated porous porcelain in a stream of carbon dioxide, which was used to sweep the vapour and gaseous products forward. The following tabulated compositions of the gaseous products obtained at the various temperatures are of considerable interest, especially in connection with Burgess and Wheeler's results and conclusions, the rapid increase in the production of hydrogen between 750°

[1] *Compt. rend.*, 1917, **165**, p. 113
[2] *Journ Chem Soc.*, 1915, **107**, p. 1582.
[3] *Journ. Soc. Chem. Ind.*, 1917, p. 3.

.perature) being

	CH$_4$	H$_2$
:	19·6	29·4
:	33·9	33·6
0	39·0	27·4
· 4	43·8	28·2
t 2	56·1	33·2
–	33·0	60·7

f hydrogen (and especi-
med up his results and
nary coal tar is formed
lly as the result of the
med at low temperatures;
s consists essentially in the
paraffins, and unsaturated
perature tar to form olefines
lense at higher temperatures
: higher (gaseous) olefines are
eir disappearance at 750° C.
of naphthalene, and immedi-
in the evolution of hydrogen;
iddle temperatures as the result
thenes; the increase at higher
be attributed to the union of
a-molecular ring closing; (5) that
of coal distillation (cf., however,
) that benzene and its homologues
sult of olefine condensation. To
lary products of coal distillation,
thermal dehydrogenation of the
and (7) that acetylene plays an
r formation.

thermal changes which accompany
nd allied substances as the tempera-
aised has recently been carried out by
University of Leeds.[1] Their experi-

m. Soc., 1915, 107, p. 1106.

mental method consisted in heating side by side, under the same conditions, a coal which underwent carbonisation and a coke which could be regarded as chemically and thermally inert, and noting, by means of a differential arrangement of thermocouples devised by the late Roberts-Austen for the examination of metallic alloys, the extent to which the temperature of the coal differed ($+$ or $-$) from that of the coke in various stages of the carbonisation.

The materials examined included the following :—

TABLE XXIX

	Percentage		Ash-free Substance				
	Vola-tiles.[1]	Ash	C.	H.	N.	S	O
Anthracite (S. Wales)	5·97	2·12	89·20	4·31	1·25	1·34	3·91
Bituminous Coal .	37·30	3·77	80·39	5·88	1·39	1·71	10 63
Cannel	45·27	4·80	80·79	5·46	1·94	1·21	10 60
Lignite . . .	65·00	5·20	63·00	6·26	0·50	1·66	28·58
Dehydrated Cellulose	65·20	1·13	58·11	4·11	—	1·10	36·68
Cotton Wool . .	—	—	44·4	6·2	—	—	49·4

Cellulose (but not dehydrated cellulose, lignite nor coals) showed a strong exothermic reaction between 300° and 400° C. which the authors in question suppose was connected with the expulsion of hydroxyl groups at 345° and the consequent condensation of the residue. In the case of dehydrated cellulose and lignite this evolution of heat was spread over a wide range (280° to 420°), and in the case of coals no signs of exothermic reactions were observed below 400°. Between 400° and 600° the thermal phenomena varied a good deal with the nature of the coal, but all coals displayed marked exothermicity in passing through the interval 600° to 800°, during which methane also was freely evolved. Above 800°, when hydrogen became the chief gaseous product, the carbonisation process appears to be either thermally neutral or slightly endothermic. In general, at low temperatures the thermal phenomena were most marked with cellulose and coals of a high oxygen content, whilst at high temperatures they were most marked with anthracite and coals of low oxygen content.

A study of the curves published in the paper leaves the impression that they do not admit of more than a very general

[1] As determined in platinum crucible by the American Method (*q. v.*).

interpretation, and that a more thorough exploration of the subject is needed before any definite conclusion regarding the differences between the thermal behaviour of various coals can be drawn from the observations made by such a method. This remark applies especially to the range of 400° to 600°, where most of the primary " low temperature " changes in the coal substance presumably occur other than the elimination of water, which Wheeler and others have shown to commence at 200° and to continue beyond 450°. The fact that Hollings and Cobb's curves do not, except in the case of cellulose itself, bring out this feature very strongly shows at once the extreme complexity of the problem and the limitations of such a method as they employed, which of course only indicates the direction ($+$ or $-$) in which the balance of the heat changes is moving at any particular range of temperature.

In this connection it may be noted that Rau and Lambris, who investigated the mode of formation of water in the destructive distillation of various fuels, found that the amount actually recovered by condensation was greater by as much as 50 to 100 per cent. with slow than with rapid heating. Thus, with a high-grade gas coal the water condensed varied from 4·8 up to 7·3 per cent. according as the temperature of coal was raised to 1000° in a few minutes or in 36 hours. As a rule, the lower the oxygen content of a coal, not only the less is the water produced from it, but also the higher the temperature at which it is produced. With cellulose the principal water formation was found to occur between 240° and 350° C., which agrees fairly well with Hollings and Cobb's observations that there is a decomposition point at 345° at which the heat evolution was " very sudden " as though it was due " to chemical action at a definite temperature." With bituminous coals the principal water formation occurred between 400° and 650° C., which, it may be remarked, is well below Burgess and Wheeler's supposed critical temperature of 750°. It is therefore certain that water is a primary decomposition product of the coal substance, and that its principal formation occurs below 600°, if not below 500°. Moreover, the amount of it produced below 600° is so large in proportion to the oxygen content of the coal that it seems difficult to ascribe it to the decomposition of any other than the principal oxygen constituents of the coal, namely, the cellulosic constituents, a conclusion which again seems to be inconsistent with Wheeler's arguments respecting the thermal decomposition of coal.

It may here be observed that hitherto too little attention has been paid by chemists to the variations in the relative proportions of oxygen appearing as water on the one hand, and as oxides of carbon on the other, among the products of the low temperature distillation of different coals. Experiments recently made in the writer's laboratory have shown that these relative proportions may vary considerably, even in the case of coals having almost the same oxygen content. Thus, for example, in a series of experiments in which 15 grams of two different (dried) coals, one a Barnsley Hard Coal, and the other a Durham Coking Coal, but with nearly the same oxygen contents, were separately distilled at 550°, the relative proportions of the oxygen eliminated as water and as oxides of carbon differed very considerably, as the following figures show :—

TABLE XXX

Coal.		Barnsley Hard Steam Coal (Maltby Colliery).	Durham Coking Coal (Langley Park Colliery).
Percentage Composition of the Dry Coal Substance	C.	84·67	85·02
	H.	5·13	4·83
	N.	1·54	1·11
	S.	0·72	1·30
	O.	7·94	7·74
Grams expelled at 550° C.	CO_2	0·0297	0·0198
	CO	0·0900	0·0498
	H_2O	0·52	0·17
Weight Ratio $\left\{ \dfrac{O \text{ as } H_2O}{O \text{ as } CO \text{ and } CO_2} \right.$		6·3	3·5

These experiments, which are regarded as merely preliminary ones, are being extended with a view to a complete exploration of the subject as a possible basis of discrimination between different types and classes of coal.

In 1914, H. C. Porter and G. B. Taylor of Pittsburg published an important memoir embodying the results of their investigations upon the mode of decomposition of certain American coals at temperatures up to 450°, which had led them to conclusions very different from those of Burgess and Wheeler, whose interpretations they freely criticised.[1]

[1] *Proc. Amer. Gas. Institute*, 1914, IX. i., pp. 234 to 288.

The object aimed at in their experiments was to elucidate the nature of the primary decomposition of the coal substance under conditions calculated to eliminate as far as possible the influence of secondary reactions, which complicate the process in industrial practice. With this end in view, the heating was carried out under a high vacuum (0·5 to 10·0 m.m.) in a glass bulb immersed in a bath of a molten mixture of sodium and potassium nitrates (m.p. 220° C.), which could be maintained continuously at any particular experimental temperature (250°, 350°, 450°) desired. By such means the walls of the bulb were at no point heated above the temperature of the coal. It was also shown experimentally that neither the character of the decomposition of the coal substance nor the temperature at which it began was materially affected by a reduction in pressure.

The following four coals, differing considerably in their contents of oxygen and " volatiles," were selected for investigation ; they had been stored since being mined in closed containers as ¼ to ½ inch lumps, and before use were " air dried " and crushed so as to pass a 40-, but not a 100-mesh sieve.

TABLE XXXI

PERCENTAGE COMPOSITION OF THE COALS

Origin.		New River, West Virginia.	Pittsburg.	West Frankfort, Illinois.	Sheridan County, Wyoming.
As used	Moisture . . .	0·60	0·93	2·07	5·98
	Volatiles . . .	21·60	33·02	35·21	41·47
	Ash	3·23	9·07	9·17	6·45
Dry Ashless Coal Substance	C. . . .	89·30	85·25	80·91	74·94
	H. . . .	4·88	5·45	5·14	5·26
	O. . . .	3·60	5·59	10·89	16·93
	Volatiles .	22·42	36·69	39·70	47·35

From the mass of experimental data and curves published in the original memoir, to which the reader is referred for fuller information, the following eight curves (Figs. 11 to 18 inclusive),[1] as well as Table XXXII showing the results of typical experiments upon all four coals at 450°, are selected as illustrating the more important results.

[1] These curves are reproduced with the kind permission of the American Gas Institute.

FIG. 11.—Percentage yields of tar, water, gas, and total volatile by heating Pittsburg coal *in vacuo* at low temperatures.

FIG. 12.—Percentage yields of tar, water, gas, and total volatile |by heating New River (West Virginia) coal *in vacuo* at low temperatures.

FIG. 13.—Percentage yields of tar, water, gas, and total volatile by heating Franklin Co. (Illinois) coal *in vacuo* at low temperatures.

FIG. 14.—Percentage yields of tar water, gas, and total volatile by heating Wyoming sub-bituminous coal *in vacuo* at low temperatures.

FIG. 16.—Quantities of various gases obtained from New River (West Virginia) coal in vacuo at low temperatures.

FIG. 15.—Quantities of various gases obtained from Pittsburg coal in vacuo at low temperatures.

FIG. 11.—Percentage yields of tar
water, gas, and total volatile by
heating Pittsburg coal in vacuo at
low temperatures.

FIG. 18.—Quantities of various gases obtained from
Wyoming sub-bituminous coal in vacuo at low
temperatures.

FIG. 13.—Per
water, gas
heating
coal in vacuo

FIG. 17.—Quantities of various gases obtained from
Franklin Co. (Illinois) coal in vacuo at low tem-
peratures.

EXPERIMENTS AT 450°

	Pittsburg.	Illinois.	Wyoming.
9·0	8·5	9·5	10·0
2·3	4·30	8·29	12·64
6·08	12·76	7·73	8·17
3·80	4·01	4·80	8·66
12·18	21·07	20·82	29·47
H_2 ...	48·0	138·0	104·0	432·0
...	223·0	174·0	533·0	2128·0
...	130·0	187·0	483·0	1426·0
...	334·0	352·0	320·0	394·0
...	3551·0	3100·0	3158·0	2647·0
...	1168·0	653·0	935·0	1129·0
...	5498	4694	5621	8194
lue of n in C_nH_{2n+2} .	1·21	1·37	1·30	1·31
ite [2] { O as $\frac{H_2O}{CO+CO_2}$ }	5·0	10·0	6·9	2·8

from the large proportions of total volatile matter expelled 450° (i. e. from 55 to about 70 per cent.) it is evident that a very considerable amount of decomposition of the coal substance had taken place up to that point. Indeed, if the volumes of the oxides of carbon evolved be taken as at N.T.P., we get the following figures for the proportions of the oxygen in the original coal which had been eliminated as steam and oxides of carbon :—

		New River.	Pittsburg.	Illinois.	Wyoming.
Per 100 Coal heated	Total Oxygen	3·4	5·03	9·67	14·81
	O evolved as H_2O	2·04	3·80	7·37	11·24
	O evolved as CO_2 & CO	0·41	0·38	1·07	4·06
	Proportion so evolved	0·72	0·81	0·87	1·03

[1] This is the water actually produced by decomposition of the coals, and does not include the moisture in the "air-dried" sample heated.
[2] In calculating these ratios, the volume of CO and CO_2 given in the memoir has been taken as at N.T.P.

It is clear, therefore, that from 70 per cent. up to the whole of the oxygen containing constituents of the coal had undergone decomposition in the experiments, a fact which seems difficult to reconcile with Burgess and Wheeler's views. The large proportions of olefines and paraffins in the total gases evolved from the three bituminous coals is remarkable, as also is the fact that the ratio of the hydrocarbon to the hydrogen in these cases was at the least 3·3, and at the most as high even as 5·3, which observations substantially agree with those of Burgess and Wheeler.

The American investigators remark, in reference to Wheeler's views, that " coal does not seem to contain a substance which remains unaltered or nearly so below 750° C. and rapidly produces hydrogen above that temperature. It seems rather to contain a substance—in fact gas coal is probably largely made up of substances—which yielded the complex paraffin hydrocarbon at low temperatures and a large amount of hydrogen at high temperatures from the decomposition residue. There is no well-marked ' critical ' point in the decomposition of coal. There is, however, a well-marked critical point between 1300° and 1450° F. (704° and 788° C.) in the secondary decomposition of the volatile matter—tar and gases."

The principal results of their own experiments may be summarised as follows :—

(1) More than two-thirds of the organic substance of coal is decomposable below 500° C., but there is a variation among different kinds of coal in their ease of decomposition. In the case of American coals, those of the Appalachian field, because of their greater maturity, are less easily and rapidly broken down than the younger coals of the Middle Western and Western fields.

(2) The first decomposition occurring in any type of coal as the temperature is raised is the breaking down of certain oxygen-bearing substances related to cellulose, from which chiefly water of decomposition, CO_2 and CO are produced.

(3) Other decompositions, producing paraffin hydrocarbons both liquid and gaseous, begin at an early stage. Whether or not such decompositions become the predominating type below 500° depends on the character of the coal, and, as a general rule, the higher the oxygen

in the coal, the less will be the proportion of hydrocarbons and tar in the volatile matter. In the case of a sub-bituminous coal the "water-CO_2" yielding reaction predominates up to 450°.

(4) Secondary decompositions of the primary volatile products occur quickly and easily at temperatures of 1350° F. (= 732° C.) and above. The liquid hydrocarbons in the tar undergo such decomposition more easily than the gaseous products and yield below 1350° F. methane, hydrogen, ethylene, hydrocarbons, and carbon.

At the conclusion of their memoir Porter and Taylor advanced the following hypothesis for the constitution of coal, which differs fundamentally from that of Burgess and Wheeler in supposing that the cellulosic derivatives decompose more easily than the resinic constituents; like Burgess and Wheeler, however, they have ignored the nitrogenous constituents of the coal substance.

" All kinds of coal consist of cellulosic degradation products more or less altered by the processes of ageing, together with derivatives of resinous substances, vegetable waxes, etc., in different proportions, more or less altered. They all undergo decomposition by a moderate degree of heat, some, however, decomposing more rapidly than others at the lower temperature. The less altered cellulosic derivatives decompose more easily than the more altered derivatives and also more easily than the resinous derivatives. The cellulosic derivatives decompose so as to yield H_2O, CO_2, CO, and hydrocarbons, giving less of the first three products the more matured and altered they are. The resinous derivatives, on the other hand, decompose on moderate heating so as to yield principally the paraffin hydrocarbons, with probably hydrogen as a direct decomposition product. The more mature bituminous coals, having good coking properties, contain a large percentage of resinous derivatives, and their cellulosic constituents have been highly altered. The younger bituminous or sub-bituminous coals are constituted of cellulosic derivatives much less altered than those in the older coals. They undergo a large amount of decomposition below their fusion point and possibly for that reason many of them do not coke."

They also predict from their experiments that the products of low temperature carbonisation on an industrial scale of a coal of the Pittsburg type at from 427° to 482° C. (800° to 900°

will consist of a rich gas amounting to 0·6 to 0·7 cub. ft. per lb. of coal, and a larger yield of oil or tar, comprising 10 to 12 per cent. of the coal; also, that this tar will, they say, consist chiefly of paraffin hydrocarbons (? what of naphthenes, *cf.* Jones and Wheeler, and also Pictet and Bouvier), and will be almost, or possibly entirely, devoid of benzene and naphthalene derivatives or of free carbon. That the gas will contain 6 to 7 per cent. of unsaturated hydrocarbons and 20 to 25 per cent. of ethane and its higher homologues, and will consequently have a high calorific and illuminating value.

From experiments carried out in the writer's laboratory upon typical British coals at the somewhat higher temperature of 550° C. it seems probable that they will yield from 5 to 8 per cent. of their weight of water, from 8 to 10 per cent. of oils, and some 3000 cub. ft. per ton of crude gas containing :—H_2S — 0·5 to 2·0, $CO_2 = 2·0$ to 5·0, $CO = 4·0$ to 18·0, $C_nH_{2n} = 3·5$ to 5·0, $C_nH_{2n+2} = 55·0$ to 75·0, and $H_2 = 5·0$ to 15·0 per cent.

Summing up now the present state of our knowledge with regard to the primary action of heat upon coal, it would appear :—

(1) That whilst the view originally advanced by Wheeler and his co-workers in respect of the relative stabilities of the cellulosic and resinic compounds requires to be modified in the light of later investigations, we nevertheless owe to them the discovery of a series of important facts which none of their critics have seriously impugned and which have been substantially confirmed by other workers. The primary decomposition of the coal substance, as they themselves proved, begins at 200° C. (or thereabouts) with an elimination of water and oxides of carbon, and continues up to and probably beyond 450°. At 350°, or thereabouts, a point is reached at which the evolution of gases (principally hydrocarbons of the C_nH_{2n+2} and C_nH_{2n} series) becomes pronounced. Hydrogen forms a small proportion of the gases evolved until the temperature rises to between 700° and 800° C. (Wheeler's " critical " temperature), when it suddenly increases in volume and becomes the predominant gaseous product.

(2) That it is still undecided whether the large increase in the evolution of hydrogen which undoubtedly occurs between

700° and 800° can be wholly attributed to the secondary decomposition of tar vapours and gaseous hydrocarbons. In part it certainly can be, from the known behaviour of these bodies, but it is still possible that it may in part arise also by the decomposition of a condensed " cellulosic " complex from which hydroxyl groups have been previously eliminated at lower temperatures. Further investigation will be needed before this point can be finally cleared up.

(3) That it is unanimously agreed that, as Wheeler discovered, aromatic hydrocarbons of the benzene series are not found, except in quite negligible quantities, among the condensable low temperature products, which apparently consist mainly of cyclic hydroaromatic products, together with smaller proportions of the higher olefines and some paraffins.

(4) That the question of how far the formation of aromatic hydrocarbons of the benzene series at higher temperatures can be accounted for by the dehydrogenation of the hydroaromatic rings, or how far it may be necessary to invoke (as D. T. Jones suggests) the aid of olefine condensations in such connection, is one which future investigations must decide. It seems generally agreed, however, that acetylene plays but an insignificant *rôle* in coal tar formation.

(5) Another moot point is whether phenolic bodies are primarily produced at low temperatures; here the available evidence is not altogether satisfactory, for whilst Jones and Wheeler have asserted that they occur to an extent of between 12 and 15 per cent. in the tars produced from British bituminous coals up to 430°, Pictet and his collaborator found less than 2 per cent. of them in the " vacuum tars " obtained by distilling a French bituminous coal at 450° under a pressure of 15 to 20 m.m. Also, the independent confirmation of Jones and Wheeler's observation of the occurrence of homologues of naphthalene in low temperature tars will be awaited with interest.

(6) The systematic exploration of the character of the resinic constituents of coals will afford abundant opportunities for chemical research, and finally, the elucidation of the nature and modes of decomposition of the " ammonia-yielding " nitrogenous constituents, so consistently

ignored by the chemists whose researches have been reviewed in this chapter, is an aspect of the main problem which greatly needs attention.

That differences should have arisen between competent investigators, both in regard to observations of fact, as well as in interpreting such facts as command unanimous assent, will cause no surprise when the great complexity of the coal substance and its behaviour are considered. Indeed, as in most other branches of scientific work, it has been through the conflict of opinion based upon honest and disinterested research that the truth has at length emerged. And from the stricken field all who have worthily contended may retire with equal honours.

CHAPTER VIII

THE CHEMICAL COMPOSITION OF COAL (*contd.*)

F. SOME SECONDARY DECOMPOSITIONS AND INTERACTIONS OF THE
   PRIMARY DISTILLATION PRODUCTS IN HIGH TEMPERATURE
   CARBONISATION

Theories as to the Formation of Aromatic Compounds

ALTHOUGH certain aspects of the secondary decompositions
and interactions of the primary distillation products have been
incidentally touched upon in the preceding chapter, the subject
is sufficiently important to warrant separate and fuller treat-
ment. It is, however, so many-sided and complicated that the
present review of it must therefore necessarily be restricted
to a few of its principal features. Moreover, although high
temperature carbonisation is now a highly developed branch of
chemical industry, it is not proposed in this chapter to deal
with either purely technical problems or the mechanical details
of large scale plant and operations. What we would rather
essay to do is to indicate the trend of recent discoveries and
investigations in regard to some of the basic principles under-
lying all industrial high temperature practice.

With regard to the manufacture of coal gas, M. St. Claire
Deville has published the following table embodying the results
of gas-making tests upon five typical bituminous coals carried
out on the testing plant of the Paris Gas Works. Judging from
the results, the carbonising temperature probably did not much
exceed 900° C.

TABLE XXXIII

EXPERIMENTS UPON COALS AT THE PARIS GAS WORKS

	1.	2.	3.	4.	5.
	88·38	86·97	85·89	83·37	81·66
	5·06	5·37	5·40	5·53	5·64
	1·00	1·00	1·00	1·00	1·00
	5·56	6·66	7·71	10·10	11·70
	2·17	2·70	3·31	4·35	6·17
	13·70	15·08	15·81	16·95	17·00
	3·40	4·65	5·08	5·48	5·59
	4·58	5·22	6·80	8·62	9·86
	73·18	68·41	66·20	62·66	60·73
	1·47	1·58	1·72	2·70	3·13
	0·08	7·19	8·21	9·85	11·93
	3·27	4·01	4·94	5·58	5·54
	34·37	34·43	35·03	36·42	37·14
	54·21	52·79	50·10	45·45	45·26
	0·352	0·376	0·399	0·441	0·482

... the results of experiments carried ... with a typical British gas coal on ... plant at the Birmingham Gas ... were carbonised in 6 hours, ... being successively raised in each

TABLE XXXIV

EXPERIMENTS AT THE BIRMINGHAM GAS WORKS

		% Composition of Gas.					
		After Purification.					
		CO_2	CO.	C_nH_m.	CH_4.	H_2.	$N_2 + O_2$
		2·1	8·05	4·78	34·1	40·2	9·68
		2·80	9·40	5·20	33·7	43·3	5·10
		2·00	10·10	4·00	34·5	42·7	5·20
		2·05	10·08	3·96	31·4	41·5	9·26

... only show the average com- ... carbonising the coal at the tem- ... 1910, p. 269.

peratures named. As the carbonisation proceeds, and the heat penetrates more and more into the decomposing charge, its temperature is gradually raised, and the stream of gases and vapours evolved not only slackens, but it has to traverse, at a progressively slower rate, a region of increasing temperature in the retorts. Hence the quality of the gas naturally falls off rather rapidly after the first hour or so of the carbonisation period; the percentages of methane, ethylene, and benzene, or in other words of the hydrocarbons generally, diminish whilst that of the hydrogen progressively increases. This is shown in the following table, which gives the composition of the gas evolved at different times during the carbonisation period for a retort charged with a Derbyshire coal which was being carbonised at about 950° C.

TABLE XXXV

		Hours after Commencement.				
		0·5.	1·5.	2·5.	3·5.	5·0.
Percentage Composition of the Crude Gas	H_2S . . .	3·8	3·1	2·8	2·1	1·2
	CO_2 . . .	3·0	2·8	2·6	2·3	1·7
	CO . . .	4·4	5·0	4·9	4·5	3·8
	C_mH_n . . .	8·6	5·2	3·6	2·4	*nil*
	CH_4 . . .	49·7	42·0	39·4	37·5	26·3
	H_2 . . .	29·8	37·5	42·2	46·2	60·8
	N_2 . . .	0·7	4·4	4·5	5·0	6·2

The composition of a purified " coal gas," as distributed from the works to consumers, will usually vary between the following limits :—[1]

	Per cent.
Carbon dioxide	0·0 to 3·0
Carbon monoxide	5·0 „ 10·0
Ethylenic Hydrocarbons	2·0 „ 4·0
Benzene Hydrocarbons	0·5 „ 1·0
Methane	30·0 „ 35·0
Hydrogen	40·0 „ 55·0
Nitrogen	5·0 „ 10·0

In the manufacture of hard metallurgical coke, as carried out in the newer types of by-product ovens, the temperatures attained by the charge (1100–1200° C.) are rather higher than those usually prevailing in gas-works retorts, which circumstance

[1] These figures refer to a " straight " coal gas without admixture of water gas which has not been " stripped " of its benzene hydrocarbons.

is reflected in a somewhat lower average quality of gas. A good coking coal containing 30 per cent. of volatile matter will yield, besides practically the theoretical amount of coke, from 3·5 to 4·5 per cent. of its weight of tar, from 2·5 to 3·0 gallons of crude " benzol " (containing benzene and its homologues), ammonia corresponding to from 20 to 30 lb. of the sulphate, and from 10,000 to 12,000 cub. ft. of gas containing (after removal of H_2S) :—

	Per cent.
Carbon dioxide	2·0 to 4·0
Carbon monoxide.	5·0 ,, 10·0
Ethylenic Hydrocarbons . . .	2·0 ,, 3·0
Methane	25·0 ,, 33·0
Hydrogen	45·0 ,, 55·0
Nitrogen	5·0 ,, 15·0

The high temperature tars obtained in the manufacture of towns gas, or from coke-oven installations, are all " aromatic " in character, containing benzene, toluene, xylenes, pyridine bases, phenol and cresols, anthracene, naphthalene, and also a so-called " free-carbon " which, however, always contains some hydrogen and is possibly composed of very dense and complex hydrocarbons which are insoluble in the tar. The specific gravities of these tars vary between 1·07 and 1·25, thinner and lighter tars being obtained when the coal is distilled in the newer " vertical " rather than in the older " horizontal " gas retorts, whilst coke-oven tars are as a rule intermediate between the two. When fractionally distilled in a laboratory test they are, in the first instance, usually divided into :—

		B.P. ° C.
(1)	Water and Light Oils. . . .	up to 170°
(2)	Middle Oils	170 ,, 230°
(3)	Heavy Oils	230 ,, 270°
(4)	Anthracene Oil	above 270°
(5)	Residual Pitch	above 360°

The composition of a representative coke-oven tar may be judged from the following particulars of the results of a distillation trial in which over 1000 tons of a North of England Coke-oven Tar were fractionated during a five weeks' run of the plant, each ton of tar yielding :—[1]

---

[1] These results are reproduced, by the kind permission of the publishers, from p. 146 of the late Mr. G. Stanley Cooper's book on *By-Product Coking* (Benn Bros., Ltd., London, 1917) to which the reader is referred ·particulars about Tar Distillation.

Containing

(1) *Water*   =   6·5 galls.   3 per cent. NH_3

(2) *Crude Naphtha* =   2·8 galls. $\left\{\begin{array}{l} \text{17 per cent. benzene} \\ \text{17·5 per cent. toluene} \\ \text{12·5 per cent. solvent naphtha} \\ \text{(xylene)} \\ \text{2·5 per cent. pyridine bases} \\ \text{3·0 per cent. tar acids} \\ \text{25·0 per cent. naphthalene} \end{array}\right.$
    (Sp. Gr. 0·936)

(3) *Light Oil*   = 23·6 galls. $\left\{\begin{array}{l} \text{15·6 per cent. phenol and cresols} \\ \text{35·0 per cent. naphthalene} \end{array}\right.$
    (Sp. Gr. 1·011)

(4) *Creosote Oil*   = 41·1 galls. $\left\{\begin{array}{l} \text{8·4 per cent. phenol and cresols} \\ \text{28·0 per cent. crude naphthalene} \end{array}\right.$
    (Sp. Gr. 1·049)

(5) *Anthracene Oil* = 17·3 galls. $\left.\begin{array}{l} \\ \end{array}\right\}$ 20 per cent. crude anthracene
    (Sp. Gr. 1·090)

(6) *Pitch*   = 11 cwt., having a twisting point of 55° C.

The chief differences, therefore, between the products obtained by the distillation of a bituminous coal at low and high temperatures, respectively, may be summarised as follows :—

TABLE XXXVI

	Low Temperature Distillation. 450° to 550° C.	High Temperature Distillation. 900° to 1100° C.
Gas.	2000 to 3500 cub. ft. per ton consisting chiefly of methane, ethane, and other paraffins, together with olefines and less than 15 per cent. of hydrogen.	9000 to 12,000 cub. ft. per ton, consisting chiefly of methane (25 to 35 per cent.) and hydrogen (45 to 55 per cent.). No paraffins higher than methane.
Tars.	7 to 10 per cent., consisting chiefly of paraffins and naphthenes (hydro-aromatic hydrocarbons), but no benzenoid derivatives, together with a soft pitch containing no free carbon.	4 to 7 per cent., consisting chiefly of aromatic (benzene) hydrocarbons, pyridine bases, phenols, naphthalene, anthracene, etc., together with a hard pitch containing free carbon.
Ammonia (*as sulphate*).	5 to 7 lb. per ton.	20 to 30 lb. per ton.
Residue.	A " semi-coke " containing up to 15 per cent. of " volatiles."	A hard coke consisting principally of carbon and ash.

If the characteristic high temperature aromatic coal distillation products are regarded as having resulted from the secondary decompositions and interactions of such primary products as methane, ethane, propane . . . ethylene, propylene . . . hexahydrobenzenes . . . during which hydrogen is continuously eliminated, as shown both by its increasing prominence in the gaseous products at high temperatures, as well as by the highly complex hydrocarbons, or carbon, produced, it is of interest to enquire how far chemical science can define the conditions and mechanism of such changes. This naturally brings us to the discussion of the formerly much-controverted question of the thermal decompositions of the simpler hydrocarbons, and the physical conditions which favour them.

It has been well known for nearly a century that under the influence of dull red heat some of the simpler hydrocarbons undergo profound changes, but it was not until after 1863-9, mainly as the result of the pioneering researches of Berthelot,[1] that the subject became ripe for systematic development in either its experimental or theoretical aspects.

As the result of an extensive series of rapidly executed experiments, Berthelot, who in 1859 had re-discovered the hydrocarbon acetylene, the remarkable properties of which he was the first to explore, put forward his well-known general theory concerning the ways in which the denser aromatic hydrocarbons may be produced at red heat from even the simplest paraffins and olefines. He assigned to acetylene a *rôle* of unique importance as the " pivot " of the whole system. Indeed he described this hydrocarbon as " *le produit ultime des décompositions pyrogenées . . . generateur fondamental des carbures pyrogenées* " in that it exhibits in an exceptional degree the power of polymerising and of condensing either with hydrogen or aromatic hydrocarbons at high temperatures.

Berthelot based his theory upon the assumption that no hydrocarbon (not even acetylene) is ever directly resolved into its elements by heat, but that its primary decomposition always involves either a polymerisation (*e. g.* acetylene to benzene), or a coalition of two or more molecules to form a denser one with elimination of hydrogen. Thus in the case of the simplest hydrocarbons, he assumed the following alternative primary

[1] *Ann. Chem. Phys.*, 1863 (iii.), **67**, 53 ; 1866 (iv.), **9**, 413, 455 ; 1867 (iv.), **12**, 5, 122 ; 1869 (iv.), **18**, 143, 148, 153, 162.

changes of which (*b*) was considered as the more frequent and probable :—

$$
\text{Methane} \quad \cdot \quad \cdot \quad \cdot \begin{cases} (a) \ CH_4 \ = C_2H_4 + H_2 \\ (b) \ 2CH_4 = C_2H_2 + 3H_2 \end{cases}
$$

$$
\text{Ethane} \quad \cdot \quad \cdot \quad \cdot \begin{cases} (a) \ C_2H_6 = C_2H_4 + H_2 \\ (b) \ 2C_2H_6 = 2CH_4 + C_2H_2 + H_2 \end{cases}
$$

$$
\text{Ethylene} \quad \cdot \quad \cdot \quad \cdot \begin{cases} (a) \ C_2H_4 = C_2H_2 + H_2 \\ (b) \ 2C_2H_4 = C_2H_6 + C_2H_2 \end{cases}
$$

The acetylene produced in what were regarded as the more probable changes (*b*) would, it was further supposed, rapidly polymerise to benzene, which in turn would coalesce with more acetylene forming styrolene, naphthalene, anthracene, etc., according to the following scheme :—

(1)

$$3(HC\colon CH) = \text{BENZENE}$$
ACETYLENE

(2) BENZENE + HC:CH = STYROLENE

(3) BENZENE + HC:CH / HC:CH = NAPHTHALENE + H_2

(4)

$$\text{benzene} + HC{:}CH + \text{benzene}$$

$$= \text{ANTHRACENE} + 2H_2$$

ANTHRACENE

Following the same line of reasoning, Berthelot supposed that it is by the further mutual coalition of such dense hydro-carbon molecules, with the elimination of hydrogen at each stage, and in no other way, that carbon is at length obtained as the final product of the decomposition of an extremely complex molecular aggregation.

Moreover, in elaborating this idea, he convinced himself that the successive changes involved in the decomposition of any particular hydrocarbons are usually either all individually reversible, or may be so grouped as to form a series of reversible cycles, and that therefore at any given temperature there would finally be established a complex state of dynamic equilibrium between hydrogen, methane, ethane, ethylene, acetylene, benzene, styrolene, diphenyl, naphthalene, anthracene . . . and carbon.[1]

---

[1] Berthelot's views are summarised in the following passage from one of his memoirs (*Ann. Chim. Phys.*, 1866 (iv.), **9**, 471) : " . . . que la décomposition immédiate d'un carbure d'hydrogène ne répond pas à sa résolution en éléments, mais à sa transformation en polymères, ou en carbures plus condensés avec perte d'hydrogène. Cette transformation ne s'effecte point d'ailleurs à une température absolument fixe et comparable à celle d'ébullition d'un liquide ; mais elle s'opère pendant un vaste intervalle de température compris entre le rouge sombre et le rouge blanc ; durant cet intervalle le carbure est décomposé en proportion d'autant plus forte et avec une vitesse d'autant plus grande que la température est plus élevée. . . . Entre

Such a theory, it must be admitted, is a singularly attractive one. It would explain how, at the temperatures prevailing in gas retorts, even the simplest of hydrocarbons can be transformed, through a whole series of successive condensations and intermediate products, into the most complex, and the assumption of the attainment at each temperature of a state of mobile equilibrium in such a system of reversible interactions fits in well with the modern thermodynamical conception of chemical changes in general. In no case, however, was the actual attainment of such a complex state of equilibrium in this " hydrogen-hydrocarbon-carbon " system ever proved by any quantitative measurement; it was considered sufficient to obtain qualitative evidence of the reversibilities of some of the principal individual reactions concerned, and then to deduce the general theory by the application of first principles.

The theory, emanating as it did from so distinguished an investigator as Berthelot, naturally commanded a good deal of support, and it was revived in a modified form by the late Vivian B. Lewes in connection with his well-known views respecting the luminosity of hydrocarbon flames.[1]

It should, however, be noted that whilst Lewes agreed with Berthelot in regarding acetylene as a principal and primary product of the decomposition of both methane and ethylene, and as responsible for the formation of aromatic hydrocarbons, he differed from Berthelot in considering it capable of direct decomposition into its elements at high temperatures with explosive effect (due to its endothermic character). Indeed Lewes's theory of the luminosity of hydrocarbon flames was based upon the belief that in the inner zone of a coal-gas flame the hydrocarbons are, under the influence of radiant heat from the outer envelope, largely converted into acetylene, which at the still higher temperatures of the luminous region is resolved into its elements, the liberated carbon particles being raised to a much higher temperature than that of the surrounding flame, consequent upon the sudden disengagement of the energy originally locked up within the acetylene molecules.

Lewes represented the primary decomposition of methane and

---

chaque genre de réaction et la réaction réciproque il s'établit fréquemment une sort d'équilibre mobile, variable avec la température et les corps qui se trouvent en présence, équilibre analoque à celui qui se produit lors la dissociation des composés binaires."

[1] *Journ. Chem. Soc.*, 1892, **69**, 322; *Proc. Roy. Soc.*, 1894, **55**, 90; 1895, **57**, 394 and 450.

ethylene by the following equations which are either identical with, or similar to, those postulated by Berthelot :—

$$\text{(i)} \quad 2CH_4 = C_2H_8 + 3H_2.$$
$$\text{(ii)} \quad 3C_2H_4 = 2C_2H_2 + 2CH_4.$$

Such then is the " acetylene " theory of the pyrogenetic formation of aromatic hydrocarbons, both in its original and in its modified form. And it must be admitted that independent experiments made even by its opponents have proved that not only does acetylene polymerise to benzene at 500° to 700°, as postulated by Berthelot, but that it also decomposes explosively into its elements at still higher temperatures (above 800°) as Lewes always maintained. Nevertheless it seems to the writer that the theory must now be abandoned on the grounds principally (1) that in fact acetylene is not necessarily a prime or principal product of the decomposition of methane, ethylene, ethane, etc., as both Berthelot and Lewes have asserted ; (2) that acetylene is never present anywhere in a gas retort in amounts sufficient to warrant its being regarded as even the principal, much less the only, progenitor of the aromatic hydrocarbons, as Berthelot stipulated ; and (3) that the formation of aromatic hydrocarbons can be satisfactorily accounted for in other and more probable ways.

Before, however, considering the modes in which the simpler hydrocarbons decompose at high temperatures, attention may be drawn to certain facts which have been established concerning the behaviour of some of the higher paraffins than methane and ethane. In 1873 T. E. Thorpe and J. Young,[1] as the result of an investigation on the combined action of heat and pressure on the paraffins, concluded that the primary decomposition gives rise to an olefine and a lower paraffin without loss of hydrogen somewhat as follows :—

$$CH_3 \cdot CH_2 \cdot CH_2 \cdot CH_3 = CH_3 \cdot CH_3 + CH_2 : CH_2.$$

Moreover, in 1886, H. E. Armstrong and A. K. Miller,[2] during an exhaustive investigation of the products obtained in the manufacture of " oil gas " from petroleum, found considerable quantities of ethylene and normal olefines of the type $(C_nH_{2n+1})CH.CH_2$, up to and including n-heptylene, as well as of benzenoid hydrocarbons. They also drew particular attention to the almost entire absence of acetylene or its homologues, and suggested the possibility of the direct formation of aromatic hydrocarbons

[1] *Proc Roy. Soc.*, **21**, p. 184.   [2] *Journ. Chem. Soc*, **49**, p. 74.

from the corresponding paraffins (say benzene from hexane) without the interaction of acetylene.

Finally, in 1896, F. Haber [1] published a paper on the decomposition of the higher hydrocarbons, in which he vigorously assailed the theories of both Berthelot and Lewes, and proved conclusively that in the case of *n*-hexane, which was selected as being the paraffin most nearly related to benzene, the primary decomposition at temperatures between 600° and 800° C. involves the elimination of methane and the formation of the next lower olefine, amylene, without any appearance of acetylene whatsoever, a behaviour which he regarded as typical of all the higher paraffins, thus :—

$$CH_3 \cdot (CH_2)_n \cdot CH_2 \cdot CH_2 \cdot CH_3 = CH_3(CH_2)_n \cdot CH:CH_2 + CH_4.$$

In the aromatic series, however, he recognised a marked disposition to form more complex molecules with the elimination of hydrogen, *e. g.* diphenyl from benzene, thus :—

It is interesting to note, in passing, that whilst Haber thus rejected *in toto* the Berthelot-Lewes theories as untenable, he nevertheless accepted the then prevailing notion, which subsequent research has disproved, of the inherent superior stability of acetylene over that of all other hydrocarbons at high temperatures. For he stated that, whilst it polymerises readily at 600°, and at 800° yields large quantities of hydrogen, it is at still higher temperatures " *in starker Verdünnung jedem anderen Kohlenwasserstoff an Beständigkeit überlegen.*"

It, therefore, may be said that nothing has been discovered regarding the behaviour of the higher paraffins at 600° to 800° which warrants the acceptance of the idea that acetylene is either the prime or principal progenitor of aromatic hydrocarbons in such pyrogenetic decompositions. Not only so, but it is now apparent, both from the identification by Pictet and Bouvier of a whole series of " hexahydrobenzene " hydrocarbons in low temperature coal-tars (see p. 112 hereof), as well as from the recent researches of D. T. Jones upon the decomposition of such hydrocarbons by heat (p. 114), that another and far more

---

[1] *Ber.,* **29**, p. 2191.

probable source of aromatic hydrocarbons in high temperature tars has been discovered, and that there is therefore no need for the chemist to invoke any longer the aid of acetylene in this connection.

The work of W. A. Bone and H. F. Coward [1] upon the behaviour of the simpler hydrocarbons at temperatures between 500° and 1200° C., which has already been referred to in the preceding chapter, may now be more fully considered in its bearings upon the secondary interaction occurring in the gas retort. Their experiments were carried out in such a manner that the pure dry gases (methane, ethane, ethylene, and acetylene), usually undiluted, but sometimes diluted either with nitrogen as an inert gas or with hydrogen as a " hydrogenising " agent, were either shut up for a definite interval of time in, or caused to flow through, a jacketed tube of Berlin porcelain heated to the desired temperature, suitable arrangements being installed for the condensation of any aromatic hydrocarbons which might be produced, as well as for the collection of representative samples of the gaseous products. In some of the experiments at temperatures below 800° the apparatus was so arranged that the gases were continuously circulated by means of an automatic Sprengel pump round a closed circuit (which included the heated tube and the condensing and gas-sampling arrangements, as well as a pressure gauge) until a state of constant pressure was finally attained, the whole process being kept under close observation from start to finish and the influence of time as well as of pressure and temperature investigated. Also, by making comparative experiments at a given temperature and pressure with the reaction tube alternately packed or unpacked with suitably sized fragments of porous porcelain or lime, the influence of surface upon the decomposition, which in the case of methane in particular is all-important, could be established.

Experiments upon methane showed not only that it is by far the most stable of all the hydrocarbons examined, but also that it is always a principal product of the decomposition of the other three, especially at temperatures above 800°. Moreover, its decomposition at temperatures between 800° and 1200° is, unlike that of the other hydrocarbons, entirely a " surface " effect, and involves the direct formation of hydrogen and carbon, the latter being deposited upon the walls or packing of the tube in a peculiarly

[1] *Journ. Chem. Soc.* 1908, p. 1197; also *Trans. Inst. Gas Engineers,* 1908, p. 178.

w
:ed
785°
>f an
.hane,
race of

ion tube
), demon-
n upon the

	985°.	1015°.
	30.	60.
nil	nil	nil
1·3	0·35	nil
·5·25	62·85	48·2
33·3	36·8	51·2
e of a in the om in- presence c hydro-	No indication of any aro- matic hydro- carbon va- pours.	

· be seen from the following
.m unpacked reaction tube :—

XXVIII

	785°.	1015°.	1150°.
· · ·	nil	nil	nil
· · ·	91·6	48·2	9·15
· · · ·	8·4	51·8	90·85
Methane de- · · · ·	4·4	35·0	83·3

The all-important influence of surface was strikingly demonstrated by two comparative experiments at 1015° to 1030°, the one with the reaction tube unpacked, in which 35 per cent. of the original methane was decomposed in an hour ; and the other with a packing of fragments of quicklime, in which no less than 96 per cent. of the hydrocarbon disappeared within 25 minutes, whilst at the end of an hour, when final equilibrium had been established in the system, only about 1 per cent. of it remained.

Another characteristic feature of the methane-decomposition is the fact that whenever a highly concentrated gas was admitted into the heated reaction tube, the observed rate of decomposition was, during the first few minutes, always proportional to some high power of the concentration, but that afterwards it rapidly approached, and finally attained, a value corresponding to a simple reaction of the first order. The facts as a whole seemed to be consistent with the view that, whenever highly condensed layers of methane are decomposing in contact with a surface at 800° or above, conditions may be produced under which the formation of acetylene and even benzene in minute quantities becomes possible, owing to the abnormally high surface concentration ; but that with the disappearance of such conditions, the normal monomolecular decomposition of the gas directly into its elements, which is always dominant under all conditions, exclusively prevails, after which neither acetylene nor benzene is formed at all. Certainly the experimental results taken as a whole were inconsistent with the supposition that acetylene is a primary decomposition product, even in those experiments in which its formation could just be detected, the main change always being in accordance with the equation :—

$$CH_4 \rightleftarrows C + 2H_2$$

The experiments therefore showed :—(1) that the secondary decompositions of methane occurring at temperatures above 800° C. in either a gas retort or a coke oven are practically, if not entirely, confined to the gas which actually comes in contact with heated surfaces such as are presented by the walls of the retort or by the hot charge of carbonised fuel ; (2) that such decompositions are much slower than those of the higher paraffins or olefines, owing to the greater stability of methane ; and (3) that whilst the peculiarly hard and lustrous form of the carbon deposited from the gas as it slowly decomposes at temperatures between 800°

and 1200° may influence the properties of the resulting coke, the yields of benzene or aromatic hydrocarbons are hardly likely to be affected in any measurable degree by methane-decompositions.

In the case of the other three hydrocarbons investigated it soon became clear that we no longer had to do with a mere surface effect, as was the case with methane, but with one which is produced throughout the whole body of the gas by heat radiated from the walls of the hot enclosure. Decomposition was always very rapid in all three cases at temperatures above 800°, as the following will show :—

TABLE XXXIX

COMPOSITION OF THE GASEOUS PRODUCTS.						
Hydrocarbon.	Ethane.		Ethylene.		Acetylene.	
Temperature C°.	800°.	1000°.	800°.	1000°.	800°.	1000°.
Time (mins.).	15.	5.	15.	5.	15.	5.
Percentage Composition of the Gaseous Products C_2H_2	0·5	0·55	3·85	0·35	1·35	*nil*
C_2H_6	0·75	1·80	9·65	1·65	*nil*	*nil*
C_2H_4	*nil*	1·15	1·30	*nil*	*nil*	*nil*
CH_4	64·65	41·95	64·45	48·35	37·65	43·0
H_2	34·10	54·55	20·75	49·65	61·00	57·0

It is not, therefore, surprising that the gas evolved from retorts and ovens, in which coal is being carbonised at temperatures of 800° and upwards, should contain, as does towns gas, comparatively little ethylene, still less ethane, and practically no acetylene, although its methane content may be as high as 35 per cent. And if, as has been shown, the gas generated below 500° in the low temperature distillation of coal is comparatively rich in olefines, ethane, and other paraffins, it is clear that these must in turn largely undergo secondary decomposition at higher temperatures (above 800°) yielding, as the above results show, large quantities of both methane and hydrogen, as well as of other products.

It is, therefore, important to be able to picture the probable behaviour of these gases in the carbonising chamber (*a*) between 500° and 800° and (*b*) above 800°. In the cases of ethane and ethylene the experimental facts accord well with the supposition that the primary effect of heat is to cause an elimination of

hydrogen together with a simultaneous loosening or dissolution (according to temperature) of the bond between the carbon atoms, giving rise (in the event of dissolution) to residues such as $:CH_2$ and $:CH$. These residues, which can only have a very fugitive separate existence, may subsequently either (a) form $H_2C:CH_2$ or $HC:CH$, as the result of encounters with other similar residues; or (b) break down directly into carbon and hydrogen; or (c) be directly hydrogenised to methane in an atmosphere of hydrogen. All these possibilities may be realised simultaneously in the decomposing gaseous medium in proportions dependent upon the pressure, temperature, and amount of hydrogen present. Moreover, (d) " condensations " of nascent molecules such as $H_2C:CH_2$ or $HC:CH$, in process of formation during the primary dehydrogenation, are also possible, especially where they are present in great concentration, so that aromatic nuclei might conceivably arise immediately after the primary dehydrogenation. The scheme for ethane and ethylene may be represented as follows :—

(d) Condensation to ⬡ $+ H_2$

$$(1) \quad H-\underset{\underset{H}{|}}{\overset{\overset{H}{|}}{C}}-\underset{\underset{H}{|}}{\overset{\overset{H}{|}}{C}}-H = \left[2(:CH_2) + H_2 \right] = \begin{cases} (a) & C_2H_4 + H_2 \\ (b) & 2C + 2H_2 + H_2 \\ (c) & plus\ H_2 = 2CH_4 \end{cases}$$

$$(2) \quad H-\underset{\underset{H}{|}}{C}=\underset{\underset{H}{|}}{C}-H = \left[2(:CH) + H_2 \right] = \begin{cases} (a) & C_2H_2 + H_2 \\ (b) & C + H_2 + H_2 \\ (c) & plus\ 2H_2 = 2CH_4 \end{cases}$$

(d) Condensation to ⬡

In the case of acetylene, the main primary change may either be one of polymerisation or of dissolution, according to the temperature, and if the latter, it may be supposed that residues $:CH$ are first formed, and subsequently either (a) recombine with others, (b) break down into carbon and hydrogen, or (c) are hydrogenised to methane, according to circumstances, as follows :—

$$(3) \quad HC:CH = \left[2(:CH) \right] = \begin{cases} (a) & HC:CH \text{ or } ⬡ \\ (b) & 2C + H_2 \\ (c) & plus\ 3H_2 = 2CH_4 \end{cases}$$

Polymerisation to ⬡

With regard to the possible secondary changes (*a*), (*b*) and (*c*) in such systems, it may be supposed that, in general, the proportion of (*b*) would increase with the temperature, whilst that of (*a*) would be influenced in the opposite sense. The occurrence of (*c*), which would obviously depend on the amount of hydrogen in the system at any given moment, is doubtless favoured by a temperature range of 800° to 1000°. Condensations or polymerisations (*d*) in the system are essentially what may be termed " low medium " temperature effects, a range of 500° to 700° being certainly a favourable one, as experiments with acetylene have proved. Moreover, at temperatures above 800°, the secondary slow decomposition of methane produced in all cases by the primary " hydrogenation " (*c*) must be reckoned with as an after-effect, the importance of which increases with the temperature.

Whilst reference must be made to the original memoir for details of the behaviour of the individual hydrocarbons at various temperatures between 500° and 1200°, the following observations will indicate sufficiently well for our present purpose the general tendencies displayed by each.

Although acetylene probably does not play any considerable part in the secondary interactions in a gas retort, yet from a study of its behaviour a good deal of information can be gleaned about the ways in which the principal types of secondary changes are influenced by temperature. The susceptibility of acetylene to polymerise between, say, 500° and 700° is easily demonstrated, and it is even more marked at the higher than at the lower temperature, as the following figures from " circulation " experiments indicate :—

Temperature C°.	Percentages of the Acetylene		
	Polymerised.	Hydrogenated to CH_4.	Resolved into C and H.
480–500°	48	13	39
650°	60	10	30

At all temperatures above 700° the tendency to polymerise rapidly diminishes, whilst the direct resolution into carbon and hydrogen increases, until at 800° the undiluted gas undergoes the characteristic luminous decomposition first observed and described by V. B. Lewes. About 75 per cent. of the gas was decomposed at 800° during this instantaneous " flash " decomposition. The remaining 25 per cent. afterwards underwent quiet decomposition

during a period of over 15 minutes, under conditions which strongly favoured the hydrogenation of the :CH residues to methane, the final gas containing no less than 43·0 per cent. of methane and 57·0 per cent. of hydrogen.

The following experiments, in which a large quantity of acetylene was rapidly drawn through the heated tube in such a way that the decomposition at each temperature was uninfluenced by the " flashing " phenomena referred to, will indicate the influence of increasing temperatures above 800° upon the various types of interactions described.

TABLE XL

Temperature C°.	800°.	1000°.	1150°.
Percentage of Acetylene polymerised.	19.	7·5.	5·0.
Composition of the Gases issuing from the Tube C_2H_2	1·35	1·55	nil
C_2H_4	0·45	2·60	nil
C_6H_6	0·50	nil	nil
CH_4	34·20	36·00	23·45
H_2	63·50	59·85	76·55

The behaviour of undiluted ethylene within the range of 500° to 700° is very interesting and complex. The :CH residues, formed by the primary decomposition, at first rapidly coalesced, forming acetylene, but as hydrogen accumulated in the system the tendency for them to be hydrogenised to methane became progressively more marked. Aromatic hydrocarbons were continuously produced, either by the secondary polymerisation of acetylene or by coalescence of :CH residues. Only a very small proportion of the carbon in the gas was liberated in the free state (thus at 570° only 0·75 per cent. of it). At 800°, the tendency to form aromatic hydrocarbons was very much less, and the separation of carbon larger, than at the lower range. The predominant effect was the hydrogenation of the :CH residues to methane. So marked is the last-named tendency that methane was found to constitute as much as 67·7 per cent. of the final gaseous products at 800° just when the last remains of the original ethylene were disappearing. At 1000°, not more than about 4 per cent. of the original gas was converted into condensable aromatic hydrocarbons during the initial rapid decomposition. The hydrogenation of :CH residues to methane was still a dominant feature of the

...of free carbon to be liberated
...of ethylene at temperatures
that, as D. T. Jones has suggested,
...ich are formed in considerable
... carbonisation, may at the higher
...works retorts be responsible for a
...mation, but the matter is one which
...investigation in this connection.
...experiments at 675° C. showed primarily
...the coalescence of :CH$_2$ residues forming
...in a diluted condition decomposed *via* :CH
...entually, a mixture of carbon, hydrogen, and
...intermediate formation of acetylene. There
...ill yield of aromatic hydrocarbons (equivalent
...n 4 per cent. of the original gas) nearly all in
...most pure naphthalene (no benzene). Thus the
...ethane at such low temperatures is in strong
...that of either ethylene or acetylene in respect of
...formations. At 800°, whilst the primary :CH$_2$
...showed a marked tendency to coalesce to ethylene,
...ogenation to methane now became the predominant
...ad remained so until after a temperature of 1000° had
...sed. The amount of "aromatics" formed during a
...ating to the latter temperature was only about 4 per cent.
...total ethane changed.

...art from having introduced the new conception that the
...mal decomposition of these hydrocarbons involves the
mary formation, by dehydrogenation, of the unsaturated
...idues :CH$_2$ and :CH, which during a fugitive but really inde-
...endent existence are free to interact with the surrounding
...aseous medium after their kind, it may be claimed that the
researches in question have established the following facts,
which have an important bearing upon the secondary chemical
phenomena in high temperature carbonisation, namely :—

(1) That the most favourable temperature range for "aromatic"
formations from such residues as :CH$_2$ or :CH (namely,
500° to 800°) lies well below that which is most favourable
to the hydrogenation of such residues to methane
(namely, 800° to 1000°).

(2) That within the aforesaid most favourable range, ethylene is,
by reason of the rapid production of :CH residues during

its primary decomposition, eminently capable of generating aromatic nuclei, although in a less marked degree than in the case of acetylene. On the other hand, ethane, which primarily produces :CH_2 residues only, does not form aromatic nuclei nearly so readily as does ethylene.

(3) That methane, whose stability exceeds that of all other hydrocarbons at high temperatures, is practically unaltered by any degree of heat up to about 800° C. Between 800° and 1000° it slowly decomposes directly into its elements, but only in contact with hot surfaces. Above 1000° its decomposition, whilst still retaining a surface effect entirely, is more rapid. The carbon deposited upon surfaces from such decomposing methane is a peculiarly hard and lustrous metallic form, which in coking operations may have an important influence upon the strength and other properties of the resulting coke. A slight formation of aromatic nuclei from decomposing methane can usually be detected whenever the conditions favour the formation of highly condensed layers of the gas in contact with the hot surfaces, but not otherwise.

With regard to the formation of benzene hydrocarbons in gas retorts and coke ovens, if the old " acetylene " theory in its original form must now be discarded, there still remain two potent causes, namely : (1) the thermal " dehydrogenation " of naphthenes of the hydrobenzene type, and (2) the condensation of olefines or, more probably, of the " unsaturated residues " produced therefrom, and both causes probably operate simultaneously. The most favourable temperatures for such changes undoubtedly lie between 500° and 800° C., and if the factor of time, as well as of stability, is taken into account, we shall probably not be far wrong in assuming a somewhat narrower range of (say) 650° to 750° C. as that which would in practice give the best yields of benzene and its homologues.

CHAPTER IX

THE CHEMICAL COMPOSITION OF COAL (*contd.*)

G.   THE ACTION OF OXYGEN AT LOW TEMPERATURES UPON COAL.   THE WEATHERING AND SPONTANEOUS HEATING AND IGNITION OF COAL

IT has long been known that bituminous coals are not only liable to spontaneous heating and combustion, but also that they deteriorate on storage, both as regards calorific power and coking properties.   All these circumstances are due to the fact that all coals, some much more so than others, absorb and slowly combine with oxygen on exposure to the air even at ordinary temperatures.   This atmospheric oxidation or weathering of coals is an action which goes on slowly and continuously whenever they are stored or handled with free access of air.   It continues with increasing rapidity as the temperature rises, and always generates heat which, if allowed to accumulate, may ultimately give rise to spontaneous ignition.   And even when precautions are taken to prevent such accumulations, and therefore any sensible heating of the mass of coal, the oxidation nevertheless goes on all the same, and causes an appreciable diminution in the heating value of the coal.   For, as two American investigators have well put it, " any heating of coal in the pile represents just so much heat that will not be available later under the boiler." [1]

The subject is, therefore, one of considerable economic importance, touching as it does not only the safety of coal mines, *i. e.* the occurrence of what are termed " gob fires " in the mines, due to underground conditions which are peculiarly favourable to a cumulative heating effect, but also the storage of coal in bulk, and especially its oversea transport in ships.

It may here be stated that, although theoretically all coals are liable to the spontaneous oxidation, anthracites and anthra-

---

[1] S. W. Parr and W. F. Wheeler in " The Weathering of Coal," *University of Illinois Bulletin*, No. 38 (1909).

citic coals are so little affected that they may be considered as practically immune from appreciable deterioration on weathering. Hence they may be regarded as almost ideal solid fuels for storage or oversea transport. Most bituminous coals are, however, so appreciably affected that they always deteriorate on storage.

Until past the middle of last century the liability of coals to spontaneous heating was generally attributed primarily to the presence of iron pyrites therein, on the mistaken supposition that the coal substance is relatively inactive towards atmospheric oxygen at ordinary temperatures. It was thought that the heat generated by the oxidation of the supposedly much more susceptible pyrites would, in favourable circumstances, be sufficient to raise the temperature of the coal substance to such a degree as would enable it in turn to combine readily with oxygen, and so to induce an outbreak of spontaneous combustion in the mass as a whole. According to this theory, the susceptibility of a coal to such spontaneous heating would, *ceteris paribus*, be determined primarily by its pyritic content.

In discussing the matter, however, it should be remembered that iron pyrites is polymorphic, and that the cubical form of it is more stable in air than the rhombic variety (marcasite); also, that the fineness of division of the pyrites would be a factor, and that its oxidation requires the co-operation of water, as follows :—

$$2FeS_2 + xH_2O + 7O_2 = 2FeSO_4 \text{ aq.} + 2H_2SO_4 \text{ aq.}$$

Such a change would liberate heat amounting to 262·5 K.C.Us. per gram molecule of the pyrites oxidised, apart from that generated by any further oxidation of the ferrous sulphate primarily formed. Taking the average specific heat of a bituminous coal as 0·35, and assuming a pyritic content of 2 per cent., then the heat liberated by the oxidation of its pyrites would, if wholly accumulated in the coal mass, be sufficient to raise its temperature by (taking a metric ton as the basis of calculation) as nearly as possible 125° C.

Such a calculated figure, assuming as it does that the whole of the pyrites is oxidised rapidly enough to prevent any dissipation of the heat evolved, gives a greatly exaggerated estimate of the rise in temperature which would be likely to occur in any circumstances.

If, as will be shown later, the atmospheric oxidation of a bituminous coal does not become autogenous, *i. e.* self-propellent, until its temperature reaches 200° C., and seeing that its ignition point usually lies above 350°, it would *prima facie* hardly appear likely that the " pyritic " theory is by itself sufficient to account for the spontaneous firing of coal.

All competent scientific opinion now regards the influence of pyrites as either a negligible, or at the most a quite subordinate, factor in initiating or developing the phenomenon, and attributes it rather to the liability of the coal substance itself to slow oxidation at low temperatures.

The first important researches on the subject were those of E. Richter, published during the years 1868–70.[1] He showed that, at the laboratory temperature of 15° to 21° C., " perfectly dry coal, as well as air-dried coal, is able to absorb oxygen without exhaling carbon dioxide, both from dry and from air saturated with water vapour." On keeping a certain dried coal at 70° to 80° C. for 14 days its calorific power diminished by 3 per cent., and the coking properties also deteriorated. Moreover, until its temperature rose beyond 170° to 190°, there was no appreciable loss, but rather a gain in weight. And inasmuch as the coals examined did not contain more than 0·31 to 0·42 per cent. of pyrites, and that a mixture of fine quartz sand with the same proportion of pyrites did not absorb any oxygen in *dry* air, and only a very small amount in *moist* air, Richter concluded that pyrites has little or no effect upon the spontaneous oxidation of coal, which he attributed to an action upon the coal substance itself.

In 1879 Henri Fayol, who thoroughly investigated the conditions under which coals from the collieries in the Commentry district of Northern France absorb oxygen, or spontaneously ignite when exposed to air at temperatures beginning at 25° and rising to 200°, or even 400° C., was unable to detect that their pyritic contents had any appreciable influence upon the process. He found, however, as might be anticipated, that the finer the state of division of a coal the more rapidly does it combine with oxygen and catch fire; he gave the following

---

[1] *Dingler's Polytechnisches Journal*, Vols. 190, 193, p. 51, and 19 p. 315. English translation published *in extenso* in the *Report of the N* *South Wales Commission on Coal Cargoes*, No. 1, 1897; *vide* also paper R. Threlfall, *Journ. Soc. Chem. Ind.*, 1909, 28, p. 759.

approximate temperatures for the relative inflammabilities of powdered coals in hot air :—

	Relative Inflammabilities in Hot Air (Fayol).
Lignites	150°
Gas coal	200°
Hard coking coal	250°
Anthracites	above 300°

In 1898 Carrick Anderson, in the course of his investigation upon Scottish coals (*loc. cit.*), found that, at temperatures below 160°, atmospheric oxidation makes rapid progress during the first 12 to 24 hours, but afterwards falls off considerably. Nevertheless a slow increase in weight continues for a long time, the period required for completing the oxidation varying greatly with different coals.

In 1901, Fischer [1] of Göttingen, after bringing forward new evidence confirmatory of the views already expressed by Richter and Fayol concerning the relative insignificance of the part played by pyrites in the weathering of coals, attributed the main cause to the presence in the coal substance of " unsaturated " compounds capable of combining additively with either bromine or oxygen at low temperatures. Hence he concluded that coals which have the greatest affinity for bromine are also most liable to spontaneous firing, and as a practical test he recommended shaking 1 gram of the finely powdered coal with 20 c.cs. of $\frac{N}{2}$ bromine solution for 5 minutes. If then any free bromine remains, the coal (he said) may safely be stored in bulk. He also showed that the absorption of oxygen which is exothermic and accompanied by a gain in weight is accelerated by a rise in temperature.

Among British investigators whose independent experiments have led them to reject the pyritic theory in its original form may be mentioned V. B. Lewes, R. Threlfall, R. V. Wheeler, J. S. Haldane, and the writer. Lewes,[2] however, thought that pyrites may play a subsidiary *rôle* because of its swelling up on oxidation which conceivably might contribute to the disintegration of the coal and so indirectly assist the action of oxygen upon the coal substance. He also assigned the following approximate

---

[1] *Gas World*, April 13, 1901.
[2] *Journ. Gas Lighting*, **55**, p. 145, 1906, **94**, p. 33.

ignition temperatures which are, it will be observed, decidedly higher than the figures given for the relative inflammabilities of coal dusts in hot air :—

Approximate Ignition Temperature ° C.
(V. B. Lewes).

Cannels	370°
Lignites	450°
Welsh Steam Coals	470°

R. Threlfall's work was mainly connected with the investigation of the New South Wales Royal Commissions between 1896 and 1908 upon the Spontaneous Heating of Coal, particularly during shipment, the result of which he subsequently reviewed in perhaps the most notable memoir on this aspect of the subject which has yet appeared.[1]

From the extensive data and experiments collected or carried out for these Commissions, as well as from general principles established by previous scientific researches, notably those of Richter and Fayol, which were highly commended, it would appear (said Threlfall) that liability to spontaneous fires in ships' cargoes may be expected to increase (1) *pari passu* with the tonnage of the cargo and the temperature at which it is loaded, (2) with the fineness of division of the coal, and (3) with only *slight* ventilation during the voyage. Also, it was stated that the Commission had failed to find a single undoubted case of a spontaneous fire in a coal cargo having originated in any other place than under the hatchways, from which it follows that the presence of a heap of dust under the hatchways should in any circumstances be specially avoided as a highly dangerous condition.

In 1909 Boudouard,[2] in experiments upon the atmospheric oxidation of coal at 100°, reported the formation under such conditions of " humic acids " from the cellulosic constituents in the coal substance, and that the coking properties had completely disappeared.

In 1909 P. Mahler[3] proved that when air is passed over dry coal free from occluded gases, at as low a temperature as 25° to 30°, water, carbon monoxide, and carbon dioxide are formed, less carbon monoxide being formed if the coal contains moisture. He also reported the finding of from 0·002 to 0·004 per cent.

[1] *Journ. Soc. Chem. Ind.*, 1909, **28**, p. 759.
[2] *Bull. de la Soc. Chem.*, 1909, **5**, 365.
[3] *Compt. rend.*, 1910, **150**, 1521, **151**, 645.

of carbon monoxide in the air of coal mines. The production of carbon monoxide during the slow oxidation of coal at such low temperatures is entirely what chemists would have anticipated from the work of H. B. Baker, and the more recent researches of R. V. Wheeler, upon the combustion of carbon, to which further reference will be made in another chapter. It has also frequently been observed, not only by R. V. Wheeler, but independently also by the writer, in researches upon the slow oxidation of coal.

Among the most informing of recent investigations from the point of view of the storage of coal on land are those of S. W. Parr and his collaborators of the University of Illinois,[1] who experimented upon a series of Illinois coals which are characterised by both high moisture (12 to 15 per cent.) and sulphur (1 to 6 per cent.) contents. The experiments were directed mainly to the ascertainment of the influence of temperature, fineness of division, moisture, and pyrites, upon the liability to spontaneous combustion. The procedure consisted in maintaining 25 lb. to 35 lb. lots of suitably screened coal in a special container at a constant temperature (40°, 60°, 80°, and 115° C.) within an insulated oven, with free air circulation, in such a manner that the rate of the temperature-rise of the coal above that of its environment could be accurately followed until it attained a steady maximum, which always happened within the 72 hours period over which each experiment extended.

Altogether some fifteen series of experiments were made upon charges whose fineness of division, pyritic, and moisture contents were varied in accordance with a carefully laid plan, and each charge was tested successively at the four temperatures above named. The principal conclusions arrived at were :—(1) that the oxidation of coal is continuous over a wide range of temperatures beginning, in the case of freshly mined coal, at the ordinary temperature; (2) that at low temperatures the initial oxidation, which is unattended by any evolution of carbon dioxide, is due to the presence in the coal substance of certain "unsaturated" compounds having a marked avidity at ordinary temperatures for oxygen with which they unite forming compounds of the humic acid type (*vide* Boudouard); (3) that although this slow oxidation is exothermic, it does not, with free air circulation, cause any material self-heating of the coal about its environment until a temperature of 60° to 80° C.,

[1] *University of Illinois Bulletin*, Nos. 17 of 1908 and 46 of 1911.

154

dependent upon the size of the coal and other conditions, is reached; (4) that this self-heating at any temperature is more rapid, and the final steady maximum in relation to the air circulation is greater, the finer the state of division of the coal; (5) that the presence of moisture increases the chemical reactivity of the coal-air system at any temperature; (6) that at a temperature of about 120° in oxygen and 135° in air the constituents of the coal begin to oxidise more freely with evolution of carbon dioxide and water, a state of things which must always be regarded as highly dangerous; (7) that the point at which the oxidation becomes autogenous (*i. e.* self-propellent) lies somewhere below 140° and 160° in oxygen and 200° to 270° in air, and that as soon as this point is reached the temperature will rapidly rise to the ignition point of the coal, which usually lies above 350°.

With regard to the influence of pyrites, it was found that the amount of " pyritic oxidation " under given conditions is always proportioned to the pyritic content of the coal, so that an increase on the latter will (it was thought) hasten " the rise in temperature up to the critical point at which the absorption of oxygen by the coal itself is rapid enough to increase the temperature up to the point of self ignition." Hence it was concluded, " that the presence of pyrites is a much more important factor in the spontaneous ignition of coal than has heretofore been ascribed to it, and its influence upon the spontaneous combustion of coal cannot be discarded in the off-hand way that has been so common with some of the previous investigations, merely because of the fact that some coals containing no pyrites at all would ignite spontaneously."

These important statements seem to be based principally upon the result of three series of experiments with the environment at 80° in which, although no condition varied except the pyritic content of the coal, ignition occurred in the cases of the two dust coals of higher pyritic contents, as follows :—

Series No.		4	6
Percentage Pyrites in *Wet* Coal	1·65	3·0	5·0
Temperature of Environment	80°	80°	80°
Rise in Temperature of the Coal. *Size of Coal.* 0	50°	to ignition	to ignition
0 to ⅛ in.	36°	57°	43°
⅛ in. to ¼ in.	21°	11°	18°

The following preventive, or precautionary, measures were suggested in connection with the storage of coal in bulk, namely:—(*a*) the avoidance of any external source of heat which would in any way contribute towards increasing the temperature of the mass; (*b*) the elimination of coal dust; (*c*) dryness in storage; (*d*) the artificial cooling of the heap by any suitable means which will keep down its temperature without increasing the access of oxygen; or (*e*) the submerging of the coal under water.

In the ·year 1913 a Departmental Committee was appointed by the Home Office to consider the question of the Spontaneous Firing of Coal in relation to the safety of mines. Various scientific investigators, including R. V. Wheeler, Professor P. P. Bedson and the .author, gave evidence as to their views and experience. Dr. Wheeler put forward an interesting new suggestion, namely, that the greater the amount of combined oxygen in the coal substance the more readily will it " self-heat," and the lower is the temperature at which " self-ignition " occurs. The Committee issued their First Report in 1916, which should be consulted for details of the evidence submitted.

The subject has been investigated by the staff of the Doncaster Coal Owners Research Laboratory, under the direction of J. S. Haldane.[1] These further experiments, whilst usefully confirming much of the results of previous work, do not appear to the writer to have added materially to our knowledge of essential facts, although in relation to the particular problem of the safety of mines the inferences which may be drawn from them may be important. In reviewing these experiments, Haldane rightly states that " the conditions underground are often peculiarly favourable to a cumulative heating effect, for, owing to the ventilation, it is very apt to happen that a continuous slow current of air passes horizontally along a layer of broken coal. The heat is thus carried on, and the temperature rises higher and higher along the course of the air current, until at a certain distance a dangerous temperature is reached. Ordinary gob fires seem to be always produced in this way."

With regard to the influence of pyrites, Haldane speaks with some uncertainty, for whilst admitting " that in the Barnsley and many other seams it is not pyrites to any appreciable extent, but other substances in the coal that oxidise," he goes on to say that " in some other kinds of coal the oxidation of pyrites was

---

[1] *Inst. Mining Engineers*, Part IV., Vol. 53, p. 194 (1917).

to play a considerable part in the heat production, and
bly a predominating part in certain cases," and he suggests
he difference may depend on whether the pyrites is present
umps " (cubical crystals), as in the Barnsley coal, or in some
re impure and disseminated condition." Further on, how-
he says that whereas " he was formerly inclined to attribute
yrites the main part in the spontaneous heating of coal . . .
now clear that in the heating of coal another type of oxidation
sually involved." He then says how the Doncaster workers
been puzzled to find that " in the oxidation of coal at low
peratures oxygen disappears but hardly any carbon dioxide
prmed," but this fact was surely well known before to chemists
le S. W. Parr in particular), and need cause no surprise to any
: familiar with the phenomena of surface combustion generally.
leed, to the writer it seems that, judging by Haldane's account
them, the Doncaster experiments have in their chemical
pects been anticipated in several important points by previous
ork.

As practical precautions against the outbreak of gob fires
ι mines, Haldane recommends :—(1) that the liability of the
oal in the seam to spontaneous heating should always be tested;
2) that if found very liable, the method of working should be
such as to reduce to a minimum the occurrence of crushing;
(3) that in order to avoid as far as possible percolation of air
through goaves containing coal, the ventilating pressure should
be kept as low as possible, which means roomy roadways in the
mines and the keeping of the goaves as air-tight as possible. The
control of such conditions is, he says, more complex when a seam
is not flat, or where faults are met with, " since the convection
currents due to difference of temperature must tend to cause
air-currents in the goaf, and coal may have to be left near a
fault." He concluded with the what may seem at first sight a
rather obvious statement, but which nevertheless needs to be
reinforced whenever conditions in mines are under discussion,
that gob fires would be entirely avoided if it were possible to
remove the whole of the coal, good or bad, including slack.

In connection with a further development of the Doncaster
experiments upon the soft coals of the Barnsley seam (S. Yorks),
Messrs. Graham and Hills have recently reported that the portion
of the coal (15 per cent.) which is soluble in pyridine does not
absorb oxygen at 90° C., and " cannot therefore be responsible
for the spontaneous combustion of coal," a conclusion which is

157

The following preventive, or __ __ __ __ __ __ V. 'V___ __
suggested in connection with ___ __ __ __ en est___ __
namely:—(*a*) the avoidance of ___ __ __ __ xperiment___ __
which would in any way cont___ __ __ __neous Combust___
temperature of the mass; (*b*) __
(*c*) dryness in storage; (*d*) th__ __ __ ___ in the author's
any suitable means which w___ __ __ __ __e and Technology
without increasing the access __ __ ___ Fuel Economy
of the coal under water. ___ __at the phenome-

In the year 1913 a Depart__ · __ ___ complicated to
by the Home Office to consi__ · __ __ as the foregoing
Firing of Coal in relation to t__ __ __ __ on one kind of
investigators, including R. \
and the author, gave evi __ __ __ of which will
Dr. Wheeler put forward an · ___ confined to the
that the greater the amo__ · __ by two *typical*
substance the more read__ __ __ __ing " coal A., and
is the temperature at __ __ __ which were *selected* as
Committee issued their i __ ___ notwithstanding
consulted for details of t__ ___, as follows :—

The subject has be__ __
caster Coal Owners R__
J. S. Haldane.[1] These
firming much of the r__

	S.	O.	Ash.
__	__	7·52	1·62 } per
:	__	7·72	2·76 } cent.

the writer to have ad__
facts, although in rela__ __ __ oxygen was in
of mines the inferen __ __ __ __al was exposed
important. In rev__ __ __ sorption was un-
states that " the c__ __ __ __ively very small
favourable to a c__ __ __bourhood of 80°,
ventilation, it is v__ __ __r. and at above
current of air pass__ __ ___ production
The heat is thus ca__ __ __ : which evidently
higher along the c__ __ __ " oxygenated "
distance a danger__ __ __ sorption of the
fires seem to be a__

With regard to · __ __ __on, the results
some uncertain__ __ __ __ven, in each
and many other __ __ __ continuously
but other subst · __ __ __ __spheres in
that " in some __ __ __ __ or other
__ __ __ __ and and

Throughout each ex-
...ly night and day over a
... the coal was exposed to
...tant temperature of 107° to

...ted results and curves (Tables
...nd 20, the latter showing the
...n was absorbed and also those
...ely were produced during each

Absorption of Oxygen by Durham Coking Coal (A).

...t is apparent (1) that, especially at the initial
...ygen was much more quickly absorbed by the
...n by the Durham coal, although the absorption
...ly complete even after 400 hours in the one case
...urs in the other; (2) that both of the two oxides of
...ere continuously and simultaneously produced through-
...xperiment, and (after the first 100 hours or so) in nearly
...our relative proportions; and (3) that from 30 to 35 per
...the absorbed oxygen was evolved as steam. It should
...stated that the coking properties of each coal were
...tely destroyed by the treatment to which it had been
ted.

159

TABLE XLI

TABLE OF RESULTS

Coal.	A.	B.
Quantity of Dry Coal used in grams .	93·7	86·9
Temperature of Coal ° C.	107° to 109°	107° to 109°
Duration of Experiment—hours . .	648	481
Total Oxygen absorbed in litres at N.T.P.	11·00	10·20
Percentage of ⎰ in the Coal	45·65	56·20
Total Oxygen ⎰ as CO$_2$	17·11	10·45
absorbed ⎱ „ CO	2·70	2·82
appearing ⎱ „ H$_2$O	34·51	30·54
Percentage of Oxygen in the " Oxygenated " Coal	13·08	16·97

FIG. 20.—Absorption of Oxygen by Barnsley Hard Coal (B).

On calculating from the experimental results the total amounts (in c.cs. per gram) of oxygen which had reacted with unit weight of the dry coal in each case both during, and up to the end of, each successive period of 100 hours, we find that during the whole of the first 200 hours the oxidation of Coal B. was decidedly more rapid than that of Coal A. Afterwards, however, the rate for B. became somewhat the slower of the two, although the

otal amount of oxidation from the beginning up to any par-
icular time always remained greater for B. than for A. throughout
he whole experiment, thus :—

TABLE XLII

Amount of Oxidation in c.cs. O_2 at 0° and 760 m.ms. per gram of Dry Coal.				
Time Interval in Hours.	Coal A.		Coal B.	
	During Interval.	Up to end of Interval.	During Interval.	Up to end of Interval.
0 to 100	37·4	37·4	57·5	57·5
100 ,, 200	20·5	57·9	23·7	81·2
200 ,, 300	16·1	84·0	15·8	96·0
300 ,, 400	13·4	97·4	12·3	108·3
400 ,, 500	12·6	110·0	7·1	115·1

Another interesting feature of the results with Coal A. was that
not only did the volumetric ratio of the CO_2 to the CO produced
remain fairly constant throughout each experiment, especially
after the first 100 hours, but also that the proportion of the
total reacting oxygen which had appeared as oxides of carbon
at any particular time did not change very materially (see below).

TABLE XLIII

COAL A.

Time Hours.	Total Volume in Litres at 0° and 760 m.m. produced of		Ratio CO_2/CO.	Proportion of absorbed O_2 appearing as CO_2 and CO.
	CO_2.	CO.		
100	0·40	0·18	2·22	0·140
200	0·65	0·26	2·50	0·143
300	0·87	0·34	2·55	0·152
400	1·06	0·40	2·65	0·154

COAL B.

100	0·66	0·34	1·94	0·145
200	1·04	0·44	2·36	0·178
300	1·25	0·50	2·50	0·17?
400	1·38	0·50	2·76	0·1?

M

These temperatures it certainly cannot that except perhaps a long process makes it the oxidation, but these gases were thus their level of the secondary thermal decomposition of a particular coal — 'secondary' gases primarily produced in the oxidation of the constituent of the coal, the nature of which is being further ascertained. These features were not, however, nearly so marked in the case of Coal B, whose oxidation proceeds in a more violent manner than in the case of Coal A.

From the scientific standpoint the subject of the spontaneous firing of coal involves a number of points which have not yet been sufficiently considered. Several of the researchers whose researches have been reviewed have obviously not paid sufficient attention to problems with in the purely scientific aspects of the mechanism of combustion, as for example H. B. Baker's work, and still more recently that of R. V. Wheeler, on the combustion of carbon.

Again, it is curious to find how some workers have, until quite recently, failed to recognise what Richters and Fayol's researches had plainly taught, that however helpful the rôle of pyrites may be, the main and predominating cause of the spontaneous combustion of coal must be sought for in the oxidation of the coal substance itself.

Finally, none of the workers who have treated the scientific aspects of the subject seem to have sufficiently realised that the whole process from first to last is essentially one of " surface combustion," which, as the writer's researches have shown, is subject to special conditions which do not apply in homogeneous gaseous combustion. It is abundantly evident that the oxygen is first of all " absorbed " by the coal substance, possibly in some " activated " form, then incorporated in some way (it may only be loosely, or, on the other hand, it may be, as S. W. Parr suggested, in some definite form), and as the temperature rises, it finally is expelled in gaseous products (H_2O and oxides of carbon). And between its initial absorption and its final expulsion a whole series of complex phenomena may be involved, which have hitherto received little attention. The subject needs more investigation from a fundamental standpoint, and in particular the following points seem to demand some experimental revision or confirmation :—

(1) If, as is clear, the old " pyritic " theory in its original form is no longer tenable, what subsidiary part (if any) does pyrites play? This question ought not to be left in the hazy

condition into which it has been thrown by the recent rather ambiguous statements of S. W. Parr and J. S. Haldane.

(2) What constituents of the coal substance (cellulosic, resinic, or nitrogenous) are most liable to spontaneous oxidation at low temperatures?

(3) Is there any " activation " of the oxygen initially absorbed by the coal which quickens its chemical action, and, if so, by what factor is it determined and governed?

(4) What is the lowest temperatures at which gaseous products (CO, CO_2 and H_2O) are freely evolved from the surface of coal undergoing such oxidation?

(5) What is in each case the lowest temperature (with varying types of coal) at which the action of oxygen become autogenous?

(6) Does the oxygen naturally present in the coal substance itself play any part at all in the phenomenon up to, say, the temperature at which the action becomes autogenous?

CHAPTER X

THE combustion in a furnace of a bituminous coal is by no means so simple or direct a process as was formerly believed. Indeed the cumulative evidence afforded by a long series of chemical investigations during the past thirty years has proved that combustion in general is, from a molecular standpoint, a highly complex transaction, usually involving several stages, and in many cases also the interaction of steam, in addition to that of oxygen, and the combustible substances.

Assuming, for the sake of convenience, that the composition of the combustible matter of an average bituminous coal approximates to the empirical formula C_9H_6O ($C = 83\cdot1$, $H = 4\cdot6$, and $O = 12\cdot3$ per cent.), such an equation as,

$$C_9H_6O + 10O_2 = 9CO_2 + 3H_2O,$$

enables us to say very little more about its combustion than that, supposing it were possible in practice to completely burn it to carbon dioxide and steam in just the theoretical quantity of air, one kilogram of it would require 8·22 cub. metres of air measured at 0° C. and 760 m.m. (equivalent to 131·7 cub. ft. per pound), and that the cold gaseous products would contain 18·87 per cent. of carbon dioxide. The equation would tell us nothing whatever about the mechanism of the combustion, which, when closely investigated, would be found to be an extraordinarily complicated phenomenon. So much misconception is still prevalent about the matter, and so much depends on a true understanding of it, that it is worth while at the outset to consider it in some detail from a fundamental standpoint, before proceeding to discuss the practical bearing of the principles involved.

When a fresh charge of raw coal is introduced into the furnace of, say, a boiler, it first of all undergoes a destructive distillation, whereby a number of combustible gases, tarry vapours and steam are expelled. The gaseous products chiefly consist of hydrocarbons (methane with smaller proportions of ethylene, benzene,

and probably also ethane), hydrogen, and carbon monoxide, whilst the tarry vapours are mingled with a certain proportion of finely divided carbon (soot). The "volatile" combustible constituents thus evolved from the upper portion of the fuel bed will amount in all to between 15 and 25 per cent. of the weight of the ash-free coal charged, and the oxygen needed for this combustion must be furnished by what is sometimes termed a "secondary" air supply which is usually introduced through adjustable openings in the doors of the furnace, or (may be) also at the fire-bridge, in such a manner that it mixes with the combustible gases and vapours at or near the top of the fuel bed. The ensuing combustion causes the well-known development of smoky flames in the furnace after each addition of fuel.

The combustion of the residual coke (carbon) takes place in the lower layers of the fire by means of the "primary" air supply drawn in through the fire-bars, the evidence of which may be seen by looking at the incandescent mass of fuel in the furnace towards the end of the interval between two successive chargings of the coal.

Accepting this as an approximately true view of the outward and visible sequence of events in the furnace, it is at once evident that we have to deal with at least two distinct cases of combustion, namely (1) that of solid carbon in the lower layers of the fire, and (2) that of the combustible "volatiles" (gases and vapours) in or above the upper layers.

The Combustion of Solid Carbon

Although the combustion of solid carbon has been studied by chemists for upwards of a century, there is still no general agreement among them as to what is the immediate product of the action of oxygen upon it.

In view of the fact that a diamond burns when strongly heated in oxygen forming carbon dioxide *without any visible flame*, it was formerly almost universally believed that such is the initial interaction, the monoxide subsequently resulting only when the primary product comes in contact with an excess of incandescent carbon, thus :—

$$(1)\ C + O_2 = CO_2$$
$$(2)\ CO_2 + C = 2CO$$

The correctness of this view, which is still very prevalent in technical literature, was challenged in 1872 by the late Sir

Bell who, as the result of his classical investigations upon the chemical phenomena of iron smelting, advanced some very ingenious, if not altogether conclusive, arguments in support of his opinion that " carbon monoxide and not carbon dioxide is the chief, if not the exclusive, and immediate action of the hot blast on the fuel " (i. e. on the coke) in the blast furnace.

In the year 1887 C. J. Baker made experiments to ascertain the nature of the gases produced by heating carbon which had previously absorbed oxygen at low temperatures. He found that whereas *moist* oxygen which had been absorbed at $-12°$ C. was evolved as carbon dioxide at $100°$, the effect of *thoroughly drying* the materials by means of phosphoric anhydride was to cause the gas to be retained until a temperature of $450°$ was reached, when it was evolved chiefly as carbon monoxide. Hence he concluded that carbon is burned directly to the monoxide by absorbed oxygen.

A year later, H. B. Baker,[1] following upon the discovery of H. B. Dixon that a mixture of perfectly dry carbon monoxide and oxygen cannot be exploded in a eudiometer by an ordinary electric spark, whereas the presence of even a trace of moisture is sufficient to determine an explosion, found that when highly purified carbon is strongly heated in a closed vessel in *well-dried* oxygen, there is no sign of the glow or scintillation which is always produced in similar circumstances when *undried* oxygen is employed, and that the resulting gases always consist of both the monoxide and the dioxide, even when there remained a considerable excess of unused oxygen. In a further series of experiments he proved that although pure carbon dioxide, thoroughly dried over phosphoric anhydride, is not reduced by charcoal at bright red heat (provided always that the presence of moisture is rigidly excluded), the monoxide is chiefly produced when the same charcoal is similarly heated in dry oxygen, as the following analyses of the resultant gases showed :—

			Charcoal heated to redness in Oxygen dried over Phosphoric Anhydride for—	
			1 Week.	2 Weeks.
Percentage Composition	CO_2.	. .	5·0 .	1·7 . 2·2
of	CO .	. .	40·0 .	39·5 . 27·8
Resulting Gases	O_2 .	. .	55·0 .	58·1 . 70·5
Ratio $CO \cdot CO_2$.		.	8·0	16 to 18

[1] *Phil. Tr.--- ·***. 178, A., 571.*

Baker, therefore, concluded (1) that moisture facilitates the oxidation of carbon, and (2) that " carbon burns first to carbon monoxide."

This new evidence was at the time accepted as conclusive by most British chemists, but when in 1891 Mendeljeff in his well-known *Principles of Chemistry* (English Ed. Vol. I. p. 388) adopted the older view that " the first product of the combustion of charcoal is always carbonic anhydride and not carbonic oxide," [1] the controversy was reopened. The Russian chemist seems to have based his opinion upon the results of a series of experiments published by Lang in the year 1888 [2] in which oxygen (*undried*) was passed at different regulated velocities through a glass tube packed with purified gas carbon maintained in a furnace at 500° C., *at which temperature Lang asserted that carbon does not reduce its dioxide.* From the following results it will be seen that the proportion of carbon monoxide found in the exit gases diminished with the stream velocity, until in one experiment with a very slow stream it entirely disappeared. Lang ascribed the formation of the monoxide in the experiments with the faster gas streams to the occurrence of local heating which, he argued, was sufficient to effect some reduction of the dioxide.

TABLE XLIV

LANG's FIRST SERIES OF EXPERIMENTS

Time required to collect 100 c.cs. of Gases.	Percentage Composition of the Resulting Gases.		
Minutes.	CO_2.	CO.	N_2.
2	89·4	8·4	2·2
4	90·0	7·8	2·2
10	90·4	7·2	2·4
20	91·4	6·1	2·5
25	92·5	5·3	2·8
60	94·3	3·0	2·7
240	96·2	*nil*	3·8

In a second series, Lang passed a mixture (*undried*) containing

[1] It may be noted that this statement is repeated on p. 423 of the third English edition published in 1905, and on p. 421 of the same edition it is also stated that carbonic oxide " is formed whenever the combustion of organic substances takes place in the presence of a large excess of incandescent carbon; the air first burns the carbon into carbonic anhydride, but th in penetrating through the red-hot charcoal is transformed into carbon oxide, $CO_2 + C = 2CO$.

[2] *Zeit. Phys. Chem.* (1888), p. 161.

77·7 per cent. of oxygen, 18·5 per cent. of carbon monoxide, and 3·8 per cent. of nitrogen at different velocities over purified carbon at 500° C. with the object of ascertaining (1) whether with a slow stream, and in the absence of local heating, the oxygen could be directly transformed into its own volume of carbon dioxide without increasing the proportion of monoxide in the flowing gases, and if so, then (2) what would be the effect of increasing the velocity of the gases until the local heating was sufficient to make the carbon glow. The results observed in three groups from experiments are shown below :—

TABLE XLV
LANG'S SECOND SERIES OF EXPERIMENTS
Temperature = 500° C.

	Time required to collect 100 c.cs. of Gases.	Percentage Composition of the Resulting Gases.			Observations.
	Minutes.	CO_2.	CO.	N_2.	
Group 1.	120 150	78·0 77·9	18·3 18·4	3·7 3·7	*No local heating.* No change in CO content; O_2 replaced by CO_2.
Group 2.	1 1 20 secs.	71·2 70·8 39·6	24·7 25·0 56·4	4·1 4·2 4·0	*No visible flame.* Increase in CO due to reduction of CO_2 by C.
Group 3.	10 secs. 5 ,,	86·4 88·4	9·5 8·0	3·8 3·6	*Carbon glowed.* Flame of CO visible.

Assuming that carbon does not appreciably reduce its dioxide at 500° C., Lang claimed to have proved that in the burning of carbon the formation of the dioxide precedes that of the monoxide ("durch das Zusammentreffen des Sauerstoffs mit der Kohle ensteht zuerst Kohlendioxyd ").

H. B. Dixon subsequently repeated and criticised Lang's principal experiments,[1] finding that some monoxide, as well as the dioxide, is always produced when oxygen is passed over purified coke at 500° C. no matter how slow the gas stream may be, although it was impossible to say that no local heating occurred in the experiment.

[1] *Trans. Chem. Soc.* (1899), **75**, p. 630.

TABLE XLVI

B. DIXON'S EXPERIMENTS ON THE ACTION OF OXYGEN UPON COKE AT 500° C.

o.	100 c.cs. of Gas collected in		Percentage Composition of the Product.			
	Minutes.		CO_2.	CO.	O_2.	N_2.
1	3·5		80·83	16·7	—	2·99
2	23		87·52	9·48	0·25	2·74
3	120		96·38	1·42	0·26	1·93
4	240		96·52	0·41	0·21	2·17

He, therefore, considered that his experiments threw doubt on the validity of Lang's conclusions, and that whereas Baker's work had greatly added to the weight of evidence in favour of the view that carbon burns in the first instance to carbonic oxide, it must be admitted that a decisive proof is still required.

Whilst such experiments left the main issue still undecided, so far as *solid* carbon is concerned, H. B. Dixon was able, during his researches upon gaseous explosions, to obtain conclusive evidence as to the primary formation of the monoxide when *gaseous* carbon (as in the form of cyanogen C_2N_2) is burned, inasmuch as he showed not only that the rate at which a wave of detonation passes through a mixture $C_2N_2 + O_2$ is greatly in excess of the corresponding rate for a mixture $C_2N_2 + 2O_2$, but that in the latter case half of the oxygen is absolutely inert in the wave, and only combines slowly with the carbon monoxide (the initial oxidation product) as the gases cool down in the rear of the wave.

In view of the fact that the molecular heat of combustion of cyanogen, when burnt completely to carbon dioxide, is 259·6 K.C.Us., whereas if burnt to the monoxide it would only be 123 K.C.Us., it might be expected that the rate of explosion for the mixture $C_2N_2 + 2O_2$ would be much higher than that for $C_2N_2 + O_2$ if gaseous carbon is primarily burnt to carbon dioxide in the wave. The exact opposite is, however, the case, as the following figures show :—

Mixture.	Rate of Detonation Metres per Second.	
(1) $C_2N_2 + O_2$ . .	2728	Note that in (3) the N_2 retards
(2) $C_2N_2 + O_2 + O_2$.	2321	the wave somewhat less than
(3) $C_2N_2 + O_2 + N_2$.	2398	does the second O_2 in (2).

These facts, together with the observations of Smithells and [...] that the internal cone of an ordinary aerated hydrogen fl[...] between CO and CO_2, in the volumetric ratio 1 : 1, leave no room [...] a say wm that the combustion of the gaseous carbon in coal [...] occurs in two well-defined stages involving the successive f[...] tion of CO and CO_2, namely :—

$$I. CO_2 - C_2 = 2CO - N_2$$
$$2. 2CO - N_2 - C_2 = 2CO_2 - N_2$$

But the interaction of oxygen and a gas is a simple molecular [...] interaction compared with the complex conditions prevailing w[...] oxygen is brought in contact with a solid. For whereas the o[...] case involves the simultaneous collision of a limited numb[...] of molecules of finite dimensions, in the other is an interaction b[...] tween a highly condensed layer of gases at the surface and m[...] molecules of a porous solid of great molecular complexity. M[...] over the combustion of solid carbon is further complicated b[...] the fact that at or near the temperature when the oxidation ju[...] begins the reversible change $CO_2 \rightleftharpoons CO - O_2$ also comes into play [...] and at somewhat higher temperatures carbon monoxide rise[...] forms, if there be a sufficient supply of oxygen.

In recent years the subject has been thoroughly r[...] investigated by Rhead and Wheeler over a range of temperatur[...] extending from 700° up to 900° C.[a] A preliminary series o[...] experiments in which either air or oxygen, was circulated ove[...] highly purified wood-charcoal maintained at various selected [...] constant temperatures between 250° and 900° C., failed t[...] afford any conclusive evidence of the exclusive primary formation [...] of either the monoxide or the dioxide, and led to the conclusio[...] that both are produced simultaneously.

Further investigation over a much wider range of temperature[...] afforded strong presumptive evidence in favour of the view tha[...] neither the one nor the other of the two oxides is initially formed [...] but that both are simultaneously produced as the result of th[...] decomposition of an unstable "physico-chemical complex," C_xO_y [...] which according to this theory must be regarded as th[...] immediate and initial product of the action of oxygen upon [...] carbon.

It may at once be admitted that not only does this new view [...] of the matter reconcile a good many well-established facts which [...]

[a] Trans. Chem. Soc. 1911, 99, p. 216.
[b] Ibid., 1911, 101, 840; and 1913, 103, 461.

therwise would appear conflicting, but also that it accords well with the results of recent investigations upon the interactions of gases and hot surfaces in general. And whilst it would perhaps be premature to accept it as a final explanation, in the sense of its having been completely proven, it may be adopted for our present purpose as being the best available working hypothesis.

Such a simultaneous production of both oxides of carbon by the decomposition of a complex C_xO_y when oxygen impinges upon the incandescent coke in the undermost layer of a furnace, would probably be accompanied by a rapid attainment and adjustment of a mobile equilibrium in the reversible system,

$$2CO \rightleftharpoons C + CO_2,$$

in consonance with the temperature in each successive layer as the mixed gases ascend through the fire. Also, and especially in such regions where the atmosphere in the spaces between the porous coke masses contains free oxygen, some combustion of carbon monoxide may occur, in which case the aforesaid equilibrium must be continuously adjusting itself, both to variation in the relative concentrations of the two oxides of carbon, as well as to the temperature changes. Consequently, the lower region of the fire must be the seat of a complex play of chemical forces which, however, may be regarded as always subject to the laws governing the attainment of mobile equilibrium in the reversible system formed by carbon and its two oxides.

THE REVERSIBLE SYSTEM $2CO \rightleftharpoons C + CO_2$

The investigation of the effects of temperature and pressure upon equilibrium in this system was also carried out very thoroughly by Rhead and Wheeler,[1] whose work in this connection must be acknowledged as having surpassed in point of carefulness and accuracy that of any previous investigators.

According to Le Chatelier's extension of Van't Hoff's well-known principle of mobile equilibrium in such a system, any change in the factors of equilibrium (*e. g.* active masses, pressure and temperature) from outside must be followed by a reverse change within the system. Thus, for example, (1) inasmuch as any change in the direction $2CO \rightarrow CO_2 + C$ is accompanied by a decrease in volume, an increase in pressure at any given temperature will cause a decrease in the " equilibrium " proportions of carbon

---

[1] *Trans. Chem. Soc.*, 1910, **97**, 2178; and 1911, **99**, 1141.

monoxide, and ... ... experiments and
said direction must be ... ... are discussed ...
at any given pressure ... in X. II

proportion of ... ... that in the ...

The law ... ... where the ... " primary " air ...
may be ... ... by the distillation of the raw ...
... probably assume very rapidly a mixture
... the equilibrium proportions corresponding
... ... perature, and ... the partial pressures ...
... at 1200° and upwards CO will constitute
... the total oxides of carbon present.[1] Also
... ... tion of CO will survive as the product
... until the further oxygen supply required
... met with.

$$5 \cdots / \overset{!}{\cdots}$$

where

L — ...
P — ...
N .

n_i

$\cdot$.

I
$\cdot$
r

... that the fuel bed in most types of coal
... ... marily as a " gas-producer," and, judging
... ... actical tests recently carried out by Ameri-
... ... on a 6-in. fuel bed, the atmospheric oxygen
... grate is all used up within the lower 4 in.
... ... ne of highest temperature (1200° to 1500° C.
... raught ") was found to be usually about 3 in.
... ... ate, and the composition of the gases in it
... ... pendent of the rate at which the air was
... ... ough the fuel bed, an increase in the draught
... ... e rate at which the carbon of the coke was
... ... the maximum temperature of the bed.
... st results with an ordinary bituminous coal
... ... ccessary to operate with a thicker fuel bed
... ... desirable to consume within such a bed more
... e oxygen required for the complete com-
... ... oal substance. The hot gases issuing from
... ... will usually contain, say, between 20 and
... ... oustible constituents (carbon monoxide,
... ... d other hydrocarbons) but practically no
... ... tely these combustible gases and vapours
... ... duce over the fuel bed an additional air
... ' air), preferably in thin streams of high

... ... an absolute state of equilibrium in the system
... ... ly attained in practice, but only that it is so
... ... ant the views here expressed. Thus, for
... ... that at 1300° C. a contact of 4 seconds of
... ... ent carbon is sufficient to establish very
... ... ystem.

. . ' L. — ·· ·ondary " air supply may advantageously
. ' ·d.

· ... ~TION OF THE COAL IN THE UPPER LAYERS OF THE FIRE

...can temperature in the upper region of the fire during
. ~tillation of each successive charge of raw coal is difficult
: imate, but it may reasonably be supposed to be at some
· intermediate between 600° and 1000° C.
i he following table, compiled from the results of distillation
t ~ at 800° C. upon a series of typical British coals carried out
1909 under the direction of the late Professor E. J. Constam, at
: ne Zürich Prüfungsanstalt für Brenstoffe,[1] will give an approxi-
: nate idea of the proportionate yields of coke, gas, tar, water, etc.,
· ,btained at that temperature, and the heat balance of the process.

TABLE XLVII

RESULTS OF DISTILLATION TESTS AT 800° C. (CONSTAM)

	100 Parts Dry Ash-free Coal yielded.				Heat Balance Expressed as Percentages of Net Cal. Value of the Coal.		
	Coke.	Gas.	Tar and Pitch.	Water.	Coke.	Gas.	Tar and Pitch.
Notts { Bright . .	59·7	21·2	9·3	9·5	61·3	22·7	10·0
Notts { Best Hard .	63·2	19·9	10·6	5·8	64·1	20·2	11·3
Lancs, Trencherbone	63·1	21·2	12·0	3·2	61·7	22·8	12·4
Durham { Hutton .	69·2	17·9	9·7	3·0	65·3	22·1	9·7
Durham { Low Main.	65·7	17·6	11·7	4·8	63·7	20·6	11·7
Yorks, Barnsley .	70·0	14·6	8·5	6·6	70·4	18·3	8·9
S. Wales, Nixon's Navigation . .	80·9	11·5	4·5	2·8	76·7	16·9	4·3

Taking then the case of a steam coal of the Barnsley type,
yielding on distillation in the upper part of the fire (say) 70 per
cent. of its energy as coke, 20 per cent. as gas, and the remaining
10 per cent. as other volatile matter (tar and pitch), and assuming
that in the lower part of the fire the carbon in the coke is converted
by the primary air supply into CO_2 and CO in the ratio 10 : 90,
then it may be shown that, of the total energy of the coal, only

---

[1] Constam and Kolbe, *Journ. für Gasbeleuchtung*, Nr. 36, 4 Sept., 19·

so in practice will be seen when Karl Wendt's experiments upon the action of air upon carbon in gas-producers are discussed in a later chapter (*vide* Chapter XVII).

We are, therefore, justified in concluding that in the lower layers of the furnace, where the incoming "primary" air meets the incandescent coke formed by the distillation of the raw coal in the upper layers, there probably results very rapidly a mixture of CO and CO_2 in nearly the equilibrium proportions corresponding to the prevailing temperature, and to the partial pressures of these gases, and that at 1200° and upwards CO will constitute nearly 99 per cent. of the total oxides of carbon present.[1] Also, that this large proportion of CO will survive as the products ascend the fuel bed, until the further oxygen supply required for its combustion is met with.

It thus would appear that the fuel bed in most types of coal-fired furnaces acts primarily as a "gas-producer," and, judging from the results of practical tests recently carried out by American investigators upon a 6-in. fuel bed, the atmospheric oxygen drawn in through the grate is all used up within the lower 4 in. of the fire. The zone of highest temperature (1200° to 1500° C, according to the "draught") was found to be usually about 3 in. to 5 in. above the grate, and the composition of the gases in it was practically independent of the rate at which the air was drawn or forced through the fuel bed, an increase in the draught merely increasing the rate at which the carbon of the coke was gasified and raising the maximum temperature of the bed.

To obtain the best results with an ordinary bituminous coal, it is usually not necessary to operate with a thicker fuel bed than 6 in., nor is it desirable to consume *within* such a bed more than about half the oxygen required for the *complete* combustion of the total coal substance. The hot gases issuing from the top of the bed will usually contain, say, between 20 and 40 per cent. of combustible constituents (carbon monoxide, hydrogen, methane and other hydrocarbons) but practically no oxygen; to burn completely these combustible gases and vapours it is necessary to introduce *over* the fuel bed an additional air supply (the "secondary" air), preferably in thin streams of high

[1] It is not suggested that an _____ state of equilibrium in the system $2CO \rightleftharpoons C + CO_2$ is ever actual_____ tice, but only that it is so nearly approached as to w_____ re expressed Thus for example, it has been prove_____ ntact of 4 seconds of the gases with the incan_____ to establish very nearly an equilibrium in _____

The initial stage involves the formation of *methyl alcohol* (stage 1), which is then further oxidised to an unstable dihydroxy compound, which immediately breaks up into steam and formaldehyde (stage 2). The latter is subsequently oxidised *via formic acid* (stage 3), which may partly break up into CO and H_2O, to the highly unstable *carbonic acid* (stage 4), which at once breaks up into CO_2 and H_2O. According to this view steam and oxides of carbon are never the *immediate*, but always the *remoter*, products of the successive oxidation stages.

At temperatures above the ignition point, as in ordinary flames, the formaldehyde produced by decomposition at stage 2 is itself so rapidly resolved by heat into carbon monoxide and hydrogen that in all probability the final stages of the process are concerned only with the independent oxidations of these gases, thus :—

$$
\begin{array}{ccc}
\text{H} & \text{H} & \text{H} \\
\text{H·C·H} \longleftarrow \text{H·C·OH} \longrightarrow & \text{H·C·OH} \\
\text{H} & \text{H} & \text{OH} \\
\end{array}
$$

$$\underbrace{\qquad}$$

$$\text{H}$$
$$\text{H}_2\text{O} + \text{H·C:O}$$
$$\underbrace{\text{CO} + \text{H}_2}$$
$$\downarrow \qquad \downarrow$$
$$\text{CO}_2 \qquad \text{H}_2\text{O}$$

The complete combustion of such gases as carbon monoxide, hydrogen, methane, ethylene, which are generated within the fuel bed, presents no great difficulties, provided that the secondary air supply be both sufficient (but not excessive) in quantity and is properly distributed. The flooding of the furnace with an excessive supply of cold air is, however, to be avoided, inasmuch as it is calculated to dilute and cool down the interacting gases to a point which either stops or greatly retards combustion ; and in hand-fired furnaces, where the fuel is thrown in at intervals through the open door, it is a prolific cause of loss " by incomplete combustion," the unburnt gases being carried up the chimney to the accompaniment of black smoke. Such losses may, however, be largely prevented by good furnace design combined with mechanical stoking arrangements, whereby the fuel is introduced continuously and the air supply can be so regulated as to maintain as nearly as possible constant conditions in the space immediately above the fuel bed.

Black Smoke and its Prevention

The combustion of the heavier hydrocarbons which constitute the tarry vapours produced by the distillation of the coal is a much more difficult matter, inasmuch as their more complex molecular constitution renders them not only more resistant to oxygen attack, but also prone, under the roasting influence of heat, to form still denser molecular aggregates by a series of internal condensations. Without doubt the production of the mixture of soot and dense hydrocarbons which constitute black smoke is largely due to this circumstance. The best way of counteracting it is to ensure a uniform supply and distribution of "preheated" air, so as to keep the interacting gaseous medium well above the ignition point of the tarry vapours it contains, and to ensure that all parts of it are sufficiently, though not excessively, supplied with the necessary oxygen for the maintenance of vigorous combustion. Also, devices which will cause the burning mixture to impinge on incandescent firebrick surfaces in the furnace (see "Surface Combustion"), thereby accelerating combustion, will undoubtedly minimise, even if it does not altogether prevent, smoke production.

It is obvious that, so long as a coal is "free-burning," the smaller the amount of volatile matter it contains the less will be its liability to cause smoke, and, inasmuch as smoke production is always a sign of incomplete combustion, the more efficiently can it be burnt. Hence arises the good reputation of the celebrated semi-bituminous Welsh "steam coals," containing from 10 to 15 per cent. of volatile matter, which burn almost smokelessly. As, however, such smokeless coals are only available in certain favoured localities, it has been frequently suggested that, as a good means of preventing smoke, suitable bituminous coals might be submitted to a preliminary process of expelling or decomposing their smoke-producing constituents by low temperature distillation in a separate apparatus before being burnt in boiler furnaces and the like. And if such a process could be carried out economically so as to yield "semi-coke" of sufficient strength, the problem of boiler firing with solid fuel would be much simplified. Even then, however, the achievement of really efficient combustion would still depend upon the proper regulation and distribution of both primary and secondary air supplies, and the maintenance of suitable conditions in the furnace. And for this purpose, both

Fig. 21 —Underfeed Stoker (Longitudinal Section)

a good draught and effective means of regulating it, are absolutely essential as a prime condition of success.

In hand-fired boiler furnaces, and especially when " forcing " tactics are not necessary, a good plan is to charge the raw coal on to the dead plate just within the door in order that it may there undergo a short preliminary " low temperature " distillation before it is distributed over and burnt in the grate. The heavier volatile matter so expelled, if properly admixed with air admitted above the grate, will be carried forward and burnt over the incandescent fuel bed, and when near the fire-bridge the gases will encounter a further supply of air. Also, the proper spreading of the fuel on the fire should be attended to; a good plan is to fire alternately to the back and front, or to the right and left side of the grate.

In the case of large boiler installations, however, there can be no question of the superiority over the ordinary hand-firing of a well-designed mechanical stoking arrangement with a moving chain grate, for not only do such devices ensure a continuous feed of the fuel, but they also allow of a much better control and uniform distribution of the air supplies, and keep the fuel bed in regular movement, all of which contribute to the maintenance of uniformity of conditions and high temperatures in the furnace.

" *Underfeed* " *Stoking.*—Mention may here be made of the system of " underfeed " stoking for boiler furnaces invented some years ago by E. W. Jones, of Portland, Oregon, U.S.A., whereby coal, instead of being thrown on to the top of the fire in the usual manner, is thrust upwards into it from below, by means of a special mechanical arrangement, in such a way that the preliminary distillation of the raw fuel takes place in the lowest regions of the fire, and the products resulting therefrom mix with streams of hot air and are completely burnt as they rise through the hottest regions of the fire.

The principle of such underfeed stoking, as applied to the flue of a Lancashire boiler, is illustrated in Figs. 21 and 22. The raw fuel is mechanically fed from a hopper, or other suitable receptacle, into a horizontal trough, A, along which it is pushed by means of a screw or worm conveyer. The neck, B, of this trough, in which the fuel is first ignited, expands upwards until it opens out on to the sloping terraced grate, CC, of the furnace, through the bars of which the air needed for combustion is admitted. Also, there is an air opening or twyer, DD, where the top of the neck opens out on to the grate. The air needed for

179

introduced is introduced through the passage, EE, below the
grate, and is thus to some extent preheated before it reaches the
fuel. Distillation of the raw fuel commences in the neck of the
retort through but a little below the level where the fuel is tipped
in the streams of air which enter through the openings, DD, and
continues as the partial mass is slowly pushed upwards on
the incline where eventually the carbonised residue is completely

Diagram of Underfeed Stoker (Cross Section).

the air stream which enter between the bars of the

It will be seen readily that the fire always presents a
surface to the flue plate, but also
the raw coal is being carbonised in the lower regions of the
the smoke-producing constituents are
brought into contact with the incandescent
admixed with hot air through the middle and
regions of the fire. This is certainly a more scientific
burning raw coal in a boiler furnace than that usually

THE FIRING OF FURNACES WITH COAL DUST

In recent years various attempts have been made to devise
systems for burning finely pulverised coal in boiler and other

furnaces. It is, of course, well known that a mixture of finely divided coal dust and air is explosive, and there can be no doubt but that in burning coal the excess of air actually required will diminish with the fineness of division of the fuel and the intimacy of its admixture with air. The rapidity and efficiency of the combustion will increase the more nearly the system approaches the homogeneity of a properly proportioned gas-air mixture.

So far as boilers are concerned, some details of one successful device will be given in the next chapter. With regard to other types of furnaces, a system of burning powdered fuel was proposed by Crampton [1] in which the coal was pulverised until it passed through a 30-mesh sieve and was fed into the furnace by an injector, air being supplied in measured quantities by means of a fan so that intense heat was generated.

In recent years the system seems to have made marked progress in America and has been applied to cement kilns and reverberatory furnaces for metallurgical purposes. In 1906 the attention of the metallurgical world was again drawn to the possibilities of utilising pulverised coal in reverberatory furnaces by S. S. Sorensen, who showed, as the result of large scale trials, that the efficiency, as measured by the ratio of the ore to the fuel consumed, is considerably increased by the substitution of coal dust for ordinary grate firing. A further development was made by Shelby at Cananea, Mexico, in 1908, but both of these pioneers experienced troubles owing to the accumulation of ash in the flues and to interruptions in the coal-dust feed.

The next step forward is to be credited to technologists in the cement industry, whose experience brought out the necessity for drying the fuel and reducing it to an impalpable powder before burning it in their kilns. As the result of recent progress the difficulties referred to are now reported to have been overcome.

It is also stated in American journals that, with the adoption of improved charging methods, which are said to obviate fettling, the modern coal-dust-fired reverberatory furnaces are likely to compare favourably with the blast furnace in the copper industry. The coal is dried and reduced to a sufficiently fine state of division that it may be easily suspended and carried forward in the air blast as a practically homogeneous mixture. The air blast (which constitutes the " primary " air supply only) is operated at a pressure of from 8 oz. to 16 oz. per square inch.

le development of the earlier work of Sorensen and

---

[1] *Journ. Iron and Steel Inst.*, 1873, p. 91.

Smelter was first made by the Canadian Copper Co. who, in ...
started operations with a reverberatory furnace, smelting ro...
... ore ... long ... 10? ft. wide, with a slanting roof ...
in height at the front end of the furnace, and 8 ft. at the fire ...
The fired coal dust was fed into bins by automatic screw ...
... the speed of which could be regulated. These screws ca...
the coal forward and delivered it into the burners about ...
from the point at which the nozzles entered the furnace. ...
were five such burners at the front end of the furnace each ...
in diameter ... 2 ft. above the slag line. The "prim...
air supply was supplied as a low-pressure blast into whic...
pulverised coal was fed and carried forward in a state of ...
fine division. The "secondary" air supply was sucked in...
furnace through suitable openings in the end walls betwee...
coal burners.

The coal as used contained —

	Per cent.
Moisture	= 4·3
"Volatiles"	= 34·7
"Fixed Carbon"	= 55·4
Ash	= 9·45

and had a calorific value of 13,500 B.Th.U's. per lb.

The combustion in the furnace is reported to have been ...
satisfactory, the flue gases contained.—

$$CO_2 \text{ and } SO_2 = 12·3 \text{ per cent.}$$
$$SO_2 \qquad = 1·14 \text{ ,, ,,}$$
$$CO \qquad \text{absent.}$$

The average temperature of these products on leaving the fu...
was 922° C. and 17 per cent. of the available heat was uti...
in the furnace. The ratio ore : fuel obtained was 7·0 as comp...
with the usual 4·0 in grate-fired reverberatory furnaces.

A further development from the foregoing investigation...
subsequently made by the technical staff of the Anaconda...
... Reduction Works) who, as the result of their experie...
... laid down the following conditions as essentia...
... best results :—

... coal should be dried so that its moisture con...
... 1 per cent. before it is pulverised.
... be pulverised until 85 per cent. of it pa...

through a 200 mesh and 95 per cent. of it through a 100 mesh.

3) That the furnace shall be specially designed both as regards shape and proportions, and be suitably equipped with burners and feeding arrangements so that the relative deliveries of coal dust and air can be well controlled.

(4) Special provision should be made for the periodic removal of the ash deposited in the flues at the far end of the furnace.

In the year 1916 trials were made of applying coal-dust firing to locomotive boilers and open-hearth steel furnaces, and it is evident that in America considerable developments of the system are likely to take place in the near future.

The reader is referred to the following papers for further information on the subject of these developments:—

(1) " Use of Pulverised Coal in Metallurgical Furnaces," by James Lord in *Proc. Eng. Soc. of West Penn.*, October, 1913.

(2) " Pulverised Coal as a Fuel," Anon. in *Eng. and Mining Journ.*, May 16, 1914.

(3) " Coal Dust Fired Reverberatories at Washoe Reduction Works," by Louis V. Bender; also another paper on the same subject by D. H. Browne, of the Canadian Copper Co., in *Trans. Amer. Inst. Min. Eng.*, January 1, 1915.

(4) Discussion of Papers on " Coal Dust Fired Reverberatories," in *Trans. Amer. Inst. Min. Eng.*, May, 1915.

(5) " Anaconda Coal Pulverising Plant," by E. P. Matthewson, in *Eng. and Mining Journ.*, July 10, 1915.

(6) " Pulverized Coal for Copper Smelting," by N. L. Warford, in *Min. and Eng. World*, November 6, 1915.

(7) " Contribution to Symposium on Utilisation of Fuels in Metallurgy," by E. P. Matthewson, in *Inter. Engin. Congress*, 1915.

(8) Kuzell (Pan American Scientific Congress, Washington), *Eng. and Mining Journ.*, **101**, No. 7, 303, February, 1916.

(9) " Developments in Smelting Practice of Anaconda Copper Mining Co.," *Eng. and Mining Journ.*, **102**, No. 15, 635, 777, October 7, 1916.

(10) *Engineering*, January 5, 1917 (E. Muhlfield, Amer. Soc. Mech. Eng., and J. W. Fuller, Amer. Iron and Steel Inst.).

(11) W. L. Robinson (Seventh American Convention of Railway Fuel Association), *Eng. and Mining Journ.*, **100**, No. 1, 19.

Chapter XI

The text in the upper and middle portions of this page is too faded and degraded to read reliably.

Taking the calorific value of a good steam coal as 13,000 B.Th.U. per lb, and the thermal equivalent of one horse-power-hour as 2544 B.Th.U., it follows that were it possible by any means to transform the available energy of coal into mechanical

* For such particulars the reader is referred to the book on *Steam Boilers* written by Mr W. Inchley, Lecturer in Engineering at University College, Nottingham (Edward Arnold, London, 1913). He is also recommended to study Professor W. E. Dalby's *Steam Power*

er without loss of any kind, a horse-power hour would be
erated by the expenditure of no more than about one-fifth of
ound of coal. But even in the very best modern practice,
ether of the largest steam turbines or of the most efficient
s-engine plants, it has not yet been found possible to obtain
regular running a horse-power hour from a smaller consump-
on than about one pound of coal, or say about five times the
eoretical figure.

So far as steam installations are concerned, such a result was
ctually achieved in 1915 during the trial of the new 35,000 H.P.
arsons turbo-alternator at the Fisk Street Power Station in
Chicago. Working with steam at 200 lb. gauge pressure and
200° Fahr. superheat, with a vacuum of 29 in., a shaft horse-
power hour was developed for a steam consumption equivalent
to 9600 B.Th.Us., which (assuming a boiler efficiency of 75 per
cent.) would be equivalent to a consumption of 1 lb. of coal of
net calorific value 12,800 B.Th.Us. per lb.

It may, however, be doubted whether in even the largest and
most modern of British power stations the coal consumption
averages throughout the year less than 2 lb. per horse-power
hour generated, whilst for the country as a whole it has been
estimated at as much as 5 lb.

Inasmuch, however, as a steam-power plant comprises both
boiler and engine, it is necessary, in apportioning the losses,
to discriminate between the two parts. And, inasmuch as the
average efficiency of the best types of land boilers may be assumed
to be about 75 per cent., the losses upon a good modern steam
plant, consuming on the average no more than 2·0 lb. of coal
per shaft horse-power hour generated, would be distributed
somewhat as follows :—

	Per-cent.	
Boiler	25 }	Total = 90 per cent.
Engine, etc. . . .	65 }	

If, however, the average coal consumption could be reduced
to that actually realised during the Chicago trial of 1915, the
losses would be :—

	Per cent.	
Boiler	25 }	Total = 80 per cent.
Engine, etc. . . .	55 }	

How the 25 per cent. lost at the boiler is made up may be jud
from the following typical heat-balance of a trial of a m

… good great deal of …
… taining 10 per cent …

	Per …
…	
… cases	…
… cases	…
… n and in ashes	4
	10

THE PRIN

… s of no more than …
… of good practice will …
… that this figure is more …
… working, especially …
… such sort of …
… taining in … cases …
… amount …
… the …
… prevails.

… waste in …
…

…
… .
…
…
… cases:
… as indicated …
… products …
… may be the miller …
… doubles, …
… the roller …
… the to …
… production into the …

… of Fric…

… of the late Professor …
… for Brewing, in …
… between … and …

referred to the " dry ashless " fuel.
...her percentage of such " volatiles,"
... to an excessive loss on account of in-
...ially if the design of the furnace is
... of those yielding a lower percentage,
...cess of air must usually be supplied in
...tion at a rate sufficient to ensure rapid
...ller, which means an excessive loss of
...imney gases.

...are well illustrated by a series of steam
... Professor Constam in conjunction with
...ich fuels of different types and origin were
...re of a hand-fired marine boiler. Each trial
...it hours, and the conditions were regulated
...as possible the same mean rate of evaporation
...oughout the whole series. The results which
...in Table XLVIII may be commended to the
...study, not only as bearing out the conclusion
... to but also as showing the general features of
...such a hand-fired boiler evaporating water
...erate rate of about 4·2 lb. per square foot of
... per hour. It may be pointed out that in
...the heat losses by radiation, etc., are decidedly
...Nos. I to IV inclusive, a circumstance which
...table except on the supposition that the chimney
underestimated in Nos. IV and V.

...a steam coal, not only should the calorific power
...tage of volatile matter yielded when it is carbonised
...taken into consideration, but also its free-burning
...l the amount and character of its ash content.
...ntent is to be avoided, not only because it involves
...it in stoking and cleaning the fire, but also, and
...it be of a fusible character, because it may entail
... loss of " unburnt carbon " at the grate and become
...source of " clinkering " troubles. These faults are
...d when the boiler is worked under high draught.
...l be a good thing if the custom were to be established
...Britain of basing contracts for steam coal on an agreed
...nth tandard, together with an agreed ash content. In the
...d States it is customary for the contract price of coal to
...lated with reference to certain stipulated figures for both

TABLE XLVIII

STEAM TRIALS WITH DIFFERENT FUELS ON A HAND-FIRED MARINE BOILER

Trial No.	I.	II.	III.	IV.	V.	VI
Description of Fuel	Gas Coke	Ruhr Coal	Rhenish Coal	Saar Coal I.	Saar Coal II.	Saar Coal
Moisture in Fuel . .	5·26	2·07	3·93	1·73	3·85	5·4
Ash in Fuel . . .	0·05	6·21	9·24	7·57	11·84	7·4
. . .	00·00	90·49	90·03	85·89	82·56	
. . .	0·2	4·10	4·13	5·39	5·29	5·4
. . .	0·00	0·03	1·15	1·04	0·96	1·2
. . .	1·3	4·39	4·09	7·68	11·22	14·2
. . .	2·0	10·5	19·1	36·7	38·0	45·1
. . .		8018	8540	8565	8514	8199
. . . Net	7079	8313	8342	8223	7915	7535
. . . per hour .	136	117	124	135·4	152·5	162·5
. . .	5·04	5·24	5·17	5·18	5·10	5·15
. . .		4·5	3·5	737	72·5	737
. . .	1021	1057	1036	1066	1035	1039
. . .	2062	2704	2708	2787	2706	2716
. . .	1·2	1·6	1·3	1·8	172	173
. . .	4·13	4·20	4·20	4·32	4·18	4·20
. . .	10·3	10·5	10·30	10·42	10·40	10·42
. . .	1·2	0·21	0·01	1·70	0·65	2·22
. . .	—	—	—	0·70	0·18	0·00
. . .		0·11	0·03	—	0·11	0·10
. . .		8·2	0·02	7·56	8·55	7·47
. . .		50·54	50·00	79·79	80·11	79·19
. . .	312°	305°	276°	297°	280°	306°
. . .	2·2	1·2	1·6	1·58	1·69	1·57
. . .	74·9	75·1	73·7	67·4	65·3	62·5
. . .	22·4	18·1	16·2	15·9	15·8	15·7
. . .	2·4	2·8	3·8	11·0	5·7	13·8
. . .	8·2	3·0	3·4	2·9	3·8	2·4
. . .	2·8	1·0	2·9	2·8	9·4	5·6

.c value and ash content. Variations within 2 per cent. her side of the particular fixed calorific standard do not the contract price, but variations exceeding these limits re a proportionate increase or decrease in the price. And, regard to ash content, anything which does not exceed the d standard by more than two whole units per cent. does not t the contract price, but if this neutral 2 per cent. margin ceeded, then each successive unit per cent. by which it is xceeded involves a steadily-increasing deduction in the price, rding to a pre-determined sliding scale, of which the following y be quoted as an example :—

TABLE XLIX

	As Agreed.	No Change in Price up to.	Cents. per Ton to be deducted for the Higher Ash Content.				
			2.	4.	7.	12.	18.
Percentage Ash Contents	5·0	7·0	7 to 8	8 to 9	9 to 10	10 to 11	11 to 12
	6·0	8·0	8 to 9	9 to 10	10 to 11	11 to 12	12 to 13
	7·0	9·0	9 to 10	10 to 11	11 to 12	12 to 13	13 to 14

(b) *Avoidance of an Unsoftened " Hard " Feed Water.*

The formation of " scale " of low heat conductivity on the tubes of a boiler is a prolific cause of heat losses and other serious derangements, especially in districts where the available supplies of water are naturally " hard." Hard waters are those which are more or less charged with " scale forming " mineral impurities such as calcium, magnesium, or ferrous bicarbonates, calcium sulphate, silica, or with salts such as the chloride, sulphate, or nitrate of magnesium which aid scale formation, especially at high boiler pressures and in the presence of iron salts, by secondary interactions such as the following :—

(1) $MgCl_2 + 2H_2O = Mg(OH)_2 + 2HCl$;

(2) $MgCl_2 + CaCO_3 + H_2O = Mg(OH)_2 + CaCl_2 + CO_2$.

With regard to the commoner " scale forming " mineral constituents of natural waters, it may be said that whilst the " soft scale " deposited in feed water heaters and the like, where the temperature is below 100° C. is almost always composed of the carbonates of calcium and magnesium, the cementing material of the " hard scale " deposited on the boiler tubes is frequently

Most of the upper text is too faded to read reliably. Only the lower portion is legible.

Loss of Power by Imperfect Combustion of the Fuel.

For the complete combustion of 1 lb. of a bituminous co...

containing —

C — ..., H = 5 5, ... = 10, N = 15, O = 50, and Ash

70 per cen...

there would theoretically be required 1352 cub. ft. of dry a

ured at 0° C. and 760 m.m. barometric pressure (= 142·6 cub.
15° C. and 760 m.m.) and the cooled products would contain
? per cent. of carbon dioxide. But in actual practice it is
r possible to burn coal perfectly on the grate of a boiler
ace with only this theoretical quantity of air, owing to the
that with relatively large masses of a solid fuel, and with
rvening fairly wide air-passages, the air-supply is never so
mately or homogeneously in contact with the combustible
tter as it is in the case of an explosive mixture of gas and air

FIG. 23.—Curve showing the Relation between the Percentage of Carbon
Dioxide in the Flue Gases and the Volume of Air drawn through the
Boiler System.

in the cylinder of a gas engine at the moment of ignition. It
would be considered exceedingly good boiler practice to burn
completely a coal such as the one in question in no more than 1·5
times the theoretical quantity of air, in which case the cooled
products would contain :—

$$CO_2 = 12·08, \quad O_2 = 7·16, \quad N_2 = 80·76 \text{ per cent.}$$

If, however, twice the theoretical quantity of air were drawn
through the furnace, the chimney gases would contain :—

$$CO_2 = 8·99, \quad O_2 = 10·66, \quad N_2 = 80·35 \text{ per ce}^{\cdot}$$

If the ultimate chemical composition of a coal is exactly known, a curve may be drawn showing the relationship between the percentage of carbon dioxide in the chimney gases and the quantity of air (in terms of that theoretically required) drawn through the boiler system. Such a curve is shown in Fig. 23 for the particular coal in question.

It cannot be too often insisted upon that an adequate and easily regulated draught is a *sine qua non* of efficient combustion in a boiler, and inasmuch as land boilers usually rely entirely upon chimney draught, the proper design and dimensioning of the chimney and connecting flues in relation to the number and total capacity of the separate units in a boiler installation is a matter of prime importance.

It must also be borne in mind that a chimney is more than a mere duct for products of combustion; its function is to create a sufficient suction at the furnace to draw in the air needed to burn the fuel, and to discharge the products of combustion into the atmosphere at a sufficient height to render them reasonably inoffensive.

The force or intensity of the draught produced by a chimney is caused by the difference in the weight of the column of heated air in the chimney and that of a similar column of the external atmosphere, the heights of both columns being equal to the vertical distance between the fire grate of the boiler and the top of the chimney. In practice, however, part of the force of the draught is expended in overcoming the frictional resistance opposed by the chimney and its connecting flues to the flowing gases.

Certain empirical formulæ are usually employed by engineers for calculating both the draught and the maximum quantity of air which a given chimney will draw through the system per hour, thus for example :—

If d = the draught in inches of water,
  h = vertical height of the chimney in feet above the fire grate,
  t = atmospheric temperature in Fahr. degrees,
  T = temperature of the chimney gases in Fahr. degrees,
  E = effective area of the chimney, which for circular chimneys
      = A — 0·6 $\sqrt{A}$ (Kent's formula), where A = least internal area,
  Q = maximum quantity of air in lbs. per hour which the chimney will draw through the system,

:—

$$d = h\left(\frac{7\cdot6}{t + 460} - \frac{7\cdot9}{T + 460}\right)^1 \quad . \quad . \quad . \quad (1)$$

$$Q = 1000 dE\sqrt{h_1} \quad . \quad . \quad . \quad . \quad . \quad . \quad (2)$$

or the purposes of boiler calculations it may be taken that
ibic foot of dry air at 15° C. and 760 m.m. barometric pressure
ghs 535 gr. or 0·0764 lb., and if it be also assumed that for the
cient combustion of 1 lb. of an average bituminous coal in
. furnace at least 1·5 times the theoretical quantity of air,
mely 1·5 × 136 = 204 cub. ft., will be drawn through the
stem, the maximum " coal-burning " capacity of a chimney
given height, area, and water-gauge draught may be calculated
r means of the foregoing formula.

This " coal-burning capacity " is, however, again limited
y the area of the grate, for it is obvious that the total area
f the effective air-passages through the grate might be too
mall to allow of the maximum chimney capacity being actually
ittained. Also, the number of boilers connected with a given
:himney, and the length of the connecting flues, introduce
another limitation which must be taken into account. Hence
the following empirical formula is sometimes employed for
calculating the smallest internal chimney area A (square feet)
required for a chimney of given height H feet to burn W pounds
of coal per hour on a grate area G square feet, assuming that
the horizontal distance between the fire-grate and the base of
the chimney does not exceed 150 ft.,

$$A = \frac{G \times W \times C}{\sqrt{H}}. \quad . \quad . \quad . \quad (3)\,[\text{\textasteriskcentered}]$$

where C is a constant dependent upon the number of boilers
connected with the chimney (C = 0·100 for 1 boiler, and 0·085
for 2 to 6 boilers).

But such formulæ as these do not, and indeed cannot, take
into account another variable factor, namely, the character of
the coal burnt and the thickness of the fire. For it is obvious
that a thick fire, or one composed of a slack coal, will require
a greater draught than a more normal one. Also, a caking coal
or an anthracite would require a greater draught than a free-
burning steam coal.

[1] From H. R. Kempe's *Engineers' Year Book*, to which the reader is
referred for much valuable information regarding chimney designs.
[2] From Inchley's *Steam Boilers* (Ed. Arnold) and Hutton's *Steam Boiler
Construction* (Crosby, Lockwood & Son).

Thus, according to V. & Forbes, &c., the total draught required to burn different coals of low volatiles is as follows :—

steam coal	.	0.25 to 0.5 inches w.g.
coke		.25 to 1.1 „ „
semi-anthracite	.	.75 to 1.0 „ „
anthracite	.	1.1 to 1.4 „ „
anthracite duff	.	1.1 to 1.4 „ „

Provided that the chimney is sufficient, it may be assumed that a chimney 150 ft. in height and of a sufficient area will burn up to 25 lb. per square foot of grate area per hour in a Lancashire boiler.

Next in importance to the adequacy of the draught to meet the maximum requirements of a boiler installation is the easy regulation of it at each separate unit, especially where hand firing is adopted. In such a case it is obvious that the amount of secondary air required will be greater immediately *after* a charge of fresh fuel has been introduced, when the volatile combustible matter is being expelled from the coal at a greater rate, than towards the end of the interval between two successive charges, and hence the importance of good control of the draught both by a damper in the flue leading to the chimney and by openings in the furnace door. Also any variation in the load on the boiler will affect the amount of fuel burnt and therefore the draught required.

When a forced or induced draught is fitted to a boiler, it is, of course, possible to increase the rate of combustion of the coal on the grate, and so to obtain better results, provided always, however, (1) that a high furnace temperature is maintained, which implies that the furnace shall be of large capacity and well lined with fire-brick; (2) that the heating surface in the boiler itself is adapted to the higher rate of heat transmission (q.v.), and (3) that, if necessary, the heating surface shall be extended so as to cool down the burnt products sufficiently before they are discharged into the chimney, and this may often best be done by installing devices for either (1) heating the feed water, or (2) pre-heating the secondary air-supply to the boiler furnace, or (3) superheating the steam. One of the advantages of forced or induced draught is its easy regulation, but with induced draught losses may occur through in-leakages of air into the system. Provided that all the precautions referred to are taken, for

duced draught may be expected to lead to increased efficiency greater elasticity under varying loads, but these advantages be entirely nullified or even outweighed if the boiler itself adly designed.

1 the case of a large boiler installation, the adoption of :hanical stoking will nearly always pay, not merely as a labour-ing device, but as improving the conditions of combustion the furnace and thereby increasing the heat efficiency of the tem, and especially when low-grade coals are used. Such proved conditions are to be ascribed mainly to the fact that th mechanical stoking the coal is fed on to the fire continuously small quantities instead of in large amounts at comparatively ng intervals, as in hand-firing. Also greater uniformity in the :aught is attained, and the inrush of cold air, which always :curs when the furnace doors are periodically opened in hand-:oking, is avoided.

There seems to be a concensus of opinion amongst competent udges that, from the point of view of heat economy, the advan-ages of mechanical stoking over hand-firing are greater the ower the grade of the fuel employed. Indeed, mechanical stoking tends to diminish the natural difference between a low-grade and a high-grade fuel in a degree which increases with the extent of such difference.

This last point is well illustrated by the results of a second series of comparative trials carried out by the late Professor E. J. Constam and P. Schläpfer (*loc. cit.*) in which a Lancashire boiler was fired, alternately by hand and by a mechanical "under-feed" arrangement, with a series of four German (Ruhr and Saar) coals of descending grades. It will be seen from the accompany-ing Table L, in which their results are set out in detail, that the effect of the "underfeed" stoking in each case was to increase both the rate at which fuel was burnt on the grate and the amount of steam raised per unit weight of coal consumed, as compared with the same coal when hand-fired. With regard, however, to the "efficiency" figures (*i. e.* the percentage of the heat utilised) the advantage gained by the mechanical stoking was not nearly so great with the two highest grades of coal (Ruhr I and II) as it was in the case of the other two, and that the advantage was by far the greatest with the lowest grade of all the coals. An examination of the various heat losses shows that whereas the *burnt* gases always carried off decidedly less heat when the boiler was hand-fired than they d   he

TABLE I

STEAM TRIALS ... A LANCASHIRE BOILER WITH (A) HAND FIRING AND (B) ... STOKER ...

Heating Surface ... { (b) 324 / (c) 34.2 }
Grate Area ...

	Ruhr I		Ruhr II		Ruhr II.		Saar	
							79.80	
	81.80		80.55		79.70		4.60	
	3.80		4.35		4.81		1.10	
	1.00		0.97		0.70		1.20	
	1.40		1.50		1.60		10.30	
	2.50		3.68		3.85		7.33	
	8.30		6.45		4.02		4.45	
	1.20		2.50		3.14			
Net Calorific Value of Coal in K.C.Us. per Kilog.	7587		7600		7000		6693	

	(1)	(2)	(1)	(2)	(1)	(2)	(1)	(2)
Coal Burnt per Hour. Kg.	167.9	281.1	187.0	192.9	180.6	199.4	232.5	243.1
Evaporation per Hour	1379.4	1745.5	1441.5	1588.6	1373.4	1652.4	1310	1654
Kg. Water at 0°C./Steam at 100°C. }								
Water at 0°C./Steam at 100°C. per Kilog Coal.	8.24	8.27	7.71	8.24	7.60	8.30	5.64	6.71
Steam Gauge Pressure Atmos.	10.79	10.95	10.66	10.71	11.00	10.70	10.90	10.71
% Composition of Chimney Gases — CO_2	11.42	9.70	11.30	9.06	9.93	10.34	11.81	10.61
CO	0.55	0.04	1.01	0.05	1.14	0.02	3.45	11.03
H_2	0.24	0.25	0.76	0.28	0.72	0.12	1.17	0.27
O_2	8.47	10.66	7.01	10.24	10.36	10.07	4.12	10.64
N_2	79.31	79.32	79.92	80.35	77.82	79.45	79.04	78.86
Temperature of Chimney Gases °C.	334°	341°	330°	328°	318°	151°	125°	147°
% Heat Utilised								

.anical arrangement was used, this advantage was always far eighed by the correspondingly greater combined losses in unburnt gases, smoke, and ashes incidental to hand-firing.

(d) *Chimney Losses*

rom the boiler there passes up the chimney a complex ture of (1) *burnt* products of combustion *plus* excess of air, t is to say, carbon dioxide, steam, oxygen, and nitrogen; small amounts of *unburnt* gases, mainly carbon monoxide, lrogen, with perhaps traces of methane; (3) combustible soot rbon *plus* tarry matter); (4) traces of ammonium compounds; d (5) a small proportion of finely-divided mineral matter shes) carried forward from the furnace by the draught. All ese constituents are hot, and therefore carry away with them eir "sensible heat," whilst the heat of combustion of those lumerated under (2) and (3) represents also a loss of chemical lergy which might have been developed in the boiler furnace ad the combustion there been more complete.

It must, however, be remembered that some part of what are usually termed "chimney losses" does not really represent a lead loss to the system, inasmuch as the expenditure of a certain proportion of the energy of combustion is necessary to create the chimney draught. For without the rapid movement of air and burnt gases thus created and maintained no combustion of the fuel would take place, nor would there be any heat transmission in the boiler. And it is obvious that if by any means the burnt gases were all cooled down to atmospheric temperature before leaving the boiler system, some mechanical device would have to be substituted for the natural chimney draught. Hence some part of the "waste heat" of a chimney is an unavoidable expenditure of energy, and therefore is not, strictly speaking, a loss. It may, however, be safely said that the heat carried away up the chimney is always greatly in excess of that which is needed to move the gases through the system, namely about 2 or 3 per cent. of the total heat of combustion of the fuel.

A glance at the tabulated results of Professor Constam's boiler trials (Tables XLVIII and L) will show that as a rule by far the most serious chimney loss is that represented by the sensible heat of the burnt gases *plus* the excess of air passing up it. It is only in exceptional cases, and with very bad stoking, that the loss due to *unburnt* gases, or even smoke, assumes large proportions, whilst that due to the presence of finely divided

matter or ammonium salts in the chimney gases may be regarded as insignificant.

In order to estimate the proportion which these various losses, both separately and in their sum total, bear to the heat of combustion of the coal, it is necessary to have exact chemical analyses both of the coal burnt and of the chimney gases, and to know the average temperature and specific heat of the latter. Determination must also be made of the calorific value of the fuel burnt and of the temperature and hygrometric condition of the air drawn into the furnace. For it must be remembered that it is never possible in practice to burn coal " dried at 100° C." in *dry* air; the coal will usually contain between 2 and 5 per cent. of moisture, and the air drawn into the system will contain anything up to 2 per cent. of moisture. Thus, for example, if 1 lb. of a coal containing 3 per cent. of moisture and 4·5 per cent. of " disposable hydrogen " be burnt with 1·5 times the theoretical quantity of air of 60 per cent. saturation at 60° Fahr. then the amounts of steam in the burnt gases will be somewhat as follows :—

From 3·0 per cent. of moisture in coal . . = 0·030 lb.

„ 4·50 „ „ „ hydrogen „ „ . . = 0·405 „

In 215 cub. ft. of air of 60 per cent. saturation at 60° Fahr. . . . . = 0·100 „

Total = 0·535 „

In this connection the importance of a proper chemical control of a large boiler installation may be emphasised. In far too many cases matters are left solely in the hands of engineers who are certainly not usually well qualified to carry out or supervise chemical analyses or operations. If only it became the custom of all large manufacturing firms to engage the services of a properly trained " fuel chemist " to supervise all coal contracts and to establish a scientific control over fuel consumptions generally, a vast saving in their annual coal bills would be effected. And groups of small manufacturers might secure similar advantages by co-operation.

Sensible Heat of Burnt Gases.—Provided that the data mentioned in the preceding paragraphs are precisely known, it is a comparatively easy matter to calculate (1) the amounts of carbon dioxide, steam, oxygen and nitrogen passing up the chimney per unit weight of coal (of known calorific value) burnt, and (2) the total " sensible heat " represented by the mean increase

he kinetic energy of the said gases between the atmospheric
temperature $t°$ and the chimney temperature $T°$. For this
purpose a knowledge of the mean heat capacities of carbon
oxide, steam, and the diatomic gases nitrogen and oxygen,
der constant pressures between, say, 15° C. and temperatures
to 600° C. is necessary.

According to Holborn and Henning,[1] whose work on the
ibject is generally accepted as providing the best available

FIG. 24.—Mean Specific Heats of Nitrogen, Carbon Dioxide
and Steam (Holborn and Henning).

data, the mean specific heats at constant pressure in calories
per gram of carbon dioxide, steam, and nitrogen between 0° and
1400° C. (steam 100° to 1400° C.) may be represented as a function
of temperature, as follows, where $t = ° C.$

MEAN SPECIFIC HEATS AT CONSTANT PRESSURE IN CALORIES
PER GRAM.

		Range °C.
Carbon dioxide	$C_p = 0.2010 + 0.0_4742t - 0.0_7 18t^2$	0 to 1400°
Steam . . .	$C_p = 0.4669 - 0.0_4168t + 0.0_7 44t^2$	100 to 1400°
Nitrogen . .	$C_p = 0.2350 + 0.0_4 19t$	0 to 1400°

The values of the mean specific heats in calories per gram

[1] Ann. de Phys. (4), 18 (1905), 7139, and 23 (1907), 809.

m
a
l
l
l
t

TABLE LII

HEAT IN NITROGEN, CARBON DIOXIDE AND STEAM

[B.Th.Us.]

re	Nitrogen.	Carbon Dioxide.	Steam.	
	B.Th.Us. per cub. ft. at 0° C. and 760 m.m.		B.Th.Us. per cub. ft. of Saturated Steam at 100° and 760 m.m.	B.Th.Us. per lb.
=	0° — T°		100° — T°	
O	3·33	4·59	—	—
)0	6·71	9·51	3·12	83·45
)0	10·13	14·37	6·24	167·1
00	13·63	20·10	9·38	251·4
)00	17·17	25·77	12·55	336·4
)00	20·76	31·65	15·81	423·7
700	24·40	37·74	19·14	512·9
800	28·11	43·98	22·55	604·6
900	31·88	50·35	26·11	699·6
1000	35·67	56·77	29·75	797·4
1100	39·53	63·36	33·59	900·3
1200	43·46	69·96	37·56	1006·3
1300	47·40	76·61	41·73	1117·8
1400	51·42	83·32	46·07	1234·8
0 — 15	0·50	0·67		

1) The density values employed in drawing up Table LII have been culated by dividing the molecular volume in litres (22·4 litres) by the ɔlecular weight of the gas in grams.

(2) The corresponding figures for the sensible heat per cub. ft. measured etween 15° and *t*° may be obtained in the case of nitrogen by subtracting ·50 B.Th.U. per cub. ft., and in the case of carbon dioxide 0·67 B.Th.U. ɪom the figures given in the table.

(3) The values for the sensible heat for other diatomic gases (oxygen and carbon monoxide) may be assumed, for the purposes of fuel calculations, to be the same as those for nitrogen.

From such calculated values, the following curves (Fig. 25) have been plotted showing the total sensible heat in B.Th.Us. between 0° and any temperature in the Centigrade scale up to 1400° for a cub. ft. measured at 0° C. and 760 m.m. of each gas and for 1 lb. of steam.

It may be considered good boiler practice if with an average steam coal, containing, say,

$$C = 80 \cdot 0, \ H = 5 \cdot 5, \ S = 1 \cdot 0, \ N = 1 \cdot 5, \ O = 5 \cdot 0,$$
and ash = 7·0 per cent.,

substantially complete combustion can be attained with no more than 1·5 times the theoretical amount of air, 135·2 = 202·8 cub. ft. at 0° and 760 m.m. per pound, and at the same time keeping the temperature of the gases down to 300° C. If the hygrometric condition of the air taken in at the furnace be 60 per cent. saturation, and if the coal as charged into the furnace contains 2 per cent. of

Fig. 25.—Sensible Heat of Nitrogen, Carbon Dioxide and Steam (B. Th. Us.).

then heat carried off by the chimney gases at 300° C. per lb. of *dry* coal burnt, will be as follows :—

					B.Th Us.	
In	23·93 cub. ft.	CO_2	=	328	}	measured at 0° C.
,,	160·62 ,, ,,	N_2	=	1547		and 760 m.m.
,,	14·19 ,, ,,	O_2	=	137		
,,	1·523 lb. Steam		=	364		
	Total .		.	2376		

total would be 17·0 per cent. of the calorific value of the coal
it, which is assumed to be 14,000 B.Th.Us. per lb.
ow prejudicial are the effects of higher chimney temperatures
. larger excesses of air upon the sensible heat losses, and there-
: upon the efficiency of the boiler, may be judged from the
owing table and curves (Table LIII and Fig. 26) which show
: calculated losses in B.Th.Us. per lb. of the dry coal in question
th varying excesses of dry air and chimney temperatures up
· 500° C.

$$\text{RATIO;} \quad \frac{\text{AIR ACTUALLY PASSING THROUGH THE BOILER SYSTEM.}}{\text{AIR THEORETICALLY REQUIRED TO BURN I LB. OF COAL.}}$$

FIG. 26.—Sensible Heat in Flue Gases—Effect of Air Dilution.

TABLE LIII

SENSIBLE HEAT LOST IN FLUE GASES

B.Th.Us. PER POUND OF COAL BURNT FOR THE TEMPERATURE
RANGE 15° — T° C.

Ratio $\dfrac{\text{Air drawn through the System}}{\text{Air theoretically required}}$.	Temperature of Flue Gases T° C.		
	300°	400°	500°
1·0	1358	1870	2382
1·5	2127	2917	3712
2·0	2779	3807	4839
2·5	3135	4697	5971
3·0	4079	5578	7092

The following calculations published by Messrs. W. H. Booth and J. B. C. Kershaw of the percentage losses in respect of sensible heat carried up the chimney by the burnt products of combustion of a good steam coal of calorific value 13,500 B.Th.Us. per lb. with a chimney temperature of 600° Fahr. (say 315° C.), according to their CO_2 contents,[1] may be cited as emphasising the needs of a careful control of the air supply as a means of minimising such losses.

Percentage CO_2 in Chimney Gases.		Percentage Chimney Losses due to Sensible Heat of Burnt Products *plus* Excess Air at 315° C.
12·0	. . . . . .	17·1
10·0	. . . . . .	20·2
8·0	. . . . . .	24·0
6·0	. . . . . .	32·8
5·0	. . . . . .	40·0

As the mere observation of the temperature of the chimney gases, without a simultaneous determination of their CO_2 content, may be very misleading, the two determinations should always be made together. Indeed the installation of recording instruments for these purposes in the flue leading from the boiler to the chimney may be recommended as one of the best aids to the achievement of the utmost economy in boiler practice, especially if the indications of the CO_2 recorder are occasionally checked by a complete chemical analysis in the laboratory of a representative sample of the chimney gases taken continuously over a period of not less than thirty minutes.

(e) *Heat Transmission in Boilers*

The factors governing the transmission of heat across the boiler surfaces from the fire and the hot products on the one side to the water on the other have so important a bearing upon both the design and general efficiency of a particular installation that it is deplorable how often they are neglected by those responsible for the management of large plants. The scientific aspects of the question formed the subject of a very able and comprehensive Report presented by Professor W. E. Dalby to the Institution of Mechanical Engineers in the year 1909,[2] which, together with the discussion thereon, is commended to the reader as embodying the best knowledge then available.

[1] *Smoke Prevention and Fuel Economy*, 2nd Ed., 1911, Appendix II, p. 221.
[2] *Proc. Inst. Mech. Eng.*, 1909, pp. 921 to 1071.

ιe transmission of heat from the fire to the boundaries of furnace takes place, to quote Professor Dalby, "in two !amentally different ways :—(1) by direct radiation from incandescent fuel and the flame and the hot gases, and (2) by agency of the matter in the path of the flow—that is, the hot es, the metal boundary, and the water on the other side of the ιndary. In the first case, transmission is effected by the vibra- n of the ether in the same way that the heat of the sun is ιnsmitted to the earth across space and is instantaneous . . . ιd) may be regarded as uninfluenced by the presence of the rnace gases, although actually the quantity is modified by their esence to a certain extent. In the second case, the matter in ιe path of the flow transmits the heat (a) by convection, and ·) by conduction." [1]

Hence in general three modes of transmission, all acting ·imultaneously, must be considered, namely (1) by radiation, ι2) by convection, and (3) by conduction. And whereas it is ιmpossible to devise any experiment in which one particular mode may, so to speak, be isolated and studied apart from the other two, yet it is very desirable that in forming a mental picture of the operation as a whole the influence of each mode should be separately considered and its relative importance weighed.

Radiation.—The outstanding importance of this factor has until recently been largely overlooked or under-rated by engineers. It should always be remembered (1) that the heat radiated from an incandescent black body, as represented by a glowing mass of coke in a boiler furnace, is proportional to the *fourth* power of its absolute temperature (Stefan's Law); (2) that the flames pro- duced by burning gases radiate an appreciable proportion of the energy developed by the combustion, as for instance, a non- luminous Bunsen flame, which radiates some 15 per cent. of the energy developed therein; (3) that the energy thus " radiated " is transmitted practically instantaneously and without sensible loss to the metal boundary between the furnace and the water; and (4) that the " radiated " energy absorbed by the said bound- ary is then "conducted" by it, as sensible heat, to the water on the other side. The limiting factors in the process are *either* (1) the conducting capacity of the metal septum, or (2) the exist- ence of a dead water film on the other side of it (see the following paragraphs). If the evolution of steam and the water circulation on the other side is sufficiently intensive, the limiting influence

[1] *Proc. Inst. Mech. Eng.*, 1909, p. 923.

of (2) may disappear, in which case the conducting capacity of the metal septum would be fully operative.

The total energy, expressed in ergs, radiated per square centimetre per second from an incandescent black body is given by the following equation (where T is its absolute temperature in degrees Centigrade) :—

$$E = 5.32 \times 10^{-5} \; T^4 \text{ ergs per cm}^2 \text{ per sec.}[1]$$

Converting this into the equivalent B.Th.Us. radiated per sq. ft. per hour, and introducing the influence of a further condition, namely that of the temperature T_2 of the absorbing surface (the metal boundary), the expression becomes :—

$$E = 16 \times 10^{-10} \; (T_1^4 - T_2^4) \text{ B.Th.Us. per sq. ft. per hour,}$$

where T_1 and T_2 represent in degrees Fahrenheit the absolute temperature of the source of radiation (the fire) and of the absorbing surface (metal boundary) respectively.

By means of this formula Professor Dalby (*loc. cit.*) has calculated that the *upper limiting* value of the heat which may possibly be transmitted by radiation from a source (assumed to fill the firebox) at a temperature of 3000° Fahr. to a boundary surface at 800° Fahr. may be as high as 129,600 B.Th.Us. per sq. ft. per hour, or equivalent to the evaporation of 134 lb. of water " from and at " 212° Fahr.

Although so high a result is probably never actually attained in practice, however nearly it may be approached, the formula indicates how supremely important the radiation from incandescent surfaces in a boiler furnace may be, and how efficient a heating surface (metal boundary) exposed to them may become, as for example in the Bonecourt Surface Combustion Boiler (*q.v.*).

Transmission by Convection and Conduction.—It has long been recognised that the transmission of the sensible heat of the hot gases during their passages through the tubes or flues of a boiler to the water on the other side of the metal plate, is limited by the existence at the boundary surface of a " dead " film, generally assumed to be about $\frac{1}{40}$ in. only in thickness, of relatively cool gas, in which convection currents apparently do not take place and which, owing to its low conductivity, offers a high resistance to the passage of heat (other than " radiant heat ") through it. There is also a similar " dead " film of water on the other side of the plate, which offers a like but considerably smaller resistance.

---

[1] Poynting's *Heat* (1904), p. 250, as quoted in Dalby's Report (*loc. cit.*).

ence it is that, unless special means can be found whereby
e films are destroyed or their retarding influence rendered
ligible, the full conducting capacity of the metal composing
boiler tube can never be fully realised in practice. This
btless explains the experience of the early locomotive engine
lders, and which long puzzled them, that the substitution of
pper for iron tubes in a boiler did not appreciably increase the
te of heat transmission as measured by the evaporation, not-
thstanding the fact that the thermal conductivity of copper
about five times greater than that of iron.

How greatly the "dead" gas film referred to retards the heat
ansmission was well illustrated by some experiments published
y J. G. Hudson in 1890 [1] from which he concluded (1) that of
he total "temperature head" between the hot flue gases and
he water in a boiler, no less than 98 per cent. is lost in forcing
the heat through the "dead" gas film into the plate, the remain-
ing 2 per cent. only being the "effective head" between the
plate and the water; and (2) that the hot side of the plate is
never more than 36° Fahr. hotter than the water side. These
conclusions were substantially confirmed in 1893 by Sir John
Durston, who, however, put the difference referred to in (2) at
68° Fahr. for water at 212° Fahr. when the plate is perfectly
clean.[2] Professor Dalby (*loc. cit.*) thinks that of the total "tem-
perature head" about 97 per cent. is required to overcome the
resistance of the gas film, 1 per cent. to overcome that of the plate,
and 2 per cent. to overcome that of the water film.

In considering the retarding influence of films of gas, oil, or
water on the tube plate, to the passage of heat, the following
table of conductivities, expressed in calories which pass per
second through a plate of the substance 1 c.m. square and 1 c.m.
thick when the opposite faces of it are kept at temperatures
differing by 1° C., may be useful :—

Air	0·000055
Carbon dioxide . . .	0·000031
Water	0·00143
Oil	Between $\frac{1}{4}$ and $\frac{1}{8}$ that of water.
Scale	2 to 5 times that of water (according to density)
Iron	0·20 } approximately.
Copper	0·90 }

[1] *The Engineer*, 1890, **70**, p. 523.   [2] *Trans. Inst. Nav. Arch.*, **84**, p. 130.

As to the influence of oil and scale, experiments carried out by W. J. Hirsch in 1890 [1] led him to conclude (1) that any fatty deposit on the internal surface of a boiler greatly impedes the transmission of heat, and (2) that a deposit of vegetable oil is more dangerous than one of mineral in causing the plate to overheat, whilst L. P. Breckenridge [2] found in 1899 that the formation of a scale $\frac{1}{32}$ to $\frac{8}{64}$ in. thick in the tubes of a locomotive boiler caused a loss in efficiency of 9·55 per cent. From such observations as these the great importance of keeping plates and tubes of a boiler clean may be appreciated.

THE EFFECT OF HIGH GAS VELOCITIES IN DESTROYING THE " DEAD " GAS FILM AND THEREBY INCREASING THE RATE OF HEAT TRANSMISSION.

If, as has been shown in the preceding paragraphs, the existence of the " dead " gas film at the surface of the metal plate separating the source of heat from the water in a boiler is the main and most potent obstacle to rapid heat transmission, it follows that its complete or even partial destruction would greatly assist the flow of heat. This was first recognised by the late Professor Osborne Reynolds, of Manchester, who, in the year 1875, published a remarkable paper [3] in which he suggested that the best solution of the problem of diminishing the influence of the " dead " gas film probably lay in increasing the velocity of the hot gases through the boiler system. From theoretical considerations he concluded that the rate of heat transmission would prove to be a linear function of the speed at which the hot gases traversed the system, and gave the following formula :—

$$Q = (A + Bdv)\,(T - \theta)$$

in which :—

Q = amount of heat transmitted in B.Th.Us. per sq. ft. per sec. from the hot gases to the water

d = the density of the hot gases in lb. per cub. ft.

v = the velocity of the hot gases in ft. per sec.

T = temperature of the gases in ° Fahr.

θ = mean temperature of the heating surface

A and B = experimental constants.

His contention that the rate of heat transmission depends upon

---

[1] *Bull. de la Soc. d'Encour. Indust. Nat.*, Vol. 5, p. 302.
[2] *Railroad Gazette*, Vol. 31, p. 60.
[3] *Mem. Lit. Phil. Soc. Manchester* (1875), Vol. XIV., p. 7.

velocity of the gases was subsequently supported by other stigators, among whom may be mentioned J. G. Hudson [1] ɔ), whose formula, however, made the rate of heat transion depend on the square root of the gas velocity, Brillié '7), [2] and Professor John Perry (1898), [3] but it was left to the Professor J. T. Nicolson of the Manchester School of Techɔgy to develop the theory and its practical application to ler design in the year 1909. [4]

Nicolson's experiments had convinced him that, inasmuch as ᵴ evaporation from the firebox due to convection was negligible comparison with that due to radiation, in designing a boiler he proper thing to do was to form a combustion chamber of ɔwing refractory—that is non-water-cooled—surface behind ᵤe firebridge and before the flues or tubes ɒr convective heating ırface commenced," in order that any unburnt gases from the re might be caught and perfectly burnt. With regard to the ransmission of heat by convection from the hot burnt gases hrough the plate to the water, his own experimental work, vhilst supporting the general validity of Osborne Reynold's ᵴquation, as expressing the law for the heat flow from fluid to metal or *vice versa* under the most varied conditions, led him to amplify it, owing to the fact that the rate of heat transmission depends not only upon the product of the density and velocity of the hot gases, but also upon such factors as the mean hydraulic depth of the tubes or flues through which the gases passed, and the nature of the metal plate. As the result of a prolonged experimental investigation of this subject he finally put forward the following revised equation :

$$Q = \left[\frac{\phi}{200} + \frac{\sqrt{\phi}}{\text{const.}}\left(1 + \frac{p}{a}\right)dv\right](T - \theta)$$

where :—

T = mean gas temperature in flue in ° Fahr.

θ = mean plate temperature in flue in ° Fahr.

ϕ = mean temperature of gas and plate in ° Fahr.

d = mean density of gas (lb. per cub. ft.)

v = mean velocity of gas in ft. per sec.

a = area, and p = perimeter of gas flue in ft.

[1] *Engineer* (1890), Vol. LXX., p. 523.
[2] *Le Génie Civil* (1897), Vol. XXXI., p. 260.
[3] *Trans. Inst. Eng. Ship. Scot.* (1898), Vol. CXXXII., p. 274.
[4] *Trans. Jun. Inst. Eng.*, Feb. 1909, and also " Discussion on Professor Dalby's Paper " (*loc. cit.*), p. 1007.

P

... through a vertical flue F, 7½ in. in diameter, called the "evaporator," containing 102 water tubes, each 11 ft. 6 in. ... by ½ in. external and ⅜ in. internal diameter. From the to... ...the gases were led downwards through another similar ... called the "economiser," containing 90 water tubes, e... ... ft. 9 in. long by ½ in. outside and ⅜ in. inside diameter, ... along the axis of each was fixed a ¼ in. square rod, 13 ft. ... ing, to reduce the cross-sectional area, and consequently

This diagram, together with **Table LIV**, are reproduced with ... permission of Mr. Michael **Longridge, M.A.**

FIG. 27.—Nicolson Experimental Boiler (at Joseph Adamson & Co. Works, Hyde, October 1909).

increase the velocity of the water and to force it into contact with the surface of the tube. From the bottom of the economiser the cooled gases were discharged through a motor-driven fan, H, which provided the necessary suction, into the chimney.

The heating surface of the boiler (excluding the surface below the grate and the firebrick lined combustion chamber, C), was 171 sq. ft., of the evaporator 192 sq. ft., and of the economiser 293 sq. ft., or a total for the whole system of 656 sq. ft. The capacity of the " water space " in the boiler was 230 cub. ft., that of the " steam space " 185 cub. ft., whilst the area of the water surface was 132 sq. ft.

During October 1909 the boiler was handed over to Mr. Michael Longridge to undergo a series of trials with the object of testing both the soundness of the underlying principle of its design and its evaporative power.

The results of two of these trials, in which the boiler was fired with a good Welsh steam coal, containing in the dry state—

$$C = 87 \cdot 60, H = 4 \cdot 23, S = 1 \cdot 52, N = 2 \cdot 13, O = 1 \cdot 18, \text{ and ash} = 2 \cdot 13 \text{ per cent.,}$$

and of calorific value 14,929 B.Th.Us. per lb., are given in Table LIV. These results showed (1) that combustion of the fuel was practically complete in the furnace and combustion chamber with only 1 25 times the theoretical amount of air, the burnt gases containing an average of 14·7 per cent. of carbon dioxide, with only 0·22 per cent. of carbon monoxide; (2) that the temperature on leaving the system had been reduced to as low as 294° Fahr.; (3) that the rate of evaporation per square foot of heating surface of the boiler and evaporator combined was as high as 23 lb. of water " from and at 212° Fahr.," or something like three times that of an ordinary Lancashire boiler; whilst (4) the heat actually utilised in the system amounted to 75 per cent. of that capable of being developed by the complete combustion of the coal in the furnace. It was also estimated that on an average as much as 32,400 B.Th.Us. per hour were transmitted to the water per square foot of the area of the flue surrounding the firebrick cylinder, E.

Taken as a whole the results certainly seem to prove the soundness of Professor Nicolson's ideas, although, as Mr. Longridge pointed out, probably in practice it would be found necessary to substitute some other more convenient device for the rather cumbrous firebrick plug, E.

TABLE LIV

RESULTS OF MR. MICHAEL LONGRIDGE'S TESTS OF THE NICOLSON
BOILER WITH A WELSH STEAM. COAL

		20/10/1909	20/10/1909
Date of Trial			
Duration in Hours		6·05	6·65
Dry Coal Burnt per Hour, lb.		724·0	721·0
Calorific Value of Dry Coal B.Th.Us. per lb. . .		14,929	14,929
Evaporation n lb. Water from and at 212° Fahr.	per Hour	8265	8372
	per lb. Dry Coal Burnt . . .	11·41	11·61
	per sq. ft. Heating Surface of Boiler and Economiser per Hr.	22·77	23·06
	per sq. ft. Total Heating Surface per Hour	12·58	12·75
Steam Pressure (absolute) in lb. per sq. inch.		135	135
Feed Water Temperature.	Entering Economiser in ° Fahr.	77°	71°
	Leaving Economiser in ° Fahr.	288°	275°
	Leaving Evaporator in ° Fahr.	350°	350°
Mean Temperature of the Gases.	in the Combustion Chamber, ° F.	3000°	3000°
	Entering Evaporator, ° Fahr. .	1360°	1418°
	Entering Economiser, ° Fahr. .	870°	871°
	Leaving Economiser, ° Fahr. .	291°	294°
Percentage Composition of the Gases.	CO_2	14·86	14·50
	CO	0·30	0·15
	O_2	3·84	4·45
	N_2	81·00	81·00
Ratio Air used to that theoretically required for Combustion		1·23	1·27
Percentage of heat of Combustion of the Coal.	Transferred to the Water . .	73·8	75·0
	Carried off by Burnt Gases and Excess Air	5·2	5·6
	Carried off by Unburnt Gases .	1·1	0·6
	Lost in the Ashes (no Carbon) .	3·7	3·3
	Balance	16·2	13·5
B.H.P. used by Feed Water Pump and the Fan		41·23	41·48
Estimated *net* Efficiency of whole Plant after deducting B.H.P. used for driving Pump and Fan		64·4	66·1

THE BETTINGTON BOILER FOR ATOMISED FUEL

As an instance of another recent development in scientific boiler design in a somewhat different direction, the Bettington boiler may be appropriately described, inasmuch as it embodies a possible solution of the difficulty of completely burning a

homogeneous mixture of pulverised coal and pre-heated ⸱⸱
a continuous flame, and is capable of being applied success⸱
to low-grade lignitic coals, which in ordinary boilers yield ⸱
poor results.

The boiler, shown diagrammatically in Fig. 28, consists ⸱⸱
cylindrical body, AB, fixed vertically on a suitable founda⸱⸱
and containing the combustion chamber, C, which is forme⸱
a circle of vertical water tubes separated by keyed refrac⸱⸱
firebricks, so that the wall of the chamber is partly the expo⸱
tubes and partly the filling of firebricks. This construct⸱⸱
a water-cooled combustion chamber has overcome one of ⸱
causes of failure in dust-burning boilers hitherto experien⸱
namely the difficulty of getting any arrangement to stand ⸱⸱
very high temperature involved. The fuel is fed from a bunk⸱
D into a rotary pulveriser and blower, E, where it is ground ⸱ ⸱
the dust and mixed with a stream of air (sufficient in quan⸱⸱
for its complete combustion) which has been pre-heated ⸱
passage through an " air-heater " at the top of the boiler at t⸱
expense of part of the sensible heat of the waste gases. T⸱
intimate mixture of coal dust and hot air is blown by the ⸱⸱
through a chamber, F, where any coarse particles of coal ar⸱
deposited and returned to the pulveriser, and thence by a duc⸱
to the burner, G, which is fixed in a central position *at the* bott⸱⸱
of the combustion chamber of the boiler.

The explosive mixture of coal dust and hot air *is ignited* as
it emerges from the mouth of the burner, producing a continuo⸱⸱
mushroom-shaped flame which fills the combustion *chamber.*
The combustion of the fuel, being thus " explosive " in character,
is completed with a minimum excess of air; the ash in *the fuel*
during its passage through the flame is converted into a liquid
spray, which is projected against the hot brick lining *of the*
furnace, and in course of time drips down into the *ash*-pit at the
bottom of the chamber, where it is sufficiently chilled to prevent
the successive drops from adhering to each other. The cold ash
is in the form of small globules ⅛ to ¼ in. in diameter which can
easily be removed periodically. Also, it is claimed *that* the
liquid spray of ash serves to close up all crevices in the fire-
brick lining of the furnace, cementing it into one solid *piece* and
glazing the inner surface as with an enamel.

The mushroom flame of the burning coal dust and air *mixture*
passes first upwards in the boiler chamber, and on striking
against the water chamber, H, at the top thereof, is *deflected*
into a downward vertical ⸱ ⸱⸱ for some distance along the

FIG. 28.—Sectional Elevation and Cross Section of Bettington Boiler, showing the Path of the Gases.

215

inner walls of the chamber, until on nearing the bottom the hot products are turned upwards again through the annular space between the inner and outer walls of the boiler in which are fixed a series of solid drawn mild steel water evaporating tubes. These tubes are arranged in double rank between the top and bottom " headers," H. and K. The gas stream after emerging into a chamber, L, surrounding the top header, H, finally passes thence upwards to the chimney *via* the tubular air-heater, M, in which part of their sensible heat is transmitted to the cold air which is drawn by the fan blowers downwards through the tubes of the heater on its way to the pulveriser where it mixes with the coal dust.

The steam generated in the vertical evaporating tubes collects in the top header, H, from which it passes downwards through the pipe, N, into the annular superheater, P, which is fixed like a belt round the lower part of the combustion chamber.

It is claimed that the boiler is capable of burning smokelessly low-grade slack coals, containing up to even 25 per cent. of ash, with a steam-raising efficiency up to between 70 and 80 per cent.; moreover that, owing to its being possible either to start or to stop the combustion almost instantaneously, not only can steam be got up or shut down very rapidly, but also that the rate of combustion can be rapidly adjusted to variations in the load.

Steam Trial.—As an example of what the boiler is capable of doing with a low-grade coal, the results of the following steam trial carried out by the author with a Malayan (Rawang) lignitic coal in the year 1912, may be described.

The boiler used was a vertical cylinder, 29 ft. in height by 10 ft. in diameter, with a water-heating surface of 2100 sq. ft., and a superheating surface of 500 sq. ft. Its rated capacity was equivalent to an evaporation of 10,000 lb. of water per hour " from and at 212° Fahr." The construction of the boiler was such as to admit of accurate steaming trials being carried out within a relatively short time, inasmuch as (1) the pulverised fuel was completely and practically instantaneously burnt as fast as it was fed into the combustion chamber; (2) there was no heat-retaining brickwork setting or the like; and (3) the water capacity of the boiler was very small in relation to its rate of evaporation.

On the day of trial, the boiler had been fired for a continuous period of several hours with the Rawang coal, before the actual official test commenced. The latter extended over a period of $1\frac{1}{2}$ hours. The coal was weighed out in 2 cwt. lots at regular intervals of from $7\frac{1}{2}$ to 10 minutes, each lot being immediately

ferred to the hopper of the pulveriser attached to the
r. A sample was taken from each charge as it passed into
hopper, so as to provide a representative sample of the fuel
the whole period of the trial.

ne graduated tank through which all the feed water passed
he boiler was subsequently calibrated by weighing the water
harged between various selected levels on the graduated scale
inst the same set of weights which had been used for weighing
: the coal during the trial, and proper corrections were applied
· the difference between the density of the feed water (at 159°
hr.) used during the trial and that of the water (at 58° Fahr.)
ed for the subsequent calibration of the tank. Systematic
mperature and pressure readings were made at regular intervals
i 15 minutes throughout the trial.

The coal as charged into the boiler contained 13·8 per cent.
f water and 4·4 per cent. of ash, whilst the calorific value of the
dry coal was 11,644 (gross) and 11,066 (nett) B.Th.Us. per lb.

The mean rate of evaporation maintained throughout the
trial was somewhat higher than the rated capacity of the boiler,
and the efficiency attained was 70·3 per cent. based on the *net*
calorific value of the dry coal; combustion was complete, and
the average amount of CO_2 in the chimney gases was 11·7 per cent.

The detailed results of the trial are set forth below :—

Duration of Trial = 1¼ *Hours*
Temperature of Air in Boiler House = 75·5° *Fahr.*
Barometer = 30·4 *in.*

(1) Total *dry* Coal fired per hour	. .	1287 lb.
(2) Total Water actually evaporated per hour		8870 lb.
(3) Temperature of Feed Water .	. .	159° Fahr.
(4) Absolute Steam Pressure, lb. per sq. inch		165
(5) Temperature of Evaporation .	. .	366° Fahr.
(6) Superheat of Steam . .	. .	114° Fahr.
(7) Factor of Evaporation, including super-heat		1·168

(8) *Evaporation* "From and at 212° Fahr."
- lb. per hour . 10·360
- lb. per sq. ft. Heating Surface per hour . . 4·93
- lb. per lb. of Coal as charged 6·9
- lb. per lb. of *dry* Coal . . 8·

9) *Average Temperature* (leaving Boiler . . . °F.
of *Waste Gases* (in Chimney Flue . . . °F.

10) Average Percentage of CO_2 in Chimney
Gases . . . .

11) *Efficiency* on *net cal. value* of *dry* Coal .

N.B.—(The current required to drive Electric Motor
integrator = 105 amps. at 220 volts.)

CHAPTER XII

ACCORDING to the Report of the British Association Fuel Economy Committee (1916), "the amount of coal annually consumed for domestic purposes in the United Kingdom probably does not fall far short of thirty-six million tons per annum, or nearly one-fifth of the total consumption for all purposes in the Kingdom. To this would have to be added the 'coal equivalent' of the gas and electricity consumed for domestic purposes, if a correct estimate of the total domestic coal consumption is to be made."

The wastefulness of the Englishman's cheerful fireplace has always been a favourite theme with those iconoclasts who would prohibit it except in their own homes, and if efficiency were the only consideration there is something to be said for its abolition. But with characteristic conservatism, and disrespect for Science when it counters his cherished customs, the average Englishman undoubtedly has a decided objection to the introduction of central heating systems into his living rooms, and much prefers to be warmed by the radiation from a bright fire.

Hence it is (to quote again from the British Association Committee's Report) " that the whole question of the domestic use of fuel bristles with difficulties and complications . . . (that) . . . the selection or recommendation of particular means or apparatus for domestic heating cannot always be based simply upon the question of thermal efficiency, because it also involves considerations of a physiological and even of a psychological character . . . (and) . . . that there is probably no single solution of the domestic heating problem which is likely to be universally adopted within any measurable period of time . . . (also that) . . . it is necessary to discriminate between fuel or energy consumed in the kitchen for cooking and other similar purposes, and that applied for the heating of ordinary living rooms. In the vast majority of the houses inhabited by the artizan population the kitchen fire or stove is the only place in the house where

fuel is burnt also in better-class houses it is only in the [...] that fuel is burnt daily throughout the whole year. [...] would appear that the kitchen is responsible for the great[er...] of our annual domestic fuel bill, and, therefore, the [...] of the relative efficiencies of kitchen ranges, gas and [...] ovens, and hot-water-supply apparatus assumes consid[erable] import[ance].

The [commit]tee put forward the following as, in their [...] the chief objects to be aimed at in any reform of domestic [...] consumption, namely :—

1. A [real] reduction in cost of domestic heating, ei[ther by] the form of direct saving of fuel or labour, or both;

(2) mitigation or abolition of the domestic smoke nuisa[nce;] and

(3) better hygienic conditions in living apartments general[ly.]

A householder in our large cities and towns is usually offe[red] a fairly wide range of choice in respect both of available f[uel] (or energy) and of the ways and appliances in which to em[ploy] them. He may, for instance, use one or more of the followi[ng] sources of heat, namely anthracite, bituminous coal, coke [...] gas from the local gas-works, or even electricity. And he w[ill] have no difficulty in finding suitable means for applying ea[ch] or any of these commodities, either for the cooking of his dinn[er] or the heating of his rooms. Moreover, with the exception o[f] bituminous coal—which, however, practically every house in th[e] [...] uses—the use of none of them will lay him open to th[e] [...] charge of the pollution of the atmosphere round h[im.]

[...]t may be asked, is raw bituminous coal th[e...] [...] of the average British citizen for his domest[ic...] [...] The question is not easily or simply answered. It [is...] [partl]y a matter of first cost, partly the force of tw[o...] [...] of custom and ingrained habit, and lastly becaus[e...] [there i]s something indefinably pleasing about the ever-changin[g...] [...]d fire with its dancing flames and genial warmth [...] appeals to the "fire-worshipping" instinct of mankind [...] the character of the British winter, with its sombre skies [...] fogs and rapid changes in temperature, makes an open [...] welcome companion; and the sitting round it is undoubtedly [...] the most cherished features of our home-life.

ne severe winters which are prevalent in the corresponding ... les of North America or Mid-Europe, and still more so ... sub-arctic climates of the farther North, either central ... ing systems or the closed stove become necessary for domestic ... ing on grounds of comfort and economy, and, therefore, are ... st universally adopted. Also, in countries such as France, ... e coal is not so abundant as with us, anthracite stoves are ... ly used. But in Great Britain central heating is mainly ... ined to hotels and country mansions.

... me idea of the wastefulness of our British open fireplaces ... kitchen ranges may be gained from the fact that, whereas ... h a population of 46 millions we annually consume in our ... ises about 36 million tons of coal, in Germany, with its ... pulation of 67 millions and its severer winter climate, where ... sed stoves and ranges are universally employed, only 17 million ... ns are so burned. In other words, each inhabitant of the ... nited Kingdom requires a domestic consumption of 15 cwts. ... coal per annum, as against only 5 cwts. in Germany.

Comparing the first cost of energy units in the form (1) of a ... ood house coal of (say) 13,500 B.Th.Us. per lb. at £1 10s. per ton; 2) of gas of 500 B.Th.Us. per cub. ft. at 2s. 6d. per 1000 cub. ft.; ... nd (3) of electricity at 1d. per unit, a pound sterling will purchase the possibility of developing the following quantities of heat :—

(1) In the form of coal . . 20,000,000 B.Th.Us.
(2) „ „ „ „ gas . . 4,000,000 „
(3) „ „ „ „ electricity . 825,000 „

These figures, however, do not represent the relative costs of the energy actually utilised in heating apartments or for cooking purposes, because a much greater proportion of the heat developed by the combustion of gas is utilised than by the combustion of coal, and the proportionate loss in the case of electricity is the least of all. The percentage losses in the three cases may be considered as approximately not less than 60 in the case of coal, about 20 in the case of gas, and not more than 10 in the case of electricity. Hence for the expenditure of one pound sterling the following number of " utilised " heat units would probably be obtained :—

(1) *Via* coal . . 8,000,000
(2) *Via* gas . . 3,200,000
(3) *Via* electricity . 750,000

Nor does a fair comparison of the three commodities end here, because not only are gas and electricity absolutely clean and can be turned on and off without trouble at a moment's notice, so that when the heat is not required it need not be developed, but also the labour necessarily expended in maintaining coal fires, and the smoke and dirt which their use entails, are serious items in household economy. Moreover, the use of raw bituminous coal, capable as it is of yielding by proper treatment products whose value to the community far exceeds their mere heating potentialities, must be regarded as a national waste. The use of coke or semi-carbonised coal would, however, remove this reproach.

Coal and Coke Fires

A good house coal should be selected for its free-burning qualities and low ash content, and in a closed-in kitchen cooking range with its stronger draught a " harder " coal should be burnt than in the open fireplace of an ordinary sitting-room, or otherwise undue waste will result. Indeed for a properly designed kitchen range of this type a good quality of gas coke is often preferable to most " house coals," either used by itself or in conjunction with the coal.

Even a well-designed closed-in kitchen range may be very wasteful of coal unless those managing it not only regularly remove the accumulation of soot and ashes which are always being deposited in the oven flues, but also control the draught by means of the various dampers according to the varying requirements of each day's operations. If the passage of the hot products of combustion round the oven flues is impeded by undue accumulation of soot and fine ashes therein, the oven cannot be brought to a good baking or roasting heat, and all attempts to force it by opening of the dampers are usually not only futile, but involve great waste of fuel. On the other hand, it may be that if the oven flues are clear and the draught is not checked by the damper, the air is drawn at an unnecessarily high velocity through the fuel, with the result that the fire " roars " and the coal is too quickly consumed. Those who operate kitchen ranges need reminding that the rate at which the glowing coal burns in the grate is determined by the rate at which the air is drawn through it.

In this connection it is well to point out that the design of

ay kitchen ranges is defective in that the air is allowed too an access to the fire when the oven dampers are open, and such a case the plan of partially closing in the open space ween the level of the firegrate and the ash-box below it by ans of a wrought-iron plate may be resorted to with the object t only of checking the flow of air, but also of causing it to be ected through the cavity below the grate so that it may be mewhat preheated before it reaches the fire. Indeed, all tchen ranges should be fitted with means of regulating the let of air to the fire, a far preferable way of reducing the draught arough the fire than by a damper in the flue, which has the isadvantage of throttling the flue and impeding the products f combustion getting freely away. Also if a pan of water be placed in the ash-box, the warm air passing over it will carry forward into the fire a certain amount of steam, which will generate " water gas " by its endothermic reactions with the incandescent coke, and thus cool the bars and diminish somewhat the loss by radiation from the grate.

A good deal of the smoke emitted from kitchen chimneys may be avoided by the selection of a cooking range provided with properly constructed grooved metal fire-cheeks, in which most of the smoke is consumed by an air supply which, entering the grooves at the bottom and being heated in passing through the cheeks, meets the smoke at the top and causes it to burst into flame.

Before leaving the question of coal consumption in kitchen ranges, something ought to be said about the boiler. In small and middle-class houses, a supply of hot water for domestic use, including baths, can be economically obtained from the range boiler, provided it is scientifically designed and constructed. But, unfortunately, this branch of engineering is not properly understood and has been very much neglected by those whose business it is to select and fix domestic ranges, with the result that tens of thousands of tons of coal are annually wasted by inefficient appliances.

For any one who has even an elementary knowledge of the principles of heat transmission, it is only necessary to examine the average small range saddle-boiler to be convinced of its inefficiency. The ordinary house is usually provided with a 40 to 60 gal. hot-water cylinder or tank, which is often connected with a boiler whose effective heating surface is only 2 or 3 sq. ft. Hence, in order to heat up such a quantity of

water quickly, the damper in the boiler flue has to be fully opened, with the result that the fire " roars " and the rate of coal consumption is at least doubled. On the other hand, with a properly designed and proportioned arrangement, a reasonable supply of hot water should be obtained with the boiler damper only slightly opened.

We owe many recent reforms in the construction of house firegrates to the pioneering work and observations of Mr. T. Pridgin Teale, F.R.S., the eminent Leeds surgeon. The principles which he advocated are set forth in a pamphlet on *Economy of Fuel in House Fires* which he published in 1883, and also in a lecture on the " Principles of Fireplace Construction " which he delivered on February 5, 1886, before the Royal Institution of Great Britain, and they have since been embodied in the well-known " Teale " fireplaces.

In the first of these publications he tells that his ideas embody a combination of two conditions, namely, " one, that no current of air should pass through the grate at the bottom of the fire; the other, that the space or chamber under the fire should be kept hot." He laid down seven rules to be observed in the construction of fireplaces, which in substance are as follows :—

(1) As much firebrick and as little iron as possible to be used.

(2) The back and sides of the fireplace should be constructed of firebrick.

(3) The back of the fireplace should lean or arch over the fire so as to become heated by the rising flame, whereby smoke is consumed, and much more heat is radiated into the room.

(4) The bottom of the fire or grating should be deep (9 to 12 in.) from before backwards, in order that the fire may be made horizontal and slow-burning instead of vertical and quick-burning.

(5) The slits in the grating should be narrow ($\frac{1}{4}$ to $\frac{3}{8}$ in. in width).

(6) The bars (if any) in front should be narrow (less than $\frac{1}{2}$ in. thick) and not more than four in number for an ordinary fire.

(7) The chamber beneath the fire should be closed in front by a shield or " economiser," so as to stop all currents of air that would pass *under* the grate and *through* the fire.

Some of these principles, or the objects aimed at by their

n, had been set forth, as Mr. Teale acknowledged, by Rumford as long ago as the year 1800, whose words are ·rth quoting here :—

n and, in general, metals of all kinds are to be reckoned st the very worst materials that it is possible to employ construction of a fireplace . . . the best materials I iitherto been able to discover are firebricks and common and mortar. The fuel, instead of being employed to heat iom *directly*, or by the direct rays from the fire, should be ·posed or placed as to heat the back and sides of the grates, i must always be constructed of firebrick or firestone, never of iron or any other metal. . . . I should increase iepth of the fireplace at the hearth to 12 or 13 in., and ild build the back perpendicular to the height of the top he burning fuel, and then sloping the back by a gentle ination forward, bring it to its proper place, that is to say, pendicularly under the back part of the throat of the mney." And in regard to a fireplace whose back was so inclined ward he said : " The flame rising from the fire broke against the rt of the back which sloped forward over the fire, and this part the back being soon very much heated, and in consequence of its ing hot (and when the fire burned bright it was frequently quite d-hot) it threw off into the room a great deal of radiant heat."

Mr. Teale also recommends (1) that the " lean over " at the ack of the fire should be at an angle of 70° to the horizontal ine of the hearth, also subsequently in a private note to the writer he added, " better an angle of 60° in some cases "; and (2) that the sides of the hearth should form an angle of 60° with the front base line so as not to cut off radiation from the back · part of the fire. Thus in plan the ideal form is based upon an equilateral triangle, as shown in the accompanying diagram (Fig. 29).

In 1887 Mr. Teale, in conjunction with his son, worked out a design, since known as the " Front Hob Fireplace," which embodied, in the most perfect form, the principles advocated in his Royal Institution Lecture the year previously. In it, either the hearth is raised to form the front of the fire, or the fire space is sunk below the level of the hearth, thereby doing away altogether with the use of front bars, and their impeding effect upon free radiation. This innovation was the forerunner of the numerous " barless " fires which have since come so much into vogue for the heating of apartments.

Among other improved domestic fireplaces should be mentioned those in which provision is made for regulating combustion, according to the needs of the moment, by means of doors or fronts closing up in sections. For very slow combustion the lower section, formed of two doors, is closed over the front of the fire so as to exclude all but the small amount of air required to keep it smouldering until such time when a greater heat is required. When it is necessary to increase the heat, the upper doors are shut and the bottom ones opened, thus forming an efficient " blower," and a hot bright fire is quickly obtained. Such a device is invaluable for sick rooms, where a fire has to be

INCHES.

FIG. 29.—" Economiser " Fireplace.

maintained throughout the night, or for dining-rooms, where it is only wanted at certain hours of the day.

Although the practice of burning raw bituminous coal in domestic stoves and fireplaces is to be condemned as dirty and unscientific, it by no means follows that the open fireplace ought to be abolished. The proper solution of the domestic problem lies rather in the directions of (1) providing all houses with stoves and fireplaces designed and constructed in accordance with sound principles; and (2) burning in them some form of carbonised coal or gas.

The proposal to manufacture for domestic consumption a smokeless " semi-coke " by carbonising bituminous coals at low temperatures is scientifically sound, if it can be carried out on commercial lines in such a way as to yield a product which will not only stand transport reasonably well, but can also be sold

the consumer at a price not exceeding that of a good house l. To make it coherent enough to stand transport by rail :h a " semi-coke " might be briquetted with, if necessary, a all addition of a suitable binding agent. If such conditions a be fulfilled on a large scale, the domestic hearth would be :ed from its present reproach of being a prolific smoke-pro- icer, and the Englishman could satisfy with a clear conscience s love of an open fire.

To burn gas-coke or anthracite requires a stronger draught ian is given by the slow combustion grates of the Teale type. .nthracite may, however, be burned efficiently in a properly onstructed closed stove, provided that a good draught is allowed ind that the flue is properly connected with a chimney, so that the products of combustion are all vented into the outside atmo- sphere without contaminating the air in the room. Such stoves are largely used on the Continent, and to a limited extent also in the London area. They are kept burning continuously day and night throughout the winter, and for many purposes, such as, for example, heating a library or a room where musical instruments are kept; they are clean and economical, and after being once lighted up they require but little attention.

Although gas-coke is more difficult to burn than bituminous coal in an ordinary domestic fireplace, there is no particular reason why fireplaces should not be constructed so as to over- come the difficulty. The main thing is a good draught with a deeper but narrower fuel bed than is used for bituminous coal. The chief objection to gas-coke as a domestic fuel is its greater ash content than a good house coal. Coke intended for domestic use should be manufactured from coal specially selected for its low ash content and should be broken and screened into a suitable size before delivery to the consumer.

Dr. A. Vernon Harcourt, F.R.S., recently described, in a paper before the Royal Society of Arts,[1] a type of fireplace designed and used for many years by him, which he claims as being specially adapted for the burning of coke in sitting-rooms.

The grate, which is designed to yield as much radiant heat as possible from the fuel, supports an upright wall of coke, 4 to 4½ in. from back to front, and varying in width from 8 to 24 in., according to the size of the room to be heated. The grate consists of a series of slender horizontal bars in front, and a firebrick slab underneath and at the back. There are

[1] *Journ. Roy. Soc. Arts*, LXIII. (1915), p. 570.

... par being 2 ... s ...
... ... the base to the ... ...
... ... and on this is ... ...
... ... and a layer of coke with a ... ...
... ... the target of the ... ...
... action from the top downwards ...
... ... of it the uppermost ...
... suction effect of a ... ...
... or pulled upwards as ... ...
... into operation. The ...
... an amount of fuel sufficient ...
... the fire having been lighted ... ...
... during the day.
... root features, which are ... ...
... of domestic fireplaces ...
... is vertical, so that the ...
... in many coal fires, ...
... the ceiling. Secondly ...
... that there is a ... ...
... each parts of the glow...
... combustion passes ...
... a grate underneath ...
... because the chief seat ...
... radiation, in a
... should, therefore
... Dr. Harcourt
... the grate is 18 inches,
... grate and *maintains* a
... per ton would

... coal and coke as a

... were as heavy as coke,
... conditions, *and from*
... more because it lasts

... for domestic
... through increased
... in size."
... the advan-
... are very great.

mall.
it is o...
After
domest...
unscie...
ought ...
problem...
with ste...
ance wit...
of carbon
The
smokele...
tem
co...
r

y people, unacquainted with the science of combustion, t various times had the notion that the sprinkling of coal e with a minute quantity of a solution of some mineral nce, such as common salt, will, somehow or other, give a : effect as regards heating a room. Thus, for example, on mber 4, 1915, there appeared a letter in *The Times* news- r from a correspondent, saying how he had considerably ced his domestic coal bill by the simple expedient of dis- ng a large tablespoonful of salt in somewhat less than a of water, and sprinkling this fluid from a watering-can : a hundredweight of coal spread out over the floor of the cellar, taking care that each piece of coal got some part he fluid. " I am aware," he continued, " that my scientific nds will regard the whole matter with scepticism; for they l say, no doubt rightly, that it is impossible to increase by y process of doctoring the number of thermal units which e contained in a hundredweight of a particular kind of coal. ut it seems possible that a method of doctoring which leads) more complete combustion may nevertheless be a method f saving coal, and I would also not exclude the possibility of a sychological process at work."

It is perhaps an index of the lamentable ignorance which prevails in this country with regard to the elementary principles of chemical science that the real efficacy of such a procedure should nowadays be seriously entertained. The results of scientific investigations certainly afford no ground for the belief that the mere sprinkling of a large quantity of coal or coke with so minute a proportion of a solution of a mineral salt will in any way materially increase its heating effect, although, of course, the wetting of a fire does tend to increase its life, without, however, adding either to the total amount of heat developed by the combustion of a pound of the fuel, or that proportion of it which is radiated into the room.

In regard to the general question raised in the letter referred to, it may be noted incidentally that Dr. Harcourt has recorded the results of some experiments which he made with his fire to test whether sprinkling the fuel with a small quantity of a solution of a powder, mainly composed of common salt, would give a better or more economical effect as regards heating a room.

A heaped teaspoonful of the powder was stirred up in a pint and three scuttlesful of coal were sprinkled with the

resulting heat. He was, however, unable to find that a
... resulted in any material difference in the ...
... the ... Any difference there was seemed to be ...
... the ... He then proceeded with the ...
... type of instrument, called a "radio-...
... and constructed for measuring the relative amount ...
... received from the fire, to carry out a number of ...
... the radiation from coal and from coke when ...
... water and ... sprinkled with a minute ...
... The results showed no material difference ...
... from the untreated or treated fuel, ...
... from those which had been *soaked* in water
was ... if that derived from the same ...
... He therefore concluded that coke, ...
... such fuel, radiates practically the same
... a result which will hardly surprise any per-
... informed about the science of combustion.

GAS FIRES

The ... for ... purposes is now so well established
in the ... of all types of houses throughout the Kingdom
that it hardly needs more than a passing reference. Its popu-
larity is ... due in the first place to its being ever ready
for operation at a moment ; next with a minimum expenditure
of time and ... next, to the ease with which the heat may be
regulated ... as to suit the work in hand ; and finally, to *its*
cleanliness, convenience and general efficiency. These advan-
tages have combined to secure for it an assured position in our
domestic economy.

Until recent years, however, the use of gas fires for living
apartments was viewed askance by perhaps the majority of
British people, as being not only unhealthy but also generally
unpleasant. And it must be admitted that the crude gas fire
of even ten years ago left much to be desired on both these counts.
The attitude of most people at that time towards the gas fire
was once aptly described by an old lady who said she could
always "smell one being lighted in the next street." The
medical profession in general was also prejudiced against the
use of gas in living apartments, on grounds which scientific
investigation has proved to be illusory, at least so far as any
modern types of such fires are concerned.

typical gas fire of to-day consists essentially of a series ospheric burner nozzles, varying usually between seven teen in number, according to the size of the apartment heated, arranged equidistantly along a common horizontal pipe, provided with suitable means for properly adjusting lative gas and primary air supplies so as to ensure a vertical of non-luminous and, as nearly as possible, silent bunsen s of uniform height and character. Above each flame is a hollow fireclay columnal "radiant," perforated in a ner expressly contrived to promote uniform heating of the mn throughout, and with each flame rising into the cavity s particular radiant. Care is taken to prevent any impinge- it of the inner cone of the flame upon its radiant. The back the fire is formed by a fireclay slab fixed vertically behind radiants, which are held in position by means of one slight rizontal iron rod. At a suitable distance above the top of e radiants is fixed a metallic hood or "canopy," by means of iich the products of combustion are collected and discharged rough the flue vent into the chimney, without contaminating ie atmosphere of the apartment. This arrangement of burners, adiants, canopy, and the flue vent is suitably enamelled dull lack. Needless to say the flue vent of the fire should not only e ample in area but should also be properly connected with a good chimney, which is as necessary to a gas as to a coal fire. The fire should be either built into an existing chimney breast, or, if placed in front of it, the chimney breast should be closed in except for an opening just large enough to allow of the passage through it of the flue pipe of the fire, and such further openings as may be required to allow of the necessary ventilation of the apartment as hereinafter mentioned.

It cannot be too often insisted that, whereas with a flue vent of sufficiently large area and a good chimney draught, a properly constructed gas fire will in addition to warming, also satis- factorily ventilate a room, everything depends on the draught, and above all, upon the absence of down-draught. For the mere substitution of a gas for a coal fire will not of itself cure a down-draught, as some people seem to think, unless the gas fire be installed in a scientific manner with due regard to all the circumstances.

The energy developed by combustion in a gas fire is dissipated in one or other of three ways, namely :—(1) a considerable pro- portion is directly radiated into the apartment; (2) another part

is carried off as "sensible heat" by "conduction" through the metal casing and fittings, whence it is imparted to currents of air which come into contact with them, thus creating "convection" currents in the room; whilst (3) the remainder is carried off up the flue in the heated products of combustion *plus* the excess air which the fire vents with them up the chimney.

Of these three portions, (1) passes instantaneously in straight lines through the air of the room, without sensibly heating it, until it strikes some surface, such as the walls or furniture of the apartment, or the body of some occupant, which will partly or wholly absorb and convert it into sensible molecular heat, which latter is eventually imparted as "convected heat" by such objects to the air of the room coming in contact with them; (2) goes to heating directly the air of the room; whilst (3) is the only part which is ultimately lost, although it indirectly does useful service in ventilating the room. The object of a properly designed gas fire should be to secure the maxima of radiant and ventilating effects with a minimum of "flue heat," and there is no doubt that the greatly improved types of fires which several of the leading makers have put on the market within recent years do achieve successful results in this direction.

The first scientific investigation of the heat balance of a gas fire was made, under the author's general supervision, at the University of Leeds on behalf of a Committee appointed in 1907 by the University in conjunction with the Institution of Gas Engineers. The experimental methods employed are described in detail in their first Report which was published in 1909.[1]

In investigating such a heat balance, it is usual to determine the aforementioned parts (1) and (3), that is to say the "radiant efficiency" and the "flue heat," by direct measurement, leaving (2), that is to say the percentage of "convected heat," to be estimated by difference. In the Leeds investigation, the method adopted for determining the "radiant efficiency" consisted essentially in firstly establishing, by thermopile readings, a relation between the intensity of the radiation at a central equatorial area in a hemisphere in front of the fire and the total radiation received over the whole hemisphere (a relation which is sometimes called the "distribution factor" of the fire), and then in determining, by means of a radiometer of the water calorimeter type, designed by Professor R. H. Smith, the actual number of calories radiated by the fire per hour on to the said

---

[1] *Trans. Inst. of Gas Engineers*, 1909, pp. 59 to 101.

ntral equatorial area. The number of such calories multiplied the "distribution factor" of the fire gives a measure of the tal energy radiated by the fire per hour in terms of calories, d the relation of this to the total *net* heat developed by the mbustion of the gas in the fire per hour gives the radiant ficiency of the fire.

The Leeds Investigation.—In the Leeds experiments a gas fire, hich may be taken as representative of those ordinarily supplied t the time (1907–9) to consumers by the leading makers, was ested in a specially constructed double-walled chamber in such a manner that the amount of air carried up the flue along with the hot products of combustion could be controlled within wide limits by means of a small electrically-driven fan, which fitted exactly into the outer end of the flue. The dimensions of the experimental chamber were 9 ft. × 9 ft. × 9 ft., and its internal capacity, after allowing for the various instruments installed therein, was 710 cub. ft. It was built of tongued and grooved boards within one of the rooms of a building adjacent to the Fuel Department of the University of Leeds, and it was made as nearly air-tight as possible by lining the inside walls, floor and ceiling with calico coated with asbestos paint, whilst the outside walls were coated with pitch. The fire had seven bunsen burners, all connected with the same gas and air supplies, which were adjustable; combustion took place within seven fireclay "radiants," along the top of which several other pieces of similar material were arranged. The back of the fire was formed of a thick firebrick slab, and the products of combustion passed away by means of a hole (4¼ × 1⅜ in.) into a copper flue (6 × 4 in.) which was well lagged by means of asbestos. The incandescent front of the fire measured 9 × 9 in.

The average gas consumption of the fire was 17 cub. ft. per hour, measured *dry* at 0° C. and 760 m.m., whose net calorific value was about 570 B.Th.Us. per cub. ft. The air supply to the burner was so arranged that, after getting a distinct inner cone, it was adjusted until a slightly hazy inner cone was obtained. The flame was then of such a size and shape that the outer cone, where combustion was being completed, very slightly impinged on the fireclay.

In the following experiments (Table LV), which are quoted as typical of the rest, the fire was so fixed that its centre was horizontally opposite that of the radiometer; in Nos. 16 and 17, the fan was not working, so that the draught conditions were

quite normal, whereas in Nos. 13 and 14, with the fan on, a considerable volume of surplus air was drawn up the flue.

TABLE LV

LEEDS EXPERIMENTS ON GAS FIRES (1907–1909)

Experiment No.	Gas Consumption Cub. Ft. per Hour at o° C and 760 m.m.	Net Cal. Value of Gas, B.Th.Us. per Cub. Ft. at o° C and 760 m.m.	Percentage of Net Heat of Combustion.			Cub. Ft. of Air passing up Flue per Hour at o° C. and 760 m.m.	Temperature of Flue Products ° C.	Carbon Di-oxide. Parts per 10,000.	
			(1) Radiated	(2) Convected	(3) Carried Off up the Flue			In Room.	Out-side.
13	17·62	546·4	35·30	19·57	45·13	2100	85·0	3·62	3·55
14	17·90	585·3	31·10	31·20	37·20	1760	89·5	3·70	3·54
16	18·10	565·3	27·37	51·21	21·42	494	132·2	6·0	3·20
17	17·34	562·2	30·60	50·63	18·77	538	128·0	5·7	3·30

The principal conclusions which may be drawn from the investigation may be summarised as follows :—

(1) That the total radiation from an open gas fire of that date averaged as nearly as possible one-third of the total net heat of the combustion of the gas burnt, and that it was unaffected by the amount of ventilation through the room.

(2) That the amount of surplus air vented up the flue pipe under normal conditions of draught was comparatively small. It is generally considered that the air of a room should be changed not less than three times per hour, and when this degree of ventilation was reached with the aid of the fan in Experiment 13, not less than 45 per cent. of the heat was carried away up the flue and about 20 per cent. of it only was imparted to the room as " convected " heat.   The total energy utilised in this Experiment was 55 per cent. of the *net* heat of combustion of the gas.

(3) That the proportion of the flue heat increased and that of the " convected " heat decreased with the ventilating effect of the fire.

(4) That the combustion of the gas to carbon dioxide and steam was substantially complete in all experiments, and that no trace of noxious products escaped into the atmosphere of the room heated.   Also that (as in Experiments 13 and 14) the amounts of carbon dioxide and steam added to the atmosphere

of the room were practically negligible, as the following figures **show** :—

Experi-ment.	Cub. Ft. Surplus Air per Hour.	Parts CO_2 per 10,000 Air		Grains of H_2O per Cub. Ft. Air.	
		Outside Room.	Inside Room.	Outside Room.	Inside Room.
13	2100	3·55	3·62	3·4	4·3
14	1760	3·54	3·70	2·7	4·1

RECENT DEVELOPMENTS IN GAS FIRES

Thanks mainly to the stimulus imparted by the Leeds investi-gation, all the leading manufacturers of gas fires have within recent years set up scientific departments in their own works, with the result that further great improvements have been made both in regard to the radiant efficiencies and the ventilating capacities of the fires. These improvements were admirably summarised by Mr. H. James Yates, whose well-known pioneering work in this direction has been responsible for many of them, in papers which he read at the British Association Meetings (Chemical Section) in 1913 and 1915.[1] In conjunction with Professor H. L. Callendar and the author he also worked out a new Bolometric Method of determining the Efficiencies of Radi-ating Bodies (now known as the B-C-Y Method) which is much more rapid and accurate than the Leeds Radiometric-cum-Thermopile Method.[2]

TESTS AT THE IMPERIAL COLLEGE OF SCIENCE AND TECHNOLOGY, LONDON, ON RADIATING EFFICIENCY OF A MODERN FIRE

In December 1914, Bone, Callendar and Yates applied their bolometric method to the determination of the radiant ency of a 10-inch gas fire working on London coal gas, of e net calorific value 521·5 B.Th.Us. per cub. ft. at 760 m.m , in a laboratory at the Imperial College of Technology, 38 ft. × 32½ ft. × 15 ft. high, the d between 14° and 17° C. during the

1913 (Birmingham), p. 435, and 1915

v, (A) XCI. (1915).

various tests. The average gas (dry) consumption was 24·25 cub. ft. per hour at 0° C. and 760 m.m., which was supplied at a constant pressure. The results of ten separate tests made on seven different days (see Table below) showed an average radiant efficiency of 45 per cent., reckoned on the *net* heat of combustion of the gas burnt, which was a very marked advance upon the performance of the gas fire as it existed at the time of the Leeds investigation.

TABLE LVI

Date.	Barometer m.m.	Dry Gas Consumption Cub. Ft. per Hour at 0° C. and 760 m.m.	Net. Cal. Value of Dry Gas B.Th.Us. per Cub. Ft. at 0° C. and 760 m.m.	Radiant Efficiency per cent.
Dec. 9 . .	750·3	24·00	523·8	44·8
,, 10 . .	752·5	24·49	519·9	45·0
,, 11 . .	746·1	24·25	518·2	43·2
,, 14 . .	732·7	23·78	516·6	46·0
,, 16 . .	748·4	24·19	523·0	46·6
,, 17 . .	761·1	24·77	525·0	44·6
,, 17 . .	764·7	24·49	525·0	44·6
,, 17 . .	763·2	24·51	522·6	45·5
,, 17 . .	763·2	24·26	522·6	45·5
,, 18 . .	751·4	23·82	518·2	44·0
				Mean = 45·0.

Mr. Yates's Work on the Problem of Ventilation.—As Mr. Yates correctly pointed out in his British Association paper in 1913 (*loc. cit.*), " the problem of total heating efficiency is however not the only one which makers of gas fires have to solve ; the equally important question of ventilating effect must be considered, for a properly constructed gas fire should effectively ventilate as well as heat an apartment."

It is not sufficient that a fire, when connected with a chimney flue in the ordinary way, should merely allow no products of combustion to escape into the room, an elementary hygienic condition which must in any case be fulfilled, but it ought to produce a ventilating effect comparable with that of a coal fire. It is not difficult to design and proportion the flue vent and the canopy of a gas fire to ensure the drawing up the flue of a large volume of air in excess of that required for combustion, thus producing good ventilation. The real difficulty has been to

avoid drawing this excess of air over the upper portion of the radiants, thus cooling them, and unnecessarily diminishing the radiant efficiency and correspondingly increasing the " flue heat." A scientifically constructed gas fire ought to ensure good " ventilation " without sacrificing radiant efficiency.

Mr. Yates's investigations have shown that the last-named condition can be fulfilled provided (1) that the area of the flue vent behind the fire is large enough; and (2) that an adequate vertical distance between the top of the radiants and the bottom of the canopy of the fire is preserved. Applying the Leeds Method to a series of gas fires of different sizes, so constructed as to fulfil these conditions, he obtained the following interesting series of results, the fire in each case being properly connected with a chimney 30 ft. high :—

TABLE LVII

Mr. H. James Yates's Tests upon Gas Fires (1913)

Width of Fire. Inches.	Dry Gas Consumption Cub. Ft. at 0° C. and 760 m.m. per Hour.	Cal. Value of Dry Gas B.Th.U. per Cub. Ft. at 0° C. and 760 m.m.	Per cent. CO_2 in Flue Products.	Temp. of Flue Products ° C.	Percentage of *Net* Heat.		
					Radiated.	Con-vected.	In Flue Products.
10	25·24	568·5	0·90	117°	47·8	21·4	30·8
14	34·02	577·5	0·80	104°	50·3	19·0	30·7
17	42·62	568·2	0·93	109°	49·2	21·4	29·4
21	52·90	574·5	0·77	101°	51·0	22·6	26·4

In his second paper (*loc. cit.*) Mr. Yates described a newly designed gas fire which, when properly connected with an ordinary chimney, not only removed at least twice as much air from a room (11,800 cub. ft. per hour as compared with 4500 to 5000 cub. ft.) as did the previous best types for the same gas consumption and radiant efficiency, but approached the ventilating capacity of an ordinary open coal fire as closely as is necessary for the maintenance of a perfectly fresh atmosphere in the apartment heated. Briefly described, the new contrivance provides two outlets to the chimney so designed and proportioned that by the under outlet the entire combustion products are carried

off, whilst by the upper or " ventilating " outlet a large volume of excess air (the amount of which may be controlled by a simple device) is also removed.

Other Improvements.—In addition to the aforesaid great improvements which have been effected in regard to the radiating efficiencies and ventilating effects of gas fires since the days of the Leeds investigation, manufacturers have devoted a good deal more attention than formerly to the construction of the burner arrangements with a view to obtaining a perfectly silent combustion of the gas, and so suppressing the unpleasant " burring " noise which the older type of fires always made. The combined result of these investigations in which the scientific staffs employed by the various manufacturers have participated, has been the evolution of gas fires which, besides having a high radiant efficiency, are both thoroughly hygienic and practically silent in their combustion, and from these points of view they may be unreservedly commended.

CHAPTER XIII

THE SMOKE NUISANCE AND ITS ABATEMENT

THE EVILS OF SMOKE

NEXT to the waste of valuable by-products, otherwise recoverable, the most serious evil attendant upon the use of raw bituminous coal as a fuel is the pollution of the atmosphere with the smoke which daily issues from our factories and domestic chimneys.

This evil, which is ever present in our large centres of population, not only deprives us of much beauty of form and colour that we might enjoy both in Nature and in Art, but spells death or disease to thousands of our fellow-men. Some years ago it was estimated that the material loss and damage due to smoke in London amounts to £4,000,000 annually, whilst, according to the Chairman of the Air-Pollution Board appointed by the Manchester Corporation in 1912, the measurable damage done in Manchester and Salford by smoke amounts to nearly £1,000,000 per annum, in addition to the immeasurable evil effects of smoke and fog upon public health.[1] Also, it must be remembered that, besides the direct damage to buildings and public health, the smoke cloud which hangs over our large industrial areas greatly reduces the amount of available sunlight, at times by as much as 50 per cent., and that the baneful effects of such reduction upon vegetation and human health, especially that of children, are very serious. Thus in the course of an investigation carried out by Dr. G. H. Bailey and others at the Owens College, Manchester, during the years 1888–90, at the instance of the Manchester Field Naturalists Society, it was found that throughout a continuous period of twelve months the inhabitants of the Hulme district, a typical artizan area within the city, received only 50 per cent. of the

---

[1] *Report of Discussion upon Smoke Abatement and Air Pollution at the British Association* (Manchester), 1915. *B.A. Reports*, 1915, p. 387; also *Report of the Sanitary Committee of the City of Manchester on Air Pollution*, April 1915.

actinic rays of sunlight which fell on the more favoured dwellers in the suburban district of Didsbury some four miles away Also, that during three days of a dense winter fog no less than 0·75 ton of soot and 1·5 cwt. of sulphuric acid fell on every square mile within the industrial area of Manchester.

According to subsequent experiments carried out in Leeds by Professor J. B. Cohen and Mr. A. G. Ruston in 1907, no less than 450 tons of soot fall per square mile per annum in the in dustrial area of Hunslet, whilst over another city area of 16 square miles the amount averages 220 tons per square mile per annum, it was estimated that the pall of smoke which continually hangs over Leeds absorbs as much as 40 per cent. of the total daylight during the year.

Mr. A. G. Ruston of Leeds University reported to the British Association in 1915 (*loc. cit.*) that, in regard to the damage done to vegetation in the Leeds area, not only do plants suffer from this general reduction of sunlight, but the black deposit upon the leaves still further hinders the sunlight from getting into contact with the green colouring matter of the leaf, while the acids present in the smoke damage its structure and hasten its fall. Damage is also done to the roots of plants, especially those possessing few root-hairs or fibrous roots. Moreover, the acid rain falling on the soil limits the activity of the bacteria, and especially of the most useful nitrifying organisms in it. It has also recently been found that the enzymes or ferments which are mainly responsible for the chemical changes taking place in the plant are inhibited by smoke pollution. This causes a distinct cutting down of the intensity of colour in the plants, and also handicaps them in forming any reserves, either in the form of bulbs or seed, and considerably reduces the germination capacity and energy of seeds, thus generally lowering the vitality of plants and preventing them from putting up a fight against adverse conditions.

PARLIAMENTARY ENQUIRIES AND LEGISLATION

The baneful effects of smoke in cities has ever since the use of raw coal as a domes Thus we find the citizens of London as long Parliament against the importation of because of the smoke nuisance created by the petition failed, it is said that some tin

clamation was issued forbidding the burning of coal whilst Parliament was sitting.[1]

At various times during the nineteenth century Select Committees of the House of Commons were appointed to enquire into the smoke nuisance with a view to legislative enactments for its abatement. The first of these reported in 1819, but apparently nothing in the way of legislation resulted from its labours. The question remained in this unsatisfactory state until 1843, when a second Committee took it in hand again and reported that, while the time was ripe for the enactment in the public interest of a law requiring the owners of stationary steam engines to abate " the issue of opaque smoke " from their chimneys, it was undesirable to include metallurgical furnaces in the suggested Bill.

The publication of this second Report led the Government of that day to appoint Sir Thomas de la Beche and Dr. Lyon Playfair to investigate the matter from a scientific standpoint. But even their recommendation (1846) of the imposition of a fine " when the emission of smoke is due to the carelessness of those entrusted with the management of the furnaces " led to no more effective action beyond the sanction in several Local Improvement Bills of Clauses dealing with smoke abatement.

In 1855 another detailed Report was made to the Government, this time by the General Board of Health, which included, in addition to much sound advice, the opinion " that notwithstanding the great and obvious advantage of perfecting the combustion of fuel, and the certainty that the cost of doing so will be amply repaid by the saving effected, such is the indisposition of practical men to depart from the beaten track, that nothing but the force of law is likely to ensure the care and attention necessary to protect the public from a grievous nuisance, the manufacturers themselves from heavy unnecessary expense, and the national resources from grievous waste of fuel to the amount of millions a year."

So ingrained and persistent, however, was the *laisser-faire* attitude of the Governments of those days in regard to legislative interference with industry, even when the clearest case had been established for such action in the public interest, that it was not

---

[1] See *Smoke Abatement*, by William Nicholson, Chief Smoke Inspector to the Sheffield Corporation (Griffin & Co., 1905), p. 18, a manual which admirably summarises the history of legislation in this and other countries against the smoke nuisance, and to which the reader is referred for further details than can be given in this chapter.

R 241

until the passing of the Public Health Act in 1875 that any special law was enacted to enforce some mitigation of the more flagrant aspects of the smoke nuisance. Sections 91 to 108 inclusive of that Act made the emission of black smoke from any chimney (not being the chimney of a private dwelling-house) " in such quantity as to be a nuisance " one of the nuisances " liable to be dealt with summarily in manner provided by this Act," and so far as general legislation is concerned, this is the only Act of Parliament under which fines for the emission of smoke can be levied. Some of the larger municipalities,[1] however, have got special provisions in their local Acts and Bye-laws for the abatement of the smoke nuisance, but it is to be feared that public opinion on the subject has been, in most cases, so apathetic that the powers thus conferred are too sparingly and haltingly used. In 1914 the Local Government Board appointed a Departmental Committee to review the whole question of Smoke Abatement in the light of recent research, but, unfortunately, its meetings were suspended soon after the outbreak of the war.

RECENT INVESTIGATIONS BY PUBLIC BODIES

The recent appointment (1912) by the Corporation of Manchester of an Air-Pollution Board composed of public men, manufacturers, and scientific experts, to investigate with the object of propaganda and research instead of the older method of prosecutions may be welcomed as a sign that in the near future public bodies will take up the matter anew on better lines. ·

The Manchester Board has set itself to tackle the question of the reduction of domestic smoke by laboratory research in the belief that much remains to be done in the direction of improvements in coal and coke fires, gas fires, and by developing the use of semi-coked coal. As regards factory smoke, the view taken by the Board is that the chief problems are the design of mechanical stokers and the supply of air at the correct point to ensure smokeless combustion, and that they can only be solved by large-scale experiments carried out either by, or in conjunction with, manufacturers.

The Health Committee of the City of Sheffield has, in conjunction with the University, recently (1914-15) undertaken

---

[1] E. g. London (1891), Edinburgh (1879 and 1892), Glasgow (1892), Manchester (1882), Salford (1862), Leeds (1866), Sheffield (1900), and Bolton (1872).

xperimental work extending over twelve months, on the distri-
bution of smoke in various areas within the city (manufacturing
and residential), the result of which has indicated that the amount
of pollution in the Attercliffe industrial area in the east end of
the city, where the armament works are situated, is roughly
about twice as great as in three other areas situated, respectively,
N.N.W., W. and S. of the centre of the city. It is also stated
by Professor W. P. Wynne, who directed the work, that if an
opinion as to the contribution of house fires to the pollution of
the atmosphere may be based on the proportion of tar and
ammonia collected by the rain, no difference could be traced
between the values for the summer and the winter six months.

Mention should also be made of the work of the Coal Smoke
Abatement Society formed in London in the year 1898, which
mainly deals with the matter as it affects the Metropolis. There
is good reason for the belief that in recent years black fogs have
been decidedly less prevalent in London than formerly, a circum-
stance which is probably partly due to improved domestic fire-
grates, and partly also to the growing and now very considerable
use of gas fires in the residential areas.

The Nature and Composition of Smoke

In order that the reader may rightly understand something of
the relative harmfulness of domestic and factory smoke, respec-
tively, as contributory factors to the general smoke nuisance,
about which diverse opinions have been expressed, it is necessary
to discuss the nature and composition of each, as revealed by
recent chemical investigation.

Speaking generally, coal smoke consists essentially of carbon,
tarry hydrocarbons, ammonium salts, and mineral matter (ash),
and it frequently has an acid character. But the soot deposited
in, or emitted by, chimneys varies considerably in character and
composition, according to the circumstances under which the
al is burnt, and the height of the chimney stack, and, in the
of boilers, the distance of the latter from the furnace.

smoke-producing constituents of coal are chiefly those
decompose at comparatively low temperatures, and black
which is always a sign of incomplete combustion, is pro-
the destructive distillation of the more volatile portions
substance. The direct heat loss occasioned by smoke,
due to the unburnt gases associated with it, is

usually not so considerable as is sometimes thought, and with good coals and careful firing need not exceed 5 per cent., but with soft coal and under bad conditions, it sometimes amounts to over 10 and even as much as 20 per cent. of the total heat of combustion of the coal (*vide* Tables XLVIII and L in Chapter XI).

We are indebted to the researches of Professor J. B. Cohen and Mr. A. G. Ruston of the University of Leeds for perhaps the most complete chemical examination yet published of the soot produced from a typical British bituminous coal when burnt under different conditions.[1]

The following analyses, taken from their papers, show very clearly how the composition of the soot from a given coal varies not only according to whether it is burnt in an ordinary domestic grate or at the higher temperature of a boiler furnace caused by the stronger draught of a chimney 110 ft. high, but also, in the latter case, according to the distance up the chimney :—

TABLE LVIII

ANALYSES OF SOOT

	Coal.	Domestic Soot.	Soot from a Boiler Chimney.		
			At Base.	70 ft. up.	Top 110 ft.
Carbon . .	69·30	40·50	16·66	21·80	27·00
Hydrogen .	4·89	4·37	0·86	1·44	1·68
Nitrogen [2] .	1·39	4·09	nil	1·18	1·21
Sulphur . .	1·74	2·99	2·07	2·58	2·84
Chlorine . .	0·27	5·19	0·11	1·46	1·60
Tar . . .	1·64	25·91	0·09	0·80	1·66
Ash . . .	8·48	18·16	75·04	66·04	61·80
Acidity . .	0·00	0·37	1·33	0·58	0·56

The chief points to be observed in regard to these analyses are, first of all, the marked difference between the composition of domestic and factory soot, and secondly, the variations in the latter as the chimney is ascended. The domestic soot contained about twice as much carbon, twenty times as much tar, nearly four times as much nitrogen (ammonium) compounds, but only a fourth of the ash, found in the boiler soot, whilst in the case of

---

[1] *Nature*, Oct. 14, 1909; *Journal of Gas Lighting*, Nov. 30, 1909; and *Journ. Soc. Chem. Ind.*, 1911, p. 1360; also their book on *Smoke and Town Air* (Ed. Arnold, London).

[2] The nitrogen in soot is chiefly in the form of ammonium chloride and sulphate.

the latter, the carbon and nitrogen contents increased, and the proportion of ash diminished, as the chimney was ascended. All this points to the coal having been less completely burnt in the domestic grate, whilst in the presumably hotter boiler chimney there was less opportunity for the more volatile constituents of the smoke to condense. The stronger draught of the boiler chimney caused more of the ashes of the coal to be carried over mechanically with the smoke, and the heavier mineral matter was deposited sooner in the flues than the lighter carbon. The composition of " domestic " soot from a given coal is also liable to considerable variation, according as to whether it is burnt in an ordinary open sitting-room grate, or at the higher temperature and in the increased draught of a kitchen range, as the following analyses indicate :—

TABLE LIX

PERCENTAGE COMPOSITION OF SOOT FROM A COAL BURNT IN
DOMESTIC FIRES

	Coal.	Soot from Kitchen Chimney.	Soot from Dining-room Chimney.		
			5 ft. up.	20 ft. up.	35 ft. up.
Carbon . .	76·80	52·3	36·5	34·1	37·2
Hydrogen .	4·90	3·7	3·5	3·5	3·5
Nitrogen . .	1·72	4·11	6·89	6·04	5·05
Sulphur . .	0·79	2·20	2·18	2·56	2·45
Chlorine . .	0·25	1·35	9·07	6·41	4·96
Tar . . .	0·88	12·5	34·9	37·2	40·4
Ash . . .	1·80	17·8	5·09	4·97	4·94
Acidity . .	0·00	0·28	0·92	0·55	0·92

With regard to the total amount of " domestic " soot produced, Cohen and Ruston, on the basis of analyses made by the late Sir W. Roberts-Austen for the London Smoke Abatement Exhibition in 1884, estimate it as equivalent to a loss of not less than 6·0 per cent. of the carbon of the coal burnt in domestic fireplaces throughout the Kingdom. This on an annual domestic consumption of 36 million tons would be equivalent to nearly 2 million tons of carbon per annum, and assuming domestic soot to contain on an average 60 per cent. of carbon (in the free state and as tar), the total weight of domestic soot produced would be about 3·3 million tons annually.

With regard to " factory " soot, the percentage loss of carbon

of the coal burnt is probably very much smaller than in the "domestic" case. According to Scheurer-Kestner's researches, the fuel loss due to the production of soot from boiler furnaces never exceeds 1 per cent. of the carbon burnt, but in Constam and Schläpfer's more recent Zürich trials (see Chapter XI., Table L), the loss of heat in "smoke" (apart from "unburnt gases") was never less than 1 per cent., and in exceptionally bad cases rose to as much as even 5 per cent. We should be inclined to put it down at about 2 per cent. with hand-fired, and at 1 per cent. for mechanically stoked boilers, with, say, an all-round average of 1·5 per cent. So that on an assumed annual "factory" consumption of 100 million tons, the heat loss due to "smoke," apart from "unburnt gases" might be estimated as equivalent to 1·5 million tons of coal per annum. Now, seeing that factory soot probably contains on an average about 25 per cent. of carbon, the total weight of soot and smoke produced in factory chimneys throughout the Kingdom may be put down as approximately 6 million tons per annum.

From such data it seems reasonable to suppose that the total weight of "factory" smoke and soot produced from the coal burnt in the Kingdom is about twice as great as the corresponding amount of "domestic" smoke and soot, although there is probably no great difference between the corresponding fuel or heat losses. But in comparing the relative damage done by the two kinds of smoke it must be remembered (1) that, on account of its very much greater tarry content, "domestic" soot will adhere much more tenaciously to anything on which it falls, and will therefore not be nearly so easily removed by wind and rain as "factory" soot; and (2) that the proportionate effect of domestic smoke is presumably much greater in the winter than in the summer. Consequently, weight for weight, domestic smoke is undoubtedly the more pernicious of the two in regard to its direct effects upon human and vegetable life and health, and in densely populated city or industrial areas the combined effects of the two must be very disastrous.

Messrs. Cohen and Ruston have reported that the average deposit of soot over the whole of Leeds amounts to at least 220 tons per square mile per annum; some idea of how this varies as between the different industrial and residential areas in the city may be gained from the following estimation of the average deposits of tar in each of six representative areas during two quarterly periods in 1910.

TABLE LX

District.	Deposit of Tar in Milligrams per Square Foot.		Deposit of Tar per Annum in Cwts. per Square Mile.
	March to June.	June to September.	
1. Hunslet	52·6	46·5	110
2. Kirkstall	26·2	31·1	64
3. Philosophical Hall . .	26·4	30·4	68
4. Headingley	11·3	17·2	27
5. Observatory . . .	15·4	9·0	32
6. Roundhay	2·0	2·1	4·5

By far the most polluted part of Leeds was Hunslet, a big industrial area to the south of the city, thickly populated with the artisan classes; next to that, but only half as bad, came Kirkstall, a residential district in a valley to the W.N.W. containing a well-known iron works and other industrial establishments. Probably, however, the unfavourable conditions apparently prevailing here are partly due to the effects of smoke which drifts up the valley from the other industrial districts in the S. and S.E. of Leeds. The Philosophical Hall is situated in the main commercial and shopping area in almost the centre of the city. Headingley is a residential suburb situated on a high ridge some 3 miles to the N.W. of the centre of the city, whilst the Observatory lies on Woodhouse Moor, a large open space about midway between the Philosophical Hall and Headingley. The district of Roundhay is a purely residential area with a fine park, situated on high open land, 450 ft. above sea level, 3½ miles to the N.E. of the centre of the city. The prevailing N.W. winds here blow straight from the Yorkshire hills and moorlands, and the air is usually clear and bracing. The pollution here is only one twenty-fourth of that in the much lower lying Hunslet area only 4 miles south of it.

DAMAGE DONE TO VEGETATION BY SMOKE

How evil are the effects of the cloud of smoke continually hanging over such an area in limiting the growth of plants may be judged from the following table of results obtained by Cohen and Ruston in regard to (1) the relative assimilation of carbon dioxide by laurel leaves, and (2) the relative total weights of

lettuce crops grown in different areas, on the same soil and under the same general conditions except as regards atmospheric conditions :—

TABLE LXI

District.	Position in Relation to Centre of City.	Relative Assimilating Power of Laurel Leaves.	Relative Weight of Lettuce Crops.
Weetwood Lane . .	2½ miles N.	100	140
Headingley	1½ miles N.	53	120
University	1 mile N.	42	104
City Square and Park Square	Central	12	56
Hunslet	South	nil	44

SOOT AS A FERTILISER

The value of soot to the farmer depends partly upon its physical effects upon the soil and partly upon its content of ammonium salts and sulphur compounds. It is largely used as a top dressing for wheat in the early months of the year. The dead black colour of soot makes it a good absorbent of solar radiations, so that the soil which has been treated with it is kept perceptibly warmer than untreated land, whilst the ammonium compounds present in the soot are valuable fertilisers, and the sulphur compounds in it are very effective in preventing the ravages of slugs and snails. Domestic soot, which contains a very much higher proportion of ammonium salts, has a greater fertilising value than " factory " soot, whilst its higher carbon content also implies a greater heat absorbent power.

THE POSSIBLE ABOLITION OF SMOKE

Whilst improved furnaces and fireplaces, together with a better system of smoke inspection might do much to abate the present smoke nuisance, the evil thing will never be finally abolished so long as raw bituminous coal in its present form continues to be used as a fuel. Fortunately for mankind, the rapid development of Science, even with our present state of knowledge and experience, encourages the hope that the day is not far distant when serious atmospheric pollution by smoke will have become a thing of the past, and that future generations

l grow up in our cities amid much healthier and less depress-
, surroundings. The present sordid ugliness of our large
lustrial areas, largely caused as it is by the pall of smoke
iich continually hangs over them, is a standing reproach to
r national economy, and we pay an appalling price for it both
direct loss and damage and even more so in physical lowering
: vitality and depression of spirits. There are in Great Britain,
erhaps, few dangers to the health and well-being of men more
niversal, insidious, and serious than those due, directly and
ndirectly, to this widespread nuisance, and few more appealing
:alls to Science than to assist in the amelioration and abolition
of its effects.

The hope of finally ridding ourselves of the evil lies mainly in
three directions, all of which are either now quite practicable, or
will shortly become so. The first is a wider extension of the
use of gaseous fuels for heating purposes, and all investigators
who are in any way increasing the efficiency of gaseous
combustion, or facilitating the generation and application
of gas, are undoubtedly helping to slay the smoke dragon.
The second is a much wider adoption of electricity as a motive
power, a prospect which is not only within sight, but if realised
would almost revolutionise industrial England.[1] The third lies
in the direction of making and distributing some form of semi-
carbonised coal as a smokeless domestic fuel at a price which
will not exceed that of raw coal, and this is a problem whose
solution is now exercising the minds of many able investigators.
We may certainly look forward with confidence to the time when
the barbarous use of coal as a direct heating or power agent, with
its attendant smoke, will practically have ceased in all civilised
communities.

[1] See the *Report of the Coal Conservation Committee* (**Ministry of Recon-
struction**) *upon Electric Power Supply*, 1917.

CHAPTER XIV

GENERAL CONSIDERATIONS RELATING TO THE USE OF GASEOUS FUELS DERIVED FROM COAL

ALL experience has shown that the most economical way of burning any fuel is in as finely a divided state as possible, and when intimately mixed with as nearly the theoretical quantity of air as circumstances permit. The ideal conditions for efficient combustion are realised when a homogeneous mixture of some gaseous fuel with just the theoretical quantity of air required for its complete combustion is burnt in any manner easy of control, and especially (as in Surface Combustion, *q.v.*) if the combustion is accelerated by contact with an incandescent surface of a sufficiently refractory character.

The chief advantages of gaseous over other forms of fuels are, (1) that they may be generated and distributed in bulk from a given centre and supplied to the various places of consumption throughout a given area under conditions which should ensure a considerable degree of uniformity as regards quality and pressure at any particular point; (2) that they may be burnt under the ideal conditions referred to in the previous paragraph, or with such a minimum excess of air as may be considered as approximating thereto; (3) that the flow of the combustible is so amenable to control that it may instantly be varied at will, or even entirely checked, in response to the requirements of a particular heating operation; (4) that the use of gaseous fuels is, or should be, perfectly clear and smokeless; and (5) that gaseous fuels are, or may be proved to be, better adapted than others to the requirements of heat " recuperative " or " regenerative " systems, the adoption of which in large scale operations is essential to economy and the attainment of the highest temperatures.

Fortunately for civilisation, coal may be partially or completely " gasified " in a variety of ways, which, either separately or in ᵇle combination, have so far proved equal to meeting nearly

requirements of our highly developed industrial system.
nost every year brings with it some new development in
eration or application of the gaseous fuels derived from
hich adds in some way or other to their energy or service-
ss. Hence, there seems no reason to doubt but that
g as coal is available, human knowledge and ingenuity
e able to get from it the right kind of gaseous fuel
1y industrial requirement within the limits imposed by
al laws upon the efficiencies and temperatures attainable
such fuels. And even when such temperature limits have
reached, the energy of the gas may, by means of an internal
oustion engine and a dynamo, be transformed into electric
gy which, in the various forms of arc furnaces now available,
apable of developing temperatures exceeding 3000° C.

The principal gaseous fuels derived from coal are the fol-
ving :—

Coal Gas.—Coal, when partially gasified by the thermal decom-
osition of its constituents at high temperatures, yields (1) be-
veen 10,000 and 13,000 cubic feet of "coal gas" of gross
alorific value from 550 to 600 B.Th.Us. per cubic foot, (2) a
eries of valuable condensable by-products (tar, benzols, naph-
halene, etc.), (3) ammonia (as sulphate), and finally (4) a
residue of coke. Altogether some 33 million tons of coal are
now being annually carbonised in this way in the kingdom,
principally either for the sake of the gas (as in "gas works"),
or for the purpose of manufacturing hard metallurgical coke (as
in the by-product coking industry).

Water Gas and Producer Gas.—Coal or coke may be wholly
gasified in a suitable "generator," either (1) by the endothermic
interaction of steam upon the incandescent fuel, which must be
maintained in some way at a sufficiently high temperature
throughout the operation, as in the manufacture of "Water Gas,"
which may be represented by the equation—

$$C + OH_2 = CO + H_2;$$

nder the influence of a combined air and steam blast
ncandescent fuel bed, as in the manufacture of "Pro-
a low-grade fuel wh   n be very cheaply produced,
used either for t   of large industrial furnaces
e used in the   cture of glass or steel), or

for the generation of power for factories by means of internal combustion engines in a central power house.

The second method (2) is one which has several advantages from the point of view of national economy, namely (*a*) that it is applicable to a wide range of low-grade coals, with a large ash content, the utilisation of which would otherwise be very difficult; and (*b*) that, with a sufficiently large proportion of steam in the blast, it enables from two-thirds to three-quarters of the nitrogen in the fuel to be converted into and recoverable as ammonium salts (" ammonia-recovery " gas-producer practice).

Blast Furnace Gas.—In addition to the above-mentioned gaseous fuels, our iron smelting blast furnaces, which throughout the kingdom altogether use upwards of 12¼ million tons of coke per annum, produce a large amount of a low-grade " blast-furnace gas," which is nowadays used in iron and steel works for power and heating purposes. (See Chapter XIX.)

CALORIFIC VALUES OF GASES

All the various gaseous fuels obtainable from coal or coke admixture whose combustible constituents chiefly consist of one or more of the following, namely, hydrogen, methane, ethane, ethylene, propylene, benzene, and carbon monoxide, the densities and calorific values of which are as follows:—

TABLE LXII

	Formula.	Molecular Weight.	Density Air = 1·000.	Calorific Values.			
				K.C.Us. per Gram-molecule.		B.Th.Us. per Cub. Ft. at 0° C. and 760 mm.	
				Gross.	Net.	Gross.	Net.
Hydrogen . .	H_2	2·00	0·06952	68·4	57·2	343·3	287·2
Carbon Mon-oxide . .	CO	28·00	0·96716	68·0		341·4	
Methane . .	CH_4	16·00	0·5538	212·0	189·5	1064·0	951·3
Ethane . . .	C_2H_6	30·00	1·0494	370·5	336·9	1860·0	1691·0
Ethylene . .	C_2H_4	28·00	0·9683	333·3	310·9	1673·0	1561·0
Propylene . .	C_3H_6	42·00	1·36	492·7	459·1	2474·0	2305·0
Benzene . .	C_6H_6	78·00	—	799·0	745·4	—	—

Note.—The density of atmospheric nitrogen (including argon, etc.) = 0·9721, and of carbon dioxide = 1·529.

ould be pointed out that inasmuch as the density and
: value of any gaseous mixture are additive properties,
ay easily be calculated from the known value of its
e constituents, provided of course that the proportion of
the mixture has been accurately ascertained by chemical
is.

h regard to calorific values, it would appear that, since
eam formed by the combustion of a given gaseous fuel
t be condensed at all except at temperatures below
ew point of the products as a whole, the *net* figure is
er index of its probable value to a would-be consumer
the corresponding *gross* one, although naturally the
of the gas prefers to have the latter recognised as the
er criterion. But if the consumer had the option of choos-
between two gases of the same *gross* but different *net*
ic values, he would rightly prefer the one with the higher
value.

ther Factors which need to be considered.—But the question of
rific value, whilst always an important one, is by no means
only factor to be taken into account in the choice of a gaseous
l for a given purpose, and especially so in regard to large power
l furnace installations. There has been in the past perhaps
great a tendency to regard calorific value by itself as the
ramount consideration, to the exclusion of other important
ctors, such, for example, as (*a*) density, (*b*) the range of explo-
ility, and the rates of back-firing, of mixtures of a given gas
id air, (*c*) flame temperature and combustion intensity, and
) the radiative power of the flame produced. And as some
these functions depend in a high degree upon chemical com-
osition, it follows that the latter ought always to receive due
onsideration, and to ignore it altogether would be foolishness.
To deal adequately with the points just mentioned would take
up a much larger space than can be allotted to them in this
volume, and it is therefore not possible to do more than merely
indicate why they are so important.

No one who intelligently uses a gaseous fuel will be inclined
to deny the importance of the *density* factor. Also, inasmuch
as many types of burners and furnaces are designed to burn
explosive mixtures of gas and air, and seeing also that the de-
velopment of flame presupposes the formation of such explosive
mixtures, the manipulation of all appliances in which such mix-
tures are used or formed must be largely influenced

factors referred to under (*b*) in the preceding paragraph. These have been fully dealt with by the author in his Report upon Gaseous Combustion to the Sheffield Meeting of the British Association in 1910, and again in his Presidential Address to Section B at the Manchester Meeting in 1915.[1]

THE STARTING AND PROPAGATION OF FLAME THROUGH EXPLOSIVE GASEOUS MIXTURES

The phenomena associated with the starting and propagation of flame through an explosive gaseous mixture are in reality so complex that it is not always easy in any particular case to analyse all the factors involved, because they vary so much, not only with the local conditions, such as the place and mode of ignition, or the form and dimensions of the containing vessel, but also according as to whether the mixture is stagnant, or flowing, or in a state of turbulence.

Ignition.—In the first place a given explosive mixture of combustible gas and air must be brought into a certain thermal (or thermo-electrical) condition before the rate of combination of its reactive constituents is sufficient to cause the chemical change to become autogenous, *i. e.* self-propellent, a condition which must always be fulfilled before flame can appear. As soon, however, as the rate of combination becomes such that the mixture " self-heats itself," its temperature will very rapidly rise to the point at which flame appears.

The *ignition temperature* of a given explosive mixture may be defined as that degree to which it must be raised, at least locally, in order that the chemical action becomes autogenous. The real ignition point, as thus defined, is not necessarily synchronous with the actual appearance of flame; there may be, and usually is, an appreciable " *pre-flame period,*" and only in the fastest burning mixtures is this period negligible.

The experimental determination of the ignition point of an explosive mixture is by no means an easy matter, because, unless special precautions are taken to prevent it, a sufficient amount of slow combustion may take place during the preliminary heating up of the mixture to vitiate the experiment and give a blurred or irregular result. Either the preliminary heating-up period

[1] *British Association Reports* 1910, pp. 469 to 506, and 1915, p. 368.

be made negligibly short, as when the mixture is fired by
atic compression, or the combustible gas and air (or oxygen)
d be separately heated to the ignition temperature before
ing them to mix.

B. Dixon and H. F. Coward, using an apparatus constructed
to allow of the latter method being carried out, succeeded
xing the following ignition ranges for various combustible
s in air or oxygen.[1]

| | | Ignition Range °C. | |
Gas.		In Air.	In Oxygen.
[ydrogen		580–590° . .	580–590°
arbon monoxide (moist)	.	644–658° . .	637–658°
fethane		650–750° . .	556–700°
Ithane		— — . .	520–630°
Propane		— — . .	490–570°
Ethylene		542–547° . .	500–579°
Acetylene		406–440° . .	416–440°

It must not be concluded from the above that the ignition
mperature of a given explosive mixture is not a really well-
efined point, for when a mixture like electrolytic gas is fired by
diabatic compression it ignites at 526° C. quite sharply.   But
n ordinary circumstances when a jet of gas issues into an atmo-
phere of air, or when flowing streams of gas and air intermingle,
nixing does not occur regularly, and an appreciable amount of
combination may occur before the most explosive mixture is
locally formed.   Hence it is not surprising that in Dixon and
Coward's experiments an ignition *range*, rather than an ignition
point, was observed.   Their results, however, give a fair idea
as to the degree of temperature requisite to ignite the commoner
combustible gases.   Hydrogen can be ignited both in air and
oxygen at an appreciably lower temperature than carbon mon-
oxide, and in the paraffin series of hydrocarbons the ease of
ignition increases with the mass of the molecule.   Again, of the
three hydrocarbons whose molecules contain two carbon atoms,
ethylene ignites somewhat more readily than ethane, and
acetylene the most readily of all.   In the case of all the hydro-
carbons examined (except acetylene) the ignition range was
appreciably lower in oxygen than in air.

Flame has been well defined as *glowing gas*, and, so far as

[1] *Journ. Chem. Soc.*, 1909 95, p. 514.

terrestrial conditions are concerned, the existing cause is chemical change (Smithells). The mechanism of the chemical phenomena associated with it is exceedingly complicated and need not be discussed here; it will be sufficient if we discuss some of its more important physical features.

LIMITS OF INFLAMMABILITY AND RATES OF FLAME PROPAGATION

Mallard and Le Chatelier, in their well-known researches upon gaseous explosions, discovered, as long ago as 1880,[1] that the propagation of flame when a given explosive mixture is ignited in a horizontal tube differs according to whether ignition occurs near the *open* or *closed* end of it. In the first case the flame was observed to travel for some distance down the tube at a uniform slow velocity, corresponding to what Mallard and Le Chatelier regarded as the true rate of propagation " by conduction." This period of uniform movement (" inflammation ") was succeeded by an irregular oscillating period, the flame swinging backwards and forwards with increasing amplitudes, and finally either dying out altogether or giving rise to a third phase of greatly accelerated combustion (in some cases even " detonation "). When, however, such mixtures were ignited near the *closed* end of the tube, the forward movement of the flame was continuously (although not uniformly) accelerated, under the influence of reflected compression waves, until an intense condition of violent explosion was set up.

According to the recent investigations of Dr. R. V. Wheeler and his co-workers at the Home Office Experimental Station, Eskmeals, and particularly those upon mixtures of methane and air, it would appear that Mallard and Le Chatelier's interpretation of the " initial uniform movement " of the flame as a propagation from layer to layer by conduction only, needs some revision. If such a thing as propagation exclusively " by conduction " ever occurs, it would appear to be a limited phenomenon, obtainable only in tubes whose diameter whilst wide enough to prevent appreciable cooling of the flame, is sufficiently narrow to suppress the influence of convection currents. Moreover, ignition must be either just at, or within one or two centimetres of, the open end of the tube, or otherwise, and particularly with the more rapidly moving flame, vibrations may be set up from the beginning.

[1] *Annales des Mines*, 8ᵉ Sec., Vol. IV.

ures of methane and air have been more extensively
than others in this connection, because of their importance
tion to the safety of coal mines; a brief statement as to
behaviour will perhaps suffice to illustrate the chief points
ich attention need be drawn.

ording to Wheeler the *limits of inflammability* for *horizontal*
igation of flame in methane-air mixtures, at atmospheric
erature and pressure, correspond to 5·4 and 14·3 per cent.
ane contents, respectively. These limits are somewhat
cent for *upward* or *downward* propagation, owing either to
helpful or impeding influence of convection currents. The
ts for mixtures of other combustible gases with air are also
ply defined, and are also similarly affected by the direction
lame propagation. Each combustible gas has a well-defined
ge of *inflammability* when mixed with air, which range varies
ording to the nature of the gas, and presumably also to the
nperature and pressure. Thus for hydrogen-air mixtures the
its for horizontal propagation of flame at atmospheric tempera-
re and pressure correspond to 10 and 70 per cent. hydrogen
ntents respectively.

Although all methane-air mixtures develop an initial uniform
ow flame movement period when ignited at or near the open
nd of a horizontal tube, neither its linear duration nor the flame
elocity is, according to Wheeler's experiments, independent of
he diameter of the tube. The speed of the flame during this
period increases with the diameter of the tube; also the linear
duration of the uniform period increases with both the diameter
and the length of the tube up to a certain maximum, and for the
same tube it varies with the proportion of methane in the explo-
sive mixture, being greater as the speed of the flame diminishes,
until with the two "limiting" explosive mixtures it appears to
last almost indefinitely.

The accompanying curves (Fig. 30) show the results of Wheeler's
determination of the speeds of the initial uniform movement
(horizontal) of flame through methane-air mixtures at atmo-
spheric temperature and pressures in tubes of different diameters
(ordinates = velocity in centimetres per second and abscissæ
= percentages of methane). It is noteworthy that the flame
velocity is still considerable at either of the two limits of inflam-
mability instead of nearly approaching a zero value, as Mallard
and Le Chatelier supposed it would do, and that it reaches a
maximum with mixtures containing from 9·5 to 10·0 per cent.

... [illegible] ... In the next curve Fig. 3° are ...
... without mixture obtained by ... A. ...
... [illegible] under Dr. ... 's direction.

But within recent years considerable ...
... that a proper ... scientific knowledge ... such ...
... to be used in the time velocity it can be considered ...
reached a satisfactory point. In regard to the field ...
our present knowledge, the author was set to ...

Fig. 3.—Stages of Uniform Movement of Flame through Me...
mixtures in Tubes of Different Diameters (Wheeler).

address to Section B of the British Association in ...
" an exact knowledge of the velocities of flame propagatio...
the initial period of uniform slow movement, as well a...
limits of inflammability for mixtures of various com...
gases and air, is very important from a practical point...
Makers of apparatus for burning explosive mixtures of ga...
want to know the speed of flame propagation throu...
mixtures, not only at ordinary temperatures and pressu...
also when the mixtures are heated and used at higher p...
Also, it would be important to know whether or not, in ...
of a complex mixture of various combustible gases and ai...

258

al composition can be determined by analysis (as for
e, coal gas and air), the velocity of flame propagation
calculated from the known velocities for its simple com-
s. Unfortunately, although more than thirty years have
d since Mallard and Le Chatelier's work was published,
cessary data are still wanting to answer such questions,
iny one who will systematically tackle the problem and
illy work it out in detail will be doing a real service to the
sing industries."

'IG. 31.—Rates of Propagation of " Uniform Movement " in Hydrogen-
Air Mixtures (Haward and Otagawa).

Another point which needs much further investigation in this
connection is the accelerating influence of turbulence upon both
the propagation of flame and the intensity of combustion of
an explosive mixture of gas and air; indeed, this as yet but
little explored subject affords vast opportunities to the coming
generation of scientific workers.

The important question of " flame temperature " in any given
case of gaseous combustion is governed by several factors, such,
for instance, as the relation of the heat capacity of the products,
and of the energy directly radiated from the flame, to the total
energy developed by combustion, as well as the size of the flame
and the intensity of the chemical changes involved.

ι of heat radiated might be as low as 2 or 3 per cent.
ults appeared to indicate that the radiation depended
. the size of the flame, as well as on the temperature,
ιe presence of CO or solid C when the air was insufficient
lete combustion."

chemists who have investigated the subject attribute
ιtion from non-luminous flames to the formation *at the
of combustion* of intensely vibratory hydrogen-oxygen or
monoxide-oxygen "complexes" which eventually give
ιteam and carbon dioxide molecules. Thus, for example,
:ase of a hydrogen flame, hydrogen and oxygen molecules
g in collision may be conceived as forming, in the first
:e, and for an indefinitely short period, not steam, but a
ory system of hydrogen and oxygen. Such a system would,
; its transitory existence, emit a considerable amount of
ιt energy which would not, therefore, subsequently appear
ιsible heat in the products. Afterwards would come the
ιtion of steam, at first in a vibratory condition, until finally
ystem would rapidly settle down to a non-vibratory state in
ι the product would gradually lose its translatory energy
perature) by ordinary cooling processes, *i. e.* by collision
ι other molecules or with the walls of the containing
el.

. very complete spectroscopic analysis of the radiation from
erent flames was made by Dr. W. H. Julius, of Berlin, in 1890,
ιse experiments proved beyond doubt that the radiation is
ιost wholly due to incipiently formed (or forming) CO_2 and
O molecules. About the same time Robert von Helmholtz
:asured the amount of radiation emitted by "solid" flames,
nm. in diameter, burning hydrogen, carbon monoxide, hydro-
rbons, and coal gas respectively. A flame burning hydrogen
diated 3 per cent., another burning coal-gas 5 per cent., and
third burning carbon monoxide 8 per cent. of the total heat
f combustion. He also determined the *relative* amounts of
adiation *per litre of gas consumed*, emitted by flames of given
ize burning various gases, the air supply in each case being
adjusted so that the flame was just non-luminous, with the
following results :—

Gas Burnt.	Relative Radiation per Litre of Gas.
Hydrogen	74
ι monoxide . . .	177
e	327
ε	510

...hat the radiating power of a CO flame is, per unit
. burnt, 2·4 times that of a hydrogen flame of the
e experience of steel workers is not only seen to
ut is also very largely explained. This illustrates
..ts of scientific investigations can be applied to the
of important practical problems, which otherwise
n in an empirical state.

FLAME TEMPERATURE

u " flame temperature " is often used very carelessly
entific and technical literature, and indeed it is difficult
a precise meaning to it. For, as Smithells [1] has truly
ist flames are composed of thin films and their external
ncludes a large quantity of unburnt gas," and whilst
..k of the temperature of such a flame as meaning the
thermal state of the burning film and the included gas "
re usual to mean the indication of some thermometric
ent wholly immersed in the region of combustion.
emperature of the flame from a burning gas must presum-
e governed or influenced principally by three factors,
v (1) the ratio of the thermal value of the reaction to
orresponding total heat capacity of the products; (2) the
nt of energy *directly* radiated from the flame; and possibly
(3) the rapidity with which the remaining energy is
sformed into sensible heat of the products.

ne " theoretical flame temperature " has sometimes been
ulated as the ratio between the heat of the reaction and the
t capacity at ordinary temperatures of the known products.
t such a calculation is not only based upon two wrong assump-
ns, namely (1) that the reaction is instantaneous and the trans-
r of the energy developed to the products is adiabatic; and
:) that the specific heats of the products do not increase with
he temperature; but it also (3) ignores the fact that part of the
energy developed by the reaction is directly radiated from the
flame.

Another misconception which, judging by the frequency with
which it crops up in technical discussions, seems to be very
prevalent is that calorific value and calorific intensity necessarily
rise or fall together. Thus it seems often to be assumed that a
gas of calorific value, say, 500 B.Th.Us. (*net*) will necessarily
burn with a hotter flame and give a higher temperature in a

[1] Article on " Flame," Thorpe's *Dictionary of Applied Chemistry*, Vol. II

... than one of say, 500 B Th U's (net, ... whereas it may easily be shown that such an ... necessary ... Indeed according to actu... blue water gas of 300 B Th U's calorific value ... flame than does a coal gas of 500 B Th U's. Al... is hardly consistent with the following experim...

	Calorific Value per cub ft at 0° C and 760 mm		
	Gross	Net	
Hydrogen	343.3	287.2	
Coal Gas	5??	500	
Acetylene	1550.0	1500.0	

I ... the possibility of making any ... flame temperatures not only is our kno... specific heats of steam, carbon dioxide and nitroge... ... imperfect but also the measurements ... been made of the energy directly radiated fro... ... hardly be considered as more than approximat... ... hardly know sufficient about the relative ... various gas or ... mixtures to effect the transfe... ... the energy developed by the reactio... ... assuming tha... ... is ... although it ... from ... on the theoretical side the subje... ... many difficulties and complications.

... recognising this to be ... to make simple calcu... ... the various gas and air mixtures th... ... to see more clearly the perspe... ... and ... readily falling into errors ...

If ... the net heat of combustion of a gas b... ... measurement of the heat liberated by ... ... and ... the mean spe... ... either and without between say 0 ... ... in the case of steam' be extrap... ... then ... we can for the com... ... the mean thermal capacity be... ... for ... the products as ...

... at usual method

·n dioxide, steam and nitrogen), formed per 100 K.C.Us.
› cals.) developed on combustion when the gas is burnt with
the theoretical quantity of air, which latter may, for the
≥ of calculation, be considered as a mixture of one volume
ζen with four volumes of nitrogen.
ratio of 100,000 calories to this number K would (assuming
rectness of Holborn and Henning's equations up to 2000° C.,
so that all the energy produced is adiabatically transformed
ensible heat of products) give us a theoretical maximum
flame temperature, T_1, above that of the environment,
ιable by the gas when burnt with the theoretical amount
r, making no allowance for the proportion of energy directly
ιted away. And by making a certain deduction (r) from the
ιr, consistent with the actual measurements which have been
ιe of the radiation from flames, we can arrive at a further
roximate mean flame temperature, T_2, which will probably
rly represent the relative calorific intensity of the combustion.
n making such calculations the author has assumed the sub-
ιtial accuracy of Robert von Helmholtz's measurements and
ιclusions regarding radiations from flames, which have already
en explained in the preceding section of this chapter.

TABLE LXIII

ALCULATION OF RELATIVE CALORIFIC INTENSITIES OF GAS-AIR FLAMES

Gas.	Net Cal. Value Cals. per Gram-molecule.	K Cals.	$T_1 = \dfrac{100,000}{K}$ C°.	r Cals	$T_2 = \dfrac{100,000 - r}{K}$ C°.
Hydrogen . .	57,200	45·89	2179°	12,000	1918°
Carbon Monoxide	68,000	44·64	2238°	24,000	1700°
Methane . . .	189,500	50·30	1988°	16,000	1670°
Ethylene . .	310,900	44·70	2238°	15,000	1900°
Acetylene . .	298,800	37·38	2675°	13,200	·2322°

The values of T_2, as calculated on the basis of the foregoing
assumptions, are not very different from those actually observed
by thermometric methods in the case of gas-air flames by the
best workers in recent years. Thus, in 1905, Féry observed
1900° C. for a hydrogen-air flame, 2548° C. for an acetylene-air
flame, and 1871° C. for a coal-gas-air flame, whilst Messrs.
White and Travers, in 1902, gave 1780° for a coal-gas-air flame.
It will be seen that the values of T_2, as above calculated, for

... al between
... mixture su...
... ed to be a...
... ... cent of
... carbon
... at 1750° C
... ess is laid
... se. The c...
... account...
... the flam...
... tion for a...
... ... to simu...
... mes T_2 will
... very falling
... ary, or ev...
... ... runes and

CHAPTER XV

INTRODUCTORY : THE GAS INDUSTRY

THE coal carbonised in the United Kingdom in the year 1916 amounted to 37·62 million tons, or about 14·7 per cent. of the total output of the mines, and 18·7 per cent. of that portion of it was consumed at home. Of this amount, 17·5 million tons were dealt with in various forms of retorts in gas-works, principally for the manufacture of towns gas, whilst the remaining 20·1 million tons were used for the production of hard metallurgical coke, which is chiefly used as a blast-furnace fuel for the smelting of iron.

The importance of these carbonising industries from a national point of view is a great and growing one. Upon the gas industry, on the one hand, the community depends for supplies of gas suitable, not only for domestic and public lighting and heating, but also, in an increasing degree, for small-scale industrial heating operations and power purposes; on the other hand, the future prosperity of our iron and steel industries is bound up with the efficiency and proper development of the coking industries. Also, we rely equally on both branches of the industry for our entire supplies of benzene, toluene, anthracene, naphthalene, and other coal tar products, which constitute the raw materials for the manufacture of synthetic dyes, drugs, and high explosives. Moreover, at present we obtain 73 per cent. of our total output of ammonium sulphate by the high temperature carbonisation of coal.

In this brief review it is not proposed to enter into details concerning either the design or operation of carbonising plants; and with so many recent good handbooks on the subject available,

pt as to population) from the Board of Trade Returns for
ithorised gas undertakings, whether municipally or privately
:d, in the Kingdom :—

Esti-mated Popu-lation. Millions.	Capital or Loans.		Million Tons of Coal Carbon-ised.	Mill. Cub. Ft. of Gas.		Length of Gas Main. Miles.	Number of Con-sumers. Millions.
	Authorised. £	Paid up or Borrowed.		Made.	Sold.		
35·9	71,863,267	35,513,570	8·378	84,637	77,393	18,967	2·095
46·0	162,346,673	139,727,277	16·971	224,517	206,474	39,099	7·103

Early History.—The foundation of this huge industry dates
back to the inventions of William Murdoch (born at Belton Mill,
Ayrshire, in 1754, died in Birmingham 1839) in the years 1792–6.
For although during the seventeenth and eighteenth centuries
many observers had found that an inflammable gas could be
obtained by distilling coal in closed vessels, it was not until
Murdoch carried out such an operation in an experimental iron
retort, which he had installed in the back yard of his house at
Redruth in 1792, and carried the resulting gas by a pipe to a
burner fixed near the ceiling over a table in one of the rooms in
his house, that the use of the gas as an indoor illuminant was
demonstrated. In November 1795, and again in February 1796,
Murdoch operated a small experimental gas-making apparatus
at the Neath Abbey Ironworks, in which coal was distilled in
an iron retort provided with an iron pipe about 3 ft. long at the
open end of which the issuing gas was burned, giving (it was
said) " a strong and beautiful light, which continued burning a
considerable time."

In 1799 Murdoch was recalled from Redruth to the Soho Works
in Birmingham of Messrs. Boulton and Watt (the firm by whom
he was employed), and continuing his experiments there, he
installed an apparatus for the generation of the new illuminating
gas, which was first publicly used in connection with an outdoor
illumination to celebrate the Peace of Amiens in 1802. In the
following year part of the Soho factory was regularly lighted
by the gas. In 1804 he put up another apparatus to illuminate
the residence of Mr. George Augustus Lee in Manchester, and so
successful was the venture that a few months later the cotton

., **Kidderminster**, and in many other towns and places of **Britain.**"

retorts then employed in the London gas-works were made t **iron**, in several different sectional forms, but chiefly : **parallelopiped**, 6 to 7 ft. long, 20 in. wide, and 15 in. high, **slightly** rounded angles, (2) *ellipsoidal*, 5½ to 6 ft. long, **axis** 20 to 25 in., minor axis 10 in., and (3) *semi-cylindrical*, 5 ft. long, 18 in. wide, and 6 in. high. A number (up to 5) **ch** retorts were set over a fireplace in an oven heated by **combustion** of small coal. The total number of retorts at **the London** gas establishments in the year 1819 amounted **300.** Each semi-cylindrical retort was charged with two **hels of** coal, the carbonising period being 6, but preferably 8, **rs,** at a temperature described as " cherry-red heat." The **ld of gas** obtained varied between 8300 and 10,000 cub. ft. r **chaldron** (27 cwt.) of coal (say between 6150 and 7400 cub. ft. r **ton of** coal), according to the duration of the carbonising **riod,** whilst the weight of coal expended in heating the retorts **mounted** to about 25 per cent. of that carbonised. We are **further** told that the crude gas evolved from the retorts was **purified** from sulphuretted hydrogen and carbonic acid by **bringing** it " confined under a pressure equal to a column of water, not less than 8 or 10 in. in height, into contact with quicklime, diffused through water."

The following balance sheet of a full week's experimental run of an installation of 96 semi-cylindrical retorts, with 8 hour charges,. at the Gas Light and Coke Company's Westminster Station early in 1819 is of great interest from many points of view, showing as it does, not merely the yields obtained, but also the prices ruling in London a century ago.

BALANCE SHEET FOR GAS PRODUCTION IN 1819

Materials Expended.	£	s.	d.	Products Obtained.	£	s.	d.
Coal decomposed : 107 chaldrons at £2 11s. 6d. the chaldron . . .	275	10	6	Coke : 124 chaldrons, at £1 7s. the chaldron	167	8	0
Small coal : 26 chaldrons 27 bushels, used for fuel, at £2 2s. the chaldron	56	3	6	Breeze, or small coke : 4 chaldrons at 18s. .	3	12	0
				Tar : 8 tons, at £6 the ton	48	0	0
				Ammoniacal liquor : 1945 galls. at 1½d. .	12	3	1½
				Gas : 1,070,000 cub. ft., at 15s. the thousand	802	10	0
Total . . £331		14	0	Total . . £1033		13	1½

commonly used in English laboratories at that time for
with a smokeless flame. The arrangement did not
Bunsen in the very least, the flame was flickering, it was
ce, and the gas was so much diluted with air that the
temperature was greatly depressed. He could make a
in which the mixtures of gas and air would burn at the
the tube without any gauze whatsoever, giving a steady,
and hot non-luminous flame, under conditions such that
only would burn without striking down when the gas
y was turned on full, but also when the supply was
ished until only a minute flame was left. This was a
ult, some thought an impossible, problem to solve, but
many fruitless attempts, and many tedious trials, he
eeded, and the ' Bunsen burner ' came to light."
view of the many fortunes which have since been made
others out of applying the principles of Bunsen's burner to
ious economic ends, it may be recalled that (to quote Roscoe's
rds again) " the notion of making money out of his discoveries,
of patenting any of them, never entered into his head." Thus
is the inestimable boon of this simple but ingenious atmospheric
irner conferred upon the world as a free gift by the great
eidelberg chemist, and it may safely be said that without it
ie gas industry would never have attained its present colossal
nagnitude.

The next discovery referred to was made exactly thirty years
later, also in Bunsen's laboratory at Heidelberg, when Auer von
Welsbach found that the oxides of certain rare metals had a
quite extraordinary power of emitting light when in a state of
incandescence. Following upon this he made, during the next
few years (1885 to 1893), a series of researches which eventuated
in the invention of his well-known incandescent mantle. This
mantle, which is got by incinerating a cotton or other fabric
saturated with a solution of a mixture of the nitrates of thorium
(9·9 per cent.) and cerium (1 per cent.), gives in conjunction with
Bunsen's burner a magnificent white light, and it is not too
much to say that the gas industry gained a new lease of life in
its competition with the electric light from this second great
invention of the Heidelberg chemists.

In thus recording these two outstanding discoveries, it must
not be forgotten that honourable mention is also due to the
labours of the late Thomas Fletcher of Warrington,
erhaps the first practical mind to appreciate and

273

develop the enormously wide field of useful... Bunsen's invention. The world undoubtedly... the rapid destruction of numerous types of... ingenious appliances specially adapted to... tables in manifold ways for both dome... heating operations.

PERIOD 1815 TO 1850—PRIMARY REQUIRE... ILLUMINATING GAS FOR OPEN FLAME...

During a period of about three-quarters of... the establishment in London of the first public... the predominant use of coal gas was for lighti... what are sometimes termed "open flame"... the actual union of the gas and air only... forming the outer surface of the flame, where... combustion and therefore very high tempera... Under the influence of the heat so developed in... the mass burns portions of unburnt gas in the... flame undergo characteristic thermal decompos... the separation of solid particles of carbon, and... very low hydrocarbons, which, being raised to... cause the well known yellow luminosity of the fl...

Sir Humphry Davy, who was perhaps the f... investigate the matter, believed that the light en... *gas flame "might be owing to the decomposition of*... *toward the interior of the flame where the air*... *quantity and the deposition of solid charcoal, w*... *ignition and afterwards in its combustion, incre*... *degree the intensity of the light"[1]* And althou... research may have revealed facts which require... tion in detail of this statement it has fully confi... proposition, namely, that the luminosity is due... position of part of the gas and the deposition... towards the interior of the flame.

This being so, the prime object of the early ga... was to obtain a gas as rich as possible in the "... carbons (ethane, ethylene, propylene, benzen... readily decompose under the influence of heat pr... For obviously such constituents as hydrogen

[1] *Journal of Science and the Arts,* Vol. II., p. 114, an... Vol. III. p. 47

being heated either do not yield carbon at all, or only
t difficulty, cannot contribute directly to the luminosity
lame, although they undoubtedly play an important
rôle by reason of the high temperature developed by their
ion in the outer regions of the flame.

igh Illuminating Gas required Fifty Years Ago.—Seeing
ch a " rich " gas is best produced by carbonising a high-
oal at medium temperatures (say 750° to 900° C.), the
e naturally followed such lines so long as high self-
sity of the gas was the controlling consideration. Hori-
-shaped or oval retorts still continued to be employed,
ey were no longer made of cast iron, as in the earliest days,
fireclay, and they were heated by the combustion of coke
direct-fired " settings, without any regenerative arrange-
s. The temperatures, whilst higher than those attained
cast-iron retorts were employed, would be decidedly lower
those aimed at to-day. In many cases a considerable
ntity of cannel coal was added to the charge, because of its
ng a very large yield of gas of high illuminating power.

he following analyses of the gas made at such " medium "
peratures (a) in Heidelberg from a bituminous coal, and
in London from a cannel coal, will give some idea of the kind
result aimed at fifty or sixty years ago :—

	(a) Per cent.		(b) Per cent.
Carbon dioxide . . .	0·37	. .	1·19
Carbon monoxide . .	5·73	. .	10·07
Olefines and benzenes .	7·27	. .	10·81
Methane	38·40	. .	41·99
Hydrogen . . .	44·00	. .	35·94

*The Modern Need of a Lower Quality of Gas for both Lighting
and Heating Purposes.*—With the wide adoption of incandescent
mantles for lighting purposes, which followed closely upon von
Welsbach's inventions, and the concurrent increasing use of gas
for domestic heating purposes, which soon resulted from Thomas
Fletcher's pioneering efforts, the need of a rich gas of high
self-illuminating power diminished, and has now practically dis-
appeared. These new conditions opened the way for cheapening
the production of gas by raising the temperature of the retort
settings, whereby much larger yields of a gas of lower calorific
and illuminating power were obtained, a policy which has now

obtainable in a modern setting of horizontal retorts, ?neratively with producer gas made within the setting rt of the coke produced, will be about 10 galls. of tar . 1·15 to 1·25), between 20 and 30 lb. of ammonium ?, and some 14 cwt. of quenched coke, of which latter to 3½ cwt. have to be used for heating the setting, leaving n 10 and 11 cwt. for outside use or sale.

. manufactured in gas-works is used (1) for cupola melting foundries; (2) for making water gas, which is largely used l welding operations; (3) for steam raising under boilers; r the heating of green-houses, and in connection with ll heating systems generally; and (5) it may also with ltage be used to mix with the coal burnt in domestic fires, especially in closed-in ranges where the draught is good.

SELECTION OF COALS FOR GAS MAKING

ne most suitable coals for gas-making purposes are those ling between 30 and 40 per cent. of volatile matter at 900° C., :oned on the dry ash-free coal substance. According to s made by St. Claire Deville at the Paris gas-works, the t results are obtained from those containing between 7·5 and per cent. of oxygen in the coal substance. In England it generally considered that the nearer the ratio O : H in the al substance approximates to 2·0 the better the results obtained. is not, however, always safe to rely on such rules, and hence . many of the larger works provision is made for the testing of ?als on a large scale by isolating a bed of retorts, with separate ?ndensing and purifying and measuring arrangements, so that he whole process can be carried out experimentally under actual vorks conditions.

The best British gas coals are found in Northumberland, Durham, South Yorkshire, Derbyshire, Lancashire, and North Staffordshire. The great London gas-works draw their supplies chiefly by sea from the Durham coalfield, because of the cheaper cost of sea-freights as compared with railway carriage. The Durham coals as a rule yield a rather harder coke, but less ammonia, than those of South Yorkshire, Lancashire or Derbyshire, which latter, however, produce a somewhat better quality of gas and thinner tars.

A gas manager, in selecting his coal, must often, however, be guided by other than merely chemical data, important as they un(ubtedly are. The question of pithead price and carriage

277

a quality as will withstand temperatures up to 1400° C.,
udden change of temperature brought about when the
t is re-charged with a cold mass of coal.
uickness of the retort walls is increased to 4 in. at each

FIG. 34.

end in order to take the cast-iron mouthpiece and door which
closes it. On to the mouthpiece, which is bolted on to each end
of the retort, and projects for a short distance beyond the wall
of the setting, is cast a socket into which is fixed a vertical iron
ascension pipe, 4 to 8 in. in diameter, with the object of con-

279

vering the crude gas tar, and other volatile con...
... the ... pipe and dip pipe into a collect...
the ... main. The latter extends in a li...
... the axis of the retorts, along the whole len...
... and in it a mixture of tar and liquor ...
... each retort, thus forming a valve which,
... passes through the seal onwards toward...
... effectually prevents any of it getting back
... ... burning purpose. The gas fr...
... ... to the condensing and ...
through a pipe called the foul main, fixed at ...

... ... for Waste Gases

... The general arrangements of these ...
... the retort and setting will be understood by ...
Fig ...

The weight of coal charged into a retort 20 ft. lo...
... 2 ft. wide is usually about 6 to 7 cwt. ...
... so as to allow of a sufficient free ...
... large ... for the passage of the gas th...
... ... allow of a rake bein...
... the purpose of discharging the coke at the end of t...
... ... some of them ...
... it is necessary to allow for such a ...
... ... completely an average ...
... ... at the point which the ter...
... be between ... and may go up to ...

where the operation is pushed to the furthest practical
ving regard to the life of the retort.   In Table XXXV
131 of Chapter VIII hereof, is shown the composition
ude gases evolved at different times during the carbonisa-
a Derbyshire coal when the final temperature was 950° C.

the chemistry of carbonisation has already been fully
ed in Chapters VII and VIII, there is no need to refer
:o the subject here.

omparing the carbonising conditions in such " horizontal "
hose in the more modern " vertical " retorts, which will be
bed later on, it is important to remember that, inasmuch

FIG. 36.—Regenerative Settings for Gas Retorts
showing Course for Secondary Air.

as in the former case the coal is heated, not only by contact with
the bottom and lower part of the side of the retort, but also
largely by radiation from the arched top thereof, the zone of
" active carbonisation " advances from the perimeter of the
charge towards the central portion of it.   Hence, during the
greater part of the carbonising period, the gases and volatile
matter evolved must of necessity pass out of the charge through
a layer of incandescent coke which is always at a higher tempera-
ture than that at which the coal has been mainly carbonised.
Also, these gases and volatile constituents, on emerging from this
incandescent coke, have to traverse the free space above the
charge, where they are subjected to intense radiant heat, and
in so doing must come frequently into contact with the incan-
descent arch of the retort.   When it is recalled that the radiation

281

from incandescent surfaces causes the heavier hydr
ethane propane, ethylene, propylene, etc.) to decomp
that contact with such surfaces greatly accelerates the
decomposition of methane, the importance of getting
out of the retorts as quickly as possible will be apprecia

Hence the gas manager endeavours to keep down the
in the retorts uniformly to a point only slightly ab
of the outside atmosphere; if he reduces it below t
spheric pressure air will be drawn through the retorts
interaction with their contents produce a mixture of
and oxides of carbon which dilute the coal gas to the d
of its quality.

The decomposition of the hydrocarbon
such as methane in the gas by contact with the inca
walls of the retort accounts for the deposition of "*gas
so-called scurf or system which is a well-known feature of ca
out in horizontal retorts. This "scurf," whilst rende
the mass conductible slightly interferes with the hea
transmission if it is allowed to accumulate unduly. Hen
wall of retort and is used for the manufacture of
producers of certain furnaces.

These are heated by means of "producer gas" ge
gas is therefore charged with a certain amount of
nitrogen and water vapour. A solid-bottom generator with
a grate situated at the end of retorts (see Figs. 32, 33,
at about the ground level, and is charged w
with coke from the retorts. The "primary" air, togeth
with some steam through the bars, and, by means
reactions are driven through a deep bed of incan
coke thereby producing a low-grade producer gas o
approximately the following analysis :—

$$H_2 = 7.5, \quad CH_4 = 0.5, \quad N_2 = 6$$

entering the setting through holes n
the narrow spaces formed by the vertic
walls of the retorts, meets with a regulated st
of secondary air sufficient for its complet
combustion which is completed as the interi
hot gas circulates round the retorts. The
products finally leave the setting at a temp
around the uppermost retorts at the r
travel gradually downwards on their way to the c

a a heat " recuperator " or " regenerator " system. This s essentially of a series of flues adjacent to, and separated hin firebrick partition from, a parallel set of flues through the " secondary " air is allowed to flow on its way to the set-ravelling in the reverse direction to the waste gas stream. : proper control and adjustment both of the " primary " he " secondary " air supplies in such a setting (by means des in the admission ports and dampers at the regenerative ts) is obviously a most important factor in determining the economy of the process. The amount of " primary " air itted should not exceed that required to generate sufficient lucer gas of good quality to maintain the carbonising heat the retorts, whilst no more of " secondary " air should be nitted than is needed to burn the gas completely.

in the smaller gas-works horizontal retorts are still charged d discharged by hand labour, but in nearly all the larger stallations this work is now entirely done by specially designed achinery. The use of machines for this purpose has done way with the necessity for leaving so large a " free space " ver the coal in the retort as was formerly so customary, and ndeed some gas managers now work the retorts on " full charges."

As an example of the results obtainable in a modern horizontal retort setting, the following summarised figures may be given (Table LXIV) of a seven days' trial with a Derbyshire gas coal made in 1910 by Mr. J. Ferguson Bell of Derby for the Carbonisation Committee of the Institution of Gas Engineers.[1]

The coal used was from the Blackshale Seam (Derbyshire), and, as charged, contained—

C = 72·22, H = 4·75, N = 1·35, S = 2·35, O = 7·36, Ash = 7·51, Moisture = 4·49 per cent., with Volatiles = 33·98 per cent.

The retorts, which were heated in settings of " eights " by producer gas in Klönne regenerator furnaces, were Ω-shaped, 18 ft. long × 22 in. wide × 16 in. deep. In one set of trials, 12 cwt. " full " charges were carbonised in 12 hours, and in the other series 8·21 cwt. charges were worked off in 8 hours, the mean average final temperature in the retort being 995° C. in the first case and 986° C. in the second. The temperature in the combustion chambers of the settings was about 1330° C.

[1] *Trans. Inst. Gas Engineers*, 1910, p. 259.

... the ... to maintain as nearly as pos...
... the inside of the retorts throughout ...

TABLE LXII

... Bell's Trials of a Derbyshire C...
... Retorts at 985° to 995°C

	No...
Average ... Temperature °...	9...
...	Full...
... in tons	...
... cwts	13
...	12
...	9
... cwts	...
... of Coal lbs	2...
... Tar	12 0
... of Coal car...	1 ...
	2
	5
	3
	...
	...
... No. 2 Metropolitan ...	15

... Per cent ...
... inside only ...

... IN VERTICAL RETORTS

... were con...
... horizontal retorts ...
... the cost of charging and ...
... either by hand labour ...
... setting the retorts at an an...
... met with encouraging su...
... were spread to oth...
... several installations of " incli...

>f **which** were operated with " full charges," were put up
tish gas-works. The technical results did not, however,
materially from those obtained in the older horizontal
ʒs.
ᵥould appear that, as long ago as 1828, an inventor named
ton had proposed a system of vertical retorts in which full
ʒes **were** to be carbonised, on the " intermittent " plan,
the gas taken off at the top of each retort. But, for some
ɔn **or another**, possibly connected with the obvious difficulty
atisfactorily heating such vertical retorts without gaseous
ɡ **under** regenerative conditions, the idea did not at that
ə **come** to practical fruition. It was, however, revived and
ɾied **to** success during the early years of the present century
the **Dessau** Gas Works in Germany by Dr. Bueb, who, in
ɔ4, **patented** his new system in England.

It **was** soon recognised that the intermittent vertical system,
ᵢt is now called, possesses certain technical advantages over
ᵢe older methods. In the first place, the problem of charging
ad discharging the retorts is reduced to its simplest form, and
he retorts are worked with full charges. Secondly, it is claimed
ᵧy **Bueb** that, inasmuch as in such intermittently charged
ᵥertical retorts the carbonisation proceeds through the coal
ᵣom the periphery inwards, the gas and " volatiles " generated
during the greater part of the period making their way out
mainly through the relatively cool central core of partially
carbonised coal, thereby avoiding very largely any contact
with the incandescent coke and retort walls. And, finally, the
system lends itself to the practice of passing steam through the
incandescent charge during the last stages of carbonising, thereby
conserving heat energy, and at the same time increasing the
total quantity of gas obtained by the addition of a certain
amount of water gas.

Contemporaneously with Bueb's investigations, a number of
British engineers were independently engaged in designing and
working out systems in which the coal was *continuously* passed
through vertical retorts, somewhat on the lines of the continuous
method for distilling oil-bearing shales invented by Beilby and
Young in 1881.

In 1902 Settle and Padfield patented a method of " vertical "
carbonisation in which the coal was continuously fed into the
top of the retort, but the coke withdrawn by hand at intervals,
but although good results were obtained, it has been said

... ttain ... ... difficulties ... ... with the ... ... were ... ... added ... the ... ... Woodall ... ... and Glover ... ... the coal is ... under ... ... conditi... ... Also Messrs. ... ... and ... ... have ... ... intermit... ... ... the Dempster ... ... as the result ... ... enterprise ... ... maintained their ... ... in this ne... ...

... ... systems which ... now ... ... have ... ... in common that it will suffice ... ... purpose ... ... exposition, to describe the ... and the Glo... ... as representative of the ... ... and continuous verti... ... ...

... Dessau Intermittent System is ... ... The retorts, which are usually ... and ... ... rounded oblong cross-section ... ... up ... ... upwards, in order to ... ... the behav... ... ... at the end of the operation. ... ... is ... ... arranged, in rows of threes ... a single ... ... heated by "producer gas" ... ... in a deep generator built ... ... so...

... ... heating the retorts is what has been d... ... ... its main feature being that the ... ... horizontal chambers or compartment... ... ... gas and air, and the hot product... ... ... this through the four chambers ... ... upwards again to the chimney flue ... ... continuous heat recuperator, where ... ... is transferred to the "primar... ... ... coming in to the setting ... ... coal, and discharged at regula... ... ... the system as an "intermi... ... ... and for each full charge ... ... during the last two of whic... ... ... incandescent coke, for the ... ... and incidentally also of ...

s **claimed** that such a system yields from a given coal **greater** volume of gas, (2) thinner tars containing less **and free** carbon, (3) a large amount of ammonia, but **uch less** naphthalene, and (5) a harder and superior coke

FIG. 37.—The Dessau Intermittent System.

than are usually made in horizontal retorts. Also, that all these advantages may be secured with a smaller consumption of fuel in the setting, and that labour costs are reduced. For further information, the reader may be referred to an instructive paper published by Mr. C. Dru Drury in the *Transactions of the Institute of Gas Engineers* for the year 1911, giving the result of

a recent practice working of the Dessau system at
Gas Works gave a German coal composition:—

Moisture = 1.58 ... 2.36 per cent. ...
... give ... 2.34 per cent.

The gases generated ... from the ... 549 tons
... during the ... were as follows:—

	Pe...
... Pitch and pure tar	12...
Tar	1...
...	2...
... Boiler or such	11...

Illuminating ... ... Gas
... No. ... Mean ... = 15.52 candles
Calorific value ... No. ... = 531 B.Th.U...

The ... (illustrated by ... Fig. 98) ... In
the ... on passing into the vertical retort
... the top of which is fitted to a special ga...
which, after ... passes when fresh coal has
from the main supply hopper overhead. The ...
tinuously drawn through the ... at a speed wh...
lated by an ingenious mechanical ... extractor at
the retort, by which means the time of carbonisa...
adjusted to suit any particular class of coal. The
coke is received from the bottom of the retort into
from which it is periodically discharged.

The retorts are normally 21 ft. long, oval in ...
tapering from the bottom upwards. Usually there
retorts in a setting, which may be divided into sec...
all ... either 2, 3, or 4 retorts to be fired as circumstan...

As a rule each setting is provided with one prod...
generators, but sometimes two such producers are p...

The ... heating and regenerative system is somewhat a...
The heating chambers round the retorts are arra...
... the top two of which called the "circulating ...
... heated by the combined waste gases from the "b...
... burners. The next lower six tiers form the "...
burners ... upper each receiving a separate supply
... together with a suitably proportioned amount of
... Below these again are two other simila...

;h which the secondary air is drawn on its way to the
aid " combustion chambers," a feature which results in
of the heat of the incandescent carbonised coke in the lower
of the retort being transferred to the incoming air, and the
being discharged in a relatively cool state without having
: quenched. It will thus be seen that (1) the waste gases

FIG. 38.—Glover-West Continuous Vertical Retort Setting.

from the "combustion chambers" impart their heat to the
incoming coal as it passes downwards through the upper part
of the retort; whilst (2) the incoming secondary air supply
abstracts the greater part of the heat from the outgoing incan-
descent coke. Another important point to observe is that on
account of the continuousness of the process, the carbonising
and other working conditions are very uniform, a circumstance
which decidedly makes for good results.

ng figures, taken from Mr. Newbigging's paper,
e tars obtained in these trials and that normally
he same coal in horizontal retorts bear out the
vertical retort tars are thinner, and contain less
se carbon than those made in horizontals.

TABLE LXV*b*

	Vertical Retort Tars.		Horizontal Retort Tar.
	A.	B.	
ravity	1·074	1·146	1·193
	%	%	%
. . . . . .	—	2·5	5·0
ils, up to 170° C. .	9·1	4·6	4·5 }By Volume
Oils, 170° to 270° C.	25·7	22·4	12·0
Oils, 270° to 350° C.	24·9	19·7	19·5
over 350° C. . . .	46·0	55·4	57·0 }By weight
arbon	3·1	5·86	17·67

u Balance.—Taking the results of Trial B as fairly repre-
ng what can be accomplished by carbonising a good gas
under the best working conditions in a modern vertical
rt at high temperatures, we may now deduce the following
roximate heat balance for the operation, which shows that
less than 89 per cent. of the energy expended is accounted
in the combined heat values of the resulting coke, tar, and
s :—

	Million B.Th.Us.		Million B.Th.Us.
Dr.		*Cr.*	
ton of Coal charged into		13·7 cwt. Coke	21·110
Retorts	30·850	13,033 cub. ft. of Gas .	7·191
210 lb. of Coke used as		105 lb. of Tar	1·731
fuel in Producers . .	2·889		
Total	33·739	Total	30·032

$$\text{Ratio } \frac{30\cdot032}{33\cdot739} = 0\cdot89.$$

Attention may here be drawn to a recent paper by Mr. J. E.
West[1] in which the results of passing steam through the retorts
during the carbonisation period are demonstrated. The object

[1] *Gas Journal,* Nov. 13, 1917, Vol. CXL., p. 314.

of this procedure is of course to obtain, in addition
arising from the distillation of the coal, a certain am
water gas, thereby increasing materially the total m
per ton of coal treated. It is also claimed that the
improvement gives rise to increased outputs of b
ammonia.

Experimental trials were described in which a gas o
under normal distillation in the vertical retort, 14,08
of gas per ton, of the following composition :—

$$CO_2 = 1\cdot9, \quad CO = 12\cdot0, \quad C_nH_m - 2\cdot0, \quad CH_4 = 26\cdot1,$$
$$N_2, \text{ etc.} = 5\cdot8 \text{ per cent.}$$

When however the same coal was put through the
the bottom of which steam was introduced at 40 lb
through ⅛ in. nozzle, the combined yield of distillation
water gas, amounted to as much as 16,607 cubic feet
coal, with the following average composition :—

$$CO_2 - 3\cdot7, \quad CO = 17\cdot1, \quad C_nH_m = 2\cdot2, \quad CH_4 - 20\cdot8, \quad H$$
$$N_2 = 5\cdot0 \text{ per cent.}$$

The total B.Th.U's in the gas made per ton of coal was 8
in the second experiment, as compared with 7,351,84
first. At the same time the increased yield of gas
obviously be obtained at the expense of part of the c

PURIFICATION OF COAL GAS

Although this subject lies somewhat outside the scope
present book, and is to be treated in detail by Mr. E. V
the Chief Chemist of the South Metropolitan Gas Co., in
sequent volume in this series, a few words upon it b
perhaps not be considered out of place, especially as th
object is to record another remarkable achievement of
technologists which fittingly closed the first century's d
ment of this pre-eminently British industry.

The most modern methods for the removal and reco
tar, benzols, naphthalene, ammonia, and other condens
soluble by-products from crude coal gas will be described
next chapter, which deals with the coking industry, whe
have been further developed than in gas-works. But w
these products have been removed, and the gas thor

, there still remain, as impurities, (1) certain cyanogen
ounds, the amount of which tends to increase with the
rature at which the coal is carbonised; and also (2) sulphur
ounds, chiefly sulphuretted hydrogen and carbon disulph-
whose presence in a gas destined for domestic use is, from
y point of view, deleterious.
onsiderations of space preclude our dealing with the removal
ne cyanogen compounds. Sulphuretted hydrogen has never
ented any serious difficulties to the gas manager, for it may
easily, and completely, removed by passing the gas through
' dry '' purifier containing layers of moist hydrated ferric
de (preferably in the form of bog iron ore), when the following
ctions occur :—

$$(1) \quad Fe_2O_3xH_2O + 3H_2S = Fe_2S_3 + (x + 3)H_2O.$$
$$(2) \quad Fe_2O_3xH_2O + 3H_2S = 2FeS + S + (x + 3)H_2O.$$

he spent oxide, after it has ceased to react with the hydrogen
alphide, may be "revivified" by atmospheric oxidation,
vhereby ferric oxide is re-formed with the separation of free
alphur. Therefore the purifying material is alternately used
in the purifier, and revivified by exposure to air several times
over, until its sulphur content rises to beyond 50 per cent.,
when it is sold to the sulphuric acid manufacturers. In this
way the sulphur existing as hydrogen sulphide in the crude
gas is ultimately converted into sulphuric acid.

The removal of carbon disulphide has, however, always pre-
sented great difficulties. For although it can be partly effected
where "lime purification"[1] is resorted to, such procedure is
so uncertain in its effects, and so liable to cause "nuisances,"
that it has been largely abandoned in modern works. Hence,
for many years, the consumer had to tolerate an undue propor-
tion of sulphur compounds in the gas supplied to him.

In 1906, however, Dr. Charles Carpenter, in conjunction with
Messrs. E. V. Evans and Doig Gibb, initiated investigations at
the South Metropolitan Gas Works upon the well-known decom-
position of carbon disulphide by heat in contact with suitable
catalysts at moderate temperatures whereby, in presence of

[1] The removal of CS_2 by this method principally depends on the fact
that the calcium hydrosulphide $Ca(SH)_2$ which is first formed by the
action of H_2S upon slaked lime, $Ca(OH)_2$, will in time absorb CS_2, forming
calcium thiocarbonate, $CaCS_3$, and H_2S, which latter must be removed
either by means of fresh lime or hydrated ferric oxide. The process,
however, is too complex to be treated here in detail.

hydrogen, which is always a predominant cons
gas, it is converted into sulphuretted hydrogen
follows .—

$$CS_2 + 2H_2 = 2H_2S + C$$

The sulphuretted hydrogen can then be remove
manner. By using nickel, as the most suitab
a temperature of 450° C, the investigators in q
succeeded in evolving a practical process wherel
content (as CS_2) of the South London gas can be
large scale, in regular day-to-day working, from
8 grains per 100 cub. ft, without in any way det
quality of the gas, at a cost (including interest and
of 0.20d per 1000 cub. ft, thus providing a str
of what may be achieved in industry by (to borrow L
own phrase) " the unrestricted and unreserved col
the chemist and the engineer " [1]

The Quality and Prices of Towns Gas in 1913.–
decade prior to the war, the adoption of a calorific
towns gas had become fairly general, and the folle
may be quoted as showing the average gross calorif
the year 1913 of the gas supplied in six of the larg
Great Britain .—

City	A.	B.	C.	D
Gross Calorific Value in B Th Us. per cub. ft. of dry gas at 60° Fahr. and 30 in. Bar	620	596	593	582

The prices charged to the ordinary consumer in
ranged from one shilling and threepence to two s
sixpence per 1000 cub. ft.

COAL GAS AS AN INDUSTRIAL FUEL [2]

The some years prior to the war, coal gas had
making headway as an industrial fuel, and sin

For further details the reader is referred to Dr Carpen
Economic use of Gas by Heat before the Institution of
... *Trans Inst Gas Engineers* 1914 p
... on this subject a lecture de
... at the National Gas Congress in L
... in Cassier's Engin

abnormal demands for gaseous fuel in connection with munitions factories have, for the time being at least, considerably increased its use for such purposes, and it may be confidently predicted that after the war it will continue to play an important part in the industrial field.

It should, however, be recognised that, apart from the special circumstances of its employment for munitions purposes during the war, its chief usefulness in normal times is most likely to be either (1) in the direction of supplying the manifold wants of innumerable, but relatively speaking, small industrial consumers; or (2) in connection with the manufacture of high-grade commodities, where the question of the cost of the heating operation is of less consequence than the certainty of attaining a particular result within a given time, as for instance in the heat treatment of special steels or alloys. In cases of other large scale operations, as in the heavy structural steel trades, where the cost of the gaseous fuel is of paramount importance, it will scarcely be able to compete with either producer gas, or with mixtures of coke-oven and blast-furnace gases, as a furnace fuel.

Before the war, the cities of Birmingham, Sheffield, and Glasgow led the way in the matter of supplying cheap coal gas for industrial purposes. Birmingham, in particular, had shown remarkable enterprise in the high-pressure distribution of gas, at 12 lbs. per square inch, to workshops, factories, and foundries within the city area. During the year ending March 31, 1913, no less than 1900 million cub. ft. (or 22½ per cent. of the total gas output) were sold for industrial purposes at an average price of fifteenpence per 1000 cub. ft., and a consumer taking more than 4 million cub. ft. per quarter was charged only 11·4*d*. per 1000. The gas was largely used for (1) brass and aluminium melting in crucibles, the total cost of which was said to have been less than in the older coke-fired furnaces; (2) lead melting in pots; (3) the annealing, hardening and tempering of small steel wares and the like; and (4) for glass annealing. During the war, the melting of aluminium bronzes, gunmetal, nickel, cupro-nickel, Admiralty metal, and brass billets have been added to the list. Also, gas-fired furnaces have been installed in connection with the manufacture of optical lenses, and porcelain.

The Sheffield United Gas Co. were no less enterprising than the Birmingham Municipal Authorities. Even the smallest

... gas in a few ... thirteen of the ... of coal gas is ... 101 million cub ft ... million cub ft ... and ... cub ft ...

During the year ending May ... tion sold 303 million cub ft ... poses (in addition to 344 million ...) average price of 10d per ... (1) for brass and aluminium melting ... pering and forging of tools, 3 for ... glass annealing. During a similar period ... 1916-17, the total supplied for manufactur... to upwards of 910 million cub ft, or more th... pre-war figure, the new outlets being principal... with shipbuilding, munitions, and general en... Also in the chemical trades, such processes as ... and concentration of salt and sugar solutions, ... of fats and oils, have all made considerable ... gas works.

Another rapidly increasing application of ... annealing of the finer grades of wire in gas fire... one works in Yorkshire uses upwards of 45 mi... annum for that purpose. It is also being larg... textile industries in connection with the ten... and aircrafting of cloth, and the conditions ... must also not be forgotten that a very large am... is now used in gas engines throughout the king...

The important part played by the gas indust... with munitions of war has already been refe... complete the story of its services to the nation... added that since the outbreak of war plant has ...

all the large gas-works for "stripping" the gas of
⸱ **and** toluene contents, thereby greatly adding to the
£ **raw** material available for the manufacture of high

⸱⸱

CONCLUSION

nd **of** the first century after its inception finds the gas
in **a** state of active growth and development, adapting
the ever-changing requirements of our complex civilisa-
d **filling** a foremost place in our national economy.
net **result** of the century's progress, so far as the public
erned, may be summed up by saying that when in 1818
ndon Gas Works produced something between 6150 and
:ub. **ft.** of gas per ton of coal carbonised and their cus-
s **paid** fifteen shillings a 1000 cub. ft. for it, during the
ending December 31, 1913, they produced 12,420 cub. ft.
⸱ **)n,** **and** charged, on the average, two shillings and fourpence
:000 **cub.** **ft.** for it. To-day the yield is substantially the
: as **in** 1913, but, owing to war conditions, the price is, for
time being, higher. •
s **it** **may** interest the reader to know how many different
ns make up the cost of supplying a modern community with
\, and the proportion which each one bears to the whole, we
ll conclude our review by reproducing (see next page), from
ficial records, the following analysis of the Accounts of the
ondon Gas Companies for the year ending December 31, 1913.

TABLE LXVI

THE METROPOLITAN GAS COMPANIES ACCOUNTS FOR THE

	Total
	£
Capital and Borrowed Money .	47,525
Income	
Gas Sold .	5,131
Meter rentals	354
Rents of Rooms, Fittings, etc .	515
Residual Products	
Coke and Breeze .	1,312
Tar and Tar Products	33
Ammoniacal Liquor, Sulphate of Ammonia .	412
Miscellaneous .	56
Total Income from all Sources . .	7,981
Expenditure	
Coal and Cannel, Including Carriage and Dues	2,868
Purification of Gas, Labour . .	—
Distribution of Gas .	334
Rents	83
Rates, Taxes, and Rent charges .	299
Salaries and Office Expenses .	175
Directors' Fees and Auditors'	301
Public Lamps, Repairs of Meters, Service Pipes, etc.	697
Maintenance and Renewals, Public Lamps	63
Repairs, Renewals, etc. .	482
General Maintenance	29
Bad Debts, Discounts, Allowances	98
Law and Parliamentary	59
Directors' Fees	10
Chemicals and Purification Material	105
Compensation to Workmen	86
National Insurance Act	15
Law and Parliamentary Charges .	8
Sundries and Extraordinary Expenses .	22
Total Expenditure on Revenue Account	6,320
Gross Profit	1,670

THE CARBONISATION INDUSTRIES (*continued*)

THE COKING INDUSTRY

⟨E manufacture of hard metallurgical coke, which is chiefly ι for the smelting of iron in blast furnaces, has always been mportant industry in Great Britain since the middle of the ιteenth century. Such coke is produced by carbonising, at h temperatures and in large ovens, coals specially selected their strongly caking properties and their relatively low h contents.

As already shown in Chapter IV, the best coking coals are ιose yielding between 20 and 30 per cent. (on the " dry ashless " ɔal) of volatile matter when carbonised at 900° C., and the ιnest of them are those found in the S.W. areas of the Durham ɔalfield, which furnish the coke used in the blast furnaces of Durham and Cleveland.

The following are the results of an analysis of a typical first-class Durham coking coal, as freshly won from the seam in large blocks free from dirt :—

		Per cent.	
On the Dry Coal	Carbon	83·75	Volatiles expelled at 900° C. = 26·7 per cent.
	Hydrogen	4·75	
	Nitrogen	1·10	
	Sulphur	1·30	
	Oxygen	7·50	
	Ash	1·60	

It does not, however, follow that coals yielding less than 20 or more than 30 per cent. of " volatiles " at 900° C. have not good coking properties. Some South Wales coals, yielding as low as 15 per cent. of volatiles, give a very dense hard coke. Also, some South Yorkshire, Derbyshire, and Lancashire coals, yielding between 30 and 35 per cent. of " volatiles," are rightly regarded as " coking " varieties, although the resultant coke from them is

somewhat inferior as a blast-furnace fuel to that ...
Durham ... coking-seams.

The most essential qualities needed in a good ...
... apart from low ash content, are a peculiar ...
... and porosity, so that the fuel, whilst ...
sustaining the weight of the superincumbent m...
... at a depth of some 65 or 70 ft below ...
... should nevertheless be sufficiently porous to be both ...
... in the ascending furnace gases and rapi...
... near the tuyere level. It is also imp...
... be as hard and resistant as possible to the ...
... the action of the furnace gases in the ...
... furnace. Indeed Mr C. D. Cochrane, a Cl...
... recently stated, in a paper read before ...
... that the practical success of the ...
... being dependent on the mechani...
... an opinion that will be endors...

... coke is also used (1) as the ...
... crucible steel smelting ...
... low ash content and comparat...

... coke manufactured ...
... was 13.42 million ton...
... million tons of coal were carbo...
... figures are taken after the w...
... of iron and steel in Grea...
... blast furnace must be supplied with at least from 2...
... according to the nature and quality of the ore, ...
... the law ...
... between the furnace gases and t...

... or thereabouts, practically ...
... coke required in the world was m...
... without any a...
... the valuable by-products ...
... at high temperatures. It ...
... the gas industry and t...
... part of the ninetee...
... should have been ...

xx

. " beehive " coke was in every way so thoroughly satis-
ıs a blast furnace fuel, and the ironmaster was so accus-
o its virtues, that he came to regard it with peculiar
ı, and thought that no other kind of coke would suit his
so well. Actual experience, however, has now proved
:judice to have been quite unfounded.

THE BEEHIVE OVEN

old beehive oven (Fig. 39) consists of a fireclay chamber
cular in section with a floor sloping slightly from back
nt, covered by a domed roof, and provided with (1) a door,
the floor level, (2) a passage, B, under the arch of the roof
ıg into the chimney flue, D, and (3) a hole, E, at the top
ıe roof communicating with the outer atmosphere, which

Fig. 39.—Old Beehive Oven.

ıay be used for charging the oven, but is always closed during
he greater part of the coking period.

In working the process, a charge of ten tons of coal is either
introduced through the door, A, or is dropped into the oven from
tubs running on a railway above through the charging hole to a
height of from 2½ to 3 ft. above the floor. The coal is then
ignited, and the door bricked up and plastered, except for a few
holes about one inch or more in diameter in one or two of the upper
courses of the door bricks which are left open for the admission
of air. The ignited coal burns, and the heat so liberated sets
up distillation in the under layers. The volatile products so
expelled, rising through the decomposing mass, catch fire and
burn in the dome of the oven where they meet with the air drawn
in through the door. The dome is thus soon heated up to a high
temperature, and by radiation powerfully assists in carbonising

... large ... below. Eventually, after ...
... when all the volatile matter has been ...
... the bar is ... and the coke que...
... in the oven ... after which it is ...
...

... will be seen that inasmuch as the wh...
... matter expelled from the coal is burnt ...
... the coking heat the ... surrounding produ...
... is the coke itself. And even part of it, usu...
... ... as burnt in the ... The burnt p...
... chimney at a high temperature and are or...
... except in the case ... batteries of ovens...
... an evaporative power equal to the conve...

... —Simon and Dixon's Coke Ovens (Sectiona...

... "steam" from and at 212° F...
... Altogether the process is ...
... ... and would never have survived...
... ... the fact that it did and alter...
... ... which, as a blast-furnace...
... ... high price.
... ... Simon and Dixon designed an...
... ... shown in Figs. 40 and 41...
... ... together with any ga...
... ... started away, through op...
... ... under the floor, which w...
... ... that these improvement...
... ... period, but also...
... ... And in the ...
... ... these ovens at a ...

. it was found that the coking period was reduced
 48 hours, and the coke yield increased from 58 to
 it.[1]

 designs of rectangular ovens, with arched roofs, were

Fig. 41.—Breckon and Dixon's Coke Ovens (Plan of Four, partly in
Sections).

(By permission from Phillips and Bauerman's *Elements of Metallurgy*.
Charles Griffin & Co.)

proposed about this time, chiefly with a view to allowing the
entire charge of coke to be withdrawn from the oven previously
to its being quenched, thus avoiding cooling the oven suddenly
wi r at the end of each carbonising period.

Bauerman, *Elements of Metallurgy*, 2nd ed. (1887), p. 80.

EARLY ATTEMPTS AT BY-PRODUCT

As long ago as 1850 M.M. Pauwels and [...] [...] Pauwels invented a system of [...] [...] rectangular chambers heated from [...] [...] part of the gas in flues specially [...] the flue, with the object of recovering tars, [...] and producing not only coke suitable for [...] [...] purposes in greater proportion than in the [...] [...] gas for burning and heating.

[...] system which is shown in plan and [...] [...] was a rectangular chamber 3 [...] [...] which had a charge of 6 to 7 tons of c[...] [...] the floor was carbonised by [...] the fire underneath the floor either by the b[...] [...] a furnace built into the setting, or by [...] The gas in the said grate and flues [...] [...] products evolved were [...] working arrangements, whereb[...] [...] were [...] and the gas, or any st[...] [...] the coking heat, could [...] through the public mains or be utilise[...] for heating purposes. At the end of the carboni[...] [...] happens in a steam ram which trave[...] [...]

[...] that [...] in some respe[...] system [...] was in some by-product coking [...] certainly it [...] a quality of coke [...] furnace purposes owing to [...] relatively thin layer in the floor [...] inoperative arrangements n[...] [...] The system was tried in [...] but the coke produc[...] [...] other pioneering att[...] [...] very with coke m[...] [...] those who made them [...] [...] by-products to ob[...] [...] hard coke. H[...] [...] part of tenn[...] [...] years was in [...]

FIG. 42.—Permolet's Coke Oven (Horizontal Section at Different Heights).

(From Phillips and Bauerman's *Elements of Metallurgy*.)

305

... mainly the outcome of the independent
... technologists, MM. Evence Coppée and
... whose inventions in this connection date back
... introduced, as an improvement upon the old
... "non-recovery" narrow rectangular oven in
... ge of coal was carbonised at high temperatures,
... urning the resulting gases and volatile matter
... ies into which was also admitted, under proper
... cessary air supply. The coke was subsequently
... the oven *en masse* by a ram and quenched outside
... h Coppée ovens were put down in the Sheffield
... 73, and in the following year another sixty were
... outh Wales. Eventually some 20,000 of them were
... ly on the Continent, but largely also in Great Britain
... outh Wales) and the United States, and some of them
... operation. The Coppée Company has developed
... d the original design for by-product recovery purposes
... erative heating arrangements.

... also (1866 to 1873), in conjunction with Knab, adopted
... ple of heating narrow rectangular chambers by means
... mbustion of gas in longitudinal side flues as well as in
... flues, with the object of attaining both higher tem-
... es and a more uniform heat distribution. He succeeded
... in shortening the carbonising period, but also in improv-
... quality of the resulting coke. And when, in 1881, the
... r. Henry Simon, of Manchester, supplemented the Carvés
... by introducing a heat recuperator, whereby the air re-
... for burning the gas in the side flues of the oven was pre-
... d at the expense of part of the sensible heat in the burnt
... ucts from the flues, the Simon-Carvés system emerged as
immediate precursor of the modern by-product oven.

... uring the years 1880–5 several other similar systems were
... ught out in Belgium and Germany, among which may be
... ntioned those of Semet-Solway, Hüssener, Lürmann, Otto and
... runck, with the result that the practice of coking coal in the
... ew types of narrow rectangular ovens, with some form of heat
ecuperation, and of recovering condensable by-products and
ammonia from the gas before it was burnt in the oven flues,
r ... led and developed on the Continent, and soon
l ... universal there.

... iods were, however, very slowly adopted both in
... nd America, in spite of the large profits to be

gained out of by-product recovery, owing mainly
the already referred to against by-product coke
only been gradually overcome as experience dem
groundlessness. It may be said that, except for
product installations here and there in the North
no great headway was made in this country until
of the present century.

With regard to the United States, the British
Commission which visited that country and subs
ported upon " American Industrial Conditions and C
in the year 1902, stated that by-product coke was
unknown in the Connellsville region which supplies
furnaces, although in other districts it was maki
At the end of 1900 there were in the United States
only 1085 by-product ovens built, the output of
coke in that year being no more than 1,075.727 to
total production of 20,533.348 tons (or say 1 in 20).
previously, the proportion of by-product coke had
83 038 out of a total of 11,788,773 tons (or say 0·7

Among the more important technical developme
recent years in connection with by-product cokin
may be mentioned : (a) the substitution of " rege
similar to those employed in open-hearth steel furna
Siemens type, for the older " recuperator," as a mor
means of utilising the serviceable heat of the hot produ
the combustion flues of the ovens, and of increasing th
of gas available for outside purposes; (b) the total r
tar from the hot gases by means of a tar spray at a te
above their dew point, combined with the *direct* re
ammonia (as sulphate) on the main gas circuit; an
recovery of naphthalene which was rendered feasibl
adoption of (b), together with improvements in the re
benzols from the gas

COMPARISON BETWEEN THE BEEHIVE AND BY-PRO PROCESSES

For purposes of showing how much more economic
by-product systems than the older beehive
they have superseded, the author cannot do be
the following data[1] given by his friend, and
the article upon Coke Manufacture and the R
in Thorpe's *Dictionary of Applied Chemistry*

.r. Ernest Bury, M.Sc., formerly of the Brackley Coke and now of the Skinningrove Iron Co. Ltd., who has done a to promote sound knowledge of the subject among manufacturers.

TABLE LXVII

BURY'S ESTIMATE OF THE RELATIVE YIELDS OF PRODUCTS FROM A COAL CONTAINING 30 PER CENT. OF VOLATILE MATTER

Types of Ovens.	Beehive.	By-product.
erating Conditions . .	(a) Coking chamber heated by the combustion of gas and volatiles *within* it. (b) Air admitted into oven. (c) Coke quenched *inside* the oven.	(a) Coking chamber heated *externally* by combustion of gas from which by-products have been extracted. (b) Air excluded from oven. (c) Coke quenched *outside* the oven.
'ercentage ⎧ Coke . . . . Yields ⎪ Tar . . . . in Dry ⎨ Crude Benzol . Coal ⎩ NH_3 as Sulphate	56·0 nil nil nil	70·0 4·0 to 4·5 1·0 1·0 to 1·2
Waste Heat	Usually not utilised, but approximately equal to the evaporation of 0·75 ton of water per ton of coal carbonised.	Always utilised : equal to 1 ton of water evaporated per ton of coal carbonised.
Surplus Gas	nil	2000 to 5000 cub. ft. per ton of coal carbonised.

With regard to the above data it may be observed :—

(1) that the absolute figures given for coke yields apply to a coal supposed to contain 30 per cent. of volatile matter; for a typical Durham coking coal containing 25 per cent. volatiles they would be 65 per cent. for beehive and for by-product ovens.

(2 it of "surplus gas" available depends on transfer of heat from the hot burnt gases

the oven combustion flues ... the ...
... as to the flues is carried out ... ...
... recuperator. Waste Heat ... ...
... ...erators similar to those ... ...
... furnaces . Regenerative Ovens ... ...
... ... the surplus gas does not ... ...
...ereas in Regenerative Ovens ... ...
... ub. ft. per ton of coal carb...
... that the figure for the yield of tar seems ... ...
... North of England Coking Coals ... ...
... and 3.65 per cent. (See Table LXIX .

... ...he rates of prices prevailing before the ... ...
... ...ors estimated the gross and net values of ... ...
... ...arbonised to be as follows :—

	Gross Value			Net ... Re...ent		
	£	s	d	£	s	d
...mmonium Sulphate	12	0	0	2	10	
... at 15s	4	1	0	...	0	
...ude Benzol at 5d.	6	5	0	1	17	...
...er two Tons	£22	6	0	£4	16	...

... ...his estimate the net profit per ...
... ... equal to 3s. 6d., to which shou...
... ...e surplus gas, reckoned at 3d. per ...
... ...bear in mind that a much la...
... ...product than in beehive ove...
... ...antity of by-product coke as a ...
... ... T. C. Hutchinson, Managing ...
... ... who during the past for...
... ...aw experience in smelting Clevela...
... ... recently assured me in writ...
... ...te to by-product coke at the ...
... ...els affected the consumpt...
... ...eel the exceptionally low ...
... ...e Skinningrove furnaces (...
... ... iron produced) of coke ...
... ... ovens from an *unwash...
... ... 10 to 11 per cent. o...
... ...usive proof that " by-...
... ...ive " coke as a blast-fu...

.iis connection, however, it should be understood that
ality of by-product coke varies according to the nature
coal from which it is produced, and therefore that com-
.is made between cokes from different localities are apt to
sleading. Thus, for example, a by-product coke from a
. Yorkshire coal would probably prove to be decidedly less
.mical in the blast furnace than the best " beehive " Durham
although the latter will not be superior to the coke made
the same Durham coal in a by-product oven. What the
er must understand is that there is no longer any ground
supposing that, *from one and the same coal,* " beehive " has
inherent superiority over " by-product " coke as a blast
.ace fuel.

)ne great advantage which the " by-product " possesses over
: " beehive " oven is that by admitting of the compressing of
e coal before it is charged into the oven, it enables inferior
.alities of coal, which it would be impossible to coke with good
sults in a beehive oven, to be utilised for the manufacture
f a satisfactory metallurgical coke. This applies particularly
ɔ Scottish coals, but compressing any coal of inferior coking
»roperties before charging it into the oven will always be found
to improve the quality of the resulting coke, making it harder
and denser. Such compression is best done with a " washed "
coal, because a moisture content of not less than 9 per cent. is
necessary to ensure the cohesion of the small particles of crushed
coal in a solid block or " cartridge " so that it does not fall to
pieces when being pushed into the oven.

PROGRESS IN THE BY-PRODUCT COKING INDUSTRY IN GREAT BRITAIN SINCE 1900

As already stated, by-product recovery methods made sur-
prisingly little headway in this country until the beginning of
the present century, but from about the year 1903 progress
became much more rapid, as the following figures indicate :—

British By-product Coking Plants.

Year.	Estimated Mill. Tons of Coal Carbonised.	Tons of Ammonium Sulphate Produced.	No. of Beehive Ovens in Operation.
1903	1·75	17,435	—
1908	6·45	64,227	—
1913	13·38	133,816	13,162
1916	14·60	159,506	6,892

... ...ed behind Germany in the pr...
... ...date in coke ovens during the first ...
... ...be apparent from the ... with figures ...
... ...of Aachen,[1] a... it may be ...
... ...in this respect was in some measure ...
... much larger dimensions of our coke-ens ...

Ammonium Sulphate ... ...
by Carbonising Coal in

	Coke Ovens.		Gas ...	
	Gt. Britain.	Germany.	Gt. Britain	...
.	10	80	145	:
.	18	111	152	.
.	44	200	200	:
.	75	278	...	.

... ...able that at the present time about th...
... ...al carbonised for metallurgical coke is ...
... ...dealt with in by-product ovens, and su...
... ...imparted by war conditions, that the ...
... ...coming when the old beehive ovens w... ...
... here as they have been for so many year...
... and Germany.

... ...vember 1917, about 8700 by-product ...
... ...in operation in the United Kingdom, w...
... ...ising capacity of 17·5 million tons of ...
... about 3500 were of the regenerative ty...
... with benzol recovery arrangements. A ...
... ...re were in course of construction, all of th...
... ...reeable that before long the number ...
... be as large as 10,000, with a total ...
... ...ion tons of coal per annum. Indeed ...
... ...ing the war, together with the fact ...
... of our plants are of the most recent ...
... ...t hoping that our *coking industries* ...
... ...wed to **fall** behind those of the ...

c...
tl...
It i...
coke ...
Co...
fuel ...
the Sk...
acquired ...
with Durh...
change over ...
Works has ...
the blast furn...
during ...
cur...
C...
(
;

... above-mentioned 20 million tons
... regenerative by-*product ovens*
... and *net* values of the by-product

... ...since 1910.

Coal No.	1	2	3	4	5	6	7	8	9	10	11	12	13	14
Origin	Scotland, Stirling	Scotland, Dumfries	Durham	Durham	Durham	S. Yorks.	S. Yorks.	Lancs.	N. Staffs.	S. Staffs.	Wilts.	Monmouth.	S. Wales, Glam.	S. Wales, Glam.
Yields of:[1] Ash	2·06	5·47	8·30	6·00	6·00	7·00	4·17	7·65	5·50	7·10	3·91	8·37	4·51	8·45
Volatiles	23·50	32·46	27·97	21·38	24·15	29·25	27·33	26·71	25·80	33·04	24·50	21·17	20·0	18·71
Gas	12·0	11·5	12·0	11·2	11·6	11·0	11·6	11·5	12·15	11·1	12·4	11·0	11·2	11·0
Tar	3·34	5·25	4·22	3·46	4·22	4·07	3·82	2·78	4·15	5·39	5·60	2·93	2·47	2·58
Ammonium Sulphate	1·59	1·68	1·59	1·13	1·58	1·35	1·39	1·83	1·54	1·67	1·23	1·09	1·04	1·01
Coke { Description	Hard	Hard	Dense and Very Hard	Dense and Very Hard	Hard	Hard	Hard	Hard	Hard	Hard	Hard	Dense, Strong Hard	Very Hard	Very Hard
% Sulphur	0·78	1·01	—	—	1·33	1·22	1·72	—	1·85	—	—	1·13	0·925	—

[1] Expressed in percentages, except "Gas," which is in thousands of cubic feet at 15° C. and 760 mm. per ton of dry coal.

· and surplus gas, based on pre-war standards, would be as follows :—

	Gross.	Net.
	£	£
600,000 tons of Tar at 18s. . . .	540,000	480,000
220,000 tons Ammonium Sulphate at £12	2,640,000	2,100,000
60 Mill. Galls. Crude Benzol at 5d. .	1,250,000	875,000
100,000 Mill. Cub. Ft. of surplus gas at 3d.	1,250,000	1,250,000
Total =	£5,680,000	£4,705,000

With regard to America, it has been reported [1] that, at the end of 1915, there were in the United States 6268 by-product coke ovens already built, and 1191 more in course of construction. And in a paper read by T. C. Clarke before the New York Section of the Society of Chemical Industry in 1916,[2] it was stated that as soon as all the new ovens then being built were in full operation, the possible production of by-product coke in the United States would amount to 24 million tons per annum, although it was admitted that neither tar nor ammonia recovery then had become so good as in either Great Britain or Germany.

BRITISH COKING COALS

Fortunately for the prospects of our metallurgical industries, we have in this country a wide range of good coking coals, although the probable supplies of the very best kinds are not unlimited, a circumstance which should make us all the more careful to use them economically and to the best advantage.

In Table LXVIII are recorded the results of comparative Laboratory Trials of a number of a series of fourteen representative British Coking Coals, which may serve to indicate their *relative* values.

Finally, the average yields of coke and by-products actually obtainable from British coking coals of different origin by the most up-to-date recovery methods may be taken to be approximately as follows :—

[1] *Iron and Coal Trades Review*, Feb. 1917.
[2] *Metallurgical and Chemical Engineering*, 1916, Vol. XIV., p. 502.

TABLE LXIX

ᴛᴀɢᴇ Yields, Calculated upon the Weight of Dry Coal Carbonised, Obtainable from British Coking Coals

gin of Coal.	Coke.	Anhydrous Tar.	Crude Benzol.	Refined Benzols.	Ammonium Sulphate.
ham . . .	75·0	3·85	0·93	0·56	1·16
Yorkshire . .	70·0	3·62	1·37	1·00	1·35
ncashire . .	70·0	3·50	1·20	0·84	1·25
Wales . . .	80·0	2·62	0·60	0·35	0·95
otland . . .	68·0	3·25	0·70	—	1·00

MODERN BY-PRODUCT COKE OVENS

The modern by-product coke oven is a rectangular chamber om 30 to 33 ft. long, 6 to 9 ft. high, and from 17 to 22 in. wide, ith side and bottom heating flues. It is closed at each end by cast-iron or steel firebrick-lined door, which is lifted by a small rane whenever the contents of the oven are discharged. There xe usually three equidistant circular holes in the roof through which the coal is charged into the oven from hoppers, and into a fourth hole near the front is fitted an iron " ascension pipe," through which the gases and volatile matter expelled during the carbonising period are led into the tar-sealed " hydraulic main " which runs along the whole battery of ovens much as in gas-works practice (*q.v.*).

In most British and Continental plants the oven linings and combustion flues are constructed of special bricks which are manufactured from a mixture of a high-grade fireclay and some siliceous material such as ganister. The finished bricks should contain not less than 80 per cent. of silica, upwards of 14 per cent. of alumina, not more than 2 per cent. of iron oxide, while the alkalies should be less than 1·3 per cent., and the lime and magnesia each less than 0·5 per cent. In the United States, silica bricks containing 92 to 96 per cent. of silica, 2 to 3 per cent. of alumina, and 1·3 to 2·5 per cent. of lime, are extensively employed on account of their superior heat conductivity. Such highly siliceous bricks, however, have so far not been favoured by British coke manufacturers, who consider that a more aluminous brick is more durable, especially with coals whose moisture content, when charged into the oven, exceeds about 7 per cent.

The design of the side-heating flues varies in different ovens;

315

in the Simon-Carvés (waste-heat), Semet-Solway, Hüssener, and Simplex, they are horizontal, whilst in the Coppée, Koppers, Otto, and Simon-Carvés (regenerative), they are vertical. Also the details of the arrangements for distributing and burning the gas (after all the condensable products and ammonia have been removed from it) in the heating flues vary in the different designs. In all cases, however, the air required for combustion is pre-heated, at the expense of part of the sensible heat in the burnt gases passing away from the ovens, before it enters the combustion flues.

The ovens are built in batteries of from 25 to 60 units. Each oven carbonises a charge of about 8 to 12 tons of coal in from 28 to 36 hours, and a battery of 60 ovens will take about 2500 to 3000 tons of coal and produce from 1750 to 2200 tons of coke per week.

The method of charging the ovens depends upon the nature of the coal. In most cases small slack or crushed coal from which the " dirt " has been removed in a " washery " is used, and it is important from the point of view of heat economy that it should be drained until its moisture content has been reduced to below 6 per cent. before being charged into the oven, excepting where the coal is to be compressed, when the moisture can only be reduced to 9 per cent.

The hard coking Durham or Welsh coals are usually allowed to flow loosely from the hoppers into the oven through the aforesaid holes in the roof, the charges being subsequently levelled by a mechanical device introduced through one of the end doors. In the case of the less strongly coking coals of S. Yorkshire and Lancashire, the crushed coal is compressed by a mechanical stamping machine in a wrot steel box slightly less in size than the oven chamber, and thrust *en bloc* into the oven as a solid cartridge through the front doorway on the movable bottom of the box which forms the charging peel. At the end of the carbonising period the coke is discharged from the ovens by an electrically driven ram on to a sloping bench where it is quenched by water. Plate IV is a back view of a battery of Otto ovens, showing the coal bunker, hydraulic main, quenching apparatus, and the sloping bench in which the quenched coke is drained.

It is of the utmost importance that the heating of the ovens should be uniform, and that after the introduction of a fresh charge the temperature of the coal should be raised as rapidly as possible. And inasmuch as the heat is applied from both of

PLATE IV. Back View of a Battery of Otto Coke Ovens.

side walls of the oven the charge is carbonised from each towards its middle plane.

or details of the design of the principal coke ovens used ireat Britain the reader is referred to the late Mr. G. Stanley >per's book on *By-product Coking* (Benn Bros. Ltd., London, 7). Through the courtesy of his publishers the author is .e to reproduce here the following diagrams of the Otto generative and Waste Heat ovens respectively (Figs. 44 to 47 :lusive), as typical examples of modern coke-oven construc-n, which, together with the foregoing descriptive matter, will, is hoped, enable the reader to understand the main features the general design.

DIRECT RECOVERY SYSTEMS

Up to a few years ago coke-oven engineers were content to ollow the main lines of the older gas-works practice in regard o the arrangements for the cooling of the gas, the condensation und removal of tars, and the recovery of ammonia (as sulphate) from the crude products. The first attempt to depart from these lines was made by F. Brunck of Dortmund, who endeavoured to absorb the ammonia by a " direct " method, on the main gas circuit, by passing the hot gases through sulphuric acid. But inasmuch as he did not first of all remove the tar, he was unable to make a good salt, and his efforts came to nothing.

Koppers's Process.—Subsequently H. Koppers of Essen devised a " semi-direct " process for the recovery of ammonia, in which, after condensing all the tars and much of the moisture from the gas, the latter was passed (1) through pipes externally heated by hot waste gas from the oven in an apparatus (called the heat exchanger) in order to raise its temperature well above the dew point, and thence (2) direct into a " sulphate saturator " containing sulphuric acid, into which was also passed the ammonia distilled in the ordinary way by means of steam and lime from any liquor made in the condensers. In this way all the combined and " free " ammonia in the gas leaving the ovens was converted into sulphate in a saturator on the main gas circuit. And inasmuch as (1) the gas passes into the saturator at a temperature well above its dew point and (2) the reaction between the ammonia and sulphuric acid in the saturator is exothermic, dilution of the liquor in the saturator may be prevented so that the separation of solid ammonium sulphate may proceed continuously.

317

Fig. 44.—Section through Otto Regenerative Oven.

318

FIG. 45.—Section through Wall of Otto Regenerative Oven.

319

Fig. 42. Section through the Abbey Heat Oven

Fig. 47.—Section through Wall of Otto Waste Heat Oven.

THE OTTO DIRECT RECOVERY PROCESS

A further advance was made by the Otto-Hilgenstock Company of Dahlhausen in their new " Otto Direct Recovery Process," of which an outline will now be given. Briefly, it consists in extracting all the tar from the hot gas above its dew point, and then forcing the tar-free gas, without any re-heating, through a saturator in the main circuit containing dilute sulphuric acid, under conditions such that the natural heat in the gas, aided by the exothermic interaction of the ammonia and sulphuric acid, keeps the volume of the absorbing liquor constant so that the separation of ammonium sulphate proceeds continuously.

Such a method of " direct recovery " entirely dispenses with the use of water coolers, ammonia scrubbers, lime mixer and ammoniacal liquor stills, and waste liquor tanks, reduces the loss of ammonia to a minimum, economises space and labour, and avoids the making of deleterious effluents which formerly were such a serious source of trouble.

The process is represented diagrammatically in Fig. 48. The crude gas leaves the ovens by means of the usual ascension pipes and thus enters the hydraulic main through which tar is continuously circulated, in order to remove any heavy tars or pitchy matter deposited therein. From this point the gas travels through a long horizontal overhead " air cooler," A, whose real function is to cool the hot gas down to a temperature just a little above its dew point, which naturally varies according to the amount of moisture which the gas carries over with it from the ovens. The amount of cooling necessary therefore depends somewhat upon the nature of the coal, but chiefly upon its moisture content when charged into the ovens.

Recovery of Tar and Ammonium Chloride.—After leaving the air cooler, the gas passes on to the " tar extractor," B. It is here met by a large volume of hot tar and liquor which is pumped into the apparatus and forced " injector-wise " through a narrow nozzle under a high pressure, in such a manner that it is broken up into a fine spray. The crude gas is drawn into the apparatus by this " injector " action, and the sprayed tar and liquor dash against the small tar vesicles contained in the gas. This mechanical spraying of the gas, together with the solvent action of the washing medium, results in the complete removal of tar, including tar fog, from the gas, which passes out of the extractor

PLATE V.

PLATE VI.—Otto Saturator.

a perfectly clean condition. Also, it should be noted that if " salty " coal is being carbonised, so that the crude gas contains nmonium chloride, the latter may be removed at the tar >rays as a fairly strong aqueous solution. Indeed, " fixed mmonia " generally may be removed at this point provided ne temperature conditions are such as will allow of the con-ensation of a small amount of liquor in the apparatus. From his the importance of a perfect control of the temperature of he gas, both in entering and leaving the apparatus, will be inderstood. A photograph of the " tar sprayers," as they are called, is reproduced in Plate V. The tar extracted from the gas overflows into the tar deposit tank, C, which also serves to recover any tars which separate out in the long " air cooler," A, already referred to.

Recovery of Ammonia.—The tar-free gas, which still contains the free ammonia, benzol, and nearly the whole of the naphthalene and water vapour, passes onwards, at a temperature (say between 65 and 75° C.) so regulated as to be near to (but not below) its dew point, into the large enclosed " saturator " D (see also Plate VI), containing a hot saturated solution of ammonium sulphate *plus* an excess of sulphuric acid. In this apparatus, which is lead-lined and cased in a cast-iron framework, the gas is divided into a very large number of small streams, and, under the suction of an exhauster, K, applied at a point further along the system, it is drawn through the seal of the acid liquor, whereby all the ammonia is removed, and precipitated as sulphate in the coned bottom of the saturator. The exothermic reaction serves to keep the temperature of the gas above the dew point, so that no condensation of steam occurs in the saturator. The salt is mechanically and continuously ejected from the apparatus by means of compressed air, together with a certain amount of solution, into the cone-shaped receiver, E. The ammonium sulphate crystals settle to the bottom of this receiver, whilst the hot mother liquor overflows from the top and finds its way back into the saturator. When this cone-shaped receiver is full of the crystallised sulphate it is passed into a centrifugal dryer, F.

In this machine the sulphate is made thoroughly dry in about three minutes, the mother liquor thus extracted mixing with the above-mentioned mother liquor and with it flows back into the saturator, whilst the dried sulphate of ammonia is dropped through the bottom of the centrifugal machine, sufficiently dry to be immediately bagged and shipped or put into stock, as shown

FIG. 48.—Otto Direct Recovery Process.

Fig. 49.—Otto Direct Recovery Process.

at G, in the diagram. A photograph of the saturator is reproduced in Plate VI.

Recovery of Naphthalene.—The gas from the saturator, which is now freed from both ammonia and tar, but still containing the benzol, moisture and naphthalene, passes through a lead-lined catch pot (not shown in the diagram, but whose situation prevents all fear of any acid spray being carried over from the saturator) and on to the naphthalene extractor and spray cooling tower, H. This tower is quite devoid of any filling or apparatus, but at the top there are several jets through which cold water is sprayed at high pressure. The action of this mass of finely-divided cold water beating suddenly on to the hot gas produces a rapid chill, which, together with the concussion brought about by the water, precipitates and washes out practically all the naphthalene, which flows away along with the water into a catch tank beneath this apparatus. The naphthalene is filtered off whilst the water can be either allowed to flow away, or re-cooled and used over again continuously, as circumstances permit. This tower also serves the purposes of cooling the gases. It is necessary to extract the naphthalene, otherwise it would pass on to the Benzol Scrubbers, where it would be dissolved by the Benzol Wash Oil, which would very soon become saturated with naphthalene and rendered useless for the purpose of collecting benzol. The naphthalene thus extracted is of a pale yellow colour, and is readily sold in this country for 50s. a ton, which more than pays the cost of running this part of the Plant.

Recovery of Benzols.—The gas now being cooled but still containing the benzol, passes through the exhauster, K, and a second water cooler, L, which takes out the last traces of moisture, and thence to the benzol scrubbers, MM, which vary in number according to the size of the plant. These scrubbers are from about fifty feet to seventy feet high, the lower portion forming a reservoir for the circulating benzol wash oil, and the remaining portion being filled with wooden grids. Benzol wash oil is constantly circulated downwards over these grids, the gas having to pass upwards through them. By this means the gas is brought into very intimate contact with the oil, with the resulting absorption of the benzol. After leaving these scrubbers the gas passes either wholly back to the ovens, or in the case of Regenerative ovens, about one half of it returns to the ovens, and the other half is used either for firing boilers, town lighting, operating gas engines, or any other purpose.

A fuller account of the process is given in a paper by Mr. E.

ry before the Institution of Mining Engineers in the year
4. from which the following temperatures of a plant at New
ancepeth Colliery (Co. Durham) are taken :—

	Cent.°		Cent.°
draulic Main . .	225°	In Saturator . .	67°
fore Tar Extraction .	86°	After ,, . .	58°
ter ,, ,, .	58°	After Exhauster . .	66°

Distillation and Rectification of Benzols.—The " Wash Oil "
ntaining the benzols in solution is sent on to the continuous
rude Benzol Still, N. (Fig. 49), where, after being pre-heated
y the hot vapours coming away from the still, it passes down-
ards over a series of trays. Dry steam at about 100 lb. pressure,
educed, however, at the still to 10 lb. pressure, is delivered into
he bottom of the apparatus, and passing upwards bubbles
hrough the Wash Oil liberating the benzol hydrocarbons which
t carries over into the condenser, P. Here the steam and benzols
are condensed, and the condensed water and oil separated. The
crude benzol then either passes into a storage tank, or (if its
rectification is to be carried out) into the " Primary Rectifying
Still," S. The debenzolised " Wash Oil " leaving the crude
benzol still is passed through the Refrigerator, R, whence, after
being cooled down to the atmospheric temperature, it is sent
into the " Oil Storage Tank," T, and from there it is used over
again in the Benzol Scrubbers.

The crude benzol is first of all fractionally distilled in the
Primary Rectifying Still, S, 3000 to 5000 gallons capacity and
intermittent in its working, in which it is heated under high
pressure by means of steam coils, and, with the aid of a long
dephlegmating column, it is separated into :—

(1) Crude 90 per cent. Benzol
(2) ,, 90 ,, ,, Toluol
(3) ,, 90 ,, ,, Xylol
(4) ,, 90 ,, ,, Solvent Naphtha

Each of these fractions is separately condensed and pumped
into a large vessel, V, termed the Agitator, where it is successively
treated with (*a*) pure strong sulphuric acid, and (*b*) a solution of
caustic soda, in order to remove all resinous, basic, or acidic
substances. Each of the " washed " fractions is finally re-
fractionated under reduced pressure in the " Secondary Rectify-
ing Still," W, and the re-distilled resulting fractions, after

[The following two paragraphs are too degraded to transcribe reliably.]

THE COMPOSITION OF COKE OVEN GAS

[Paragraph largely illegible due to page degradation.]

TABLE LXX

COMPOSITION OF COKE OVEN GAS FROM TYPICAL BRITISH COALS WITHOUT BENZOL RECOVERY

	A. Durham	B. Lancashire	C. 50 p.c. S. Yorks. 50 p.c. Derbyshire.
Percentage Moisture	x·o	30·2	—
Type of Oven	Otto-Regenerative	Semet-Solway Waste Heat	Koppers's Regenerative; heated by Mond Gas.
Percentage Composition of the Gas — CO_2	2·5	2·5	2·1
CO	6·5	6·4	7·8
C_2H_4	3·2	3·7	2·9
CH_4	28·0	33·9	30·0
H_2	48·0	49·1	50·0
N_2, etc.	11·8	4·4	7·2
Yield of Gas cub. ft. per ton of Coal	—	—	12,640
Calorific Value of Gas, B Th Us. per cub. ft. at 15° C. and 760 mm. — Gross	536·5	611·3	560·7
Net	475·7	542·9	497·1

[1] See a paper on " Recent Developments in By-product Coking," by Mr. G. Blake Walker. (*Proc. Inst. Civil Engineers*, 1917.)

bemzolised Gas.—The amount of benzol vapours included
ng the unsaturated hydrocarbons C_nH_m in the above Table
ld be approximately 1 per cent. in each case, and the effect
emoving them would be to reduce the calorific value of the
by from 5 to 10 per cent. The average percentage com-
ition of the " debenzolised " gas from typical Durham and
th Yorkshire coking coals is somewhat as follows :—

	CO_2	CO	C_nH_m	CH_4	H_2	N_2	Calorific Values per cub. ft. at 15° C. and 760 mm.
irham	2·5	6·5	2·0	25·0	55·0	9·5	{ 484·6 gross 425·5 net
Yorks	2·4	5·6	2·0	26·4	54·6	9·1	{ 493·6 gross 434·2 net

Amount of Surplus Gas.—Assuming that with regenerative
/ens the surplus " debenzolised " gas per ton of coal carbonised
mounts to 5000 cub. ft. the corresponding calorific values
vailable for outside purposes would be 2,450,000 B.Th.Us.
;ross) and 2,150,000 B.Th.Us (*net*) respectively.

With a battery of sixty such ovens carbonising 1680 tons of
oal per week, the hourly yield of surplus " debenzolised " gas
would be 50,000 cub. ft., at 15° C. and 760 mm., and the corre-
sponding calorific values would be 24,450,000 (gross) and
21,500,000 (net), or sufficient to generate in an internal com-
bustion engine 2150 B.H.P. continuously day and night.

Taking the country as a whole, and assuming that the whole
of the 20 million tons of coal now annually carbonised for metal-
lurgical coke were dealt with in regenerative ovens, the *net*
calorific value represented by the surplus gas available for
outside purposes would be about 5000 million B.Th.Us. per
hour, day and night, throughout the whole year, or sufficient
to generate about 500,000 B.H.P. continuously in internal
combustion engines.

The most effective utilisation of such a huge surplus of energy
is a matter of the highest importance to the nation, and there
is no doubt but that a good deal of the coke-oven gas available
from existing plants is not being used to the best advantage.

So far as the manufacture of coke for the heavy structural
steel trade is concerned, it is now generally agreed that the
best scheme would be to build the coke ovens always on the
same site as the blast furnaces, steel works, and rolling mills,
so that the surplus gas, together with that generated in the blast
furnaces, could be wholly used for power and heating purposes

in connection with the steel works and rolling mills. This aspect of the question will be more fully dealt with in a subsequent chapter.

A large proportion of our by-product coking plants have, however, been erected either (*a*) at the collieries, away from the ironworks, or (*b*) adjacent to the blast furnaces, but away from the steel works and rolling mills. In such cases the surplus gas cannot as a rule be wholly utilised on the spot, and outside uses for it must be found.

Among the more obvious directions in which the surplus gases from such plants can be utilised to good advantage may be mentioned :—

(1) *For Steam Raising and Power Purposes.*—By burning the gases in the tubes of a Bonecourt Boiler, on the principle of "surface combustion," it is possible to transform 92 per cent. of the *net* heat of combustion into the energy of steam which can be either (*a*) converted into mechanical power by means of a steam turbine, or (*b*) used for evaporative purposes in connection with chemical operations. Or, power may be generated from the gases by means of large internal combustion engines, with a thermal efficiency of, say, from 20 to 25 per cent. (*i. e.* from *net* calorific value of the gas to B.H.P. at the engine). And by suitable combinations of either (*c*) boilers, turbines, and dynamos, or (*d*) gas engines and dynamos, electrical energy can be generated at a very low cost. Many collieries now generate from their surplus coke-oven gases (or waste heat) sufficient power to meet all the requirements of the mine. Others, again, sell their surplus gas (or waste heat) to a Power Company, who convert it into electric energy which is distributed for public consumption over a wide area, as in the North East Coast Power Scheme (*q.v.*).

If no Power Company or group of power users is at hand to purchase the surplus gas (or waste heat), it might with great advantage be utilised in an adjacent chemical factory. Indeed, there is no reason why the crude tars, benzols, and naphthalene produced on the coking plant should not be refined and transformed into other more finished products on the spot in the chemical factory, the heat and power from which shall be wholly derived from the surplus gases. Or, alternatively, any chemical operations requiring cheap electric current might very well be carried out in factories erected in close proximity to by-product coking plants.

(2) *As a Heating Gas for Industrial Establishments.*—From

330

...en said in the preceding chapter about the increasing ...ses of coal gas, it will be understood that in districts ...xample, as the Sheffield area) where there are on the ...a large number of coking plants, and on the other ...strial establishments needing large supplies of a high-...ting gas, a scheme for connecting up the coke-oven ...h the works by means of high-pressure gas distribution ...one worthy of consideration.

...*a Domestic Lighting and Heating Supply.*—Coke-oven ...r purification in the usual manner from sulphuretted ...a and cyanogen compounds, is already extensively used ...Germany and in America as a public supply for domestic ...ption. And it is probable that in the near future its ...this country for this purpose will become much more ...nt than it is to-day, especially now that the incandescent ...is so universally employed for indoor gas-lighting and ...he former self-illuminating standards for towns gas supplies ...ing largely superseded by calorific standards. Indeed, in ...onnection it is perhaps significant that in some gas-works ...Vienna and Birmingham) regenerative by-product coke ...s, fired by gas generated from either coal slack or coke ...ze in outside " producers " under ammonia recovery con-...ons, have recently been installed in preference to even vertical ...rts for the production of a combination of good coke, with ...isfactory gas and yields of by-products. And there seems no ...son why coke ovens should not be extensively fired with ...producer gas " made from low-grade fuel, if suitable markets ...r all the high-grade coke-oven gas produced could be found.

In Germany a large number of towns in Rhineland and ...Westphalia are supplied with purified gas from the neighbouring ...oke ovens at prices which are said to be less than 9*d.* per 1000 cub. ft. Also in the United States, the city of Boston, Mass., to mention one centre of population only, has since 1901 been supplied with purified gas from a battery of 100 Otto-Hofmann coke ovens installed at Everett, Mass., and owned by the Dominion Iron and Steel Company. The average yield of gas from these ovens is 10,390 cub. ft. per ton, of which 5143 cub. ft. are available for supplying the city of Boston.

both Germany and America the plan has been adopted of ...ng for town's supply the richer gas evolved during the ...n hours immediately following the first two hours of the ...carbonisation period. For this purpose the hydraulic

331

main, and all the by-product recovery arrangements and connections on the plant are duplicated, so that the richer gas may be separately treated, purified, and sent out for public distribution, leaving the poorer gas made during the first two and the last twelve hours of the carbonising period to be retained for consumption in the heating flues of the ovens.

The first application of coke-oven gas for public lighting in England was made in 1910 when Parliament sanctioned the use of gas from the Brackley Coke Works to the Urban district of Little Hulton (near Bolton, Lancs.), under a guarantee of a minimum illuminating power of 14 standard sperm candles when tested in a No. 2 Metropolitan Argand Burner, and a gross calorific power of 550 B.Th.Us. per cub. ft. at 60° Fahr. and 30 in. pressure. Since that year, however, the Corporation of Middlesbrough has entered into an arrangement whereby the town now draws its entire supply of gas from a battery of Otto regenerative ovens situated at the neighbouring Newport Ironworks of Sir B. Samuelson and Co., Ltd. Also the city of Leeds now takes part of its supply from the Simon-Carvès ovens of the Middleton Estate and Colliery Co., Ltd., and, as already stated, the City of Birmingham Gas Committee has installed a battery of sixty-six Koppers Regenerative Ovens, fired by Mond gas, at their Saltley Works for the production of towns gas and furnace coke.

CHAPTER XVII

THE COMPLETE GASIFICATION OF COAL

PRODUCER GAS AND AMMONIA RECOVERY

INTRODUCTION. THE CHEMISTRY OF THE PROCESS.

FOR the rapid production of gaseous fuel for large furnace opera-
tions, as well as, in some cases also, for power purposes, no cheaper
process has yet been discovered than the complete gasification
of bituminous coal, coke, or anthracite by means of a mixed air-
steam blast (sometimes air alone is employed) in some form of
' gas-producer," whereby the fuel may be converted into a mixture
of oxides of carbon, hydrogen, methane, and nitrogen containing
between 40 and 45 per cent. of combustible constituents. More-
over, by pre-heating the air-blast and adding to it a proportion
of steam corresponding to saturation at 85° C., nearly two-thirds
of the nitrogen in the fuel may be obtained as ammonia, which
may then be recovered as ammonium sulphate, a circumstance
which greatly enhances the economy of the process, making it
one of the most scientific ways of utilising coal.

A modern gas-producer consists of a cylindrical furnace (6 to
12 ft. internal diameter and 10 to 15 ft. high), lined with firebrick,
with an outer mild steel casing, and usually water-sealed at the
bottom. Means are provided (1) for the introduction of the blast
through some form of grate or tuyère fixed immediately above
the level of the water in the seal, and its regular distribution
through the bed of incandescent fuel (usually 3 to 5 ft. in thick-
ness) which rests upon a lower bed of ashes; and (2) for the
charging in of the raw fuel through some form of bell hopper
fixed centrally on the top of the producer, round which are
arranged a number of equidistant poking holes closed by iron
balls. The gas outlet is fixed near the top of the cylindrical
furnace.

Taking as a typical example the case of a producer of 10 ft.
internal diameter, gasifying some 10 cwt. of bituminous coal

333

per hour, with a bed of fuel 3 ft. in effective depth, the chemistry of gasification may be epitomised as follows—

When a fresh charge of coal is dropped into the producer, it first of all undergoes, in the uppermost layers of the fire, a process of destructive distillation, whereby hydrogen, methane, tarry hydrocarbons, oxides of carbon, together with some steam and also small quantities of ammonia and sulphuretted hydrogen, are evolved, probably in much the same proportions as in the high temperature distillation of coal. It seems likely that nearly the whole of the 3 per cent., or thereabouts, of methane usually found in producer gas originates in this way. Olefines and higher paraffins are, however, so rapidly decomposed that they rarely, if ever, appear in the gas passing out of the producer.

The carbonaceous residue (coke) containing, as it does, the whole of the ash and four-fifths of the nitrogen originally present in the coal, is rapidly gasified as it descends through the incandescent fuel bed by the upward flowing air-steam blast, yielding chiefly the oxides of carbon and hydrogen, together with further small quantities of both methane and ammonia.

The blast on entering the bottom layers of the fuel bed almost immediately loses the whole of its free oxygen, and the gases withdrawn from this region invariably contain a considerable proportion of carbon dioxide. This latter, together with the steam in the blast, rapidly attacks the incandescent carbon in the middle portion of the fuel bed, so that if the fuel be of sufficient porosity, and the requisite high temperature be maintained, the gases as they pass into the uppermost layer of " distillation " should consist principally of carbon monoxide, hydrogen, and nitrogen, with only a small proportion of carbon dioxide, or of undecomposed steam. These gases, mingling with the distillation products, make up the crude " producer gas," which passes out of the furnace.

In order to understand better the chemistry of the process, it is necessary to consider separately the well-known interactions between incandescent carbon and air or steam, respectively. For these reactions, occurring simultaneously, are responsible for the gasification of the whole of the carbonaceous residue (coke) in the middle and lower regions of the fire.

A. *The Action of Air upon Incandescent Carbon.*—In a solid bottom producer operated with a *dry* air blast, the initial action of the oxygen upon the incandescent carbon, which may be supposed to give rise initially to the transient formation of a physico-

chemical complex $CxOy$ (*vide* Rhead and Wheeler, Chap. X, p. 171), is rapidly succeeded by the reversible reaction—

$$2 CO \rightleftharpoons C + CO_2,$$

in which the state of dynamic equilibrium is a function of both temperature and of the partial pressures of the CO and CO_2, in accordance with the Le Chatelier thermodynamical equation already considered in Chap. X (*q.v.*). It has also been demonstrated that the time required for the establishment of the equilibrium at the temperatures prevailing in the fuel bed of such a producer (1200° to 1500° C.) is far shorter than the time occupied by the reacting gaseous mixture in traversing the same.

Moreover, from Rhead and Wheeler's experimental researches (*q.v.*), as well as from the aforesaid equation, it is evident that at such high temperatures the percentage of carbon dioxide remaining when equilibrium is established must be very small; so small, indeed, that for all practical purposes the conversion of the " carbon residue " into the monoxide may be regarded as complete, although, theoretically, in no circumstances can the dioxide be entirely absent.

Hence, provided that the temperature in the lower regions of the fuel bed exceeds 1200° C., the principal action of the air blast upon the incandescent carbon may be considered to involve the almost instantaneous formation of carbon monoxide, and the liberation of as nearly as possible 30 per cent. of the total potential energy of the coke, thus—

$$2 C + O_2 = 2 CO \ . \ . \ . \ + 2 \times 29 \text{ K.C.Us.}$$

KARL WENDT'S EXPERIMENTS WITH AN AIR-BLOWN PRODUCER

The nature and sequence of the chemical reactions in a coal-fed air-blown producer are clearly demonstrated by experiments carried out in Germany by Karl Wendt on a dry bottom producer charged intermittently with a suitable bituminous coal, and blown by an air blast without any addition of steam. The fuel bed, which rested upon an ordinary bar grate, had a total depth of 7 ft. 6 in., and in order to ascertain the temperature and composition of the gases at various levels in it, a series of seven holes were drilled through the walls of the producer at regular intervals of 10 in. along a vertical line commencing on a level with the blast pipe. The results showed that not only

did the whole of the oxygen in the blast disappear, but that equilibrium in the system

$$2\,CO \rightleftharpoons C + CO_2$$

was practically established before the asce traversed the lowest 10 in. of the fuel bed.

TABLE LXXI

RESULTS OF KARL WENDT'S EXPERIMENTS WITH PRODUCER

	Height above Tuyères. Inches.	Temp. °C.	Percent o	
			CO_2.	CO.
Rapid Gasification of the Coke by Blast and attainment of equilibrium in the System $2CO \rightleftharpoons C + CO_2$	0	—	15·0	9·7
	10	1400°	0·2	34·1
	20	—	0·2	34·3
	30	1250°	nil	34·5
Distillation of the Coal	40	—	0·4	33·4
	50	1030°	0·6	30·0
	60	—	1·0	28·9
	Gas Outlet	580°	0·7	31·3

From the foregoing it would appear possible such as coke, the combustible part of which is es: with a dry air blast, so as to produce a gas of th

$$CO_2 = 0·2, \quad CO = 34·3, \quad N_2, \text{ etc.} = 65·5 \,]$$

provided that the temperature in the fuel bed v at about 1300° to 1400° C. The chief practical arise out of the fusibility of the ash, which in m cause serious clinkering troubles. These migh overcome by the addition of an amount of lin fuel charge sufficient to form a fusible slag with procedure was, as a matter of fact, adopted by : first " gas producer " erected by him at Audinco 1840 ; the gas obtained, from wood charcoal and co having the following percentage composition—

	CO_2.	CO.	H_2.
Wood charcoal . .	0·50	33·30	2·80
⌐ ⸤ke . . .	0·83	33·53	1·48

Some years ago the same idea was carried out in the **Thwaite Cupola Producer**, which is still in use in some works in the United Kingdom. This producer is of the blast-furnace type, 30 ft. in height, with internal diameter 6 ft. The blast is introduced through a series of tuyères placed horizontally a little above the hearth, and a slag-notch is provided for running off the molten slag formed by the fluxing of the ash of the fuel with the limestone added to the charge. The rate of gasification is rapid, and the gas is of uniform composition and rich in carbonic oxide; moreover, owing to the great height of the producer, it leaves at a comparatively low temperature. Typical analyses of the gas produced from a Lancashire raw slack coal are as follows—

	CO_2.	CO.	H_2.	CH_4.	N_2, etc.
(i)	2·25	28·85	5·80	1·95	61·15
(ii)	1·80	29·20	4·90	2·15	61·95
Average	2 0	29·0	5·35	2·05	61·6

Total combustibles = 36·4 per cent.

Mean calorific value per cub.
feet at 0° C. and 760 mm.
$\left. \begin{array}{l} \text{Gross } 138\ 7 \\ \text{Net } \quad 130·8 \end{array} \right\}$ B.Th.Us.

The objection to such a procedure as the above, apart from the necessity of adding limestone to the charge when dealing with clinkering fuels, as well as from the great wear of the lining of the producer, lies in the fact that the gasification of coke or charcoal by means of a dry air blast means the conversion of at least 30 per cent. of the potential energy of the fuel into sensible heat, which in many cases would be dissipated by radiation before the resulting gas reaches the place where it is to be utilised.

B. The Action of Steam upon Incandescent Carbon.—The best possible way of utilising the heat necessarily generated by the exothermic action of the air-blast upon the incandescent carbon in the producer is to immediately re-absorb it by effecting the endothermic interaction of steam and carbon, thereby increasing the potential energy of the resulting gas at the expense of some of its sensible heat.

The composition of the gas obtained when steam reacts with solid carbon depends chiefly upon the temperature, assuming that the fuel be of sufficient porosity and depth. At comparatively

low temperatures (500° to 600° C.) the chief p.
dioxide and hydrogen, in accordance with the

$$(1) \quad C + 2H_2O = CO_2 + 2H_2 \quad . \quad . \quad -$$

whereas, at temperatures of 1000° C. and upwar
is the production of equal volumes of carb
hydrogen (the so-called " water gas " reaction)
equation,—

$$(2) \quad C + H_2O = CO + H_2 \quad . \quad . \quad -$$

At temperatures intermediate between 600°
products correspond to the simultaneous oc
reactions, the second gradually asserting itsel
ture rises, until, at 1000° C., it almost entire
first.

Both reactions are strongly endothermic, the
the absorption of 19·0, and the second of 29·0 K.
atom of carbon gasified. Hence it is that whe
to the air-blast of a producer the *exothermic* eff
oxygen combustion is partly counteracted by
carbon-steam reaction. The resulting gas is
its hydrogen content notably increased, and mo
energy of the original fuel is transferred to the fi
of gas.

The function of the steam in a gas-produce
absorb part of the heat liberated during the par
tion " of the carbon by doing chemical work, tl
potential energy of the resulting gas at the ex
its sensible heat. Incidentally, also, clinkerin,
fusible ash is greatly diminished by the admix
the blast.

C. *The Influence of the Reversible System* (
+ H_2.—The composition of the resulting ga
affected by the mutual interactions between (*a*)
and steam, on the one hand, and (*b*) carbon diox
on the other, which at all temperatures above !
an active reversible cycle,—

$$CO + OH_2 \rightleftharpoons CO_2 + H_2 \quad . \quad . \quad . \quad \pm$$

In accordance with the laws of mass-action,
·'·imately attain a state of dynamic equilibriu

338

ned in terms of the relative concentrations of the reacting
es and the absolute temperature. Thus we may write—

$$\frac{CO \times OH_2}{CO_2 \times H_2} = K$$

ere K is a constant (the "equilibrium constant"), the numerical
ue of which depends upon the temperature.[1]
On thermodynamical grounds it may be predicted that the
lue of K will increase with the temperature, since the equili-
um in a reversible system must shift with rising temperature
the direction of negative heat change. This conclusion has
en verified by Oscar Hahn in his determinations of the values
" K " for the above system at various temperatures between
6° and 1405° C., as follows [2]—

Temp. °C.	K.		Temp. °C.		K.
786° .	. 0·81	.	1086° .	.	1·95
886° .	. 1·19	.	1205° .	.	2·10
986° .	. 1·54	.	1405° .	.	2·49

As shown some years ago by the author, in conjunction with
Dr. R. V. Wheeler, this reversible system also comes into play,
nd may profoundly affect its composition, when "producer
gas " passes through the hot regenerators of an open-hearth
urnace. For a full discussion of this point the reader is, how-
ever, referred to the original memoir.[3] Suffice it here to say that,
n generating a gas for furnace purposes, care should be taken
not only that the gas *as it leaves the producer* shall have a given
desired composition, but also that it shall be in a hygroscopic
condition conformable with the said composition remaining
unaltered as the gas passes through the furnace regenerators,
where its temperature may be raised to as high a point as 1200° C.

KARL WENDT'S EXPERIMENTS WITH AN AIR-STEAM-BLOWN PRODUCER

The influence of the addition of steam to the blast upon the
temperature distribution, and the chemical interchanges taking

[1] Since the movement in either direction in the system is unattended
by any " volume " change, variations in pressure only at a given tem-
perature would be without influence upon the value of K.

[2] *Zeit. für Physikal. Chemie*, 1903, *43*, p. 705, and *44*, p. 513.

[3] *Journ. Iron and Steel Institute*, 1908; also *Journ. West of Scotland
Iron and Steel Institute*, 1911.

place in the incandescent fuel, is well brought
of another experiment carried out by Karl Wei
fuel and with the same producer as was referr
chapter. In this further experiment, live stear
blast until the latter was saturated at about 6c
were then made of the composition of the gas
tures at different levels of the fuel bed, whi
experiment, was 7 ft. 6 in. in depth, as follows

TABLE LXXII

RESULTS OF KARL WENDT'S EXPERIMENTS WITH AI
PRODUCER

	Height above Tuyères. Inches.	Temp. °C.	Percentage C		
			CO_2.	CO.	CI
Interaction of Air and Steam with Incandescent Coke	0	—	11·4	nil	n
	10	1110°	9·3	22·0	0
	20	—	5·5	28·0	0
Distillation of the Coal	30	925°	3·0	32·7	I
	40	—	5·0	28·7	5
	50	810°	6·0	28·3	4
	60	—	5·3	28·0	4
	Gas Outlet	440°	5·5	26·8	3

Comparing these results with those obtained
ment, where a dry-air blast was used (*vide* Tat
in the first place, that the temperatures at co
in the fuel bed were considerably lowered by
thus we find—

Height above Tuyères.	Dry-Air Blast.	
10″	..	1400°	..
30″	..	1250°	..
50″	..	1030°	..
Gas Outlet		580°

In the second place, owing to this temperatı

s at corresponding levels when steam was used (except just
re the blast entered) contained much more carbon dioxide
less carbon monoxide than when the blast was dry, although
deficiency in carbon monoxide was outbalanced by an increase
he hydrogen, as might be expected. Thirdly, and probably
, in consequence of the general lowering of the temperature,
zone of distillation extended further downwards in the fuel
l when steam was used than with dry blast.

NE AND WHEELER'S INVESTIGATIONS ON THE USE OF STEAM
IN GAS-PRODUCER PRACTICE

The influence of successive additions of steam to the blast of
gas-producer upon the general character and efficiency of the
sification process was thoroughly investigated on a large scale
me years ago by Dr. R. V. Wheeler and the author, with results
hich were embodied in two papers read before the Iron and Steel
istitute.[1]

The plant placed at our disposal for the investigation was
tuated at the Iron and Steel Works of Messrs. Monks, Hall
t Co., Ltd., Warrington, and was of a slightly modified Mond
ype, with arrangements for superheating the blast and saturating
t with steam at any desired temperature. It comprised two
iroducers, each 10 ft. internal diameter (rated capacity =
t6 cwt. of coal per hour), with the usual "superheaters" (*vide*
Mond System) connected with a condensing system in which
the gas was suitably cooled and scrubbed for subsequent con-
sumption in (1) two engines, one of 650 H.P. driving a 10-inch
bar rolling-mill, and the other of 250 H.P. generating electricity;
and (2) gas-fired puddling, swarfe, and re-heating furnaces.

The plant was operated day and night continuously throughout
each working week of between 112 and 136 hours, but, owing to
the fact that the rolling-mill worked during the day-shifts only,
the average rate of gasification during the 12 hours day-time
(about 23·5 cwt. of coal per hour) was nearly double that during
the 12 hours night-shift (10·8 to 13 cwt. per hour). The fuel
used throughout the investigation was washed nuts from the
Florida Seam of the Collins Green and Bold Collieries near Earls-
town, Lancashire. It had been previously screened over a one-
inch linear mesh, and as charged into the producer it contained

---

[1] *Journ. Iron and Steel Institute*, 1907, i, p. 126; 1908, ii, p. 206.

anything between 3 and 7 per cent. of moist contained on the average—

		Per cent.	
Carbon	. .	78·0	⎫
Hydrogen	. .	5·4	⎬ Volatiles at 90c
Nitrogen	. .	1·4	⎭ per ce
Sulphur	. .	1·0	
Oxygen	. .	10·0	Calorific Value
Ash	. . .	4·2	B.Th.Us. per lk
		——	
		100·0	

The investigation comprised altogether ten one exception) extending over a full workin the blast-steam saturation temperature was lowered, week by week in each successive trial, of 5° C. between 45° and 80° C. During each fore, this saturation temperature was kept qι during the interval between two successive ti raised or lowered by 5° C.

In one series of trials (which in point of tim the second) the whole load was put on one of only, which was worked throughout with a be fuel 3 ft. 6 in. deep. The producer gasified tl day-time at 1·47, and during the night-time rated normal capacity. The blast-steam satura beginning at 60°, was between each successive 5° until it finally fell to 45° C. At this last-na however, the fire bars got so hot that the trial ha after 60 hours' duration, it being clear that tl practical working had been reached.

In the other (chronologically, however, the of the producers, each with a bed of incandesce were used for substantially the same load. Tl comparison with the former series, a fire twice a at only half the blast speed, and therefore tha of contact between the ascending gases and fuel would be about four times as long. The bl tion temperature, beginning at 60°, was raisι successive trial by increments of 5° C. up to 80 tions of the ammonia yields at different blast sat tures were made. A comparison between the

TABLE LXXIII

RESULTS OF BONE AND WHEELER'S GAS-PRODUCER TRIALS

	1	2	3	4	5	6	7	8	9	10
Average Depth of Incandescent Fuel	3 Feet 6 Inches					7 Feet				
Average Rate of Gasification (Day-shift) per Hour per Producer	22.5 Cwt.					11.5 Cwt.				
No. of Trial	1	2	3	4	5	6	7	8	9	10
Steam Saturation Temperature of Blast	45°	50°	55°	60°	70°	60°	65°	70°	75°	80°
Carbon Dioxide	2·35	2·50	4·40	5·10	9·25	5·25	6·95	9·15	11·65	13·25
Carbon Monoxide	31·60	30·60	28·10	27·30	20·85	27·30	25·40	21·70	18·35	16·05
Hydrogen	11·60	12·35	15·45	15·50	19·75	16·60	18·30	19·65	21·80	22·65
Methane	3·05	3·00	3·00	3·05	3·45	3·35	3·40	3·40	3·35	3·50
Nitrogen	51·40	51·55	49·05	49·05	46·70	47·50	45·95	46·10	44·85	44·55
Total Combustibles	46·25	45·95	46·55	45·85	44·05	47·25	47·10	44·75	43·50	42·20
Calorific Value of the Gas, B.Th.Us. per cub. ft. at 0° C. and 760 m.m. { Gross	180·0	178·5	180·8	178·7	175·5	185·6	185·4	177·5	172·0	169·5
Net	170·5	168·7	169·1	166·9	161·0	173·0	172·0	163·3	157·3	154·3
Yield of Gas, cub. ft. at 0° C. and 760 m.m. per ton of Coal	133,700	132,500	132,700	135,000	—	138,250	134,400	141,450	145,800	147,500
Steam added to Blast, lbs. per lb. Coal	0·2	0·21	0·32	0·45	—	0·45	0·55	0·80	1·10	1·55
Percentage Steam Decomposed	All	All	All	76·0	—	87·0	80·0	61·0	52·0	40·0

in the trials with a blast-steam saturation ten
in each series showed how very little the qua'
affected by the great difference between thei
rate of gasification.

The general results are reproduced in Table

Whilst the reader must study all the resu'
original memoirs, in order to understand the v
by the investigation, and its many-sided appli
gas-producer practice, its main conclusions m
as follows—

(1) That with an ordinary bituminous prod
is usually employed in the North of England, so
of the total carbon in the fuel is converted ir
(*i. e.* into oxides of carbon and methane). Anc
leaves the producer either as dense tarry hy
soot, and the remaining 1·25 per cent. is lost in
proportions are independent of the steam satura

(2) That with steam saturation temperatun
and including 55° C., the whole of the steam ir
decomposed in passing through the incandesc
depth of which need not exceed 3 ft. 6 in. at
blast dome. As the blast saturation tempera
raised beyond the limit of 55° C. a decreasi
the steam introduced is decomposed, althou
amount decomposed may increase; this is show
table—

Steam Saturation Temp. of Blast. ° C.	Lbs. of Steam in Blast per lb. of Coal Gasified.	Per cent. Steaı Decomposed approx.
45°	0·20	
50°	0·21	100
55°	0·32	
60°	0·45	
65°	0·55	80
70°	0·80	60
75°	1·10	50
80°	1·55	40

(3) That, in accordance with thermodynamic
successive increments in the proportions of stea
the blast, by reason of their increasing cooling

bed, profoundly affect the course of the reactions occurring rein, and consequently also the composition of the resulting .. For the lower the temperatures throughout the fuel bed, more will the interaction $C + 2OH_2 = CO_2 + 2H_2$ displace $C + OH_2 = CO + H_2$ change, and the more also will the uilibrium in the two reversible systems $2 CO \rightleftharpoons C + CO_2$ and $) + OH_2 \rightleftharpoons CO_2 + H_2$ shift towards the right hand. These mbined effects were strikingly reflected (a) in the marked crease in the CO-content, and (b) in the corresponding in- eases in both the CO_2- and the H_2-contents of the resulting as as the blast-steam saturation temperature was progressively iised during the trials. There was, however, no material hange in the production of methane, which as a distillation roduct would only be slightly (if at all) affected by a lowering of the temperature.

(4) That the best " furnace " gas is obtained with a blast-steam saturation temperature of about 50° C. Lowering the steam saturation temperature below this limit had a detrimental influ- ence upon the general working conditions, without any compensat- ing improvement in the quality of the gas, whilst on raising the saturation temperature beyond 50°, the quality of the gas, from the furnace standpoint, at first gradually, and afterwards rapidly, deteriorated, owing to the increasing production of hydrogen at the expense of the more effective carbon monoxide. Moreover, what is of great importance, the proportions of carbon dioxide, carbon monoxide, hydrogen, and steam in the gas generated with a steam saturation temperature of 50° C. will correspond to those in equilibrium at 1200° C., provided that the dew point of the gas leaving the producer is about 20° C., which will be the case unless the fuel charged into the producer is very wet. Hence the gas as generated under such conditions will not alter in composition during its passage through the furnace regenerators.

(5) That the ratio of the net calorific value of the cold gas obtained to that of the coal gasified did not vary very much with the blast-steam saturation temperature throughout the investiga- tion. For if the result of Trial No. 6 in Table LXXIII (where there was reason to suppose that the yield of gas per ton of coal had probably been overestimated by about 2 per cent.) be neg- lected in this connection, the particular ratio in question worked out between the limits of 0·744 and 0·773 in all other cases, with a mean value of 0·76. On the other hand, however, if the thermal value of the steam added to the blast be brought into account,

r w... s.... that the thermal efficiency of the gasi....
..... w... n.. be appreciably affected thereby up to a sa...
... . after which limit, however, there w...
.. a .... Hence it would seem that the condi...
..... w... the best furnace gas is generated are compa...
w... the maximum thermal efficiency, which probably is rea...
w... a ... . temperature within the range 45° to 55 ...

That, as might be expected from theoretical considerat...
the ... of ammonia rapidly increases with steam satura...
temperature, as the following figures show—

Steam Saturation Temperature	60°	65°	70°	75°	&
Ammonia as lbs. sulphate per ... of ... ... gasified	35·0	44·7	51·4	65·25	7...
Proportion of N in the coal recovered as NH₃	0·265	0·304	0·35	0·444	0...

That given a suitable construction of grate and bla...
arrangements a very high rate of gasification—exceeding ...
.... per hour per producer of 10 ft. internal diameter
or ... . 30 lbs. per hour per square foot of fire area)—ca...
be continuously maintained night and day, without detrimen...
..... to the quality of the gas or to the general working con...
...... Moreover it is quite possible to vary the load within
very wide limits without appreciably altering the *quality* of the
gas or impairing the efficiency of the process. A producer which,
with a suitable quality of coal i. e. not strongly caking or clinker-
ing will not permit of such rapid gasification, or variation in
.... without impairing the quality of gas, must be *regarded* as,
... some way structurally defective.

GAS FOR FURNACE PURPOSES

In gas generated for use in furnaces, and particularly of the
open-hearth type as used in connection with the *manufacture*
of glass and steel, it is desirable that the CO-content should be

as high as possible, and that the proportion of hydrogen present should not exceed 12 or 14 per cent. Steel works managers find from practical experience that the most suitable gas for a melting furnace is one containing between 10 and 12 per cent. of hydrogen, and with as high a percentage of carbon monoxide as possible, and the author has found similar views prevalent among glass-makers. Probably the facts that (1) the radiation from a CO-flame is 2·4 times that from a hydrogen flame of like dimensions (*vide* Chap. XIV); and (2) that the rates of back-firing of CO-air mixtures are much less than those of the corresponding H_2-air mixtures, have a considerable influence upon the furnace results, and account, at least in some measure, for the supposed greater efficiency of carbon monoxide as compared with hydrogen.

Moreover, for a regenerative furnace supply, the gas leaving the producer should not only contain a high percentage of carbonic oxide, but should also be in a hygroscopic condition such that the proportions of CO_2, CO, H_2, and H_2O in it shall substantially conform to their equilibrium ratio at the highest temperature in the regenerator (say 1200° C.), as expressed by the equation—

$$CO \times OH_2 = 2·0 \ (CO_2 \times H_2)$$

These requirements would be fulfilled by gasifying a suitable bituminous coal with an air-blast saturated with steam at a temperature of 50° C., so that it leaves the producer plant in a hygroscopic condition corresponding to saturation at 20° C. The composition of the (dry) gas so produced would be approximately—

$$CO_2 = 2·5, \ CO = 30·0, \ H_2 = 12·0, \ CH_4 = 3·0,$$
$$\text{and } N_2 = 52·5 \text{ per cent.}$$

SELECTION OF FUEL

The best "gas-producer" coals are the non-caking or only weakly caking classes yielding (as a rule) 34 to 40 per cent. of volatile matter at 900° C., such as are found in Scotland, Northumberland, Derbyshire, Nottinghamshire, and Staffordshire. A strongly caking coal should, if possible, be avoided, and also one with a large percentage of a very fusible ash.

Anthracites and anthracitic coals, with a low ash content, are often used for small "power" plants, because they yield an almost tar-free gas, and occasion no clinkering troubles. Coke

The ... relative to the gas-producer ... the ... and accurate control of the blast-steam ... temperature ... a suitable form of grate or tuyère ... a rapid rate of gasification, together with ... blast through the fuel bed; (3) the

contour of the furnace body; and (4) the arrangements for charging the producer and removal of the ashes.

Historical.—One of the earliest forms of gas-producers (Ebelmen, 1840) was of the cupola type, in which charcoal or coke was gasified, with a positive blast introduced through tuyères, limestone being added (if necessary) to the charge to flux the ash. In 1845 Ekman, a Swedish ironmaster, designed a furnace and producer combined, for which the fuel was charcoal. The producer itself consisted of a cylindrical firebrick chamber, enclosed in an iron casing, a space being left between the brickwork and the casing through which the air supply was admitted and preheated on its way to the fire.

In 1861 the Brothers Siemens patented their well-known producer,[1] consisting of a firebrick chamber, rectangular in section, the front of which was inclined at an angle of from 45° to 60°, provided with a grate at the bottom, through which a current of air was induced. Below the grate was a trough of water, which, on evaporation by heat radiated from the grate, added a certain proportion of steam to the induced air supply. Subsequently the front of the producer was closed by an iron door, and the air supply forced in under the grate by steam injection. This producer was the first to gasify successfully bituminous coals; it was capable of generating a fairly good quality of gas, but its rate of gasification was low.

In 1876 Messrs. Brooke and Wilson patented a producer consisting of a cylindrical chamber having a solid hearth but no fire bars. The mixed air-steam blast was obtained by steam injection, and was introduced into the fuel bed by means of a box-shaped casting which traversed the middle of the hearth. In 1882 Mr. Wilson patented another form of generator in which the ash and clinker were automatically removed by means of two worm screws revolving in a water seal. Water-sealed producers have now almost entirely superseded the older solid or bar-bottom types.

About the same period (1879–81) Mr. J. E. Dowson succeeded in devising a practical apparatus for generating, cleaning, and cooling producer gas with the object of applying it for small scale-heating (including domestic) operations where taps and burners are used, and also for driving gas engines. In the original Dowson Plant a bed of incandescent fuel (small anthracite) was blown, in a cylindrical generator, by a jet of high-pressure

[1] For use in connection with their new regenerative furnace.

389

PLATE VII.—Dowson 800 B.H.P. Power Plant for Bituminous Coal.

gas outlet is at F. The dotted lines at GG indicate **oles.** Ashes are withdrawn from the water trough at **ntervals** in quantity corresponding to the rate of accumula- **he** furnace. A producer of 10 ft. internal diameter will **o cwt**s. of coal per hour, or about 15 lbs. per sq. ft. of **t.**

SECTION THROUGH WATER SEAL.

FIG. 50.—The Duff Producer.

(2) **The Mond Producer** (Fig. 51) shows the latest form of this well-known producer, which, although designed with special reference to ammonia-recovery practice, is eminently adapted to all working conditions. The chief features about it are : (1) the annulus, A, between the inner firebrick lining and outer steel shell through which the incoming preheated air-steam blast passes before reaching the grate ; (2) the hanging bar grate, B, which takes the shape of an inverted truncated cone, with spaces between the bars for the admission of the blast, an

arrangement which ensures an adequate grate area and a very uniform and effective distribution of the blast in the fuel bed; and (3) the large bell, C, at the top of the producer below the

Fig. 51.—The Mond Producer.

charging hopper, D, which is supposed to expedite the preliminary distillation of the raw fuel. The Mond producer is usually worked with a very deep fuel bed, as indicated in the diagram, but if the spensed with, a much shallower fuel bed may be used

1vantage. In Fig. 52 is shown a similar producer, with an red form of hanging bar grate, which was patented in 1909 author in conjunction with Dr. R. V. Wheeler, as having hown by their investigations to be specially adapted for gasification with a shallow fuel bed. In a producer of this 10 ft. internal diameter, from 20 to 25 cwts. of coal (or 30 to 35 lb. per square foot of fire area) may be gasified our.

The Morgan Producer. — Some years ago considerable

FIG. 52.—The B.-W. Producer.

attention was given to the automatic and continuous feeding of the fuel into producers so as to ensure a more even distribution over the fire-bed, and more uniform working conditions. The "George" feed of the Morgan producer (Fig. 53) was designed to effect this purpose. The essential feature of this device is an inclined and slowly rotating water-cooled feeding-spout, A, fixed immediately under the charging hopper, B, the fuel being continuously forced from B into A by the slowly revolving circular disc, C, working up against the fixed bracket, D. The producer itself is water-sealed and circular in section, but tapering from the middle downwards. The blast is introduced through the central dome, E, and

AA   353

...settling down of the charge.

duoer (Fig. 54) embodied one of the first
r such purpose It consists of a revolving
xed eccentrically upon the foundation, and
ittened top. The cone comprises a number
hich the steam-air blast reaches the fire. The

FIG. 54.—The Kerperley Producer.

ate is fixed in one piece with the shallow iron water trough BB,
hich is continuously rotated at the slow rate of one revolution
very 2½ to 3 hours. The lower part of the producer surround-
ng the zone of active chemical action is water-jacketed, CC,
in order that no incipient clinkers can adhere to the cold side
plate. The slowly revolving eccentric grate disintegrates clinkers
before they attain large dimensions, and, pushing the ashes

355

outwards into the water trough, causes them to discharged.

Several others of the leading makers or produc fully fitted their designs with similar mechanical for the automatic removal of ashes, and they are in increasing numbers on large installations in the like.

(6) **Blowing Arrangements.**—All large gas-prod on the pressure system, either by means of ste preferably, by a suitable fan or blower, stean driven. The pressure required is usually only water gauge, according to the thickness of the f of a blower-produced blast, the requisite stean through a lateral opening into the air duct a fe enters the producer. It cannot be too often un control and adjustment of the steam saturation the blast is of the utmost importance from the efficient and uniform working.

POWER PLANTS AND SUCTION-PRODUC

For the cleaning and cooling of producer gas various arrangements of plant are employed, cor (1) a dust-catching chamber, (2) atmospher usually of annular type, (3) water-sprayed cok scrubbers, (4) water-sprayed fans or tar extract (5) sawdust scrubbers or other equivalent devi of tar fog. A photograph of a Dowson 800 B.H for Bituminous Coal is shown in Plate VI.

For small (up to 200 H.P.) power installation which the blast is induced by the suction of the ("suction producers") are now largely employed or coke as fuel. The first successful attempt to ducer by suction in conjunction with a gas engin Léon Bénier in 1896, who employed a suction pui by side with the engine cylinder and driven by n nection with the fly-wheel axle. Soon afterwar of the engine itself, on the outstroke of the piston, for the Bénier suction pump, thus cheapening coi at the same time reducing frictional losses.

By the year 1901 "**Suction Gas Plants**" were the market, and their use has since steadily exte

as illustrated in Fig. 55) consists of the following essential
(1) a firebrick-lined *generator*, A, of cylindrical section
ch the fuel is gasified by means of an air-steam induced
it. The fuel is introduced through an *air-tight feeding*
, B, which drops it into a *storage and distillation bell*, C,

Fig. 55.—A Suction-Gas Plant.

situated within the generator. The fire rests upon a horizontal
grate under which is a shallow chamber, D, with a solid bottom,
and a lateral opening communicating with the air and steam
supplies. (2) A *vapouriser*, E, fixed either within or without
the upper part of the shell of the generator, in which a regulated
water supply is vapourised, usually at the expense of some of the
sensible heat of the hot gas leaving the generator, or sometimes

357

by the heat of the fire. A [...] F for cooling and washing the gas and [...] which serves the double purpose of a gas [...] and, on the suction stroke, of minimising the [...] suck.

The generator is started up by kindling a [...] grate with a layer of coke or anthracite [...] blown up by means of a hand fan, which is [...] to the apparatus. During the starting-up [...] of combustion are sent into the atmosphere [...] but as soon as a rich enough gas is generated [...] minutes from the start) the engine is started and [...] shut off

A typical "suction gas," generated from gas coke [...] saturated with steam at 51·7°, contained—

$$CO_2 = 5.15, \ CO = 25.45, \ H_2 = 13.10, \ CH_4 = [...]$$
$$\text{and } N_2 = 56.00 \text{ per cent.}$$

its net calorific value being 127 B.Th.Us. per cub. ft. [...] [...]

The thermal efficiency of the gasification, allowing [...] power required to draw the gases through the system, and [...] on the net calorific values of the coke and gas respectively [...] about 85 per cent. The fuel consumption on a suction [...] is about 1 lb. or even slightly less, per B.H.P. developed [...] water consumption for scrubbing the gas being about 12 gal. [...] per B.H.P.

Although the earlier Suction Producers were all designed [...] gasify either anthracite and coke (and for plants up to 200 H.P. capacity this is still recommended) attempts have been made with some success to solve the problem of dealing with bitu- minous coal on the suction principle for power purposes. This is a development which will be watched with interest by all who wish to see power generated from coal more economically in medium-sized units.

AMMONIA RECOVERY SYSTEMS

In the Young and Beilby Patent, No. 1377 of 1882, in con- nection with the distillation of oil-bearing shales, etc., the claim was made for—

" The production of ammonia from coal, shale, ironstone, or

other bituminous or carbonaceous mineral containing nitrogen by decomposing or burning the carbon resulting from the distillation thereof . . . at such a temperature and in the presence of such an excess of steam, either alone or co-mingled with air or with the products of combustion of carbon and air as will burn the carbon and will eliminate the nitrogen contained therein substantially as hereinbefore described."

In a paper by Mr. (now Sir) George Beilby in the *Journal of the Society of Chemical Industry,* in 1884, large-scale experiments were described in which small coal (dross), containing nitrogen equivalent to from 165 to 170 lb. of ammonium sulphate per ton, was fed into the top of a red-hot vertical retort by screw feeders and was there distilled, yielding tar vapours and steam, which on passing downwards through the red-hot coke below were decomposed into permanent gas and ammonia. The gaseous distillation products were taken off through a suitable duct situated about the middle of the retort. The coke passing down into the lower half of the retort was there burnt in a mixture of air and steam ($1\frac{1}{4}$ parts by weight of steam to 1 part of coal). The united gases from the upper and lower regions of the retort were subsequently drawn through condensers and scrubbers, where the ammonia was separated and recovered.

In this way between 60 and 70 per cent. of the nitrogen in the coal was recovered as ammonia (the yields of ammonium sulphate ranging from 90 lb. to 125 lb. per ton of the coal charged), together with a gas, one sample of which contained—

$$CO_2 = 16 \cdot 6, \ CO = 8 \cdot 1, \ H_2 = 28 \cdot 6, \ CH_4 = 2 \cdot 3,$$
$$\text{and } N_2 = 44 \cdot 4 \text{ per cent.}$$

The author of the paper remarked that this composition indicated " a rather excessive air supply, as we aim generally at a consumption of one half of the fixed carbon with air, the other half with steam. With such an admission of air the composition of the gas would probably be—

$$CO_2 = 21 \cdot 32, \ CO = 10 \cdot 72, \ H_2 = 37 \cdot 19, \ CH_4 = nil,$$
$$\text{and } N_2 = 30 \cdot 77 \text{ per cent.}"$$

These experiments, extending as they did continuously over a period of many weeks, clearly demonstrated the possibility of completely gasifying incandescent coal, or the carbonaceous residue formed by distillation therefrom, in a current of air

carrying with it a large amount of steam, so combustible gas together with ammonia equiτ average two-thirds of the nitrogen in the coal.

The Mond System

The final solution of the problem on a comm due to the late Dr. Ludwig Mond, who, in Address to the Society of Chemical Industry iτ described how he had evolved the well-knowτ for generating producer gas from bituminous c conditions which admitted the recovery of as m of ammonium sulphate per ton.

A modern Mond producer has already beeτ p. 351. The best practical results are obtained producer with a blast-steam saturation tempera the mixture of air and steam being preheated tτ before it enters the fuel bed. There is carried in by the blast about 2 lbs. of steam for every 1 lb. ⟨ One-third only of this steam is decomposed, by i carbon in passing through the fuel bed, the ι thirds passing with the hot gases out of the proτ

The outstanding features of the process are ⟨ to the cooling influence of the large proportion τ blast upon the fuel bed, the low temperature inτ

$$C + 2H_2O = CO_2 + 2H_2$$

predominates over the high temperature " water-

$$C + H_2O = CO + H_2,$$

so that the resulting gas has a high hydrogen aτ monoxide content as compared with ordinary] and (2) that for economical working it is neces large proportion of steam leaving the producer shaτ to the system by some efficient recuperative arraτ

From a coal containing between 1·2 and 1·6 per gen, it is possible to obtain up to 90 lbs. per ton sulphate, together with up to 150,000 cub. ft. of ⟨ 760 mm.), of calorific value about 150 gross and 13ξ per cub. ft. at 0° and 760 mm., containing—

$$CO_2 = 17\cdot0, \ CO = 11\cdot0, \ H_2 = 24\cdot0, \ CH_4$$
$$\text{and } N_2 = 45\cdot0 \text{ per cent.}$$

360

A. PRODUCER
B. SUPERHEATERS
C. MECHANICAL WASHER
D. ACID TOWER
E. SETTLING TANK.
F. ACID PUMP

G. GAS COOLING TOWER
H. SETTLING TANK
J. WATER PUMP .
K. AIR SATURATING TOWER
L. BLOWER
M. SETTLING TANK.

N. WATER PUMP.

GAS ——→
ACID ——·——·——

AIR ——————
WATER ——————

FIG. 56.—Mond System of Ammonia Recovery.

According to the original Mond System of Ammonia Re... and steam recuperation, the gas leaves the producer in... charged with steam and tarry vapours at a temperature ... between 500° and 600° C. It then traverses the centra'... of a series of three annular " superheaters," indicated b... the diagram (Fig. 56), each about 20 ft. long. The in - steam-air blast passes through the annulus between the ... and outer tubes in the reverse direction. The temperat... the gas is thus reduced to between 300° and 400° C., whi... of the blast is raised to about 250° C. Further " superheat... of the blast occurs as it subsequently traverses the an-... between the inner and the outer steel casings of the pro... itself.

The partly cooled gas next passes through a long rectan... and water-sealed chamber (the " mechanical washer") ... where it encounters a water spray thrown up by a serie... revolving dashers, by which means dust, soot, and a large amc... of heavy tar are removed, and the gas itself is further cooled : about 100° C. It next passes up the lead-lined scrubbing tow... D, packed with perforated bricks or tiles, down which an an... liquor containing ammonium sulphate *plus* 2·5 per cent. ... sulphuric acid is sprayed, the volume of liquor being so adjuste... in relation to the upward flow of gas that the latter leaves th... tower at a temperature of 80° C. and free from ammonia.

The liquor from the bottom of the tower, D, runs into a... open tank provided with suitable partitions, in order to eliminat... any small quantity of surface tar in it. To the main bulk o... the circulating liquor is added a regulated quantity of sulphuri... acid, after which it is again pumped up to the top of the acid tower, D. A portion of the liqour is, however, removed from the circuit, and evaporated to crystallising point in a special vacuum evaporator heated by means of steam pipes. After separation of ammonium sulphate, the mother liquor is pumped back into the main liquor circuit.

The ammonia-free gas, on leaving the acid tower at 80° C., is passed up the " gas-cooling tower," G, where it encounters a downward spray of cold water, so regulated that, whilst the gas is cooled down to about 60° C., the water is heated up to between 75° and 78° C.

The gas passes thence onwards to the place of consumption, a second water-sprayed cooling tower being previously used in order to cool the gas down to 30° C., at which temperature it

A PRODUCER
B SUPERHEATER
C WASHER CONDENSER

D OUTLET BOX
E LIQUOR TANK
F AIR SATURATING CHAMBER

H OUTLET BOX
K EVAPORATOR
L SALTING TABLE

PATH OF GAS ———→   PATH OF AIR ←————←——

FIG. 57.—The Crossley and Rigby System of Ammonia Recovery

364

FIG. 59.—" Moore " Water-jacketed Producer with By-product Recovery (Elevation).

365

Fig. 58.—" Moore" Water-Jacketed Producer with By-product Recovery (Plan).

FIG. 59.—" Moore " Water-jacketed Producer with By-product Recovery (Elevation).

365

... free from moisture

The Lynn System.—... ... ...
has recently been developed ... ...
is shown diagrammatically ... ...
formed that there are already between ... ...
plants under construction or in ... ...
the world, including two in this ... ...
described as follows —

An ordinary Blower A is used ... ...
(shown thus ------ in the diagram, ...
a vertical static intensive Air-saturator ... ...
which it is brought into intimate contact with ... ...
hot by cooling the gas at a later point in the ... ...
becomes saturated with steam, and after receiving ... ...
supply of steam, it passes into the Superheater ... ...
the air and steam mixture is superheated by means ... ...
leaving the Producer (D). The air and steam mixture ...
passes to the grate of the Producer.

The Producers (D), which may have a mechanical ...
mechanical grate (E), according to circumstances and ...
to be used, are provided with a water seal F), ...
ashes may be removed in the former case automatically ...
the latter manually—without interfering in ...
operation of the Producers. The hot g...
ammonia leave the Producers at the top and ...
heaters (C) and superheat the air and st...
passing (in the opposite direction) to the pr...

368

same time the gases are cooled thereby—thus recovering a great amount of heat. On leaving the superheaters the gases, after passing through special Dust Separating Apparatus (G), enter the vertical intensive static Ammonia Absorber (K), where they are brought into intimate contact with an atomised solution of sulphate of ammonia, containing a small excess of sulphuric acid, which absorbs the ammonia thus produced. The said

FIG. 60 —Lymn Ammonia Recovery Producer Gas Plant

(A) Blower.	(B) Air Saturator	(C) Superheaters.
(D) Producers	(E) Mechanical Grate	(F) Water Seal.
(K) Ammonia Absorber.	(L) Gas Cooler (1)	(M) Gas Cooler (2).
(N) Circulating Vessels.	(O) Fuel Bunker.	(R) Charging Hopper.
	(S) Ash Remover.	

Air - - - > - -   Gas ———→

solution thereby becomes very concentrated and requires very little evaporation for the crystallising out of the solid salt.

From the Ammonia Absorption Apparatus the gases, after being freed from the ammonia, pass into the vertical static intensive Gas Cooler (L), in which they are brought into intimate contact with cooled water. The Gas Cooler and the Air Saturator work in one cycle, the water first passing through the Gas Cooler in order to cool the gas (the water being heated thereby), and then into the Air Saturator in order to saturate the air and again cool the water ready for the Gas Cooler. It will be seen

that by this means a very large amount of ste
from the gas.

⁻ From the Gas Cooler the gases pass to a sec
(M), wherein they are brought again into con
water. The gases are now sufficiently cool and
boilers or furnaces. If for use in gas engines, th
pass through one or perhaps two centrifugal
they are almost entirely freed from tar; from her
ing a special Water Spray Separator), the ga
through a dry Scrubber filled with sawdust or
in which the last traces of tar are removed; the la
are not shown on the diagram. The gas is tl
and suitable for use in gas engines.

The circulating vessels (N) receive the water
the washers, whence they are repumped to the v
the overhead fuel bunker, and (R) the charging
producer. (S) is the automatic Ash Removing *i*

Before leaving the subject of Ammonia Rec
should be made of the enterprise of the Sout
Mond Gas Company, who, from a central genei
Dudley Port near Tipton (a photograph of whicl
in Plate VIII) distribute gas of net calorific valu
per cubic foot at 0° and 760 mm. to various con
industrial area of 123 square miles. The average
before the war was as low as 1¾*d.* per 1000 cub.
equivalent to ordinary town's gas at about 7*d.* pe

In concluding this short review of modern gas-pr
attention may be directed to its importance in 1
problem of the utilisation of low-grade fuels, e
combined with ammonia recovery methods.
adoption within recent years of mechanical d
automatic removal of ashes has enlarged its e
bilities in regard to gasifying non-caking or feebl
containing, or associated with, a large proporti
matter, which could not be treated in a Washer
to subsequent coking.

With an efficient type of generator, properly
is possible to gasify practically the whole of the (
in such a way that the net calorific value of the
when cooled and washed free from tar, shall be
75 per cent. that of the original fuel. Moreover,
of the recoverable ammonia, with a coal contai

PLATE VIII.—Mond Gas Central Generating Plant at Dudley Port, Tipton.

cent. of nitrogen, may amount (on pre-war prices) to from 3s. 6d. to 4s. 6d. per ton of coal gasified. The chief hindrance to the more general adoption of ammonia recovery methods has hitherto been the ground space required by the plant and the initial capital outlay needed; but it is undoubtedly a profitable undertaking where these factors are of subordinate consideration.

In operating on a large scale, and especially in metallurgical or ceramic works, where gas is being generated mainly for furnace purposes, concentration of the gasification in one central battery of producers under proper scientific control is, in the author's experience, an essential condition to the attainment of the best results. The running of such plants is too often left to unskilled workmen under the supervision of a foreman who understands little or nothing about the principles involved. In such cases it is not surprising that the results attained fall far short of what they might be under better direction. In the course of his professional experience the author has sometimes come across cases, and especially in steel works, where, for want of proper scientific control, upwards of 100 tons of coal per diem were being gasified in producers under conditions which mean the needless waste of fully 25 per cent. (and sometimes more) of the fuel consumed. And, so far as this country is concerned, there is perhaps no branch of fuel technology in which the substitution of scientific for rule-of-thumb methods would realise greater margins of improvement than in connection with the generation and application of producer gas for furnace purposes.

CHAPTER XVIII

WATER GAS AND ITS APPLICATIONS

THE need of a cheap gaseous fuel of high calorific intensity for certain industrial purposes (e. g. steel welding) has led to the utilisation of the well-known endothermic interaction of steam and incandescent carbon at high temperatures, discovered by Fontana as long ago as the year 1780.

$$C + OH_2 = CO + H_2 \ . \ . \ . \ . \ . \ . \ - 29 \ \text{K.C.Us.}$$

A mixture of carbon monoxide and hydrogen in nearly equal volumes, which is generally known as " Water Gas," can be easily generated on a large scale by passing steam, preferably super-heated, through a bed or column of coke or charcoal maintained at a temperature of 1000° C. or upwards.

For the process to be made continuous in practice, heat would have to be transmitted, from an external source, through the walls of the reaction chamber (e. g. a retort), made of some suitable refractory material whose heat conductivity would be fairly low. And inasmuch as such procedure would certainly be uneconomical, all idea of adopting it was soon abandoned in favour of an intermittent process, in which the bed of fuel (usually coke) is alternately blown (1) with air, until the whole mass attains the necessary high temperature, and (2) with super-heated steam for so long as the high temperature reaction,

$$(1) \ C + OH_2 = CO + H_2 \ . \ . \ . \ . \ . \ . \ - 29 \ \text{K.C.Us.}$$

(which may be termed the true " water-gas " reaction) can proceed without undue occurrence of the low temperature change,

$$(2) \ C + 2 \ OH_2 = CO_2 + 2 \ H_2 \ . \ . \ . \ . \ . \ . \ - 19 \ \text{K.C.Us.}$$

The influence of (2), which begins to be felt as soon as the temperature falls much below 1000° C., rapidly increases as the fuel bed is further cooled, until at 600° it becomes predominant.

Under conditions prevailing in large-scale practice, it is never

372

possible to exclude altogether the operation of (2); all that can be done is to restrict it within narrow limits. Hence the " water gas " which is generated for industrial uses is never the theoretical mixture of equal volumes of carbon monoxide and hydrogen resulting from the true " water gas " reaction (1), but usually contains at least 3 or 4 per cent. of carbon dioxide, and somewhat higher proportions of hydrogen than of carbon monoxide, because of the simultaneous but limited operation of the aforesaid reaction (2).

The manufacture of the gas on a large scale is always carried out in a " generator " whose form and dimensions are similar to those of an ordinary " dry bottom " gas producer (*vide* the preceding chapter) in which the fuel bed is supported on a suitable grate. Indeed, it may be said that the main difference between the processes of making " producer gas " and " water gas " is that whereas (1) in the former case a mixture of air and steam is passed *continuously* through the fuel bed, in such proportion as will maintain its temperature conditions as nearly constant as possible, so that a gas of uniform composition is *continuously* generated, (2) in the latter case the two gasifying agents (*i. e.* the air and the steam) are admitted *alternately*, each for a definite period, and the products of the action of each are kept separate. In both cases gasification of the fuel goes on continuously, in the first case uniformly all the time, but in the second case in accordance with *alternating* reactions.

THE ORIGINAL LOWE PROCESS

In reviewing the commercial history of water gas, it should be noted that already in 1830 the use of a carburetted gas for illuminating purposes had been introduced by Donovan, but apparently the project was only very short-lived. Also, that in 1849 Gillard devised a system of generating the gas, which embodied the principle of alternately blowing the incandescent fuel with air and steam so as to avoid any external heating of it. Moreover, during a period of nine years ending 1865, the town of Narbonne was lighted by blue water gas in conjunction with mantles or meshes of platinum wire, and in this connection internally heated generators were employed. The use of the gas in Europe seems to have died out altogether with the abandonment of this Narbonne project.[1]

[1] See Prof G Lunge's article on " Gaseous Fuel," *Encyclop. Brit.*, 10th ed. (1902), XXVIII , p. 602.

The later revival and development of water gas a fuel must be credited to the pioneering labours of Strong, and Tessié du Motay in the United Stat early seventies of last century. The first permane achieved in the year 1873, when Lowe introduced Phœnixville. In 1882 a Lowe apparatus was insta

Nothing, however, was done in this country un 1888, when the British Water Gas Syndicate inst Lowe plant in Great Britain at the Leeds Forge embodied the now obsolete idea of, during the " air facturing a low-grade " producer gas " (a mixture of carbon and nitrogen in which carbon monoxide dominating carbon constituent), for furnace purpos a deep fuel bed with an air blast at moderate pi operation was alternated with the usual " steam b production of water gas." The " air blow " occupie and the " steam blow " only 4 minutes, and each to yielded no more than about 34,000 cub. ft. of " wa as much as 140,000 cub. ft. of " producer gas," onlj of the carbon in the fuel appearing in the " water ga:

According to the late Professor V. B. Lewes the of this " producer gas " made during the " air blow

$$CO_2 = 4\cdot0,\ CO = 29\cdot0,\ H_2 = 2\cdot5,\ \text{and}\ N_2 = 64\cdot5$$

so that it could be used as a low-grade furnace gas, the whole cycle of operations thermally more econ might appear at first sight.

THE DELLWIK-FLEISCHER SYSTEM

About ten years later the process was much ir Dellwik and Fleischer, who proposed, during the a heat up a comparatively thin bed of fuel as rapidly by means of a powerful blast supplied in such quantit the carbon as completely as possible to the dioxide.

In the Dellwik-Fleischer system (Figs. 61 and 62), ; by Mr. Dellwik in a paper before the Iron and Ste in the year 1900,[1] the generator is of cylindrical sec firebrick lining encased in a steel shell. The fuel bed in thickness) rests on a flat bar grate on a level wit

[1] *Journ. Iron and Steel Institute*, 1900, I., p. 123

kering bars, and below which are doors for the removal of
es.   The air blast always enters the fuel bed from below
ough a valve, and the products of the " air blow " leave the
erator by the central stack valve, through which also the fuel
harged from a small hopper waggon.

During the " steam blows " superheated steam from a boiler,
rking at a pressure of 150–160 lbs. per square inch, is blown
rough the incandescent fuel bed in either an upward or down-
ird direction, the direction being reversed in each successive

Fig. 61.—Dellwik-Fleischer Water Gas Plant.

blow. Accordingly, there is one " water gas " outlet at the top
of the generator, and another below the grate, each provided with
a valve leading to the annular " superheater," which serves to
effect a heat exchange between the outgoing hot gas and the
incoming steam blast, thus superheating the latter.

At the bottom of the " superheater " is a water seal through
which the gas passes onwards to a coke-scrubber, where it is
cooled and cleaned from dust by means of a water-spray ; from
thence the cold gas passes into a holder. Th   valves
of the generator are operated by an inter¹   which
makes it impossible for the operator to r   or ￼

get an explosive mixture in any part of the pl
water gauges and a test flame on the operating pl
the working conditions in the generator at any m
the quality of the gas during the " steam blow."

The method of working the process is as fc
having been built on the grate, and the generat
proper level with coke, the blast valve is openec
raised as quickly as possible to a high degree of
The products of combustion, which should contair
proportion of carbon dioxide than of the monoxii
to escape through the central stack valve. At ;
of the " air blow," one of the two gas outlets—fc
upper one—is opened, the blast and stack valve
taneously closed by means of a gearing on the
Steam is then admitted to the bottom of the gen
passing up through the bed of incandescent coke
by interaction with the carbon, forming water ga
the temperature of the fuel bed has fallen belov
which carbon dioxide is generated in larger propoi
normal, the steam is shut off, the gas-valve being s
closed and the stack valve opened again. The
then opened for another blow of 60 to 90 seconds.
gas-making period the lower gas outlet is opened,
admitted above the fuel bed, which it then traver:
ward direction. By thus reversing in alternate run
of the " gas-making " current, the temperature oi
is, as far as possible, equalised, and excessive we;
point on the lining of the generator avoided. In nc
each air blow lasts from 60 to 90 seconds, and eac
run from 4 to 6 minutes.

The Dellwik-Fleischer system was investigated
Professor V. B. Lewes, who found that " one thous;
of water gas, containing 15 lb. of carbon, are obl
total expenditure of 29 lb. of carbon, so that over 5
the carbon is obtained in the gaseous form . . . t
in the experiment made contained 87·56 per cent.
1961·3 lb. per ton . . . and this amount yielded
feet of water gas." The latter (average of three a
tained—

$$CO_2 = 4·73, CO = 38·90, H_2 = 51·76, O_2 =$$
and $N_2 = 3·8$ per cent.

376

Fig. 62.—Dempster-Dellwik Water-Gas Plant.

According to Mr. Carl Dellwik, the average composition of the gas produced from coke by the system is approximately—

$$CO_2 = 4 \cdot 0, \; CO = 42 \cdot 0, \; H_2 = 51 \cdot 0, \; CH_4 = 0 \cdot 5,$$
$$\text{and } N_2 = 2 \cdot 5 \text{ per cent.}$$

In a ten-hours test of a Dellwik-Fleischer Plant carried out some years ago under the author's supervision at a large works in the North of England, where the gas was used for steel-welding purposes, the yield of gas per ton of *dry* coke containing $87 \cdot 4$ per cent. of carbon was 61,800 cub. ft. at 0° C. and 760 mm (= 65,200 cub. ft. at 15° C. and 760 mm.), and the ratio of the carbon in the gas obtained to that on the dry coke used was $0 \cdot 505$. The average calorific value of the gas was 321 *gross* and $293 \cdot 1$ *net* B.Th.Us per cub. ft at 0° C and 760 mm., and its average chemical composition was as follows :—

$$CO_2 = 3 \cdot 90, \; CO = 42 \cdot 90, \; H_2 = 49 \cdot 15, \; CH_4 = 0 \cdot 55,$$
$$\text{and } N_2 = 3 \cdot 5 \text{ per cent.}$$

The ratios between the heat units in the gas and those in the coke were *gross* $= 0 \cdot 656$ and *net* $= 0 \cdot 605$. The average duration of each of the " air blows " was 60 seconds, and that of each " steam or gas-making run " was 234 seconds.

The " K and A " System

Another system of water-gas making is that embodied in the Kramers and Aarts patents (the " K and A " system), according to which two generators, A and B (Figs. 63 and 64), connected through a double "regenerator," C, are operated in parallel during the " air blow," but in series during the " steam blow," somewhat as follows :—

During the " air blow " the fires (5 to 6 feet in thickness) in both regenerators are simultaneously blown in parallel by a powerful blast, which is introduced from below. The hot products (CO_2, CO, and N_2), on leaving the top of the generators pass upwards through the " double regenerator," a cylindrical structure filled with firebrick checker work and divided vertically into two chambers or compartments by a central firebrick wall. As the hot products enter in parallel streams at the base of one or other of the two chambers, they meet a secondary air supply sufficient to burn completely all the carbon monoxide which they may contain. The checker work in the chambers absorbs part

of the heat of the burnt gases which eventually make their er into the outer atmosphere through the stack valve, D (Fig. 6) at the top of the double regenerator.

FIG. 63.—Kramer and Aart's Water Gas Producer.
(From Brame's *Fuel*.)

As soon as the fires in the two generators have attained the necessary high temperature, the air and stack valves are shut. and the steam valve simultaneously opened. The steam, entering the base of the first generator, traverses the fire contained therein in an upward direction. The products (CO_2, CO, H_2, and some

378

ELEVATION.   SECTION

SECTIONAL PLAN.

FIG. 64.—Kramer and Aart's (the " K and A ") Water-Gas System.

379

undecomposed steam), passing out at the top, t
direction the two chambers of the " double re,
which they enter, in a highly " superheated " c
of the second generator, through which they pas
direction.

In this way, it is claimed, the gases, just pri
system, come into contact with a bed of higl
carbon, the temperature of which has not been
by the main endothermic steam-carbon interacti
pally occurs in the first of the two generatoi
" steam blows" the direction of the steam and ɛ
in order to ensure the maximum of uniformity
conditions.

The plant (Plate IX) is operated by means oi
valve gear, which prevents mistakes on the part
The hot gas produced passes from the botton
generator upwards first of all through the annula
heater," E (Fig. 64), whereby part of its sensible he
to the in-going steam blast, and then through ɪ
where it is cleaned and cooled by a downward ɪ

Soon after the process had been established
the author had the opportunity of thoroughly ɪ
working in conjunction with steel welding operati
of England. The results of a measured trial,
altogether over a period of 6 hours, may be
follows :—

(1) The gas coke charged into the generator
per cent. of moisture.

(2) The *dry* coke contained—
Carbon = 87·20, Hydrogen = 1·20, aɪ
per cent., and its net calorific value was ɪ
per lb.

(3) Total weight of *dry* coke gasified = 35·45 c
per hour.

(4) Total *dry* gas made, at 0° C. and 760 ɪ
cub. ft. = 21,833 cub. ft. per hour.

(5) The average composition of the dry gas wa
$CO_2 = 3·75$, $CO = 43·70$, $H_2 = 45·10$, C
$N_2 = 6·95$ per cent.

(6) The average calorific value of the dry gas v
and 284·0 net, B.Th.Us. per cub. ft. at 0'

PLATE IX.—"K and A" Water-Gas Installation at Hunslet, Leeds.

The average duration of each " air blow " was 70 seconds. The average duration of each " steam run " was 308 seconds.

ɔm the foregoing figures it follows that—

The yield of dry gas at 0° C. and 760 mm. per ton of dry coke gasified = 73,920 cub ft. = 77,980 cub. ft. at 15° C. and 760 mm.

) The ratio of the carbon in the gas obtained to that in the coke gasified was 0·6065.

) The ratio between the heat units in the gas to those in the dry coke were : *gross* = 0·766, and *net* = 0·705.

t should be observed, however, that the above figures do take into account the energy expended either in raising the am required to generate the gas or in blowing the fuel bed ring the air blows.

From the foregoing descriptions and data, it seems reasonable conclude that the more efficient types of water-gas plants ɛ capable, in regular daily working, of transforming into water .s between 50 and 60 per cent. of the carbon in the coke ɪarged into the generator, and of yielding a gas whose *net* ɪlorific value may be anything between 60 and 70 per cent. ɪ that of the fuel gasified, without counting the energy required ɪther to raise the steam or blowing the fuel bed.

In pre-war days, with coke at 12s. 6d. per ton, the cost of naking " blue water gas " in this country, based upon an assumed ɪield of 70,000 cubic feet per ton, would with continuous running ɔe from 4¼d. to 4½d. per 1000 cub. ft., including fuel, wages, ɪnterest, depreciation, and all standing charges. This would be equivalent to coal gas at from 8½d. to 9d. per 1000 cub. ft. The cost of purifying the gas from sulphuretted hydrogen by means of oxide of iron may be taken at between 0·60 and 1·0d. per 1000 cubic feet.

BLUE WATER GAS

The gas generated from coke by such processes as the foregoing has the following representative composition :—

Carbon dioxide (and H_2S) . .	4·5
Carbon monoxide . . .	43·0
Hydrogen	48·0
Methane	0·5
Nitrogen	4·0

Its density, referred to air as unity, is 0·553 and its *gross* and *n* calorific values, per cub. ft. at 0° C. and 760 mm. are 316·4 = 289·4 B.Th.U's. respectively. It burns with a blue non-luminous flame (hence the name "blue water gas"), and requires rather less than half of its own volume of oxygen for complete combustion (*e. g.* one volume of gas of the above composition would require 0·465 volumes of oxygen or 2·22 volumes of air).

Owing to the fact that the heat capacity of the products *per unit of heat developed on combustion* is comparatively *low* and to the shortness of its flame, its calorific intensity is higher than that of coal gas, and it is well adapted for operations requiring intense local heat. On this account it is much used for steel welding and like purposes.

Its high CO-content makes it a very poisonous gas, and in

Fig. 65.

using it special precautions should be taken to avoid escapes or leakages of it into the workshops. Moreover, on account of its large hydrogen content, its mixtures with air have a rather wide range of explosibility, and are very liable to back fire.

Steel Welding by Water Gas.—The most important industrial application of blue water gas is undoubtedly steel-plate welding and a large industry has grown up, especially in Germany, for the manufacture of welded steel tubes of large dimensions. The overlapping joint to be welded is heated simultaneously from both sides by special burners (Fig. 65) fed with both water gas and air under pressure, which on mingling produce aërated flames of great heating powers. As soon as the joint attains the proper welding heat, it is quickly passed through special rolls which bring about a perfect weld. The gas has also been used in Sweden for small steel melting and re-heating furnaces.

CARBURETTED WATER GAS AND ITS USE IN COMBINATION
WITH PUBLIC SUPPLIES

...wing to the ease and rapidity with which it can be generated ... plant of moderate dimensions, together with its comparatively speaking, low cost of production, water gas has in many ...s past, been largely used ... ... in mixing with ...nary coal gas for public supply.

...ometimes "blue water gas" purified from sulphuretted ...drogen is so used. Thus, one large English gas-works sent out a ...xture composed of 80 per cent. of coal gas and 20 per cent. ...e water gas, having a 14.5 to 15.0 candle illuminating power ...d a net calorific value equal to 5.5 B.Th.U. per cubic ...

Usually, however, it undergoes a process of enrichment with ...seous hydrocarbons, generated by cracking petroleum oil at ...gh temperature, before being mixed with the coal gas. This ...riched water gas, which is really a homogeneous mixture of ...blue water gas" and "oil" gas is generally known as "car-uretted water gas." Its composition depends of course upon ...he proportion of oil used in its manufacture, but the following ...nay be given as typical analyses :—

	1	2	3
Carbon dioxide . . .			
Carbon monoxide . .			
Ethylene and Propylene .			
Benzenes			
Methane			
Hydrogen			
Nitrogen			
Density (Air = 1) . .			—
Candle Power . . .	22		—
Vols. of Air required to burn 1 vol. of the gas			—

The density of the gas (Air = 1) usually varies between 0·57 and 0·75 and, compared with coal gas of equal candle power, it burns with a smaller and more brilliant flame. Moreover, as it contains hardly more than a fifth of the sulphur usually present in crude coal gas, and this almost entirely in the form

of sulphuretted hydrogen, it is readily purified l
treatment only, which is said to reduce the sulph
as low as 5 grains per 100 cub. ft.

In the United States, where the manufactur<
originated in 1885, some of the gas companie<
retted water gas only to their consumers. Ir
mixture of one part of coal or coke oven gas w:
to five, or even six, parts by volume of carburet
supplied. The following figures, kindly furnishe
by Messrs. Humphreys & Glasgow, Ltd., showi
proportion of each gas contained in the publi<
number of the largest American cities, are
interest in this connection :—

City.	Percer Coal Gas.	
Baltimore, Ind.	46·2	. .
Boston, Mass.	44·5	. .
Chicago, Ill.	17·5	. .
St. Louis, Ms.	71·0	. .
Rochester, N.Y.	17·0	. .
Springfield, Mass.	47·5	. .
Washington, D.C.	nil	. .
Worcester, Mass.	61·0	. .
New York and Brooklyn Area . .	13·4	. .

The quality of the gas supplied to these cities,
self-illuminating power and calorific value, is, as a
higher than that which we in England are nowad;
to. Thus the results of the tests made by the
Commission on the gas supplied in New York,
Metropolitan District between January 1 and A<
at various public testing stations in the area wer<

Illuminating Value in Candles.   *Gross Calorific Vc*

No. of Tests.	Max.	Min.	Mean.	No. of Tests.	Max.
3146	27·4	16·9	22·4	2644	750

The following may be given as a represent;
composition of the Carburetted Water Gas manuf
Consolidated Gas Company of New York durin;

384

ws that it contained as much as one-eighth of its volume of
vy hydrocarbons ("illuminants"), and nearly 20 per cent.
methane :—

CO_2.	CO.	H_2.	C_nH_n.	CH_4.	O_2.	N_2.
3·2	27·0	30·6	12·5	19·3	1·0	6·4 per cent.

FIG. 66.—Diagrammatic Section of the Humphreys and Glasgow
Carburetted Water-gas Plant.

In Great Britain, on the other hand, owing to the prejudice
against having a gas supplied for domestic consumption con-
taining more than 16 per cent. of carbon monoxide (which is
regarded as a reasonably safe limit), the proportion of carbu-
retted water gas mixed with the "straight" coal gas rarely
exceeds one in three by volume.

Manufacture.—The accompanying diagrams (Figs. 66 and 67)
represent the well-known Humphreys and Glasgow Plant, which

is now largely used for manufacturing carburei
The generator, A, is worked with a deep bed (
anthracite), and during the " air-blow " the blas;
that the gases evolved from the generator cc
carbon monoxide to make them burn readily.
the generator through successively (1) the carb
(2) the superheater, C, each of which is filled
checker work. At the top of B, and again at tl
the gases meet secondary air streams, by means of
burnt, and the heat developed raises the checker
and C to red heat. The products of combusti
outwards into the air through a stack valve, D, a
superheater.

As soon as the fuel bed in the generator has
the necessary high temperature (3 to 4 minutes),
as well as the stack valve, is closed, and steam is t
bottom of the generator. This, on rising througl
cent fuel, produces " blue water gas," which p;
to the top of the carburettor. Here a petroleum oil
the gas, and passing with the latter over the hot c
the carburettor and superheater, it is successi'
and decomposed into permanent hydrocarbon gas
The resulting mixture of " blue water gas " and " (
out from the top of the superheater and onwar(
through (1) a water-sealed oil heater and wa;
scrubber, F, where it is water-sprayed, and finall
cooled tubular condenser, G. It is afterwards]
usual manner from carbon dioxide and sulphure
by means of lime and oxide of iron.

The " steam run " usually occupies between 5 a
and the alternating " air blow " between 3 and 4 1
checker work of the carburettor and superheater
tained at 750° C. or thereabouts. A small qua
tar (sp. gr. 1·00 to 1·05), consisting chiefly of arom;
bons, separates out in the washer and scrubber.

The coke consumption (including that required
steam) does not exceed 50 lb. per 1000 cub. ft. of ga;
the oil consumption varies with the quality of the ;

[1] This description of the H. and G. Plant has been ab
that given in Dr. H. G. Colman's article on the subject in
tionary of Applied Chemistry, Vol. II., p. 685; the auth(
indebted to Messrs. Humphreys and Glasgow for their cour1
him to reproduce Fig. 67.

FIG. 67.—Humphreys and Glasgow Carburetted Water-gas Plant.

It is usually considered that with good management each gallon of oil used per 1000 cub. ft. of gas will give an illuminating power of 7 or 8 candles, so that to make a 15-candle-power gas, 2 gallons of good petroleum oil per 1000 cub. ft. would be required.

It should also be stated that Messrs. Humphreys and Glasgow have erected many successful blue water-gas plants in different parts of the world.

CHAPTER XIX[1]

FUEL ECONOMY IN THE MANUFACTURE OF IRON AND STEEL

INTRODUCTION

IT is proposed in this and the next following chapter to review briefly the salient features of the problem of fuel economy in relation to the smelting of iron ores in the blast furnace and the subsequent conversion of the resulting pig iron into finished steel sections.

In the year 1913, the total output of pig iron in the United Kingdom amounted to 10·48 million tons, from which the following quantities of steel were subsequently produced :—

			Tons.	
Bessemer	{ Acid	.	1,048,772 }	or 20 per cent. of the total.
	{ Basic	.	551,929 }	
Open Hearth	{ Acid	.	3,811,382 }	or 80 ,, ,, ,,
	{ Basic	.	2,251,793 }	
Total	.	. .	7,663,876	

The amount of fuel consumed in the blast furnace per ton of pig iron produced would obviously depend upon the grade and character of the ore smelted, and therefore would vary in different localities. But from recent information placed at the author's disposal, the average coke consumptions per ton of pig iron from the different ores smelted were approximately as follows :—

Ore.							Coke per Ton of Pig Iron. Cwts.
Haematite	.	.	.	.	.	.	21·0
Cleveland	.	.	.	.	.	.	23·5
Lincolnshire	.	.	.	.	:	.	32·5
Other varieties	.	.	.	.	.	.	28·0

It would also appear from the aforesaid inforn
average coke consumption for the whole Kin£
amounted to about 25 cwt. of coke per ton of pig
And if it be further assumed that the corresponc
coal probably would be 37·5 cwt.,[1] it follows tha·
used in producing the 10·48 million tons of pig ii
1913 would amount to 19·65, or say approximate
tons.

Again, from similar information regarding the
of coal consumed in producing the 6 million tons
steel sections from pig iron, including all the fu
furnaces, soaking pits, rolling mills, and the like, ii
that this probably did not fall far short of 4½
Altogether, taking into account the 1·6 million t·
products from Bessemer steel, the manufacture of
and the coke consumed in iron foundries, it seems
suppose that the total consumption of coal in cc
the manufacture of iron and steel during the ye
would amount to not much less than about 30 mi.

With a view to concentrating attention upon th
it is proposed to leave out of consideration in tl
production of special steels (such as are employed
facture of guns, armour plates, cutting tools, cutl
like appliances), and to confine it to the larger and
problem of how fuel may be economised in the
pig iron and ordinary structural steel, which, of cor
by far the greater part of the total output.

The central and ruling fact which confronts evei
and upon which the whole question of fuel econo
that the natural laws governing the reduction of 1
blast furnace are such as make it practically impos:
within the furnace itself more than about 60 pei
total available energy of the coke charged into it
from the well-known fact of the reversibility at all
within the furnace of the interactions between c£
and the oxides of iron :—

$$Fe_xO_y + yCO \rightleftharpoons yCO_2 + xFe.$$

---

[1] The average yield of coke made in *all* coke ovens in
amounted to 13·422 million tons from 20·145 million tons
over 64 per cent.; the above estimate is, however, b£
assumption that two tons of coke were obtained from thre·

Sir Lowthian Bell's Scientific Investigations upon Coke Consumption in the Blast Furnace

We owe the demonstration of the above cardinal fact to the researches of the late Sir Lowthian Bell, who, following up the earlier work of Bunsen and Playfair upon the actions of the furnace gases upon the descending charge of ore, fuel, and flux, so elucidated the chemistry of the process in all its sequences that he may be said to have transformed blast-furnace practice from an empiric art into a truly scientific process. His treatise on the *Chemical Phenomena of Iron Smelting*, published in 1872, deservedly ranks among the world's metallurgical classics, and will long remain a standard work of reference for all who are engaged in iron smelting.

It is perhaps worth while to recall the circumstances which led Bell to publish his work, and some of the conclusions which he established by it.

The startling results in the direction of economising fuel which had followed the general adoption of Neilson's invention of hot blast in 1828, followed by Bunsen and Playfair's scientific investigations on the composition of the furnace gases at various levels in 1845, led, about fifty years ago, to the building of furnaces of much greater heights and capacities than had ever before been thought practicable. The temperature of the ingoing blast was also progressively raised by the gradual adoption of improved types of coal-fired stoves. And with each successive increment in either furnace height or blast temperature there followed more economy in fuel.

The first six furnaces erected in 1853 for smelting Cleveland ore at Messrs. Bell. Bros., Clarence Works, were each 48 ft. in height and 6174 cub. ft. in capacity. When put into operation with a moderately heated blast, the output reached per furnace was almost 130 tons per week with a coke consumption of nearly 34 cwt. per ton of pig iron. On increasing the blast temperature the output per furnace rose to a maximum of 220 tons per week, whilst the coke consumption fell to about 28·7 cwt. per ton.

In 1865 two new furnaces were added, each 80 ft. high and 15,000 cub. ft. capacity. The immediate result was an increase in the average weekly output per furnace to 310 tons and a drop

in the coke consumption to 23·11 cwt. per toi
1874, four new furnaces were built, each 80 ft.
cub. ft. capacity; the resulting average coke c
to 22·4 cwt. per ton of iron produced, whilst th
rose to between 440 and 470 tons.[1]

Whilst these developments were in progress, ·
gained ground that a progressive increase in fun
in combination with gradually increasing blas
must necessarily result in further fuel econom}
designers of two furnaces erected at Ferryhill, i
Durham, built them 103 ft. high and 33,000 ci
confidently expecting to reduce the coke consum
considerably below what had been achieved in
then 80 ft. furnace. But their expectations were

In the same year Charles Cochrane, a promi
blast-furnace engineer, in a paper before the Societ
Engineers, had gone so far as to express the opinic
*heat might be conveyed into the furnace with the l
ton of iron to be produced from Cleveland stone
coke."*

Bell at once realised that any such notion w
with the results of his own scientific investigatio
had proved beyond all question the reversibilit}
of carbonic oxide upon the oxides of iron. He t
undertook the responsibility, in a paper read befo:
Steel Institute in 1869, of refuting what he consi<
error underlying Cochrane's opinion.

In his subsequent treatise in 1872 he gave
clear exposition of the laws governing blast-fui
and especially of the operation in the furnace c
mass action," a principle which, although origina
by Berthollet in his famous *Essai de Statique Ch*
had been strangely disregarded by chemists untii
a modified form by Guldberg and Waage in 1867.
realised its importance, and assuming 1000° C. t
beyond which it would not be practicable to prel

---

[1] In his *Chemical Phenomena of Iron Smelting* (1872)
that by increasing the dimensions of their furnaces and t
of the ingoing blast, Cleveland ironmasters had already e
equivalent to 1 million tons of coal per annum, exclusi
0·75 million tons which had resulted from their adopting t
tice of using the waste gases from the furnaces for comp
heating the blast.

, summmed up his views upon the whole question in two main
nclusions, namely :—

(1) **that** no advantage can possibly accrue from an increase
in the height or capacity of the furnace beyond the
limits which would permit of the gases leaving the fur-
nace at a temperature of about 300° C., and

(2) **that** the practical limit beyond which the reducing power
of the gases cannot be further utilised in the furnace is
reached when at their point of exit therefrom, and at a
temperature of 300° C., they contain 45 to 50 of carbon
dioxide to every 100 of carbon monoxide by volume.

The fundamental importance of Bell's investigations in rela-
tion to the central problem of fuel economy in the blast furnace
is now universally acknowledged throughout the industry. And
since his main conclusions are founded upon the recognition of
the operations of certain immutable natural laws in the furnace,
it follows from (2) that, no matter how blast furnace practice
may in future change, either in the direction of increasing the
weekly output, or in respect of greater mechanical efficiency,
it will never be possible to utilise more than a certain fraction
(which judging from Bell's experiments would seem to be about
53·3 per cent.) of the total available energy of the coke which
must be charged into it.

With regard to the practical consequences of his experiments,
Bell was led to believe that no further increase in the furnace
dimensions beyond certain limits (which from actual observa-
tions he put at 80 ft. in height and about 16,000 cub. ft. in
capacity) will be conducive to greater fuel economy. And he
expressed the opinion that, " taking the ordinary run of Durham
coal and Cleveland ironstone, the ironmaster who produces a
ton of No. 3 iron with 21¼ cwt. (of coke), with the blast heated
to 500° C., may consider himself as working very closely up to
these limits of economy which are prescribed by the nature of
the materials he is operating upon." And again, in another
place he stated " with some degree of confidence that it is useless
to hope to smelt a ton of grey iron from the Cleveland stone
yielding 41 per cent. of pig metal with anything notably under
20¼ cwt. of coke." And the accumulated experience of the
five years which have elapsed since the conclusion was
may be said to have substantially con its validity

If, then, as Bell's researches seem to show, the *practical working limit* imposed by the proved reversibility of the interaction—

$$Fe_xO_y + yCO \rightleftharpoons yCO_2 + xFe,$$

is reached when the gases, leaving the furnace at about 300° C, contain 50 of CO_2 to every 100 of CO, it follows :—[1]

- 1. that the heat of combustion of the exit gases can never be less than about 47 per cent. of that of the coke charged, and
- 2. that, so soon as the said limit is attained, any further fuel economy in blast-furnace practice must be sought after in the better utilisation of the heat of combustion of the exit gases *outside* the furnace, except in so far as the heat in the molten slag or iron may be so utilised.

Hence the blast furnace, though primarily designed for the smelting of iron ores, is, by virtue of the laws governing its operation, also a producer of combustible gas, which must be utilised to the best advantage for power and heating purposes if the utmost economy in the process is to be attained.

A SUMMARY OF THE PRINCIPAL CHEMICAL CHANGES OCCURRING IN THE BLAST FURNACE

In order that the lay reader may the better understand the drift of the subsequent argument, it is desirable at this point

[1] This statement must not be read as meaning that the *theoretical* equilibrium ratio CO/CO_2 for the temperature at which the gases leave the furnace 250° to 300° C is as high as 50. Indeed, as will be seen in the next chapter, in American practice, where hematite ores are smelted with blast pressure from 12 to 15 lbs. per sq. in., hot blast at 350° to 465° C and exit gases at as low as 160° to 200° C, ratios as low as 1·75 with "normal" blast and 1·25 even with "dry" blast have been attained. What Bell claimed to have established, as the result of numerous experiments, was that, in smelting such iron ores as Cleveland ironstone, the reducing action of the gases at the temperature at which they leave the furnace (250° to 300° C) becomes so extremely feeble when they contain from 40 to 50 of CO_2 per 100 of CO, that the ratio $CO/CO_2 = 2·0$ may be regarded as "*the real practical limit*." And he further argued that any increase in the blast temperature beyond a point at which the gases would leave the furnace at 300° C. or thereabouts, with this CO/CO_2 ratio, would not result in any further economy in coke consumption in the furnace. It is possible that, as the result of future research, the actual limiting ratio assigned by Bell for Cleveland ironstone may be somewhat lowered, although there is no indication in practical working that it will be, but that some limit imposed by natural law is indisputable.

make a short digression with the object of explaining the character and sequence of the principal reactions occurring in the blast furnace. Limitations of space forbid any exhaustive treatment of the subject, nor indeed is any such necessary to the purpose in view; it will suffice if a clear outline of the main phenomena is given. And the case of a furnace smelting calcined Cleveland ironstone with Durham coke will be taken as a typical example of present-day British blast-furnace practice.

A modern blast furnace is shown in section in Fig. 68. The height from the bottom of the hearth to the charging platform may be taken as approximately 80 ft., whilst the greatest diameter at the boshes averages about 22 ft., and the total capacity between 18,000 and 20,000 cub. ft. Such a furnace will, with blast at 5 to 6 lb. pressure preheated to 725° C., produce between 800 and 1000 tons of pig iron (Fe = 92·5 per cent.) per week from ironstone containing, in the raw state 27·0, and after calcination prior to being charged into the furnace 37·0, per cent., of metallic iron.

(A) *The Materials entering the Furnace per Ton of Pig Iron produced are—* [1]

(1) About 56 cwt. of calcined Cleveland ore, containing ferric oxide *plus* a matrix principally composed of silica, alumina, lime, and magnesia.

(2) 15 cwt. of limestone, containing 90 per cent. of $CaCO_3$;

(3) 22·5 cwt. of coke, containing 89 per cent. of carbon;

(4) 138,700 cub. ft. (at 15° C. and 760 mm.) of air as blast, which is preheated to a temperature of (say) 725° C.

(B) *The Principal Changes occurring in the Furnace may be summarised as follows :—* [2]

(1) The fuel is gasified by the hot blast in the neighbourhood of the tuyères, producing a mixture of carbon monoxide and nitrogen.

[1] The data embodied in the calculations in the following paragraphs, (A) to (E) inclusive, are taken from a paper by Mr. T. C. Hutchinson, of the Skinningrove Iron Co, in the *Journ. Iron and Steel Institute*, 1908, III, ... supplemented by later information

... ns in the furnace are actually ... mmary, but for the purposes ... to go beyond the simplest ... cipal changes involved.

Fig. — Sectional Elevation of Cleveland Blast Furnace.
(From Turner and Primrose's *Metallurgy of Iron and Steel*.)

(2) The ferric oxide in the ore is reduced, principally by interaction with the carbon monoxide in the gases, as the materials descend the shaft of the furnace, yielding ultimately spongy iron and carbon dioxide, in accordance with the reversible system—

$$Fe_2O_3 + 3CO \rightleftharpoons 2Fe + 3CO_2.$$

This reducing action begins in the furnace at a temperature of 300° C. and continues up to, and probably beyond, 800° C.

(3) The spongy iron is impregnated with carbon, chiefly as the result of the catalytic decomposition of carbon monoxide at comparatively low temperatures in the furnace shaft—

$$2CO \rightleftharpoons C + CO_2.$$

(4) A certain proportion of the silica and phosphoric anhydride in the charge is reduced by solid carbon at the high temperatures prevailing in the lower regions of the furnace. No doubt also the reduction of the oxide of iron is completed in this way.

(5) The limestone ($CaCO_3$) is decomposed into lime (CaO) and carbon dioxide, principally at temperatures between 800° and 900° in the " upper middle " region of the furnace. The carbon dioxide so liberated mixes with the ascending furnace gases, and participates with them in the changes occurring in the upper regions of the furnace.

(6) The CaO resulting from (5) subsequently fluxes both with the matrix of the ore and with the ash in the fuel, at the highest temperatures prevailing in the lower regions of the furnace, forming the slag, which is essentially an alumino-silicate of calcium.

(7) The incombustible solid constituents of the charge, after undergoing the aforesaid reduction or decomposition in the shaft of the furnace, are all ultimately brought into a state of fusion as they pass through the zone of highest temperature in the neighbourhood of the tuyères, and leave the furnace either as (a) molten pig iron or (b) the slag.

(C) *The Products leaving the Furnace, per To*
are—

(1) 20 cwt. of molten pig iron, containing 92 ɪ
and 3·2 per cent. of carbon;

(2) 35 cwt. of molten slag (CaO = 34·3, MgO =
MnO = 2·1, Al_2O_3 = 25·7, and SiO_2 = 3(

(3) 185,700 cub. ft. (at 15° C. and 760 mm.
temperature of 250° C., containing—

$$CO_2 = 10·0, CO = 30·0, H_2 = 1·0, and N_2 = $$

Its *net* calorific value = 100 B.Th.Us. ɪ
15° C. and 760 mm.

(D) *Heat Account of the Furnace.*

Although as high a ratio of $CO : CO_2$ as 3·
exceeds the practical limit of 2·0, as defined by
more than forty years ago, it is nevertheless typ
day Cleveland practice, which aims at larger weel
furnace than formerly was the rule. Comparing
foregoing conditions, the amounts of energy repr
ingoing coke and hot blast with that represented ɪ
hot gases per ton of iron produced, we get—

(1) Heat of Combustion of 1·125 tons of Coke cc
taining 89 per cent. of Carbon .   .
Sensible Heat in Hot Blast at 725° C.   .

Total ingoing Energy   .   .

(2) Heat of Combustion of 185,700 cub. ft. of G
Sensible Heat in the Gas at 250° C.   .

Total Energy in outgoing Gas   .

It is thus seen that the heat of combustion of th
counting its sensible heat) is equivalent to rather ɪ
of the total energy supplied to the furnace in the
and hot blast, and to no less than 57 per cent.
combustion of the coke.

ourly *Production of Gas in a Furnace making* 1000 *Tons ... ron per Week.*

... nace making 1000 tons of pig iron per week (or, say, ... per hour) under the aforesaid conditions, would produce ... × 6 = 1,114,200 cub. ft. of gas at 15° C. and 760 mm. ... ur. This on combustion would develop 111,420,000 ... Js., and its sensible heat on leaving the furnace at 250° C. ... amount to a further 8,862,000 B.Th.Us., or a total of as ... as possible 120,000,000 B.Th.Us. Neglecting its sensible ... and assuming that in a gas engine the energy developed ... combustion could be converted into mechanical power ... an efficiency of 25 per cent., it would be capable of ... oping continuously—

$$\frac{111,420,000}{2564 \times 4} = 10,864 \text{ B.H.P.}$$

... hen it is realised that the total output of pig iron from ... ish furnaces in the year 1913 was 200,000 tons per week, ... 200 times the output of such a furnace as the above, the ... rmous fuel value of the whole gas production will be ... reciated.

(F) *Comparison of Foregoing Calculations with the Heat Balance a Staffordshire Furnace.*

Although the foregoing figures relate to a furnace smelting alcined Cleveland ironstone, they lead to nearly the same conlusions, as regards the proportion which the energy in the exit ases bears to that of the coke charged, as does the heat balance of a Staffordshire furnace smelting mill cinder at Darlaston published by Mr. W. J. Forster in the year 1904.[1]

This furnace was 72·5 ft. high (capacity 16,000 cub. ft.), and, with blast preheated to 454° C., it consumed 1·46 units of coke (1·285 units of carbon) per unit of pig iron (containing Fe = 90·78, C = 3·5, Si = 3·25, P = 1·49, S = 0·03, and Mn = 1·05) produced. The total make of pig iron amounted to 78·25 tons per day, or 537·6 tons per week. The following figures, summarised from Mr. Forster's results, show the percentage distribution during the smelting process of the energy represented by the total heat of combustion of the coke charged into the furnace.

[1] *Journ. Iron ... te,* 1904, I. p. 314.

UTILISATION OF BLAST-FURNACE G(

Although it is recorded as long ago as 1814
gases from blast furnaces had been employed by
France for making steel by the cementation proc
burning of bricks,[1] it was not until the year 183;
drew attention to the matter, that ironmasters l
the enormous amount of energy daily wasted b
gases to burn as they issued from the furnaces.
it needed the classical investigations of Bunsen uj
gases at Verkerhagen in 1838, followed by those
Playfair at Alfreton (Derbyshire) in 1845, to a
interest in the problem of applying them gei
practical purpose.

Bunsen and Playfair, in their Report to the E
tion at Cambridge in 1845 upon the " Gases evo:
Furnaces," made the following very pointed comr

" Hence it follows that hot-blast furnaces fed
peculiarly adapted for the economy of gaseous ft
be conducted from the furnace and applied with(
interfering with its operations.

" We have already shown, in the very lowest ca
at least 81·54 per cent. of valuable fuel must es
mouth of the Alfreton furnace. Now, as about 1

---

[1] *Vide* Prof. Thomas Turner's book on *Iron* (Griffin
(1900), p. 26.

[2] The Alfreton furnace investigated was 40 ft. high, wi
11 ft. at the boshes, narrowing to 3¼ ft. at the throat, a
was raw coal. Bunsen and Playfair reported the volume
of the exit gases to be as follows :—

$CO_2 = 8\cdot370$, $CO = 26\cdot846$, $CH_4 = 2\cdot536$, $H_2 = 1\cdot126$, (
$H_2S = 0\cdot045$, $NH_3 = 0\cdot058$, and $N_2 = 60\cdot907$ p(

used in that furnace every twenty-four hours, it follows, ording to our experiments, that 11·4 tons of coal are lost ry twenty-four hours by escaping in the form of gases still »able of being used as excellent fuel."

During the following fifteen years some progress was made the direction of utilising the gases, principally for raising .am in boilers, and also to some extent for heating the blast.

1845 J. P. Budd of Ystalyfera patented a stove, for heating e blast, which was fired by the furnace gases, and later on he ccessfully employed them for firing boilers. It is also said .at iron ore was calcined by means of blast-furnace gases as urly as 1852 at Coltness in Scotland. In 1850 G. Parry intro-uced at Ebbw Vale the now commonly used " cup and cone " evice for closing the throat of the furnace, so that the gases, istead of burning to waste, could be conducted away by a wide ube inserted just below the cone to any point where they may »e conveniently utilised.

The independent inventions by E. A. Cowper and Thomas Whitwell, during the years 1860–5, of hot-blast stoves fired by the furnace gases upon the regenerative principle, were not only a great advance upon any previous attempts to utilise the gases, but also enabled ironmasters to preheat the blast to much higher temperatures than had formerly been possible in the old pipe stoves. Fig. 69 shows a Cowper Stove in vertical section. The general adoption of these stoves immediately resulted in much larger weekly furnace outputs, together with a marked decrease in the coke consumption in the furnace per ton of iron produced.

Up to the end of last century no further new departure was made, and the distribution of the furnace gases on a blast fur-nace plant during the period 1875 to 1900 would usually be somewhat as follows :—

(1) 40 per cent. would be used for heating the blast in the stoves ;
(2) 10 per cent. would be lost at the bell ; leaving
(3) 50 per cent. to be used for steam-raising in Lancashire boilers, fitted with special combustion chambers, to drive the blowing engines, furnace hoists, etc.

The utilisation of the gases by such methods was always greatly impeded by the fact that they left the furnace laden with
DD.

dust, some of which was deposited both in the boiler tubes and on the checker-work of the hot-blast stoves, where it hindered

FIG 69.—Cowper's Stove (Vertical Section).
(From Phillips and Bauerman's *Elements of Metallurgy*.)

the heat transmission. Moreover, the gas-firing of Lancashire boilers is at best inefficient.

Steam-raising in Boilers.—It has been estimated that with

e best type of water-tube boiler no more than 54 per cent. of e heat developed by the combustion of the gas was actually ∖ ansmitted to the water, and that the combined efficiency of ιe boiler and steam-blowing engine did not exceed 6·732 per ∷nt. And according to the author's own observations upon ∖ιe utilisation of the gases under Lancashire boilers fitted with ∶onomisers, the efficiency realised under the best working .onditions (*i. e.* using softened water, and after the boiler flues ιave been recently cleaned) does not exceed 60 per cent. of the ιeat developed by their combustion.

Heat Balances of Hot Blast Stoves.—According to an investiga-:ion carried out in 1915 by Mr. R. S. G. Knight (then a research student in the Department of Chemical Technology at the Imperial College of Science and Technology) upon the combustion of the gas in a modern Cowper hot-blast stove at the Skinningrove Ironworks, the heat balance, when working on uncleaned gas entering the combustion chamber at an average temperature of 240° C., was as follows :—

Dr.		*Cr.*	
Sensible Heat in the Gas at 240° C.	7·3	Heat transmitted to Blast	65·9
Heat of Combustion of the Gas	92·7	Heat carried off by Burnt Gases at 366° C.	29·1
		Loss by Radiation	5·0
Total	100·0	Total	100·0

The average composition of the burnt gases was—

$$CO_2 = 15·2, \ O_2 = 7·4, \ \text{and} \ N_2 = 77·4.[1]$$

DEVELOPMENT OF THE LARGE GAS ENGINE FOR CLEANED BLAST-FURNACE GAS

Up to the end of last century, and until the development of the large gas engine for power generation in steel works had brought the recognition of the enormous advantages to be gained by concentrating coke ovens, blast furnaces, steel works, and rolling mills on one and the same site, there was no great incentive for ironmasters to improve the old methods for utilising the waste gases from their blast furnaces. For without any new

[1] *Iron and Steel Inst. Carnegie Scholarship Memoirs*, VII. (1916), pp. 83–99.

departure they could heat the blast, get all the power required for driving the blowing engine and doing other mechanical work connected with a blast-furnace plant, and still have a margin of gas to spare, for which, so long as the plant remained an isolated smelting unit, there was hardly any profitable use to be found.

The advent of the large gas engine, as an adjunct to the blast furnace, at the beginning of the present century suddenly transformed the whole aspect of the industry in regard to power production and fuel economy, and it will now be our business to trace the course of the rapid developments which have followed thereon.

Although blast-furnace managers must long have been aware of the possibilities of the gas if it could be used for power generation in an internal combustion engine, it was not until the year 1895 that any serious attempt was made to realise them in practice. Three *a priori* objections were usually raised, which, taken together, were regarded as serious enough to justify a policy of inactivity, namely—

(1) It was considered that the low calorific value of the gas, together with the fact that its combustible part is almost wholly made up of the slow-burning carbon monoxide, would cause uncertainty of ignition in the engine cylinder.

(2) The fact that the gas leaves the furnace at 250° C. highly charged with dust, which unless removed would be a fruitful source of trouble in the engine, was held to be a formidable obstacle to its utilisation. The problem of effectually cleaning and cooling such enormous volumes of gas as would continuously be required by a large power station would, it was thought, involve such a great capital outlay and working expenses as would largely counterbalance the prospective benefits accruing from the greater economy of the gas engine as compared with the existing steam-power installations.

(3) The alleged relative unreliability of the gas engine in sufficiently large enough units for steel-works power purposes.

The experience of the past twenty years has, however, proved that all such objections were either entirely groundless or more than a temporary significance. The force of

appeared as soon as it was recognised that the thermal efficiency of a gas-engine cycle depends primarily upon the compression of the charge at the moment of ignition. Moreover, it happens that, owing partly to the higher temperature of ignition of carbon monoxide as compared with, say, hydrogen, and doubtless also partly to its containing so much carbon dioxide and nitrogen, an explosive mixture of blast-furnace gas and air will stand a high degree of compression without danger of pre-ignition in the engine cylinder. Also, the slower burning nature of carbon monoxide, as compared with either hydrogen or methane, make it in some respects an ideal gas-engine fuel.

To the late Mr. B. H. Thwaite undoubtedly belongs the credit of first demonstrating, in the years 1894–5, the practicability of generating power from blast-furnace gas in an internal combustion engine. Having previously satisfied himself that a synthetic gas similar in composition to that obtained from blast furnaces, and containing as much as 12 per cent. of carbon dioxide, could be used with no misfires in an engine, he patented his idea in May 1894 (No. 8670 of 1894).

Soon afterwards (Feb. 1895), with the help of the late Mr. James Riley, he put down a small horizontal 15 H.P. Acme 4-cycle engine, coupled with a direct-current dynamo, at the Wishaw Ironworks, near Glasgow, and successfully drove it with cleaned gas from the coal-fed blast furnaces of the following average composition :—

$$CO_2 = 6 \cdot 22, \ CO = 26 \cdot 23, \ H_2 = 4 \cdot 65, \ CH_4 = 3 \cdot 18,$$
$$\text{and } N_2 = 59 \cdot 72 \text{ per cent.}$$

The consumption of gas in two different tests amounted to 105 and 138 cub. ft. respectively per E.H P. generated.

In 1897, at Frodingham, he successfully ran a similar engine on gas from an ordinary coke-fed blast furnace containing—

$$CO_2 = 6 \cdot 0, \ CO = 27 \cdot 3, \ H_2 = 1 \cdot 5, \text{ and } N_2 = 65 \cdot 2 \text{ per cent.}$$

In 1899 he put down his first large engine (100 H.P.) from blast-furnace gas at Sheepbridge.[1]

[1] The author is indebted to Mr. W. H. Booth, who witnessed these early experiments, for much of this information. The reader is also referred to (1) *The Iron and Coal Trade Review* of Nov 16, 1894, (2) a paper by Prof. Watkinson before the West of Scotland Iron and Steel Institute on March 15, 1895, and the discussion thereon, and (3) to statements made during a discussion at the Iron and Steel Institute in July 1906 (*Journ. Iron and Steel Inst.*, 1906, III., p. 155), for fuller information about Mr. Thwaite's work and claims in this connection.

But whilst Thwaite's idea met with small encc
his own countrymen, it was eagerly taken up o1
especially by MM. Bailly and Kraft, under the 1
late M. Adolphe Greiner,[1] at the Seraing work
Cockerill in Belgium (Dec. 1895 onwards), and
German engineers at the Hoerder Works near Do

The subsequent rapid development of the larg
blast-furnace gas was largely due to M. Greiner
engineers associated with him. In 1900 the S
exhibited a 600 nominal H.P. single-cylinder
Paris Exhibition, which on trial developed 670
thermal efficiency of 25·2 per cent., whilst in
Company installed at their own works a 140c
two-cylinder tandem engine, which on trial with b
developed 1582 B.H.P. with the remarkably hi
29·84 per cent.[2]

The Cleaning of Blast-furnace (

Simultaneously with these developments, th
effectively cleaning blast-furnace gas on a large
purposes had to be tackled. The gas as it leaves
a temperature between 200 and 300° C., is heavil
dust, the coarser and heavier portions of which
in the " dust catchers " inserted in the main dov
from the furnace, as well as in the flues leading th
there remain on an average about 5 grams per
finer dust which is never so removed. Before t
used in large engines it must be cooled down to
and its dust content reduced to something like 0·01
metre.

One of the most successful solutions of the cle
was due to E. Theissen of Munich, who devised
(Figs. 70 and 71) in which a drum is rotated at a
300 to 400 revolutions per minute within an outer sli
fixed casing of circular cross-section. The circum
drum is provided with a number of inclined spi

---

[1] It is pleasing to note that M. Greiner in his Presider
the Iron and Steel Institute in 1914 paid a well-deservec
pioneering work of Mr. B. H. Thwaite, adding that his "
prevented him from reaping the fruits of his investigations
and Steel Inst., 1914, I., p. 43).

[2] *Vide* a paper by Prof. H. Hubert, *Journ. Iron and S
III., pp. 16–35.

effect of which is to make the gas take a long spiral course through the tapering annulus between the drum and the outer casing.

FIG. 70.—Theissen Washer (End Elevation).

FIG. 71.—Theissen Washer (Side Elevation.)

Water is forced tangentially into the apparatus, and made to travel through the annulus in a contrary direction to that of the gas. Theissen washers are now made in sizes which will clean up to a million cubic feet of gas per hour, and reduce the

dust content down to the aforesaid limits. The p
in cleaning the gas may be taken as about 5 pei
developed from it in the engines, and the watei
is about one litre per cubic metre of gas.[1] Bui
wet-cleaning, involving, as it must always do, i
expenditure of water, and the employment of :
for the troublesome slurry produced, cannot be
finally satisfactory. Also, except for that portic
intended for the gas-engines, the dissipation of the
in the gas by water-cleaning involves an unnec
energy.

Processes of dry-cleaning, such for example :
Halberg system, in which the gas is filtered thro
fabric, have also been successfully developed within
but many competent judges consider it probable 1
solution of the problem will eventually be found in
static system, at any rate, for all but the finest p:
the whole, of the dust, and it is, therefore, in some s
that future progress may confidently be looked for.

REGENERATIVE BY-PRODUCT COKE OVENS AS AN
THE BLAST FURNACE

Suppose now that the whole of the coke put in
furnace referred to in the preceding paragraph is r
Durham Coking Coal in a battery of by-product c
regenerative type erected on a site adjacent to t
Then to produce 6 tons of pig iron (*i. e.* the hourly
furnace making 1000 tons per week), about 9·6 1
must be carbonised in the ovens, which would yield 5(
48,000 cub. ft. of surplus " debenzolised " coke-c
average *net* calorific value 430 B.Th.Us. per cub. ft.
bined hourly outputs of blast-furnace and coke-
resulting from the dual operation would therefore be

			B.1
1,114,200 cub. ft. of Blast-furnace Gas	=	111,4
48,000 ,, ,, ,, Coke-oven Gas	=	20,6
Total B.Th.Us.	=	132,0

(p

[1] For further details of the Theissen Washer see a paper by I
in the *Journ. Iron and Steel Inst.*, 1906, III., pp. 47 to 50.

is amount of heat is equivalent to the heat of combustion of 5 tons of coke or 67 per cent. of that charged into the blast rnace to make the iron. So that if 22·5 cwt. of coke be charged to the furnace per ton of pig iron produced, the heating value the combined blast-furnace and surplus coke-oven gas is luivalent to 15 cwt. of the same coke.

The Organisation of a Modern Iron and Steel Plant with a View to Fuel Economy

The British iron and steel industry still labours under a isadvantage compared with its German rival on account of its nuch earlier development. We built and organised most of our blast-furnace plants and rolling mills during the "iron age," n the years preceding the epoch-making inventions of Bessemer ind the Siemens brothers, which ushered in the "steel age" in the early eighties of last century, and before by-product coking methods had been developed. It then mattered little whether or not the smelting of iron was carried out on the same site as the subsequent manufacture of rails and plates, on the one hand, or that of coke on the other.

The modern German industry took its rise *after* the inventions referred to, when the great advantages of close proximity of blast furnaces, steel works, and rolling mills were so manifest that all subsequent installations of plant were expressly planned and laid out so as to secure them. Consequently, whereas practically all the great German works erected during the past thirty years have from the outset embodied and profited by these advantages, most of the older British plants have had to be gradually re-modelled, as circumstances permitted, so as to conform, as nearly as possible, to the new conditions. And as such a change will necessarily take time, there are still many of our works that have not either undergone or completed the change.

In times past, and before the aforesaid advantages had become so obvious as they are now, the blast-furnace plant was frequently isolated both from the steel works and rolling mills on the one hand, and from the coke ovens on the other. Coke was always manufactured, as it still is in many places, at the pit-head in beehive ovens and then railed to the blast furnaces. The pig iron made in the blast furnace was then sent (often cold) to the steel works, where it was converted into steel and the latter subsequently rolled into girders, plates, rails, etc., operations

necessitating a considerable additional expei
For this purpose raw coal was gasified in produ
works and a further quantity of it was also burr
to provide steam power for driving the rolling 1

For every ton of iron produced in the blast fu
of raw coal would be coked in beehive ovens ,
and a further 0·75 ton, at least, had to be consu
works and in the rolling mills, involving in all
of not less (and often much more) than 2·5 tons
ton of finished steel sections produced. This
is represented diagrammatically in Fig. 72.

The introduction of by-product coking metho
ment of the large gas engine for blast-furnace gas,
for cleaning the latter on a large scale for both po
purposes, and lastly the recent invention of suit
for electrically driving the rolling mills, have e
the whole complexion of the case, and inaugurat
fuel economy in the manufacture of iron and ste
in this country, are only beginning to reap the fi

The advantages of concentrating by-product ct
furnaces, steel works, and rolling mills on one
with the utilisation of the combined surpluses of
cleaned blast-furnace gases, partly in large gas
dynamos generating electrical energy for driv.
mills and all other machinery on the plant, and
displace producer gas as a fuel for the steel furni
mills, became manifest during the early years
century, largely as the result of Continental e
in Germany, Austria, and Belgium).

It has been the author's privilege during recei
these new possibilities demonstrated at the Skii
and Steel Works, which have been re-modelled
after a careful study of the best British and Contii
under the direction of Mr. T. C. Hutchinson, w
bear upon the task a life's experience in the 1
economy in connection with blast-furnace smelting

In 1910 Mr. Hutchinson, in his presidential i
Cleveland Institution of Engineers, predicted, as
his investigations both abroad and in his own wo.
a proper concentration and arrangement of the vi
the producing units, *the time would shortly con
stone would be brought in at one end of the works anu*

PRODUCTION OF FINISHED STEEL

0.75 TON of COAL to STEELWORKS

FINISHED STEEL SECTION

WASTE

STEAM POWER

ROLLING MILL

BOILER & ENGINE

STEEL INGOTS

EXHAUST STEAM

GAS

GAS PRODUCER

SOAKING PIT

HOT COMBUSTION PRODUCTS

C - STEELWORKS

GAS

STEEL INGOTS

OPEN HEARTH STEEL FURNACE

STOVES

COLD BLAST

HOT BLAST

½ TON PIG IRON TO STEEL WORKS

? SURPLUS GAS

GAS

BLAST FURNACE

HEAT IN MOLTEN IRON

BOILER AND BLOWING ENGINE

GAS

HEAT IN MOLTEN SLAG

1.25 TONS COKE RAILED TO BLAST FURNACE

B = BLAST FURNACE PLANT

Total Coal Consumed = 2·50 tons.

BEEHIVE COKING PLANT AT COLLIERY

1.75 TONS COAL

? SURPLUS GAS

A = COLLIERY

COAL MINE

Fig. 72.

*would be turned out at the other, only such coal be
required for the coke ovens to make sufficient co,
ironstone;* and in September 1913 he repeated
in the course of a discussion at the Brussels Meet
and Steel Institute. With his kind permissio
was able to give supporting evidence and calcul
a paper read before the British Association in 1<
in his Lectures on Fuel Economy before the Ro
in 1916.

The cardinal feature of this new development i
concentration of by-product coke ovens, blast
works, and rolling mills on one plant, coupled wi
utilisation of the surplus blast-furnace and coke-
power and heating purposes. When this conditi
it should be possible, under the new arrangemer
outlined, to produce a ton of finished steel section f
ironstone and Durham coke, with the expenditur
than 1·6 tons of coal, as sketched in Fig. 73.

CONDITIONS TO BE FULFILLED FOR THE REALISA
MAXIMUM OF ECONOMY

For the realisation of the large economies ou
preceding paragraphs it is either necessary, or d
certain conditions should be fulfilled. Broadly sp
may be summarised as follows :—

(1) By-product coke ovens, blast furnaces, stee
rolling mills must all be concentrated on <
suitably laid out thereon in relation to eac

(2) The by-product coke ovens must be of the
type, so as to yield the largest possible su
which may be debenzolised.

(3) The coal charged into the ovens should cont
than 10 per cent. of ash, and 7 per cent.
The volatile matter in the dry coal shoul
be between 25 and 28 per cent.

(4) The quenched coke for the blast furnace should
more than 2 per cent. of moisture, and the b
½ in.) should be removed and utilised in t
kilns or otherwise.

(5) The blast furnaces should be fitted with dou
order to minimise loss of gas, and there shou

PRODUCTION OF FINISHED STEEL ON NEW PLAN

A = COLLIERY   B = COKE OVENS, BLAST FURNACE AND STEELWORKS.

Total Coal Consumed = 1·6 tons.

FIG. 73.

413

distribution in the furnace of the material (c
and coke) by means of a suitably dimensi

(6) The blast should be generated by means of
   blowing engine.

(7) The furnaces should be driven by blast at
   (6 lb. per square inch), using large tuyèn
   nozzles), pre-heated to 700° C.

(8) The gases leaving the furnace should be
   preferably by some electrostatic method, s
   the dust to about 0·1 gram per cubic metre,
   of cleaning is sufficient so far as using the
   or furnaces is concerned. Such portion of
   used for generating power in gas engines m
   to below 20° C., and further cleaned until its
   does not exceed 0·015 gram per cubic metr

(9) The hot blast stoves should be heated by dry
   Three stoves should be used per furnace, tv
   on gas whilst one is on blast.

(10) If conditions (6), (8), and (9) are fulfilled, th
   of the gas as between blowing engines,
   available surplus, should be somewhat as :

   (a) Not more than 20 per cent. for the Blowing
   (b) „ „ „ 30 „ „ „ Stoves,[2]
   (c) Not less than 50 as surplus for the steel

(11) Assuming a minimum surplus of 50 per c
   furnace gas available for the steel works an
   this, together with the surplus gas from th

---

[1] With regard to the question of bells, it has been vari(
that the loss of gas at existing single bells amounts to :
10 per cent. of the whole, and of course it mainly occurs d
when the bell is lowered. The use of double bells is inten
this. As to the important question of the proper dimer
bell relative to the stock line, Mr. T. C. Hutchinson, in :
before the Iron and Steel Institute (May 1918), showed ho·
the results of careful experiments, he had reduced the col
in the Skinningrove furnaces per ton of pig iron from 23·9.
merely by substituting a 15½ ft. diameter bell for one of 1
The Blast Furnace Committee of the Iron and Steel
recently laid down the rule that "the area of the bell shou
the area of the annular space between the brickwork and
the bell is lowered."

[2] This is based on a stove efficiency of 66 per cent. with
(*vide* Knight's results, p. 403), but if *cleaned* gas were use(
should be higher. If an efficiency of 75 per cent. were reali:
of gas required for the stove would only be 25 per cent.
Also it should be possible to utilise some of the waste heat i

would make available, as a maximum, the following heat units per ton of pig iron :—

		B.Th.Us.
92,000 cubic feet of blast-furnace gas	=	9,200,000
8,000 „ „ „ coke-oven gas	=	3,400,000
100,000	Total =	12,600,000

This amount of heat would be equivalent to that in 8 cwt. of average bituminous coal. But inasmuch as the efficiencies gas producers and boilers as used in steel works can hardly put higher than about 75 per cent. (*i. e.* coal to gas or coal to 3am), and also as steam engines are less efficient than gas engines, he coal equivalent of the surplus gas should really be counted

s at least $8 \times \dfrac{100}{75} = 10\cdot6$ cwt., and possibly more.

(12) There should be separate supplies of surplus coke-oven and blast-furnace gases throughout the plant; mixing of the two supplies should be carried out at the several points of consumption as required.

(13) The gas engine in the power house should be run on cleaned blast-furnace gas only.

(14) The gas used for the steel furnaces and soaking pits should be a mixture of blast-furnace and coke-oven gases, preferably in such proportion as will yield a heating gas of between 160 and 180 B.Th.Us. per cubic foot.

(15) The pitch from the coke ovens should be utilised as fuel in connection with the steel plant.

(16) The waste heat in the molten slag from the blast furnace should be utilised.

(17) The waste heat from the gas-engine exhausts and the steel furnaces and soaking pits should be utilised for steam-raising purposes.

(18) The rolling mills should preferably be electrically, and not steam, driven.

(19) There must be scientific management and control from beginning to end throughout the whole heating system, for it is essential that every available heat unit on the plant should be tracked down and effectively utilised to the best advantage.

The conclusion that it should be possible, as M
predicted, to convert iron ore into finished steel
only such coal as is required to make the coke
furnaces, was supported by a very valuable pa
Utilisation of Blast-furnace and Coke-oven Gases in
read by E. Houbaer of the Cockerill Company's wo
(Belgium) before the Iron and Steel Institute al
Meeting in September, 1913. In summarising 1
actual experience gained at the Cockerill works up
M. Houbaer stated that, in the case of a works
production of 1000 tons of pig iron and 1000 tons of c
the latter all to be made in regenerative ovens
available surplus of blast-furnace gas, after providin
and all the furnace services, would be 40 per cent
output, it might be expected that—

(1) The blast-furnace gases would supply motiv
to 28,500 horse-power continuously.

(2) The daily quantity of coke-oven gas availabl
of the production either of 625 tons of s
hearth furnaces, or the raising to the prope
of 1150 tons of ingots or semi-manufactι
in re-heating furnaces.

(3) The combustion of the pitch from the coke o'
capable of producing 150 tons of steel in aι
furnace.

Therefore he concluded that " the tendency of
works producing coke and pig iron and converting ι
steel and rolling it in their own mills, should be ι
fuel requirements solely by the coking coal requi
supply of their smelteries." This is obviously the i
a greater or lesser degree of approximation is being
ing to the varied circumstances which intervene
economical running of the plant.

It may be taken for granted that the more a
progressive sections of the iron and steel produc
Britain have already accepted in principle the vi
in this chapter, even if circumstances have not yε
of them to translate them into actual practice.]
that, with the results of recent experience and re
them, those responsible either for the putting up

orks or for the re-organisation of old ones, would insist on ost of the conditions laid down in the foregoing paragraphs eing as far as possible fulfilled. There would, it is almost ertain, be general agreement (1) as to the necessity of concen- rating coke ovens, blast furnaces, steel works, and rolling mills n one site; (2) that the coke ovens must be of the regenerative ype; (3) that the present loss of gas at the blast-furnace tops, which is inevitable so long as single bells are employed, must be diminished; (4) that *all* surplus blast-furnace and coke-oven gases shall be utilised for power and heating purposes in, or in con- nection with, the steel works and rolling mills; and (5) that, so far as the blast-furnace gas is concerned, this would be best utilised, so far as is possible, for power purposes in gas engines.

Whilst it may be conceded that these five points are of prime and dominating importance, attention may here be drawn to the possible economies which seem to deserve more serious consideration than they have hitherto usually received :—

(a) *The Dry Cleaning of Blast-furnace Gas for Stoves and Heating Purposes.*—When it is realised how large a proportion of the blast-furnace gas is at present burnt in the hot-blast stoves, and that (according to Mr. Knight's determination) at least 30 per cent. of the available heat in the gas so used is lost up the chimney, it is at once evident that there is a considerable margin for further economy in the present method of heating the blast. And probably the best means of saving in this direction would be to clean the gas as it leaves the furnace by some electro- static method so as not to dissipate its sensible heat. Already promising attempts have been made to subject the gas to a preliminary cleaning in this way, and it does not seem unlikely that the near future may see considerable further developments. And if the dust in the gas, which, owing to its potash content ought on other grounds to be removed, can be reduced to 0·1 gram per cubic metre, without dissipating the sensible heat, economies in the hot-blast stoves will undoubtedly follow.

(b) *The Utilisation of Waste Heat in Gas Engine Exhausts, and Chimney Gases.*—A careful investigation of the heat balance of a steel-works plant would probably disclose very considerable in both these directions. The sensible heat energy of xhaust gases of a modern gas engine is probably equivalent ween 35 and 40 per cent. of that developed by combustion cylinder, and about two-thirds of this is, or should be, rable by means of a good waste heat boiler. Simila

E

considerations apply to a considerable part of the
burnt gases from steel furnaces and the like.

(c) *The Utilisation of the Heat in the Molten Sla*
portion which the heat carried off by the molten
modern blast furnace bears to the total heat of c
the coke charged into it will obviously largely depe
proportion of slag-forming material in the furnac
pig iron produced, and it increases with the leann
smelted. In a furnace smelting Cleveland ironst
production may be as much as 35 cwt. per ton of pi
it leaves the furnace at a temperature of 1400° and
heat loss is considerable.

Sir Lowthian Bell, in his calculations of the hea
in the blast furnace, always adopted 550 calories a
1 gram of molten slag, a number which was based
metric determination by M. Vathaire. The specific l
furnace slags have been variously determined as
and 0·33, and their latent heats of fusion as betwee
Taking the means of these determinations, and assu
to leave the furnace at 1400° C. above the atmc
perature, we should get for the heat in a unit weig
slag (1400 × 0·31) + 105 = 539, which is not v
from Bell's figure.

In the case of the Cleveland furnace referred t
one unit of pig iron and 1·75 units of slag for every u
charged into it as coke, the heat in the molten sla
(943 cals.) would be 11·65 per cent. of the total
bustion of the carbon in the coke charged (8080 cal
words, the recoverable heat at present lost in the
for the said furnace is equivalent to that in about
coke per ton of pig iron produced.

Within recent years attempts have been made c
mental scale to utilise the heat by quenching the
with water and using steam generated in a low-pres
Particulars of the performance of an experimental
lines at Sir B. Samuelson and Co.'s works at Middle
published in 1912. It was stated that chemical
shown no trace of sulphuric acid in the water conder
steam, and that the amount of sulphuretted hydrog
was not sufficient to damage the blades of the tu
that the steam, though almost instantaneously
superheated about 70° Fahr. and that the amount

from a furnace producing 1800 tons of slag per week could be relied upon to develop 500 K.W. of electric current per hour with an expenditure of 6 H.P. per operating plant.[1]

In 1914 Mr. Walter L. Johnson published particulars of experiments made at the Clarence Works of Messrs. Bell Bros., Ltd., Middlesbrough, on the subject.[2] The method consisted in (1) quenching and granulating the molten slag in water, and (2) using the dirty steam at 100° so generated to evaporate clean water in a Kestner single-effect climbing-film evaporator (heating surface 548 sq. ft.) under a pressure of about 9 in. of mercury (at which water boils at 90° to 91° C.). In this way 91 lbs. of clean water were evaporated from each 100 lbs. of dirty steam generated by quenching the slag, and the experimental results showed that 855 lbs. of clean steam could be obtained per ton of slag quenched. And, inasmuch as a modern exhaust turbine, working with a full load and under a vacuum of 28·5 in., uses no more than 27 lbs. of steam per horse-power under the said conditions, the available horse-power would be 31·6 per hour per ton of slag. On this basis, the power which could be generated by a Cleveland furnace making, say, 6 tons of iron and 10·0 tons of slag per hour would be 316 H.P.

Mr. Johnson stated that, as the mean result of seven experiments, he obtained 1017 lbs. of dirty steam (at 100° C.) per ton of slag quenched. Assuming that the water was fed into the quenching apparatus at 15° C., these figures enable the following approximate estimate to be made of the proportion which the heat of the molten slag recoverable by such a method of quenching would bear to the total heat of combustion of the coke in respect of a furnace producing 1·75 tons of slag and using 1·125 units of coke (say, 1 unit of carbon) per unit of pig produced.

Heat of Combustion of 1 unit of Carbon = 8080 cals.

1·75 Units of Slag would evaporate $\dfrac{1017 \times 1·75}{2240} = 0·80$ unit of water.

Heat recovered by quenching = 620 × 0·8 = 496 cals.

Therefore, the heat in the molten slag, recoverable by the quenching method in question, would be 6·14 per cent. of total heat of combustion of the coke to carbon dioxide, and, allowing for the subsequent generation of clean steam in the Kestner evaporator employed, the heat finally recovered was as nearly

[1] Journ. Iron and Steel Inst. 1912, I., p. 510; also Iron and Coal Trades Review, **84**, p. 607.
[2] Journ. Iron and Steel Inst., 1914, II, p. 98.

as possible equal to 5 per cent. of the total heat o of the coke charged into the furnace, or say abo coke per ton of iron produced.

SOME GENERAL CONSIDERATIONS

In discussing the organisation of an iron and ste a view to fuel economy, it is important to take acco conditions which have not yet been considered.

In the first place, by no means all the iron pro blast furnaces in the kingdom is converted into ste year 1913, 10·46 million tons of iron but only 7·66 of steel were produced), and therefore the total t of the blast-furnace and coke-oven gases produce steel would on the average be greater than the for indicate, except in the case of such plants whe output of the blast furnace is converted into steel.

Secondly, whereas the blast furnaces and coke continuously day and night throughout the whole furnaces are shut down from 20 to 30 hours ea and the rolling mills often work only one shift per there is always a large surplus of gas at the weel without special and costly storage arrangement utilised in the plant ; also when the rolling mill is the amount of gas required for power purposes is reduced. In other words, the problem which c iron-master is complicated by the fact that whe duction of gas, both at the coke oven and in the goes on fairly uniformly day and night throughout demands for it are constantly fluctuating.

To provide storage capacity for the millions of surplus gases which are produced on the plant ea when the steel furnaces and rolling mills are using would probably involve far too great a capital out M. Houbaer (*loc. cit.*) reported that the Cockerill C in 1913 erecting a 50,000 cubic metre (say, 1,650, holder to store coke-oven gas made during the week works.

The solution of the problem would be extraordin were each plant to be treated as an isolated unit. however, it usually happens that a large number of concentrated in a particular smelting area, as in t

District, and by linking them all up, through the medium of a Public Electric Power Company, much can be done towards equalising the load throughout the whole area during six days of the week. Indeed, without some such linking up, it would be almost impossible, even with the most perfect organisation and the most efficient producing units at each isolated works, to achieve the full benefits of the policy outlined in this chapter. Hence the need of some effective co-operation, so far as power services are concerned, between all the producing plants within a given area. This would, however, hardly solve the week-end problem, because all the steel works and rolling mills throughout the area are then requiring but a minimum of power, as also usually are all the other industrial establishments in the area.

CHAPTER XX

THE present review would be incomplete without
ence to the fuel economies associated with the use
in the blast furnace.

As long ago as 1853 Prideaux suggested in his b(
Economy that the desiccation of the blast woul
result in the saving of coke in iron smelting; and the t.
Devonshire, in his Presidential Address at the Inaugʋ
of the Iron and Steel Institute in 1869, mentioned ⟩
great variations in the moisture contained in the air
at different seasons of the year as being one of thᵉ
furnace problems which at that time remained unso

In his *Chemical Phenomena of Iron Smelting* (187ᶻ
Bell referred to the water vapour introduced in thᵉ
disturbing agent in the furnace, because of its
quantity. He said that it lowered the temperature
of combustion, but whether this decomposition of
real heat loss over the entire process depends on th
which hydrogen reduces the oxides of iron higher
furnace. But notwithstanding this, " there is alwaⅰ
derangement in the working of the smelting proc
admission of water, due to the fact that heat i
where it is most wanted, and evolved where its pɪ
questionable benefit."

In November 1890, W. H. Fryer read a paper
Cleveland Institution of Engineers on " The Desiccᵃ
Blast in the Manufacture of Pig Iron," as a means
creasing the output and making the furnace condi
uniform.

When it is realised that a Cleveland furnace, wor
conditions such as have been described in the foregᵉ
consumes nearly 140,000 cub. ft. at 15° C. and 76

early 9·65 cwt.) of air per ton of iron produced, and that the mount of moisture in the air varies enormously according to he state of the weather and the season of the year, it is quite lear, that whatever else may be done to secure uniformity of working conditions in the furnace, so long as there is no means of controlling the hygroscopic condition of the blast, the whole smelting process will remain dependent upon the caprice of the atmosphere.

The problem of desiccating such huge volumes of air as are needed to work a modern blast-furnace plant appeared to be almost outside practical politics until Mr. James Gayley of New York, in two papers before the Iron and Steel Institute in 1904–5,[1] brought forward some remarkable, not to say astonishing, figures as to the fuel economies which had resulted from the experimental adoption of dry blast at the works of the Carnegie Steel Co. at Etna, Pittsburg.

The nature of these results will be sufficiently indicated by a description of the first experimental run with dry blast on the Isabella Furnace at the above works in September 1904, confirmed as these were by more thorough and extensive trials in the following year.

The furnace in question (height = 90 ft., diameter at boshes = 21 ft., capacity = 18,090 cub. ft.) smelted a mixture of Mesabi and Michigan hæmatite ores, containing 53·5 per cent. of iron, with coke containing between 10·5 and 12·5 per cent. of ash. In accordance with the usual American practice of hard driving and big outputs, it was blown through twelve 6-in. tuyères, with blast at 12 to 15 lbs. per sq. in. pressure, preheated to 850° Fahr., and it produced a basic iron with as low a percentage of silica as possible consistent with the essential low sulphur content.

The experiment in question extended altogether over a period of forty days, divisible into three, namely :—

(*a*) *1st to 4th August* 1904.—Furnace blown with normal (*i. e.* undried) blast, with a burden proportioned as follows :—

Coke = 10·0, Ore = 20·0, Limestone = 5·0.

During this period the moisture content of the blast varied between 3 and 8 (mean = 5·56) grains per cub. ft., and with an average blast temperature of about 720° Fahr., the average daily output of pig iron was 358 tons, with a coke consumption of 2147 lbs. per ton.

[1] *Journ. Iron and Steel Inst.*, 1904, II, 274, and 1905, I, 256.

The waste gases leaving the furnace at 538° Fahr. contained—

$$CO_2 = 13 \cdot 0, \quad \text{and} \quad CO = 22 \cdot 3 \text{ per cent.}$$

(b) *12th to 25th August.*—An intermediate period during which dry blast was gradually introduced until by 25th Aug. dry blast was being used entirely. The first noticeable effect of gradually drying the blast was a brightening in the zone of combustion in front of the tuyères of the furnace and an increasing temperature of the slag. This was followed by the furnace gradually taking a proportionately heavier burden of ore and limestone, and giving a larger output of iron from the same consumption of coke, until these favourable results reached their consummation during the subsequent run with "all dry" blast.

(c) *25th August to 9th September.*—Furnace blown with blast dried by refrigeration until it contained very uniformly between 1·33 and 1·85 (average 1·75) grains of moisture per cub. ft. The burden was proportioned as follows :—

$$\text{Coke} = 10 \cdot 2, \quad \text{Ore} = 24 \cdot 0, \quad \text{Limestone} = 6 \cdot 0.$$

It was found that the speed of the blowing engines, which before applying dried blast were running at 114 revolutions and supplying 40,000 cub. ft. of the air per minute, could be reduced to 96 revolutions per minute, owing to their working on a refrigerated blast ; also that the blast temperature on leaving the

TABLE LXXIV

RESULTS OF MR. GAYLEY'S EXPERIMENT WITH THE ISABELLA FURNACE, PITTSBURG, AUGUST 11 TO SEPTEMBER 25, 1904

Period.	(a) Normal Blast.	(c) Dried Blast.
Average Moisture in Blast. Grains per cubic foot .	5·56	1·75
Average Daily Output of Iron in tons	358	447
Average Coke Consumption. lbs. per ton of iron	2147	1726
Temperature of Hot Blast. ° Fahr . .	720°	870°
. ° Fahr . . .	530°	370°
. . . .	1·0	1·5

424

regenerative stoves rose to 870° Fahr. But the most remarkable result of the trial was that, whilst the average daily output increased to 447 tons, the average coke consumption fell to 1726 lbs. per ton. The gases leaving the furnace at 376°, or at 162° lower than in (*a*) contained—

$$CO_2 = 16 \cdot 0 \text{ and } CO = 19 \cdot 9 \text{ per cent.}$$

Summarising the whole experiment (*vide* Table LXXIV, p. 424), we find that desiccation of the blast had increased the daily output by about one-third, and at the same time had reduced the coke consumption per ton by about one-fifth, a truly remarkable result.

Astonishing as these results were, they were substantially confirmed by those of a further extended series of trials at the same works during the following winter (October to March), in which two furnaces, Nos. 1 and 3 respectively, were alternately worked on " normal " and " dried " blast; thus (to select two months, November and February, as a typical example) :—

TABLE LXXV

Month.	Furnace.	Average Daily Output. Tons.	Average Coke Consumption. lbs. per ton Iron.	Average Blast Temperature.
November 1904	{ No. 1 (Dry Blast) { No. 3 (Normal Blast)	447 386	1816 2279	854°} 750°}
February 1905	{ No. 1 (Normal Blast) { No. 3 (Dry Blast)	424 412	2248 1815	800°} 784°}

In 1909 were published the following results of the adoption of dry blast at Messrs. Guest, Keen, and Nettlefold's Dowlais Works, near Cardiff :—

	Weekly Output of Iron. Tons.	Coke Consumption. lbs. per ton of Iron.
Average of 50 Weeks of Normal } Blast	2001	2278
Average of 5 Weeks on Dry Blast } operated for Increase in Output	2530	1972
Average of 4 Weeks on Dry Blast } operated for Economy in Fuel	2286	1857

Although the claim that the use of dry blast increased output and a saving of coke in the fu generally admitted, opinion has been much divid, (*a*) the causes of these improvements, and (*b*) the (which would justify the adoption of dry blast, hav the capital involved in installing the necessary desi

With regard to the causes of the considerable effected, although no complete explanation has ye the following may be assigned as either probabl contributory factors, namely :—

(1) That any marked diminution of water in the must of necessity increase the temperature of the bustion in the region of the tuyères, and thus act way as an increase in the blast temperature. An be pointed out that the hot-blast temperature in Ga ments were not very high (720° to 870° Fahr. or, 465° C.), a circumstance which would be likely t the effect of this cause. In order to understand tl of this cause upon coke consumption, it must be that when steam reacts endothermically with incand at high temperatures producing carbon monoxide a in accordance with the equation—

(*a*) $\quad C + OH_2 = CO + H_2$ . . . . . . $- 29$]

exactly as much heat is absorbed as is generated by of the same amount of carbon to the monoxide, t.

(*b*) $\quad C + O = CO$ . . . . $+ 29$]

Consequently, when the steam and oxygen in th with the incandescent carbon in front of the tuyè every participating molecule of steam, two atoms (gasified without producing on the balance any evolv thus—

(*c*) $\quad 4C + 2OH_2 + O_2 = 4CO + 2H_2$ . . . . .

whereas, without the presence of water, the sam carbon would on burning to the monoxide evolve 58

(*d*) $\quad 4C + 2O_2 = 4CO$ . . . . . . $2 \times 29 = 58$

And, inasmuch as the reducing actions of either carb or hydrogen upon the materials in the charge (actually into play until temperatures below, say, :

ι reached, it follows that, *so far as the hottest regions of the ιace where the materials undergo fusion are concerned*, the ιence of a weight unit of water in the blast nullifies, so to ak, the heat-producing power of 1·33 weight units of carbon. ιpplying this reasoning to Gayley's experiment of August 1 September 1904 with the Isabella furnace, where the differ- ιe between the " normal " and " dry " blast conditions meant, the average, the elimination of 69 lbs. of moisture per ton of ιn produced, it might possibly account for an average saving 92 lbs. of carbon (= say, 104 lbs. coke), but no more, per ton iron produced. The actual saving, however, was as much as ι1 lbs., or more than 4·5 times that amount. Clearly, then, hilst the endothermic interaction of steam and carbon in front ι the tuyères must be a contributory cause, it is by no means he only, or even the main, one.

(2) Another probable cause is that the higher temperature at vhich the mixture of carbon monoxide and nitrogen generated ιt the tuyères would leave the zone of fusion, when most of the water was eliminated from the blast, would almost certainly accelerate its reducing action in passing upwards through the middle region of the furnace. Moreover, the amount of water reformed by the catalytic oxidation of hydrogen higher up in the furnace would presumably be some function of the propor- tion of hydrogen in the gases leaving the zone of combustion. And O. Boudouard has found that the reduction of oxides of iron by carbon monoxide was stronger when *dry* than when *moist*, and that this difference was most marked at about 400 to 500° C., gradually diminishing as the temperature rises, until at 1050° C. it disappeared altogether.[1] Such considerations as these would indicate that any considerable elimination of mois- ture from the blast would be very likely to accelerate the reducing action of the furnace gases upon the oxides of iron in the middle and upper regions of the furnace, and thus utilise more of their potential energy. And the fact that in Gayley's experiment the ratio CO/CO_2 in the exit gases fell from 1·7 to 1·25 when the average moisture in the ingoing blast was reduced, from 5·56 to 1·75 grams per cubic foot, may be cited in support of the view.

(3) Many competent judges among blast-furnace managers ι ͨexpressed the opinion that the main cause of the economy ͺ from dry blast is mainly to be found in the greater ιity in the working conditions thereby established, and

---

[1] *Comptes rendus*, 140, p. 40.

doubtless this is an important contributory, thoug the only, factor.

Mr. Gayley himself put forward the view that ' the air not only removes an unfavourable and v; from the blast, but by keeping the content of mois air practically uniform, through refrigeration to a perature, permits the delivery into the furnace o constant weight of air, and therefore of oxygen— cannot be obtained through an increase in blas The elimination of moisture removes a heat-extr; at the tuyères, and, together with the uniform wei constantly supplied, intensifies the combustion, the fusion zone. With natural air the fusion zone fluctuating; when the zone is lowered, incipient : on the area through which it is lowered; and wh(again raised, these scaffolds are melted loose, an into the hearth, absorb heat. For this purpose al of safety in fuel must be 'carried in the burden."[1]

In considering the other important question o stances that would justify the adoption of the Ga it must be remembered that in America, where it has ful, furnaces are as a rule driven very much harder Britain. It is not unusual for an American fur with high-pressure blast on hæmatite ores, contai 50 and 60 per cent. of iron, to produce 3000 ton week, whereas British furnaces, working mainly on ores, are rarely driven harder than is necessary output of 1000 tons per week. And it by no n that what is both technically and commercially feasible, in the one case will be equally beneficial Each case must be decided after due consideratio; ticular local climatic conditions, of the character o: ores smelted, and of the product aimed at, as w(speed at which the furnace is to be operated.

Thus Dr. Josef von Ehrenwerth of Leoben, afl study of the problem from the point of view of Styr has concluded, in a paper read before the Iron a; stitute in 1913,[2] that " whereas the economical resι the blast in some instances is very remarkable, it siderably, and the question of introducing dry bl;

[1] *Journ. Iron and Steel Inst.*, 1906, IV., p. 818.
[2] *Ibid.*, 1913, p. 118.

tled in each case on its own merit. The advantages are **pendent** in every case on local conditions, such as the dampness **the** atmosphere, and the cost and quality of the fuel. They **e** influenced besides by the kind of product, the quantity of **tput**, the reduction period, and the type of furnace." But, **suming** that the average amount of moisture normally present **the** atmosphere is high enough, he considered that the use of **ry** blast would unquestionably be advantageous in the following **ses** :—

(a) Where the furnaces are working with high blast temperatures, and correspondingly high waste-gas temperatures, as in smelting ferro-manganese, ferro-silicon, or ferro-chromium;

(b) also, where the furnaces, working under conditions similar to (a), produce Bessemer, foundry, or high silicon pig iron; and

(c) generally in localities, such as near the sea coast in climates where the atmosphere is normally very moist.

In the discussion which followed Ehrenwerth's paper it was made clear that, so far as British conditions are concerned, the cost of putting down a suitable desiccating plant would in most cases probably outweigh any prospective saving in fuel. Mr. T. C. Hutchinson, who had gone carefully into the question as regards the conditions prevailing in the Cleveland District, had arrived at the conclusion that it would not be " economically wise " to instal the Gayley system there, and, generally speaking, he doubted whether it would be so in Great Britain as a whole.

But, apart from the important question of capital outlay, there is one paramount consideration which, in the author's opinion, ought not to be overlooked. If in a modern steel-producing plant comprising coke ovens, blast furnaces, steel furnaces, and rolling mills, the objective to be aimed at, in the interests of an all-round fuel economy, is such a utilisation of the combined surpluses of coke-oven and blast-furnace gases as will do away with the necessity of gasifying coal in producers, or burning it under boilers, and to use no more fuel than is charged into the coke ovens to make the coke required for the nace, it is obvious that there must be a certain *mini-*lity of blast-furnace gas which is compatible with the t of such an ideal.

... The ... *experimental* run with ...
... ... the gas *evolved* from ...
... ... , as it did, no less
... ... and no *more than* 199%
... ... instead of the 100 and 300 ...
... contained in the gas from a Cleveland ...
... ... in the blast furnace, *if accompanied* by
... ... than a certain *limiting* ...
... ... the necessity *of having* to ...
... the ... amount of coal *elsewhere* on ...
The ... question would therefore involve *other* cons...
... ... in the *blast furnace*, ...
... ... from a very careful *review of the* requi...
... ... whole.

CHAPTER XXI

POWER PRODUCTION FROM COAL

ᴇ subject of power production from coal is so many-sided
ᴛny brief review of it in these pages is bound to be inadequate.
seeing that the omission of any reference to it might be
dered as detracting from the complete exposition of the
ᴛtific uses of coal, an endeavour will be made in this chapter
ᴠe in outline the more salient aspects of the problem, without
rence to its technical details.

t has already been explained in a former chapter that were
possible to transform the available energy of coal into
chanical power, without loss of any kind, a horse-power hour
ᴜld be obtained by the expenditure of about one-fifth of a
ᴜnd of coal of average quality. Needless to say the attainment
anything like such perfection is altogether precluded, alike
y the nature of the materials available for the construction of
ᴛe various machines which must be used as prime movers, and
ᴸso by the natural conditions under which they must be operated.

There are two principal ways in which the energy of coal may
be converted into mechanical work. One is by raising steam
in a boiler, and then utilising as much as possible of the energy
of the steam in some form of steam engine, either of the recipro-
cating or turbine type. The other is by gasifying the coal com-
pletely in some form of gas-producer, and then burning the
resulting gas in an internal combustion engine. Both these
methods are of course imperfect, but it may perhaps be of interest
to compare them from the point of view of thermal efficiency.

In the first place, it may be stated that the thermal efficiency
of a good modern type of coal-fired boiler is not far short of that
ᴀ ᴄ cation of coal in a gas-producer, when due allowance
the fact that in the latter case it is necessary to clean
ᴇ resultant gas before it is delivered to the engine.
t be far wrong in putting down the efficiency of each
ᴛer good working conditions at about 75 per cent.

Again, under favourable working conditions, a ga
convert about 27 per cent. of the energy of the gas
available horse-power, so that the coal consump
to obtain a shaft horse-power hour by means of the
of an efficient gas-producer and a gas engine need
than 1 lb.

$$\frac{0 \cdot 20}{0 \cdot 75 \times 0 \cdot 27} = 1 \text{ lb.}$$

Within recent years great advances have been
development of the steam turbine. And, accor
published results of trials on the new 35,000 H.P. P
alternator erected at the Fisk Street Power Statio1
the fuel consumption on so large a turbo-steam set
boiler efficiency of 75 per cent.) has now been reduc
coal per shaft horse-power hour. Therefore, it wou
there is now probably little to choose between
efficiencies of the best types of steam and gas s'
working under the most favourable conditions.

Broadly speaking, the selection of a power scheme i1
case will usually involve several considerations. F:
course, there is the question of the relative therma
of the different systems of converting the energy
available power. But this is by no means the only
cases even the most important, consideration. I
sometimes more, important is the further question o
planning and organisation of the scheme as a whole
capital outlay, running costs, and other condition
character. The question of the ultimate net cost o
including cost of fuel, labour, supervision, interest,
and depreciation, must always be the main consider
given case, and it by no means follows that the m
system from a purely thermal point of view will, und
conditions, be necessarily the cheapest in the long r

Bearing this in mind, certain general considerati
to the rival claims of gas and steam systems in rela
economy may be pointed out. Some years ago, it :
if the combination of the gas-producer and internal
engine would soon out-distance the boiler and st
partly because of the then much superior thermal
the internal combustion engine, and partly also bec
capacity of the gas-producer to gasify low-grade

ammonia-recovery conditions—two very important considera-
tions. For it must be remembered that a great deal of coal
obtained by the miner is so inferior in quality that it does not
ordinarily pay to bring it up to the surface, and it is therefore
usually left below in the mine. It has been claimed that the
gas-producer is more capable than any form of boiler of dealing
with such inferior grades of fuel, and, moreover, that it can
gasify them under ammonia-recovery conditions. On the other
hand, the capital outlay and the ground area involved in the
erection of an ammonia-recovery gas-producer plant, as compared

A.

FIG. 74.

with a boiler installation, have hitherto formed formidable
obstacles to the extension of the system.

The above diagram (Fig. 74) shows approximately the net
efficiency(coal to brake horse-power) of a gas-producer and internal
combustion engine combination. Calling the coal energy to be
debited against the system 100, the items to be credited to it
under full working conditions are 20 in respect of brake horse-
power, and up to 80 lbs. of ammonium sulphate per ton of coal
gasified. Of the energy losses involved per 100 coal energy,
are in respect of radiation and sensible heat of the hot gas
he producer, and approximately 50 at the gas engine—20 in
ct of loss in cooling water and radiation, and 30 in respect
exhaust gases.

F   433

Now, it is possible to improve this result by c
engine exhaust to some form of waste-heat boiler. I
with the author's investigations upon surface co
relation to steam raising, a type of multitubular
boiler was evolved in which the exhaust gases from
combustion engine are passed through tubes packed w
material, the effect of which is to bring about a ver
transmission between the hot gases and the water i
so that a considerable proportion of the energy in
gas is quickly transferred to the water and is obt
form of steam. Assuming it to be possible in this w

B.

FIG. 75.

the temperature of the engine exhaust (say) from 600
and to generate steam at 60 lbs. pressure for a turbi
brake horse-power efficiency of the system might l
from 20 to about 25 per cent., as shown in Fig. 75.

Turning, now, to the results obtainable from the
of coal-fired boiler *plus* turbine, which are shown diagr
in Fig. 76, it is seen that against the debit of 100 i
coal energy, the only credit is 20 in respect of avail
assuming 27 per cent. as the turbine efficiency.
possible credit in respect of ammonium sulphate, anc
the boiler should be supplied with a fairly good gr

With regard to the gas-firing of boilers, it may l
until recently such procedure has usually been so

that its adoption on a large scale was out of the question, except where great surpluses of gas were available which would otherwise have been wasted. The invention of the method of burning gases flamelessly in contact with incandescent surface (Bonecourt System), by providing a means of achieving both very high efficiencies and evaporative powers with gas-fired multitubular boilers, has completely changed the outlook in this direction.

In view of this new development, the nature of which will be further considered in the next chapter, another effective system of power production may be suggested. The raw coal would, in the first instance, be gasified in a producer under ammonia-recovery conditions; the resulting gas would then be burnt in a surface combustion boiler the efficiency of which with producer gas may be put down at certainly not less than 87 per cent.

C.

Fig. 76.

The resulting steam would then be turned into a steam-turbine, of assumed 27 per cent. efficiency, whereby a net result of 18 per cent. in respect of power on the available energy of the coal consumed, *plus* 80 lbs per ton of ammonium sulphate would be obtained (Fig. 77). So much then for the efficiencies of coal to power energy conversion obtainable, either now or in the near future, with the most modern and scientific apparatus and methods.

With regard to the rival merits of the steam-turbine and internal-combustion engine, which time alone can finally decide, it would seem under present conditions (1) that from the point of view of the size of the units, the turbine has shot far ahead of its rival. The large Parsons turbo-alternator recently installed at Chicago of 35,000 H.P. capacity, far surpasses anything yet attempted with an internal combustion engine unit; (2) that, whereas a gas engine only works at its highest efficiency with a

high load factor, a turbine maintains its efficiency o
range of load, and at low load surpasses its rival; (3
engine requires much more lubrication, but, on the
usually less cooling water, than the turbine; and (4)
to its simpler construction, the turbine requires less
and repairs, and is more reliable than its rival.

These considerations have led to the almost univers
of the steam turbine for large power stations, exce
where there are available supplies of surplus gases
ovens, blast furnaces, or the like. On the other hand
generating units—say up to 3000 H.P.—where the lo

D.

AMMONIUM SULPHATE
= 80 LBS PER TON OF COAL

100 COAL

GAS PRODUCER

75 GAS

BONECOURT BOILER

65 STEAM

TURBINE

18

AIR and STEAM

LOSSES

25

10

45

SENSIBLE HEAT OF
GASES. RADIATION,
UNBURNT FUEL.

RADIATION,
CHIMNEY

FIG. 77a.

uniformly high and not subject to abrupt variatio:
engine has certain important advantages which spe
to power plants in connection with steel works. I
however, the choice between the two rival syster
always be determined on purely thermal considerati
other equally important factors.

THE ORGANISATION OF PUBLIC POWER SCHE

The recent development of comprehensive elec
schemes in various parts of the world, notably in Chica
on the north-east coast of England, on the Rand, an
industrial districts of Germany, has shown that power
in large super-plants, with generating machines of s
or more, is not only far more economical than in a la

of smaller plants, but will ultimately involve great economies of capital by ensuring a better load and a more effective use of the plant.

Given suitable conditions, there are undoubtedly great advantages to be gained in the way of cheap power production by the co-operation of consumers with a properly organised electric power scheme operating over a large industrial area. And probably no other European country is better adapted than our own for such co-operative schemes, because of the compactness of our great industrial areas, the density of their populations, and their proximities to the coal-fields.

In every industrial area there are factories which under normal conditions work during the day only; others must of necessity work both day and night continuously. In some cases the power requirements are fairly uniform throughout the day's run, whilst in others they are subject to large and abrupt variations.

Some establishments, as, for instance, steel rolling mills, have intermittent loads for short periods far in excess of their average hourly requirements. Others again, such, for example, as isolated by-product coke ovens or blast furnaces, have large surpluses of gas which cannot be fully utilised on the plant itself. Some factories, also, may have surplus energy to dispose of in the form of so-called " waste-heat " or of unutilised " exhaust steam." In every large industrial area there are enormous energy losses continuously going on in different ways, which the individual manufacturer may be unable to utilise effectually himself, but which he would be willing to sell to a public organisation empowered not only to sell electrical energy, but also to purchase surplus gas, waste heat, and exhaust steam from any of its customers, and convert the same into electrical energy for general distribution.

The question of the future of electric-power supply in Great Britain has been the subject of an Interim Report by Lord Haldane's Coal Conservation Committee (of which the author was a member) under the Ministry of Reconstruction, which was issued on December 7, 1917,[1] for the information of the public.

This Report reviews the present position of power generation throughout the Kingdom and makes a number of important recommendations for its future organisation, and the reader will find that the manifold points dealt with therein will amply repay

[1] His Majesty's Stationery Office, 1918, price 3*d*.

437

a careful perusal in detail. Whilst various considei clude any lengthy survey of the subject in these pa two outstanding features of the Report may be men

In the first place the Committee point out it is onlj increasing the amount of power used in industry that output per individual worker can be increased in this They find that the amount of power used in the Ui per worker is on the average 56 per cent. more than in Kingdom, and that if workers in trades where the u: is limited, or even impossible, be eliminated, the fig United States would probably be nearly double what country. They also estimate that if power supply in Kingdom were dealt with on comprehensive lines and were taken of the most modern engineering devel« would be possible either (*a*) to save 55 million tons annum on the present output of power and manufa ducts, or alternately (*b*) from the present coal cons factories to generate continuously day and night the year, no less than 15 million additional horse-pov

On the assumption that power may be most efficiei to industry by the medium of electricity, the Comm the opinion that the present system of electrical tribution throughout the country, which is undertal 600 authorities in as many separate districts, is both wrong and commercially uneconomical.

The present average size of generating stations i be only 5000 H.P., or about one-fourth of what shoulc smallest generating machine in a power station. The accordingly made a number of recommendations foi vision of the present system by a comprehensive Great Britain, of which the first six may here be quo·

(1) It is essential that the present inefficient sysi 600 districts should be superseded by a cor system in which Great Britain is divided sixteen districts, in each of which there sh« authority dealing with all the generation distribution.

(2) Centres, or sites, suitable for electric generatii should at once be chosen on important w; the future main centres of supply for each of· into which the country is to be divided.

(3) **The** sites so chosen should be as large as possible, having in view the land available in suitable localities, and should have ample water and transport facilities. Land is required, not only for the power stations themselves—which for the sake of security and safety would have to be suitably subdivided, that is, they would not be contained all in one building—but for the processes involved in the extraction of by-products from the coal before it is used for the production of power, where such extraction is found to be justified. It is also required for the development of electro-chemical processes, which may be most conveniently carried on in close proximity to the power plant. This condition entails the sites being chosen outside, not inside, towns. The health of the great industrial centres and the congestion of the railway lines in their neighbourhood would be radically improved by arranging that the conversion of coal into motive power was carried out away from the densely populated centres.

(4) Plans should be prepared for the construction immediately after the war on these sites of the first instalment of large super-power plants capable, first, of supplying through a comprehensive electric power distribution system which must also be arranged for, the existing demands of the community; and, secondly, of supplying electrical energy at the lowest possible price for new processes and manufactures.

(5) Such plants would be designed so that, as methods are perfected for extracting by-products from the fuel, before using it for the purpose of the production of electric power, the by-product plant can be combined with the power plant. Each site should be laid out with this in view, and with a view to the unrestricted extensions of the plant as required.

(6) Power available from surplus gas or waste heat should be turned into electrical energy on the spot in local plants which would feed into the main distribution system. As gards waste coal, *i.e.* coal which it does not at present ~~ly~~ to bring to the surface—this could, where transport is the ruling consideration, also be used on the spot.

t of delivering electric current from a public power

station to a consumer is made up of two parts, namel
rating costs at the station, and (*b*) distribution costs
(*b*) is usually by far the larger item, for it is princi
up of the interest upon the heavy capital expenditu
in the laying of the main cables. The cost of general
at a public supply station of average size in this cou
not, as a rule, exceed a fraction of a penny. It inc
cipally, three items, namely, (i) fuel, (ii) interest an
tion on capital, and (iii) other charges, such as s
wages, lubrication, and repairs to plant.

The pre-war cost of generating electric current at a
efficient station in this country (including fuel, ir
depreciation, and all other charges) might be put ;
0·25 and 0·60*d*. per unit, of which the cost of fue
reckoned as about half of the total. The increased (
the war may perhaps be put at about 50 per cent.
war figure, so that to-day (1918) the total cost woul
range between 0·37 and 0·90*d*. per unit.

The coal consumed in a fairly efficient station, with
good load factor, should not exceed 2·25 lbs., or
thousandth part of a ton, per unit of electricity gene
under the most favourable conditions it might be :
1·75 or even 1·50 lb. per unit. The last-named :
indeed, been achieved under the North-East Coast Pow
which is perhaps, from a technical standpoint, the mc
in Great Britain.

The author has already drawn attention, in his L
" Fuel Economy " before the Royal Institution in 1c
present unsatisfactory organisation of London's elect:
which perhaps may be cited as a conspicuous examp
Lord Haldane's Committee have described as " :
wrong and commercially uneconomical." The popula
area covered by Greater London is about 7¼ millions.
trical supply, instead of being organised under a simp
ling authority on one uniform scheme, is at present in
of no less than 65 separate authorities, which genera
on 49 different systems at no less than 70 different ;
stations, containing altogether some 585 prime mov
average size of the generating stations is only 5285 :
many of the older stations still contain reciprocatin
and some are so situated that it is necessary to ca
them. Current is distributed from these stations at 5<

>ltages, and the consumer is charged at one or other of some
> different rates for the current he buys. There is no doubt
ut that were the London supply to be reorganised on lines
:commended by the Committee's Report, electric current would
e considerably cheapened throughout the area, to the great
enefit of the whole population.

The North-East Coast Electric Power Scheme

As an example of what has already been done since the begin-
ning of the century in one important industrial area in the
Kingdom in the direction of organising a comprehensive scheme
of electric power supply, the following particulars of the North-
East Coast Scheme may be given :—

The area in question (1400 square miles), which includes the
Northumberland and Durham Coalfields and the Cleveland Iron
District, together with the cognate and associated engineering
and shipbuilding industries of the Tyne, the Wear, and the Tees,
extends for a distance of 70 miles from Morpeth and Blyth in
the north to Stockton and Middlesbrough in the south.

The district is a remarkable one in many respects. With a
population (in 1911) of 2·3 millions, or about 5 per cent. of that
of the whole country, it produced in 1913 nearly 20 per cent. of
total coal, 36·5 per cent. of the total coke, and 37·7 per cent.
of the total pig iron raised or made in the kingdom. And owing
to its three deep estuaries, the Tyne, the Wear, and the Tees,
it built in that year no less than 51 per cent. of our total output
of merchant shipping tonnage. It was the district which gave
birth to the first public railway in 1825, and later on, after the
discovery of the Cleveland ironstone deposits, it led the world
in the development of that mighty engine of production the
modern blast furnace, and brought to fruition the basic steel
process.

The local conditions governing power supply throughout the
district are (1) a good supply of cheap coal; (2) the large size
and considerable technical development of most of the industrial
establishments; and (3) the fact that there are abundant supplies
of potential energy in the form of surplus coke-oven and blast-
e gases and waste heat which only a comprehensive power
an fully utilise.

esent scheme owed its inception to an amalgamation
tion of three power companies—namely, the Newcastle

Company, which started in 1889 as a small lightin
the Durham Company, which started in 1901 with tl
ting stations at Jarrow, Gateshead, and Durham, an
land Company, which started in 1903, with its principe
station at Grangetown, near Middlesbrough. In
these three Companies, the scheme has absorbed t
Collieries Electric Power Company and the Northe
Electrical Supply Company.

There are now seventeen generating stations
LXXVI), namely, five coal-fired (total capacity, 11

TABLE LXXVI

PARTICULARS OF GENERATING STATIONS (ALL 3-PHASE, 40
THE YEAR 1915

Power Station.	Type.	Horse-pov of Generatii Plant.
Carville, Old Station .	Coal-fired . . .	53,500
„ New Station .	Coal-fired . . .	32,000
Dunston	Coal-fired and Gas .	45,500
Philadelphia . . .	Coal-fired . . .	16,000
Neptune Bank . . .	Coal-fired . . .	5,800
Hebburn	Coal-fired . . .	4,300
Blaydon	Waste Heat and Gas	3,200
Bankfoot	Waste Heat and Gas	8,000
Bowden Close . . .	Waste Heat and Gas	6,400
Grangetown	Coal-fired and Waste Heat	11,200
Newport	Waste Heat . . .	7,300
Weardale	Waste Heat and Coal-fired . . .	7,300
Clarence	Waste Heat . . .	4,000
Ayresome	Waste Heat . . .	3,200
Tees Bridge	Waste Heat . . .	1,500
Shotton	Waste Heat . . .	1,300
Horden	Waste Heat . . .	1,300
	Total . . .	211,800

six waste-heat stations (total capacity, 18,600 H.P.
coal-fired and partly gas-fired (capacity 45,000 H.P.
coal-fired and partly waste-heat (total capacity, 1
and three partly waste-heat and partly gas-fired (tc
17,600 H.P.). The total capacity of the genei
installed up to the end of last year was 211,800 H.P
utilised are either coke-oven gas or blast-furnace g
there are enormous surpluses in the area. The

PLATE X.—Dunston Power Station.

PLATE XI.—Newport Waste Heat Power Station.

stations utilise either the sensible heat in the burnt gases from coke-ovens or the exhaust steam from blowing engines in iron-works, which, before being delivered to the steam engine, is sometimes "superheated" by the combustion of blast furnace gas. All the prime movers are steam-turbines, no gas engine being used. When gas is employed as a source of energy, it is always burnt under boilers, generating steam for turbines.

I am permitted, through the courtesy of Messrs. Merz and McLellan, the Consulting Engineers for the scheme, to give, by way of example, the following particulars relating to two of the generating stations. The first is the Dunston station of the Newcastle Company (Plate X), which is not only the most modern, but also, when completed, will be one of the largest in Europe. It is fired partly by coal and partly also by surplus gas from the Teams Otto by-product coke ovens. Its five large turbo-alternators have an output capacity of 45,500 H.P. But the station is laid out for six generating units, with a maximum total capacity of about 70,000 H.P. Steam is generated from coal-fired Babcock and Wilcox boilers at a pressure of 200 lbs. per square inch, and is then superheated to 570° Fahr. before delivery to the turbines. Three-phase current is generated at a normal pressure of 6000 volts and a frequency of 40 complete cycles per second.

The second example is the Newport Waste-Heat Station (Plate XI) near Middlesbrough, which is equipped with four 1666 H.P. Parson's turbines, driven by exhaust steam from the blowing engines in Sir B. Samuelson & Co.'s ironworks close by, and also a 900 H.P. Brush turbo-alternator, driven by supplies of high-pressure steam from the same works. The two main alternators were built by the British Westinghouse Company, and run at 2400 revolutions per minute, generating electrical energy at 3000 volts and 90 cycles per second, the greater portion of which is transformed up to 11,000 volts before being fed into the Company's high-tension main. All the power stations generate three-phase current at 40 cycles per second. At the larger stations the generating pressure is 6000 volts; but in the "waste-heat" stations it is 3000 volts, while at Grangetown it is 11,000 volts. In some of the stations it is at once transformed up to 11,000 or 20,000 volts, at which it is transmitted throughout the area to the various sub-stations, where it is transformed down to 6000, 3000, 600, or 440 volts.

Fig. 77*b* illustrates the phenomenal development of the scheme during the fifteen years (1900-1915) since its inception.

The total horse-power connected is now nearly 3
the total capacity of the generating plant is nearly

The system
tricity in b
and urban
prices cons
than it wo
local autho
ate it. The
Railway C
electrified
miles of t
suburban r
in additio:
electricity f
Company's
locomotive
Gateshead,
shops at
H.P.), the

North East Coast Power System

Horse Power
Connected

Capacity of
Generating Plant

Fig. 77b.

at Walker Gate, Tyne Dock, and Percy Main, as
goods stations at Newcastle, and their docks at
(800 H.P.) and Hartlepool (540 H.P.). Many tram
and most of the large industrial establishments ir
also large customers. Most of the large industrial
in the area—including collieries, ironstone mines,
works, shipbuilding yards, engineering shops, ceme
and alkali works, flour mills, and electro-chemi
are connected with the system.

The average price for electric energy is less
unit, whilst the coal consumption per H.P. hou
consumer's terminals is only 1·54 lb. It has l
that this latter figure has replaced a former coa
of 7 lbs. per H.P. hour when the various indus
ments now connected with the power scheme g
own power individually. On the total of 56c
hour delivered at consumers' terminals during t
this would represent a saving of no less than 1,3
coal per annum. The utilisation of " waste hea
the area now amounts to an equivalent of abou
of coal per annum.

CHAPTER XXII

" SURFACE COMBUSTION " [1]

iscourse by the Author before the Royal Institution of Great Britain on Friday, February 27, 1914

ɔRING his researches upon Flame,[2] Sir Humphry Davy
>vered, in 1817, that the constituents of a combustible
:ure will combine slowly below the ignition temperature;
led him to enquire whether, seeing that the temperatures
ames far exceed those at which solids become incandescent,
etallic wire can be maintained at incandescence by the com-
ition of gases at its surface, without actual flame: He there-
n tried the effect of introducing a warm platinum wire into a
:ontaining a mixture of coal-gas and air rendered non-explosive
an excess of the combustible constituents; the wire imme-
:ely became red hot, and continued so until nearly the whole
he oxygen had disappeared.
Ve will repeat the experiment, in a modified form, with the aid
ı platinum crucible and a Bunsen burner. If the platinum
cible be warmed by the flame, and the flow of the explosive
:ture through the burner be momentarily arrested, and then
nediately renewed, the gases, instead of burning with flame at
burner head, will immediately combine without flame over the
tinum surface, causing it to glow.
ɔuring the twenty years which followed Davy's discovery,
'eral distinguished chemists (William Henry and Thomas

points, namely: (1) that "this invisible flameless
: is only possible under certain conditions;" (2) "that
stible mixture shall come into absolute contact with
·e at high temperature . . .;" and (3) that "in the
·f a solid substance at a high temperature, it is im-
.o cause combustion without flame"; but, so far as I
·:, he did not follow up the matter beyond this point,
ι its theoretical aspects or practical applications, and
: had but little influence upon contemporary opinion
ιice.

wn investigations upon surface combustion began in 1902
systematic attempt to elucidate the factors operative in
w combination of hydrogen and of carbon monoxide in
t with various hot surfaces (*e. g.* porcelain, fireclay, mag-
platinum, gold, silver, copper and nickel oxides, etc.) at
·ratures below 500° C. Into the details of these earlier experi-
·s, which preceded and led up to the technical developments
t which I shall speak later, I do not propose to enter; it
be sufficient for my present purpose if I say that it was proved
ond all question (1) that the power of accelerating gaseous
ιbustion is possessed by *all* surfaces at temperatures below
· ignition point in varying degrees, dependent upon their
ımical characters and physical texture; (2) that such an
celerated surface combustion is dependent upon an absorption
the combustible gas, and probably also of the oxygen, by
ιe surface, whereby it becomes "activated" (probably ionised)
·y association with the surface; and (3) that the surface itself
›ecomes electrically charged during the process. Finally, certain
ımportant differences between homogeneous combustion in
ordinary flames and heterogeneous combustion in contact with
a hot surface from a chemical point of view were established, so
that there can be no longer any doubt as to the reality of the
phenomenon.[1]

The fact that such catalytic combustion depends upon an
intimate association of the surface with the combining gases is
beautifully illustrated by two photomicrographs of the surface
of a silver gauze taken *before* and *after* a long series of experiments
in which it was employed as the catalysing medium for the

[1] Bone and Wheeler, *Phil. Trans. Roy. Soc.*, 1906 (A. 206, pp. 1–67).
also further (unpublished) results (1905–12) in collaboration with Messrs.
'rew, A. Forshaw, and H. Hartley, which are summarised in
Deutschen Chem. Ges., 1913.

combination of hydrogen and oxygen at 400° C. (84
shows the original smooth condition of the surfa
shows the " frosted " effect produced by the de
action of the reacting gases during their a
" activation " by the surface.

My next contention is that if hot surfaces posses
accelerating gaseous combustion at temperatures b
neighbourhood of, the ignition point, the same po
be manifested in even a greater degree at higher
and especially so when the surface itself becomes
Indeed, there are experimental grounds for the h
only does the accelerating influence of the surface r
with the temperature, but also that the difference
catalysing powers of various surfaces, which at low
are often considerable, diminish with ascending
until at bright incandescence they practically disa

Such considerations as I have thus briefly explai
me some years ago that if an explosive gaseous mixt
injected on to or forced through the interstices of a p
tory incandescent solid under certain conditions,
hereafter explained, a greatly accelerated combustio
place within the interstices or pores, or, in other v
the boundary layers between the gaseous and solid
ever these may be in contact and the heat devel
intensified combustion would maintain the surface
incandescence *without any development of flame*, t
the conception of *flameless incandescent surface com*
means of greatly increasing the general efficienc
operations wherever it can be conveniently applied.

There are critics who, whilst admitting the accel
ence of an incandescent surface upon gaseous com
sceptical about the process being really flameless.
such objections largely disappears when we get into c
with the phenomenon, and realise how extremely s
action flame combustion really is when considered
molecular time. Take, for example, the case of su
burning mixture as electrolytic gas ($2H_2 + O_2$). W
ignited at atmospheric pressure, the flame is initially
by conduction with a uniform slow velocity of 20
second, and during this initial period of " *inflamma*
total duration of chemical change in each successive lay
thing like the order of $\frac{1}{80}$ second, an interval of at least o

Fig. 78.

Fig. 79

Photomicrographs of Silver Gauze before and after Surface
Combustion Experiment.

million times as long as the average interval between successive molecular collisions in the gas. Even after "*detonation*" has been set up in the mixture, when the combustion is propagated from layer to layer as a wave of adiabatic compression, at a velocity of 2820 metres per second, the total duration of chemical change is still of the order of $\frac{1}{5000}$ or $\frac{1}{10000}$ second, or about a million times as long as the interval between successive molecular collisions.

To illustrate how a flame may be extinguished by the introduction of an active catalysing surface, I will perform an experiment which was first exhibited here a year ago by my colleague Professor the Hon. R. J. Strutt, who has very kindly lent me his apparatus. Most of you will be familiar with his discovery of the active modification of nitrogen produced by a powerful electric discharge. This bulb (capacity 300 c.c.) is full of rarefied nitrogen, at a pressure of about $\frac{1}{10}$ mm.; and in the side tube lies an oxidised copper wire, which fits it as closely as is consistent with easy sliding.

If the nitrogen in the bulb be subjected to a powerful electrodeless discharge, it is transformed into an active condition; the gas continues to glow brilliantly, owing to the fact that the "active" modification is reverting to the ordinary kind producing a luminosity which may be regarded as a condition analogous with flame. The glow will last for a minute or more during the progress of the chemical reversion, and finally dies out when the latter is completed.

But if, on repeating the experiment, the bulb be tilted so that the oxidised copper wire drops into the glowing gas, the luminosity is instantly extinguished. This shows that the reversion process is so enormously accelerated by the surface that practically the whole of the chemical action is concentrated at the surface, and instantaneously completed there, thus extinguishing the glow.

I think we have, in Professor Strutt's experiment, a close analogy to what I conceive as occurring when an incandescent surface is employed to accelerate ordinary gaseous combustion; the action is so concentrated at the surface that a substantially "flameless" effect results. I want to emphasise the fact that the incandescent solid plays a specific rôle in this surface combustion; it is no mere idle looker-on at the surging crowd of reacting molecules which swarm around it. On the contrary, it so galvanises and incites the dormant affinities between the

combustible gas and oxygen, that the stately minuet
combustion gives place to the wild intoxication of the

The manner in which the surface acts is still perhaj
of conjecture, but the fact that it so acts can no longer l
In a discussion which took place at the British Ass
1910, Sir J. J. Thomson insisted that combustion is
not only with atoms and molecules, but also with
i. e. bodies of much smaller dimensions and moving
high velocities, and suggested that in reference to tł
of hot surfaces in promoting combustion it was not
that the emission of charged particles from the sur
factor of primary importance. It is known that ir
surfaces emit enormous streams of electrons travellin
velocities, and the actions of these surfaces in promoti
tion may ultimately be found to depend on the fac
bring about the formation of layers of electrified gɛ
chemical changes proceed with extraordinarily high ·

THE NEW PROCESSES OF INCANDESCENT SURFACE C

Leaving the theoretical aspects of the subject,
describe some of the more important features of two]
incandescent surface combustion evolved at the work
Wilsons and Mathiesons, Ltd., in Leeds under mɔ
with the assistance of Mr. C. D. McCourt, in which a
ous explosive mixture of gas and air, in the proper ·
for complete combustion (or with air in slight exce
is caused to burn without flame in contact with
incandescent solid, whereby a large proportion of th
energy of the gas is immediately converted into rac
The advantages claimed for the new system, now
the " Bonecourt " system, are : (1) the combustion
accelerated by the incandescent surface, and, if so de
be concentrated just where the heat is required ; (2) t
tion is perfect with a minimum excess of air ; (3) the
of very high temperatures is possible without the aid c
regenerative devices ; and (4) owing to the large amoun
energy developed, transmission of heat from the seat
tion to the object to be heated is very rapid. These ɛ
are so uniquely combined in the new system that th
heating effect is, for many important purposes not
eminently economical, but also easy of control.

DIAPHRAGM HEATING AND ITS APPLICATIONS

In the first process the homogeneous mixture of gas and air is allowed to flow under slight pressure through a porous diaphragm of refractory material from a suitable feeding chamber (see Fig.80), and is caused to burn without flame at the surface of exit, which

FIG. 80.

is thereby maintained in a state of red-hot incandescence. The diaphragm is composed of granules of firebrick, or other material, bound together into a coherent block by suitable means; the porosity of the diaphragm is graded to suit the particular kind of gas for which it is to be used. The diaphragm is mounted in a suitable casing, the space enclosed between the back of the casing and the diaphragm constituting a convenient feeding-chamber for the gaseous mixture. Such a mixture may be obtained in either of two ways, namely (1) by means of suitable connections through a Y-piece with separate supplies of low-pressure gas and air (2

451

or 3 in. W.G. is sufficient), or (2) by means of an arrangement connected with a supply of gas at a pre: 2 lbs. per sq. in.; the gas in this case draws in its o the atmosphere in sufficient quantity for complete the proportions of gas and air being easily regulated device.

We will now start up a diaphragm. Gas is first of a and ignited as it issues at the surface; air is then grad until a fully aërated mixture is obtained. The flai comes non-luminous, and diminishes in size; a m(it retreats on to the surface of the diaphragm, wh assumes a bluish appearance; soon, however, the the surface attain an incipient red heat, producin, mottled effect; finally, the whole of the surface layer becomes red hot, and an accelerated "surface c comes into play. All signs of flame disappear, and tl an intensely glowing surface throwing out a genial 1 which can be steadily maintained for as long as requ

Whilst the diaphragm is in operation before you, out some of the more striking features of the phenon it presents. *Firstly*, the actual combustion is confir very thin layer—⅛ to ¼ in. only—immediately below and no heat is developed in any other part of the Kindly observe that whilst the front of the diaphragm hot, the back of the apparatus is so cold that I can 1 on it. *Secondly*, the combustion of the gas, althou within such narrow limits, is perfect, for when once proportions of gas and air have been properly adjust of unburnt gas escapes from the surface. *Thirdly*, t ture at the surface of the diaphragm can be instant will by merely altering the rate of feeding of the gasec there is practically no lag in the temperature respons stance of great importance in operations where a fin of heat is required. *Fourthly*, a plane diaphragm : may be used in any position, *i. e.* at any desired an the horizontal and vertical planes. *Fifthly*, the method is amenable to a variety of combustible ga: coke-oven gas (either undiluted or admixed with natural gas, petrol-air gas, carburetted water gas suited in cases where unimpeded radiation is require the incandescence in no way depends upon the ext sphere. When once the diaphragm has become in

.d the proportions of air and gas supplied in the mixing chamber
the back have been properly adjusted, the surface will maintain
; incandescence unimpaired, even in an atmosphere of carbon
oxide.

I need hardly point out to you the many obvious purposes,
ɔmestic and industrial, to which " diaphragm heating " may be
pplied. In the domestic line, the boiling of water, grilling,
ɔasting and toasting are at once suggested, and although the
est existing types of gas fires are thoroughly hygienic and effi-
ient, I think that the diaphragm may come in for the heating
f apartments; at any rate experiments are being carried out in
hat direction.

I have recently been told of a large restaurant in London where
hey are grilling by means of an electric radiator fixed horizontally
ɩbove the work so that the radiant energy is directed downwards
ɔn to it. It has been claimed that the value of the recovered
ːat, which in the ordinary method of grilling drops into the fire
ɔnd is consumed, has more than paid for the electricity used.
With a diaphragm, similar advantages can be secured with gas at
a considerably less cost; for comparing gas of net calorific value
500 B.Th.Us. per cub. ft. at 2s. 6d. per 1000 cub. ft. with elec-
tricity at 3d. per unit, the initial cost of a given amount of energy
is about 14 times greater in the form of electricity than in the
form of gas.

Turning now to the industrial field, I had the satisfaction of
visiting not long ago a large confectionery factory where the
diaphragms have been employed for more than a year for
boiling and concentrating sugar solutions. The solution is boiled
in a copper pan over a 13-in. diameter circular diaphragm (see
Fig. 81); the supply of gaseous mixture is controlled by one lever
which operates in a single movement the gas and air cocks. The
ignition is effected automatically by means of a small pilot light.
Each boiler does 10 to 12 heats per diem, each lasting twenty
minutes, and some of the diaphragms have been in continuous
daily use for about a year. I saw in the factory a battery of thir-
teen such boiling pans, all in constant use, and was informed that
the gas consumption was not more than half what it formerly
used to be when the pans were heated over ordinary atmospheric
flame burners. The secret of this higher efficiency lies in the
fact that gas flames are a very unsatisfactory means for boiling
liq 'ds in metallic vessels, owing to the non-conducting layer of
rel ːvely cool gas which forms between the flame and the under-

3

surface of the pan; but with a diaphragm the lar of radiant heat is quickly absorbed by the vessel ar to the liquid with high efficiency.

Moreover, in evaporating liquids it is possible to head diaphragm, directing the radiation downwa surface of the liquid, thus eliminating altogether of the containing vessel. In this way only the u the liquid are actually heated up to the working whilst the evaporation is extraordinarily rapid Given a sufficiently cheap high-grade gas there wo be endless possibilities for diaphragm heating in field.

FIG. 81.

INCANDESCENT SURFACE COMBUSTION IN A BED OF GRANULAR MATERIAL

The second process is applicable to all kinds vaporised fuels; it consists essentially in injectin suitable orifice at a speed greater than the velo firing, an explosive mixture of gas (or vapour) an combining proportions into a bed of incandescent gr tory material which is disposed around or in proximit to be heated.

I can perhaps best describe the process by th diagrams showing its applications to the heating of muffle furnaces. Fig. 82 shows the process as applied furnace. The crucible is surrounded by a bed incandescent granular material. The mixture of g injected at a high velocity through a narrow orific

454

of the furnace, and as it impinges upon the incandescent bed, combustion is instantaneously completed without flame.

The seat of this active surface combustion is in the lowest part of the bed; the burnt gases, rising through the upper layers, rapidly impart their heat to the bed, maintaining it in a high degree of incandescence. Fig. 83 shows a similar arrangement

FIG. 82.

for the heating of a muffle furnace which needs no further explanation.

It is obvious that this process is capable of adaptation to all of furnace operations, as, for example, to the heating of muffles, retorts, and to annealing and forging furnaces Moreover, it is not essential that the bed of refractory uld be very deep; indeed a quite shallow bed suffices he combustion. Neither is it necessary that the osec' the vessel or chamber to be heated; products is not objectionable, a

shallow bed may be arranged *within* the heating ch
(Fig. 84, p. 458); or the refractory material may be
packed into tubes, or the like, traversing the s
medium to be heated. The last-named modificatie
shall see later, specially important in relation to s
in multitubular boilers.

By means of this process much higher temperature
able with a given gas than by the ordinary methods o
bustion without a regenerative system, and, as a ma
we have found that with any gas of high calorific int

F𝗜𝗴. 83.

as coal gas, water gas, or natural gas) the upper
temperature limit is determined rather by the refra
the material composing the chamber to be heated (*i. e*
or crucible) than by the possibilities of the actual
itself. When I tell you that in a crucible fired by coal
system we have melted Seger-cone No. 39, which a
the latest determination of the German Reichsansta
1880° C. (3416° F.), and also that we can easily melt
you will appreciate the possibilities of the method ii
high temperatures with gas-fired furnaces.

The maximum temperature obtainable, without
tive " appliances, with any particular gas will obviou
upon the relative heat capacities of their products of

for a given heat development in the bed. In this connection, it is of interest to compare the principal gaseous fuels available for industrial operations in the order of their calorific intensities, as follows:—

TABLE LXXVII

THE COMBUSTION OF TYPICAL GASEOUS FUELS

	Per Cubic Foot of Gas Burnt.			Per 100 B.Th.US. *net* developed on Combustion.			
	Net B.Th.Us	Vol. of Air Required.	Vol. of Products	Vol. of Air Required.	Vol. of Combining Mixtures	Vol. of Products	Relative Heat Capacities of Products
Blue Water Gas . .	290	2·290	2·82	0·79	1·14	0·97	0·95
Coal or Coke Oven Gas	500	4·656	5·36	0·93	1·13	1·08	1·00
Producer Gas . .	140	1·166	2·00	0·84	1·50	1·43	1·38
Blast-furnace Gas .	100	0·716	1·58	0·72	1·72	1·58	1·52

Now, whilst with coal gas, coke-oven gas or water gas, it should be easily possible, without regeneration, to obtain in a refractory granular bed temperatures of up to at least 2000° C. (or say 3630° F.), with a low-grade producer gas, such as Mond gas, about 1500° C. (or say 2730° F.), would probably be the approximate maximum without regeneration. But with some degree of heat recuperation, which in large furnaces is quite practicable, still higher temperatures would be attainable.

Moreover, within the maximum limits, the heating with any kind of gas is very uniform, economical, and controllable; indeed the temperature for a given furnace fired by gas of uniform composition is chiefly controlled by the amount of gas burnt, or in other words, the rate of heat development in the bed. And as for economy, tests made about three years ago in Leeds under my supervision upon medium-sized muffle furnaces convinced me that to maintain a given temperature between say 800° and 1400° C., a properly constructed " surface combustion furnace " would require between 70 and 40 per cent. only of the gas used in an ordinary flame-heated furnace of the same dimensions, and that the advantage in favour of " surface combustion " would increase rapidly with the working temperature.

This was confirmed by independent competitive trials carried

out in New York shortly after my lectures there in t
of 1911, in which our surface-combustion furnaces 1
against the best American types; it was proved th;
to maintain a temperature of 1400° C. we practically h
gas consumption, whilst to maintain 800° C. our cc
was about 0·7 of theirs.

Any one who understands furnace design and consti
appreciate the many difficulties which are necessarily e;
in applying a new and revolutionary idea of this sort t
of large industrial furnaces.   Indeed, the new conditio
ing are so radically different from the old, that a new
has to be built up.   There are problems connected with
feeding and distribution of gaseous mixture, with t
sions and arrangement of the combustion beds, and
refractiveness of the furnace walls, which have to
Nevertheless, judging from reports that reach me fro
time, substantial progress has been made in the direct
fired crucible furnaces for brass and aluminium meltin
ing furnaces, and forging furnaces, the latter fired witl
gas with regeneration of gas and air.   Some large
furnaces (for example, Fig. 85) are now running satisf;
industrial establishments on both Mond gas and towr
I understand that brass melting can be carried out in 5
charges in tilting crucible furnaces with the remarl
consumption of about 1·75 cub. ft. per pound of mel
and poured.

SURFACE COMBUSTION AS APPLIED TO STEAM RA

I now come to an important application of the new 1
the raising of steam in multitubular boilers; not that th
tion of surface combustion is limited to boilers of the mu
type, but because our investigations have so far been p
made with these.

It is well known that the gas-firing of steam boiler
been very successful from the point of view either o
efficiency or of rate of evaporation.   In this country
available for steam-raising purposes on a large scale a
pally (1) blast-furnace gas, of which there are large surpli
able in all iron-smelting areas; (2) the surplus gas c
during the manufacture of coke in by-product ovens
producer gas of various compositions, but more particu

FIG 84.

manufactured under ammonia recovery conditions. In the United States, and some other oil-producing countries, natural gas of high calorific power is also available. All these gases have been found to be amenable to the system I am about to describe.

It has been estimated by a prominent British blast-furnace engineer that the thermal efficiency of the best type of water-tube boiler, fired by blast-furnace gas, does not exceed about 55 per cent., whilst in the case of boilers fired by coke-oven gas the average thermal efficiency probably does not much exceed 65 to

Fig. 86.

70 per cent. But on applying the principle of surface combustion to the gas-firing of multitubular boilers we have been able to obtain results with coal gas corresponding to the transmission of nearly 95 per cent. of the *net* calorific value of the gas to the water in the boiler.

Our first experiments in Leeds were made with a single steel tube 3 ft. in length and 3 in. in diameter, packed with fragments of granular refractory material, meshed to a proper size, and fitted at one end with a fireclay plug, through which was bored a circular hole, ¾ in. in diameter, for the admission of the explosive mixture of gas and air at a speed greater than that of back-firing ⁻ig. 86). The tube was fitted into an open trough, such as you ¬ here on the table. in which water could be evaporated at

459

atmospheric pressure. After the lecture my assis
demonstrate the boiling of water in this apparatus.

Such a tube may be appropriately termed the fu
unit of our boiler system, because boilers of almost an·
be˙constructed merely by multiplying the single tul
each tube is, so to speak, an independent fire or unit, th·
of the whole is that of the single tube, or in other ·
efficiency of the whole boiler is independent of the ·
tubes fired.

Experimenting with such a tube, it was found possib
completely a mixture of 100 cub. ft. of coal gas plus 5·
of air per hour, and to evaporate about 100 lb. of ·
and at 100° C. (212° F.) per hour (20 to 22 lb. per
heating surface), the products leaving the further end o
at practically 200° C. This meant the transmission to
of 88 per cent. of the net heat developed by the combu·
an evaporation per sq. ft. of heating surface nearly t
of an express locomotive boiler. The combustion of th
completed within 4 or 5 in. of the point where it en
tube. Of the total evaporation, no less than 70 per cent
over the first linear foot of the tube, 22 per cent. over t·
foot, and only 8 per cent. over the last foot. This p·
very effective " radiation " transmission from the inc·
granular material in the first third of the tube, where
of active combustion is located, although it should be ·
that the *loci* of actual contact between the incandescen·
and the walls of the tube are so rapidly cooled by the tra·
of heat to the water on the other side that they never
temperature even approaching red heat. The granular
in the remaining two-thirds of the tube serves to baffl·
products of combustion, and to make them repeatedly
with high velocity against the walls of the tube, thus n·
accelerating their cooling, and either preventing or m·
the formation of the feebly-conducting stationary film of r
cold gases which in ordinary boiler practice clings to
walls, seriously impairing the heat transmission.

Having thus satisfied ourselves of the efficiency of th·
mental unit as an evaporator, we proceeded to construct
experimental boiler, made up of ten tubes, each 3 ft. long ·
in diameter, fixed horizontally in a cylindrical steel shell
of withstanding a pressure of over 200 lb. per sq. i·
boiler is shown diagrammatically in Fig. 87 (section showi·

FIG. 88.—Surface Combustion 10-Tube Experimental Boiler.

tubes only), whilst Fig. 88 is a photograph of it (back view showing feed-water heater). The gaseous mixture was forced through the tubes under pressure from a special feeding chamber attached to the front plate of the boiler; the products of combustion, after leaving the boiler, passed through a small feed-water heater containing nine tubes, each 1 ft. long and 3 in. in diameter, filled with granular material to facilitate the exchange of heat.

This combination of boiler and feed-water heater proved phenomenally successful in every way; in a trial run at Leeds on December 8, 1910, with coal gas of net calorific value 562


FIG. 87.

B.Th.Us. per cub. ft. at N.T.P., and evaporating at the rate of 21·6 lbs. of water " from and at 212° F." per sq. ft. of heating surface per hour, the ratio of the heat utilised to the net heat developed in the tubes was 0·943. But this remarkable result eclipsed in another independent trial carried out by German ers in London on January 8, 1913, when, with coal gas calorific value 510 B.Th.Us. per cub. ft. at N.T.P., and ing at the enormously high rate of 33·9 lbs. " from and at per sq. ft. of heating surface, the ratio of the heat

utilised to the net heat developed by combustion w₁
The details of these tests are shown herewith:—

TABLE LXXVIII

	I. Dec. 8, 1910.
1. Net cal. value of gas : B.Th.Us. per cub. ft. at N.T.P.	562
2. Rate of evaporation : Lbs. of water per sq. ft. heating surface per hour (from and at 212° Fahr.)	21·6
3. Pressure of gaseous mixture entering the tubes : Inches W.G.	17·3
4. Pressure of products entering the feed water heater : Inches W.G.	2·0
5. Steam-gauge pressure : Lbs. above atmospheric	100
6. Boiling point of the water : Fahr. Degrees .	338°
7. Temperature products leaving boiler : Fahr. Degrees	446°
8. Temperature products leaving feed-water heater: Fahr. Degrees	203°
9. Net heat supplied to the boiler per hour : B.Th.Us.	559,800
10. Net heat transmitted per hour : B.Th.Us. . .	527,800
Efficiency Ratio	0·943

THE 110-TUBE BOILER AT THE SKINNINGROVE IRONW₍

Six months' continuous experience with our first exper
unit gave us great confidence in its reliability, so that ₁
the early months of 1911 we received an enquiry from tl
ningrove Iron Co., Ltd., for a boiler of about ten times the c
of the experimental unit, to be fired by means of the surₚ
from their new Otto by-product coking-plant, we had no
tion in accepting a commission to instal our first large boile
under a strict guarantee as to its output and efficiency
boiler (Fig. 89) was built by Messrs. Richardsons and Wes
Ltd., of Middlesbrough, to the design of Mr. Michael Lor
to whom I had been indebted for much valuable advi
encouragement during the earlier experiments. It consis
cylindrical drum 10 ft. in diameter and 4 ft. from front t₍
traversed by 110 steel tubes, each of 3 in. internal diₐ
which are packed with fragments of suitable refractory g₁
material. To the front of the boiler is attached a sₚ
designed feeding chamber which delivers washed coke-oᵥ

utilised to the
The details of t

1. Net cal.	N T P
2. Rate of	heating / Fahr
3. Pressure	Inches
4. Pressure	heater
5. Steam	
6. Boiling	
7. Temperat	Degrees
8. Temperat	Fahr
9. Net heat	B Th
10. Net heat	

THE 110-

Six months
unit gave us
the early me
ningrove Iron
of the experi
from their new
tion in accepta
under a strict
boiler (Fig. 89
Ltd., of Middle
to whom I ha
encouragement
cylindrical drum
traversed by 11
which are packed
material. To the
designed feeding

air , and under a pressure of 1 to 2 in. W.G., to combustion tubes; this gas, together with a ~tion of air from the outside atmosphere, is ~tion from a fan, through a short mixing tube, said combustion tubes, where it is burnt without t with the incandescent granular material. The ~mbustion having traversed the 4-ft. length of pass outwards into a semicircular chamber at the ~der, and thence through a duct to the tubular ~ater. The fan which is attached just beyond this ~eater and is driven by a three-phase A.C. electric

Fig. 90.

~ucks out the cooled products, at a temperature of 100° C. ~r under, and discharges them, through a short vertical ~ atmosphere. The arrangement of the whole plant ~e accompanying diagram (Fig. 90). ~s successfully started up on November 7, 1911, ~al run—day and night continuously—after ~up for an official inspection by the representa- ~nce Company. Everything worked without ~steam was generated, at 100 lb. gauge ~of about four degrees of hardness, ~e of the waste gases leaving the ~80° C. (say 175° Fahr.), a sure ~ciency of the plant. When,

$$\text{Ratio} \frac{\text{Heat utilised}}{\text{Net heat supplied}} = 0\cdot927\,[1]$$

$$\left.\begin{array}{l}\text{Power taken by fan}\\ \text{[Suction = 20 in. W.G.]}\end{array}\right\} = 6097 \text{ watts} = \text{(say) } 8\cdot2 \text{ H.P.}$$

The heat balance of the test is as follows, and for purposes of comparison I will give the heat balance for a trial of a marine boiler fired with a good steam coal of net calorific value 13,800 B.Th.Us. per lb. (volatile matter = 16·1 per cent.).

TABLE LXXIX

	Gas-fired Surface Combustion Boiler.	Coal-fired Marine Boiler.
	Per cent.	Per cent.
Heat utilised	92·7 [2]	75·1
Heat lost } in Burnt Gases . . .	3·0	18·1
in Unburnt Gases . . .	nil	2·8
by Radiation, etc. . .	4·3	4·0
	100·0	100·0
Rate of Evaporation in lbs. per sq. ft. heating surface per hour . .	14·1	4·3

The engineer who superintended these trials was very anxious to find out whether, in view of the intensity of the combustion and the high rate of heat transmission, the boiler tubes after five months continuous running day and night would show any signs of deterioration. Consequently, one of the boiler tubes, selected by him, was cut out and subjected to severe mechanical tests, similar tests being simultaneously made with a new and unused boiler tube of same dimensions. The results proved conclusively that the five months service had not in any way impaired the mechanical properties of the boiler tubes, thus falsifying the

uld be stated that the boiler was *not lagged* during the trial, figure would have been about 0·94.
the steam equivalent of the power consumed in driving Skinningrove boiler, the "*over-all efficiency*" of the plant *per cent.* To complete the comparison, the coal-fired imilar' with the power (whether human or
d i

commercial scale in Germany, and in anticipation of the publica-
tion of the results of the official German trial, I wish, with your
kind permission, to mention a matter which, although it may
appear personal, is nevertheless bound up with the credit of
British scientific invention.

This boiler, invented and developed as it was in Leeds, by a
group of British chemists, all University trained men, aided by
the advice of Mr. Michael Longridge and by the enterprise of my
friends of the Skinningrove Iron Co., may truly be claimed as an
“ all-British ” invention, if ever there was one. Nevertheless,
it has recently been described in the German technical press as
the “ Bone-Schnabel,” or the “ Schnabel-Bone ” boiler, instead
of the “ Bonecourt ” boiler, as it should be. It may be necessary
at some future time to deal more fully with this aspect of the
matter, but to-night I will content myself with a protest against
any attempt to claim or represent this boiler as, in part, a German
invention.

I have perhaps said enough already about the boiler and its
working to convince you that it combines high thermal efficiency
and concentration of power, in a unique degree, and perhaps I
may be permitted to summarise the other important advantages
which may be claimed for it. *Firstly*, from the constructional
point of view, nothing could be simpler or more compact than a
cylindrical shell only 4 ft. long by 10 ft. in diameter, traversed
by straight tubes, supported on a casting, and requiring neither
elaborate brickwork setting nor expensive chimney flues and
stack. *Secondly*, it has a further advantage over all multitubular
boilers in that the front plate can never be heated beyond the
temperature of the water, however much the firing may be
forced, a circumstance which, coupled with the extremely short
length of the tubes, implies an absence of strain and greatly
reduces the risk of leaky joints. *Thirdly*, the high rate of mean
evaporation obviates scaling troubles, and the very steep evapora-
tion gradient along each tube causes a considerable natural
circulation of water in the boiler, a factor of great importance from
the point of view of good and efficient working. In this connec-
tion I may remind you that under normal working conditions
we obtain a *mean evaporation* of 20 lbs. per sq. ft. of heating
surface per hour, and can, if need be, force this up to 35 lbs.; of
                              o per cent. occurs over the first *third*
                              cent. over the *second* third, and only
   ird. *Fourthly*, inasmuch as each tube

FIG. 91.—Front View of Bonecourt Surface Combustion Boiler.

FIG. 92.—Back View of Bonecourt Surface Combustion Boiler.